

# Shell Helix Super

## *Trusted protection whatever your car*

Shell Helix Super is a guaranteed quality lubricant based on a blend of high viscosity index mineral oils and selected additives that give your car unbeatable clean up action with special cleansing agents that actively and continuously lock away harmful dirt and deposits.

Shell Helix Super is blended to provide reliable passenger car engine protection in normal motoring conditions.

With Shell Helix Super you know you are doing the right thing for your car

---

### Applications

- **Gasoline and Diesel engines**  
Naturally aspirated and turbocharged multivalve passenger car engines.

### Performance Features

- **Unbeatable clean up action**  
Shell Helix Super has significantly more engine clean up power than other leading brands. (Tests carried out by SWRI USA).
- **Dependable protection**  
Shell Helix Super will provide all-year-round protection
- **High oxidation resistance**  
Long operational oil life.
- **Excellent engine cleanliness and low combustion residues**  
For maximum engine performance and life.
- **Superior viscosity retention**  
High 'VI' (Viscosity Index) ensures adequate viscosity at all operating temperatures.

### Performance Specifications

Shell Helix Super is suitable for use where the following specifications are called for:

API Service Classification SL/CF  
ACEA: A2/B2

### Health & Safety

Shell Helix Super is unlikely to present any significant health or safety hazard when properly used in the recommended application, and good standards of industrial and personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

For further guidance on Product Health & Safety refer to the appropriate Shell Product Safety Data Sheet.

### Protect the environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

### Advice

Advice on applications not covered in this leaflet may be obtained from your Shell Representative.



## Typical Physical Characteristics

Shell Helix Super	10W-30	10W-40	15W-40	20W-50
<b>SAE Viscosity Grade</b>	10W-30	10W-40	15W - 40	20W-50
<b>Kinematic viscosity</b> @ 40°C cSt 100°C cSt (IP 71)	60.5 10.5	94.8 14.3	105.4 13.9	157.0 19.0
<b>Viscosity Index</b> (IP 226)	161	155	132	137
<b>Density</b> @ 15°C kg/l (IP 365)	0.862	0.874	0.885	0.888
<b>Flash Point</b> (PMCC) °C (IP 34)	226	210	220	215
<b>Pour Point</b> °C (IP 15)	-35	-33	-30	-27

