

Nautilus Premium Outboard Oil

Two-stroke premium outboard oil



Nautilus Premium Outboard Oil is a high performance lubricant for the superior protection of all two-stroke gasoline outboard motors.

Its advanced formulation, which exceeds all outboard motor manufacturers' standards, is a guarantee of long and reliable engine life.

Applications

- All two-stroke gasoline outboard motors with or without separate oil tanks.

Performance Specifications

Nautilus Premium Outboard Oil exceeds the requirements of all major outboard motor manufacturers and all industry specifications.

Certified by NMMA (National Maritime Manufacturers' Association) for service TC-W3 at the manufacturer's recommended fuel/oil ratio (up to 100:1)

Self-Mixing Properties

Nautilus Premium Outboard Oil is a self-mixing oil. It is blended to the correct viscosity for use in oil injection systems fitted to two-stroke gasoline outboard motors.

Health & Safety

Nautilus Premium Outboard Oil is unlikely to present any significant health or safety hazard when properly used in the recommended application, and good standards of industrial and personal hygiene are maintained.

Avoid contact with skin. After skin contact, wash immediately with soap and water.

For further guidance on Product Health & Safety refer to the appropriate Shell Product Safety Data Sheet.

Advice

Advice on applications not covered in this leaflet may be obtained from your Shell Representative.

Typical Physical Characteristics

Nautilus Premium Outboard Oil	
Kinematic Viscosity @ 40°C cSt 100°C cSt (IP 71)	38.0 7.0
Density @ 15°C kg/l (IP 365)	0.871
Flash Point °C (PMCC) (IP 34)	70
Pour Point °C (IP 15)	-35
Sulphated Ash % wt (IP 163)	0.01

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.