

Pennzoil Platinum VX SAE 5W-30

Ultimate protection for performance motoring

Pennzoil Platinum VX is a premium-grade, fully synthetic engine oil scientifically formulated that gives you maximum engine keep clean properties with special cleansing agents that actively and continuously lock away harmful dirt and deposits to provide protection in motor oil designed for today's latest diesel engines and emission systems.

Pennzoil Platinum VX is a unique, fully synthetic lubricant giving ultimate engine protection for performance motoring, is approved by leading car manufacturers such as VW and other car brands equipped with diesel particulate filter (DPF) emission control systems.

With Pennzoil Platinum VX you know you are doing the right thing for your car

Applications

- **Modern VW and other diesel passenger cars equipped with Diesel Particulate Filters (DPF), requiring an ACEA C2 or C3 oil in the owner's manual.**

Performance Features and Benefits

- **Fuel economy**
Exceeds fuel economy requirements of VW cars.
- **Protection Against Wear**
Enriched with long life additives and protective agents to provide a prolonged protection against sludge and to ensure maximum engine protection against costly engine wear, even in the toughest driving conditions and harshest climates.
- **Environmental Protection**
Specially formulated to reduce CO₂ (greenhouse gas) exhaust emissions. The use of selected base oils reduces oil consumption.
An extremely low chlorine content reduces the environmental impact of product disposal.
- **Easy start-up**
Even in cold conditions rapid oil flow assures any easy start and contributes to engine protection.

Specification and Approvals

Pennzoil Platinum VX SAE 5W-30 exceeds the following industry standards:

ACEA:	C2/C3 ; A3/B4-04
VW	504 00 / 507 00
BMW	LL-04
MB Approval	229.51
Chrysler	MS-11106

Advice

Advice on applications not covered in this leaflet may be obtained from your Shell Representative.

Health and Safety

Guidance on Health and Safety are available on the appropriate Material Safety Data Sheet that can be obtained from your Pennzoil representative.

Protect the environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Typical Physical Characteristics

Pennzoil Platinum VX		5W-30
SAE Viscosity grade		5W-30
Kinematic Viscosity	ASTM D 445	
at 40°C mm ² /s		67.1
at 100°C mm ² /s		12.0
Viscosity Index	ISO 2909	178
Density at 15°C kg/m ³	ASTM D 4052	847
Flash Point COC °C	ISO 2592	230
Pour Point °C	ISO 3016	- 39

These characteristics are typical of current production. Whilst future production will conform

to Pennzoil's specification, variations in these characteristics may occur.