



FORMULASHELL® HIGH MILEAGE FORMULA MOTOR OIL

Meets API Service Categories SN, SM, SL etc. specifications.

Has enhanced wear protection and outstanding resistance to thermal breakdown at operating temperatures.

PRODUCT DESCRIPTION

FORMULASHELL® HIGH MILEAGE FORMULA OILS are formulated for engines with 75,000 miles and more. They provide extra protection to extend the life of the engine. The SAE 5W-30 or SAE 10W-30 grade engine oils meet and exceed all automobile and light duty truck requirements for gasoline engines where API SN service performance is recommended. These oils can be used in place of earlier API SL, SJ, and SH rated oils.

Follow manufacturer's recommendations for viscosity grade and API Service.

FEATURES

FORMULASHELL® HIGH MILEAGE FORMULEA MOTOR OIL meets or exceeds:

- North American warranty requirements for U.S., European and Japanese cars and light trucks with gasoline and gasoline turbo-charged engines where API SN, SM, SL, SJ etc. oils are specified..

BENEFITS

Some of the features of FORMULEASHELL® HIGH MILEAGE FORMULA MOTOR OILS :

- Help reduce oil consumption
- Provide protection for worn engine parts
- Contain a Seal Conditioner to help reduce leaks

**TYPICAL PHYSICAL AND CHEMICAL PROPERTIES
FORMULASHELL[®] HIGH MILEAGE FORMULA MOTOR OIL**

TEST	5W-30	10W-30
SAE Viscosity Grade	5W-30	10W-30
API Gravity	34.4	33.8
Viscosity, cSt, 40°C	57.47	61.5
Viscosity, cSt, 100°C	10.51	10.5
Flash Point, °C	225	228
Pour Point, °C	-36	-33
CCS Viscosity, cP (°C)	4,300 (-30°C)	4,090 (-25)
MRV Viscosity, cP (°C)	17,300 (-35°C)	11,100 (-30)