

# **PENNZOIL PLATINUM<sup>®</sup> SAE 5W-30 FULL SYNTHETIC MOTOR OIL** **MADE FROM NATURAL GAS**



## **TECHNICAL DATA SHEET**

Pennzoil Platinum<sup>®</sup> with PurePlus<sup>™</sup> Technology is a first of its kind full synthetic motor oil made from natural gas and designed for COMPLETE PROTECTION for top engine performance. Formulated for modern turbocharged engines.

### **PERFORMANCE, FEATURES & BENEFITS**

Pennzoil<sup>®</sup> is the first motor oil made from natural gas, not crude. Our PurePlus<sup>®</sup> Technology is the revolutionary process that converts pure natural gas into high quality full synthetic base oil, with fewer impurities than traditional base oils made from crude. Pennzoil Platinum<sup>®</sup> Full Synthetic motor oil is designed to deliver complete engine protection for top engine performance.

Complete protection:

#### **CLEANER PISTONS**

Keeps pistons up to 45% cleaner than required by the toughest industry standard.<sup>1</sup>

#### **BETTER FUEL ECONOMY.<sup>2</sup>**

#### **PROTECTS HORSEPOWER**

Helps protect engines from loss of power.

#### **UNSURPASSED WEAR PROTECTION**

No other leading motor oil provides better protection from friction.<sup>3</sup>

#### **EXCELLENT PERFORMANCE IN EXTREME TEMPERATURES**

Provides faster low temperature oil flow and protects in extreme heat.

<sup>1</sup> Based on ILSAC GF-6A and Sequence IIH piston deposit test using SAE 5W-30

<sup>2</sup> Based on the latest industry standard

<sup>3</sup> Based on Sequence IVA wear test using SAE 5W-30

### **MAIN APPLICATIONS**

Pennzoil Platinum<sup>®</sup> 5W-30 with PurePlus<sup>™</sup> Technology is recommended for use in all vehicles requiring the use of SAE 5W-30 viscosity grade engine oils under all driving conditions.

Pennzoil Platinum<sup>®</sup> with PurePlus<sup>™</sup> Technology can be mixed with other synthetic and mineral oils and is recommended for use in all vehicle applications under all driving conditions.

SAE 5W-30 may not be suitable for use in older engines, so always consult your owner's manual for the correct viscosity grade and performance recommendation required for your vehicle.

SAE 5W-30 viscosity grade oils are commonly recommended for use in many new vehicles with modern engine technology for maximum fuel economy and performance.

### **SPECIFICATIONS, APPROVALS & RECOMMENDATIONS**

Meets or exceeds the following OEM requirements:

- Chrysler MS-6395
- Ford WSS-M2C961-A
- GM dexos1<sup>™</sup> Gen 3

Exceeds the requirements of the following industry specifications:

- API SP-Resource Conserving and all previous Categories
- API SP
- ILSAC GF-6A and all previous ILSAC Standards
- GM dexos1<sup>™</sup> Gen 3 (license D325AACJ014)

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Helpdesk.

© SOPUS Products 2021. All rights reserved.

# **PENNZOIL PLATINUM® SAE 5W-30 FULL SYNTHETIC MOTOR OIL MADE FROM NATURAL GAS**

To find the right Pennzoil® product for your vehicles and equipment, please consult [www.pennzoil.com](http://www.pennzoil.com) to look-up the right motor oil recommendation using our oil selector.

## **TYPICAL PHYSICAL CHARACTERISTICS**

<b>Properties</b>	<b>Method</b>	<b>Pennzoil Platinum® SAE 5W-30 Full Synthetic Motor Oil</b>
<b>Viscosity Grade</b>	SAE J300	5W-30
<b>Service Category</b>		SP-RC
<b>ILSAC</b>		GF-6A
<b>ACEA</b>		A1/B1
<b>Density</b> kg/m <sup>3</sup>	ASTM D4052	837
<b>Flash Point</b> °C	ASTM D93	207
<b>Pour Point</b> °C	ASTM D97	-48
<b>Kinematic Viscosity</b> @ 40°C cSt	ASTM D445	53.9
<b>Kinematic Viscosity</b> @ 100°C cSt	ASTM D445	9.8
<b>Viscosity Index</b>	ASTM D2270	170
<b>CCS Viscosity</b> @-30°C cP	ASTM D5293	4 480
<b>MRV Viscosity</b> @-30°C cP	ASTM D4684	10 600

These characteristics are typical of current production. While future production will conform to Pennzoil's® specification, variations in these characteristics may occur.

## **HEALTH, SAFETY & ENVIRONMENT**

### **Health and Safety**

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from <https://www.epc.shell.com>

### **Protect the Environment**

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

## **ADDITIONAL INFORMATION**

### **Advice**

Advice on applications not covered here may be obtained from your Shell or Shell Lubricants distributor representatives or Shell technical helpdesk.