



Shell Helix HX8 5W-30

Maximises performance right up to the next oil change

Shell Helix HX8 is a premium, fully synthetic motor oil scientifically formulated with Shell's ultimate active cleansing technology. It works harder to protect than conventional motor oils by continuously helping to prevent dirt and sludge build-up, for better responsiveness and improved performance, thus helping your engine to operate at its full potential right up to the next oil change.

DESIGNED TO MEET CHALLENGES

Performance, Features & Benefits

■ Engine clean up

Actively and continuously locks away harmful dirt and deposits

■ Long-term oxidation stability

Up to 30% more protection than other fully synthetic leading brands tested

Low viscosity, rapid oil flow and low friction

Greater fuel efficiency and easier cold starting

High shear stability

Maintains viscosity and stays in grade throughout the oil-change interval

Main Applications

 Suitable for modern gasoline engines and diesel passenger car engines without particulate filters.

Typical Physical Characteristics

Properties			Method	Shell Helix HX8
SAE Viscosity Grade				5W-30
Kinematic Viscosity	@40°C	cSt	ASTM D445	68.2
Kinematic Viscosity	@100°C	cSt	ASTM D445	12.2
Density	@15°C	kg/l	ASTM D4052	0.840
Flash Point		°C	ASTM D92	215
Pour Point		°C	ASTM D97	-39
HTHS Viscosity	@150°C	mPaS		3.50

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

Specifications, Approvals & Recommendations

■ API: SL/CF (meets the engine test performance of API SN)

ACEA: A3/B3, A3/B4VW: 502.00/ 505.00

■ Mercedes-Benz: Approval 229.3

Renault: RN0700, 0710

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Help Desk, or the OEM Approvals website.

Health, Safety & Environment

Health and Safety

Shell Helix HX8 is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained from your Shell representative.

■ Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

Additional Information

Advice

Advice on applications not covered here may be obtained from your Shell representative.