Shell Gadus S2 V220 0

Version 3.3	Revision Date 23.10.2022	Print Date 24.10.2022
SECTION 1. PRODUCT AND COMP	ANY IDENTIFICATION	
Product name :	Shell Gadus S2 V220 0	
Product code :	001D8448	
Manufacturer or supplier's det	ails	
Supplier :	Viva Energy Australia Pty Ltd (Formerly: The Shell Company of A (ABN 46 004 610 459) 720 Bourke Street Docklands Victoria 3008 Australia	ustralia)
•	: +61 (0)3 8823 4444 : +61 (0)3 8823 4800	
Emergency telephone number	: 1800 651 818 (Australia). ; POISOI CENTRE: 13 11 26 (Australia).	NS INFORMATION
Recommended use of the che	mical and restrictions on use	
Recommended use :	Automotive and industrial grease.	
SECTION 2. HAZARDS IDENTIFICA	TION	
GHS Classification		
Based on available data this sub	stance / mixture does not meet the cl	assification criteria.

GHS label elements Hazard pictograms	: No Hazard Symbol required
Signal word	: No signal word
Hazard statements	 PHYSICAL HAZARDS: Not classified as a physical hazard under GHS criteria. HEALTH HAZARDS: Not classified as a health hazard under GHS criteria. ENVIRONMENTAL HAZARDS: Not classified as an environmental hazard under GHS criteria.
Precautionary statements	: Prevention: No precautionary phrases.
	Response:

No precautionary phrases.

Storage:

Shell Gadus S2 V220 0

Version 3.3

Revision Date 23.10.2022 No precautionary phrases. Print Date 24.10.2022

Disposal:

No precautionary phrases.

Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.Used grease may contain harmful impurities.High-pressure injection under the skin may cause serious damage including local necrosis.Not classified as flammable but will burn.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture	:	Mixture
Chemical nature	:	A lubricating grease containing highly-refined mineral oils and additives. The highly refined mineral oil contains <3% (w/w) DMSO- extract, according to IP346. Classification based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L).

Chemical name	CAS-No.	Classification	Concentration (% w/w)
Bismuth Naphthenate	85736-59-0	Skin Sens.1B; H317 Eye Irrit.2; H319	0.1 - 0.99
Zinc naphthenate	12001-85-3	Skin Sens.1B; H317 Eye Irrit.2; H319 Aquatic Chronic2; H411	0.1 - 0.99
Naphthenic acid	1338-24-5	Skin Irrit.2; H315 Skin Sens.1; H317 Eye Irrit.2; H319	0.1 - 0.99
Alkyl thiadiazole	13539-13-4	Skin Irrit.2; H315 Skin Sens.1A; H317 Acute Tox.4; H332 Aquatic Chronic4; H413	0 - < 0.09

Hazardous components

For explanation of abbreviations see section 16.

SECTION 4. FIRST-AID MEASURES

If inhaled	: No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
In case of skin contact	: Remove contaminated clothing. Flush exposed area with

Shell Gadus S2 V220 0

Version 3.3	Revision Date 23.10.2022	Print Date 24.10.2022
	water and follow by washing with If persistent irritation occurs, obta	
	When using high pressure equip under the skin can occur. If high casualty should be sent immedia for symptoms to develop. Obtain medical attention even in wounds.	pressure injuries occur, the itely to a hospital. Do not wait
In case of eye contact	: Flush eye with copious quantities Remove contact lenses, if preser rinsing. If persistent irritation occurs, obta	nt and easy to do. Continue
If swallowed	: In general no treatment is necessare swallowed, however, get me	
Most important symptoms and effects, both acute and delayed	: Oil acne/folliculitis signs and sym of black pustules and spots on th Ingestion may result in nausea, w	e skin of exposed areas. /omiting and/or diarrhoea.
	Local necrosis is evidenced by d tissue damage a few hours follow	
Protection of first-aiders	: When administering first aid, ens appropriate personal protective e incident, injury and surroundings	equipment according to the
Notes to physician	: Treat symptomatically.	
	High pressure injection injuries re- intervention and possibly steroid damage and loss of function. Because entry wounds are small seriousness of the underlying da determine the extent of involvem anaesthetics or hot soaks should can contribute to swelling, vasos surgical decompression, debride foreign material should be perfor anaesthetics, and wide exploration	therapy, to minimise tissue and do not reflect the mage, surgical exploration to ent may be necessary. Local be avoided because they pasm and ischaemia. Prompt ment and evacuation of med under general

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	:	Do not use water in a jet.
Specific hazards during firefighting	:	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and

Version 3.3	Revision I	Date 23.10.2022	Print Date 24.10.2022
	occurs.		if incomplete combustion
Specific extinguishing methods		uishing measures that a ices and the surrounding	
Special protective equipment for firefighters	gloves are large conta Breathing a confined	act with spilled product is Apparatus must be worr	esistant suit is indicated if s expected. Self-Contained n when approaching a fire in er's clothing approved to
Hazchem Code	: NONE		
SECTION 6. ACCIDENTAL RELEA	SE MEASUR	ES	
Personal precautions, protective equipment and	: Avoid cont	act with skin and eyes.	
emergency procedures Environmental precautions	contamina		void environmental ading or entering drains, rth, or other appropriate
Methods and materials for containment and cleaning up		om spreading or entering sing sand, earth, or othe	
Additional advice	see Sectio For guidan	n 8 of this Safety Data S	onal protective equipment Sheet. d material see Section 13 of
SECTION 7. HANDLING AND STO	RAGE		
General Precautions		whavet ventilation if the	re is risk of inhalation of

General Precautions	 Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
Advice on safe handling	 Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.

Shell Gadus S2 V220 0

Version 3.3	Revision Date 23.10.2022	Print Date 24.10.2022
Avoidance of contact	: Strong oxidising agents.	
Storage		
Other data	: Keep container tightly closed and place. Use properly labeled and closable	
	Store at ambient temperature.	
Packaging material	: Suitable material: For containers of steel or high density polyethylene. Unsuitable material: PVC.	u
Container Advice	: Polyethylene containers should no temperatures because of possible	

SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m3	AU OEL
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m3	Australia. Workplace Exposure Standards for Airborne Contaminant s.
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m3	OSHA Z-1
Oil mist, mineral	Not Assigned	TWA (Inhalable particulate matter)	5 mg/m3	ACGIH

Components with workplace control parameters

Biological occupational exposure limits

Biological Limit Values (BLV) have not been established for this material.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate. Validated exposure measurement methods should be applied by a competent person and

samples analysed by an accredited laboratory. Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Shell Gadus S2 V220 0

	Devision Date 22.40.2022	Drint Data 24 40 2022
ersion 3.3 Occupational Safety and Healt	Revision Date 23.10.2022 th Administration (OSHA), USA: Sam	Print Date 24.10.2022 pling and Analytical Methods
http://www.osha.gov/		
Health and Safety Executive (I http://www.hse.gov.uk/	HSE), UK: Methods for the Determina	ition of Hazardous Substances
Institut für Arbeitsschutz Deuts	schen Gesetzlichen Unfallversicherun	g (IFA) , Germany
http://www.dguv.de/inhalt/inde	x.jsp ne et de Securité, (INRS), France http	://www.iprs.fr/accueil
		.// www.iiii3.ii/accacii
Engineering measures	: The level of protection and types	of controls necessary will
	vary depending upon potential ex	posure conditions. Select
	controls based on a risk assessm Appropriate measures include:	nent of local circumstances.
	Adequate ventilation to control ai	rborne concentrations.
	Where material is heated, spraye	ed or mist formed, there is
	greater potential for airborne con	
	General Information:	
	Define procedures for safe handl controls.	ing and maintenance of
	Educate and train workers in the	hazards and control
	measures relevant to normal acti	
	product. Ensure appropriate selection, tes	ting and maintenance of
	equipment used to control expos	ure, e.g. personal protective
	equipment, local exhaust ventilat Drain down system prior to equip	
	maintenance.	
	Retain drain downs in sealed stor subsequent recycle.	rage pending disposal or
	Always observe good personal h	ygiene measures, such as
	washing hands after handling the	material and before eating,
	drinking, and/or smoking. Routin protective equipment to remove of	
	contaminated clothing and footwe	
	Practice good housekeeping.	
	Due to the product's semi-solid c	onsistency, generation of
	mists and dusts is unlikely to occ	ur.
Personal protective equipme	ent	
Protective measures		
Personal protective equipmen	t (PPE) should meet recommended n	ational standards. Check with

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Respiratory protection	 No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the

sion 3.3	Revision Date 23.10.2022 Print Date 24.10.202
	specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for the combination of organic gases and vapours and particles [Type A/Type P boiling point >65°((149°F)].
Hand protection	
Remarks	 Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material.
	Glove thickness should be typically greater than 0.35 mm depending on the glove make and model.
Eye protection	: If material is handled such that it could be splashed into eyes protective eyewear is recommended.
Skin and body protection	 Skin protection is not ordinarily required beyond standard work clothes. It is good practice to wear chemical resistant gloves.
Thermal hazards	: Not applicable
Environmental exposure c	controls
General advice	: Take appropriate measures to fulfill the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given i Section 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment pla before discharge to surface water.

Version 3.3		Revision Date 23.10.2022	Print Date 24.10.2022
		Local guidelines on emission limits must be observed for the discharge vapour.	
SECTION 9. PHYSICAL AND CHE	MI	CAL PROPERTIES	
Appearance	:	Semi-solid at ambient temperature	
Colour	:	brown	
Odour	:	Slight hydrocarbon	
Odour Threshold	:	Data not available	
рН	:	Not applicable	
Dropping point	:	>= 180 °C / >= 356 °F Method: Unspecified	
Melting point/freezing point		Data not available	
Initial boiling point and boiling range	:	Data not available	
Flash point	:	Not applicable	
Evaporation rate	:	Data not available	
Flammability (solid, gas)	:	Not applicable	
Flammability (liquids)	:	Not classified as flammable but will	l burn.
Upper explosion limit	:	Typical 10 %(V)	
Lower explosion limit	:	Typical 1 %(V)	
Vapour pressure	:	< 0.5 Pa (20 °C / 68 °F) estimated value(s)	
Relative vapour density	:	> 1estimated value(s)	
Density	:	1,000 kg/m3 (15.0 °C / 59.0 °F) Method: Unspecified	
Solubility(ies)			
Water solubility	:	negligible	
Solubility in other solvents	:	Data not available	
Partition coefficient: n- octanol/water	:	log Pow: > 6 (based on information on similar pr	oducts)
Auto-ignition temperature	:	> 320 °C / 608 °F	
Decomposition temperature	:	Data not available	

Shell Gadus S2 V220 0

Version 3.3	Revision Date 23.10.2022	Print Date 24.10.2022
Viscosity		
Viscosity, dynamic	: Data not available	
Viscosity, kinematic	: Not applicable	
Explosive properties	: Classification Code: Not classified	
Oxidizing properties	: Data not available	
Conductivity	: This material is not expected to be a	a static accumulator.
Particle size	: Data not available	

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.
Chemical stability	: Stable.
Possibility of hazardous reactions	: Reacts with strong oxidising agents.
Conditions to avoid	: Extremes of temperature and direct sunlight.
Incompatible materials	: Strong oxidising agents.
Hazardous decomposition products	: No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Basis for assessment	: Information given is based on data on the components and the toxicology of similar products.Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).
Exposure routes	: Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.
Acute toxicity	
Product:	
Acute oral toxicity	 LD50 rat: > 5,000 mg/kg Remarks: Low toxicity: Based on available data, the classification criteria are not met.
Acute inhalation toxicity	: Remarks: Based on available data, the classification criteria are not met.

Shell Gadus S2 V220 0

Version 3.3	Revision Date 23.10.2022	Print Date 24.10.2022
Acute dermal toxicity :	LD50 Rabbit: > 5,000 mg/kg Remarks: Low toxicity: Based on available data, the classificati	on criteria are not met.

Skin corrosion/irritation

Product:

Remarks: Slightly irritating to skin., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis., Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Product:

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Product:

Remarks: Not a skin sensitiser. Based on available data, the classification criteria are not met.

Components:

Naphthenic acid:

Remarks: May cause an allergic skin reaction in sensitive individuals.

Chronic toxicity

Germ cell mutagenicity

Product:

: Remarks: Non mutagenic, Based on available data, the classification criteria are not met.

Carcinogenicity

Product:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

Remarks: Product contains mineral oils of types shown to be non-carcinogenic in animal skinpainting studies., Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC).

Material	GHS/CLP Carcinogenicity Classification
Highly refined mineral oil	No carcinogenicity classification.

Shell Gadus S2 V220 0

Version 3.3

Revision Date 23.10.2022

Print Date 24.10.2022

Reproductive toxicity

Product:

Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are not met.

STOT - single exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

Aspiration toxicity

Product:

Not an aspiration hazard.

Further information

Product:

Remarks: Used grease may contain harmful impurities that have accumulated during use. The concentration of such harmful impurities will depend on use and they may present risks to health and the environment on disposal., ALL used grease should be handled with caution and skin contact avoided as far as possible.

Remarks: High pressure injection of product into the skin may lead to local necrosis if the product is not surgically removed.

Remarks: Slightly irritating to respiratory system.

SECTION 12. ECOLOGICAL INFORMATION

Basis for assessment :	Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).
------------------------	---

11/16

Version 3.3 Ecotoxicity	Revision Date 23.10.2022	Print Date 24.10.2022
Product:		
Toxicity to fish (Acute	:	
toxicity)	Remarks: LL/EL/IL50 > 100 mg Practically non toxic: Based on available data, the cla	
Toxicity to crustacean (Acute toxicity)	: Remarks: LL/EL/IL50 > 100 mg, Practically non toxic: Based on available data, the cla	
Toxicity to algae/aquatic plants (Acute toxicity)	: Remarks: LL/EL/IL50 > 100 mg, Practically non toxic: Based on available data, the cla	
Toxicity to fish (Chronic toxicity)	: Remarks: Based on available da are not met.	ata, the classification criteria
Toxicity to crustacean (Chronic toxicity)	: Remarks: Based on available da are not met.	ata, the classification criteria
Toxicity to microorganisms (Acute toxicity)	: Remarks: Based on available da are not met.	ata, the classification criteria
Persistence and degradability		
Product:		
Biodegradability	: Remarks: Not readily biodegrad inherently biodegradable, but co persist in the environment.	
Bioaccumulative potential		
Product:		
Bioaccumulation	: Remarks: Contains components bioaccumulate.	s with the potential to
Partition coefficient: n- octanol/water	: log Pow: > 6Remarks: (based o products)	n information on similar
Mobility in soil		
Product:		
Mobility	: Remarks: Semi-solid under mos it enters soil, it will adsorb to soi mobile. Remarks: Floats on water.	
Other adverse effects		
no data available <u>Product:</u>		
12 / 16		800001006651

Version 3.3	Revision Date 23.10.2022	Print Date 24.10.2022
Additional ecological : information	Does not have ozone depletion potentia ozone creation potential or global warm is a mixture of non-volatile components released to air in any significant quantit conditions of use. Poorly soluble mixture., Causes physic organisms. Mineral oil does not cause chronic toxic organisms at concentrations less than	ning potential., Product s, which will not be ies under normal al fouling of aquatic sity to aquatic

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	 Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Do not dispose into the environment, in drains or in water courses Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination. Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.
	MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides technical aspects at controlling pollutions from ships.
Contaminated packaging	: Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.
Local legislation Remarks	 Disposal should be in accordance with applicable regional, national, and local laws and regulations.

SECTION 14. TRANSPORT INFORMATION

National Regulations

Shell Gadus S2 V220 0

Version 3.3 ADG Revision Date 23.10.2022

Print Date 24.10.2022

Not regulated as a dangerous good

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code Not regulated as a dangerous good

Maritime transport in bulk according to IMO instruments

MARPOL Annex 1 rules apply for bulk shipments by sea.

Special precautions for user

Remarks

: Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Standard for the Uniform : No poison schedule number allocated Scheduling of Medicines and Poisons

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Product classified as per Work Health Safety Regulations – Implementation of the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) 2012 and SDS prepared as per national model code of practice for preparation of safety data sheet for Hazardous chemicals 2020 based on Globally Harmonized Classification version 7.

National Model Code of Practice for the Labelling of Workplace Hazardous Chemicals (2011).

Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG code). Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

Other international regulations

The components of this product are reported in the following inventories:

REACH	: Not all components listed.	
TSCA	: All components listed.	
AIIC	: Listed introduction	

SECTION 16. OTHER INFORMATION

Full text of H-Statements

Causes skin irritation.
Causes skin irritatio

Version 3.3	Revision Date 23.10.2022	Print Date 24.10.2022
H317	May cause an allergic skin reaction.	
H319	Causes serious eye irritation.	
H332	Harmful if inhaled.	
H411	Toxic to aquatic life with long lasting effects.	
H413	May cause long lasting harmful effects to aquatic life.	
Full text of other ab	breviations	
Acute Tox.	Acute toxicity	
Aquatic Chronic	Long-term (chronic) aquatic hazard	
Eye Irrit.	Eye irritation	
Skin Irrit.	Skin irritation	
Skin Sens.	Skin sensitisation	

Abbreviations and Acronyms

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC -New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development: OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG -Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Date of preparation or review : 23.10.2022

Further information

Other information

: A vertical bar (|) in the left margin indicates an amendment from the previous version.

Shell Gadus S2 V220 0

Version 3.3Revision Date 23.10.2022Print Date 24.10.2022The information provided in this Safety Data Sheet is correct to the best of our knowledge,
information and belief at the date of its publication. The information given is designed only as a
guidance for safe handling, use, processing, storage, transportation, disposal and release and is
not to be considered a warranty or quality specification. The information relates only to the
specific material designated and may not be valid for such material used in combination with any
other materials or in any process, unless specified in the text.

AU / EN