AeroShell Grease 6

Version 2.3		Revision Date 17.12.2024	Print Date 18.12.2024
SECTION 1. PRODUCT AND CO	MP	ANY IDENTIFICATION	
Product name	:	AeroShell Grease 6	
Product code	:	001A0064	
Manufacturer or supplier's Supplier Telephone Telefax	:	ails Viva Energy Australia Pty Ltd (Formerly: The Shell Company of Aust (ABN 46 004 610 459) 720 Bourke Street Docklands Victoria 3008 Australia : +61 (0)3 8823 4444 : +61 (0)3 8823 4800	ralia)
Emergency telephone number		: 1800 651 818 (Australia). ; POISONS INFORMATION CENTRE	: 13 11 26 (Australia).
Recommended use of the o	cher	nical and restrictions on use	
Recommended use	:	Mineral grease for aircraft., For further AeroShell Book on www.shell.com/avia	
Restrictions on use	:	This product must not be used in appli listed in Section 1 without first seeking supplier.	

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Based on available data this substance / mixture does not meet the classification criteria.

GHS label elements	
Hazard pictograms	: No Hazard Symbol required
Signal word	: No signal word
Hazard statements	 PHYSICAL HAZARDS: Not classified as a physical hazard under GHS criteria. HEALTH HAZARDS: Not classified as a health hazard under GHS criteria. ENVIRONMENTAL HAZARDS: Not classified as an environmental hazard under GHS criteria.

AeroShell Grease 6

Version 2.3	Revision Date 17.12.2024	Print Date 18.12.2024
Precautionary statements	:	
	Prevention:	
	No precautionary phrases.	
	Response:	
	No precautionary phrases.	
	Storage:	
	No precautionary phrases.	
	Disposal:	
	No precautionary phrases.	

Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.Used grease may contain harmful impurities.High-pressure injection under the skin may cause serious damage including local necrosis.Not classified as flammable but will burn.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture	:	Mixture
---------------------	---	---------

3.2 Mixtures

The highly refined mineral oil contains <3% (w/w) DMSO- extract, according to IP346. Classification based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L).	mical nature	extract, according to IP346. Classification based on DMSO extract content < 3%
--	--------------	---

Components

Chemical name	CAS-No.	Classification	Concentration (% w/w)
Disodium sebacate	17265-14-4	Eye Irrit.2; H319	1 - 3
Alkaryl amine	68411-46-1	Repr.2; H361f	1 - 2.9

For explanation of abbreviations see section 16.

SECTION 4. FIRST-AID MEASURES

If inhaled

: No treatment necessary under normal conditions of use.

AeroShell Grease 6

Version 2.3	Revision Date 17.12.2024 Print Date 18.12.2024
In case of skin contact	If symptoms persist, obtain medical advice. Remove contaminated clothing. Flush exposed area with
	water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.
	When using high pressure equipment, injection of product under the skin can occur. If high pressure injuries occur, the casualty should be sent immediately to a hospital. Do not wait for symptoms to develop. Obtain medical attention even in the absence of apparent wounds.
In case of eye contact	 Flush eye with copious quantities of water. Remove contact lenses, if present and easy to do. Continue rinsing. If persistent irritation occurs, obtain medical attention.
If swallowed	: In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.
Most important symptoms and effects, both acute and delayed	: Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea.
	Local necrosis is evidenced by delayed onset of pain and tissue damage a few hours following injection.
	Local necrosis is evidenced by delayed onset of pain and tissue damage a few hours following injection.
Protection of first-aiders	: When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
Notes to physician	: Treat symptomatically.
	High pressure injection injuries require prompt surgical intervention and possibly steroid therapy, to minimise tissue damage and loss of function. Because entry wounds are small and do not reflect the seriousness of the underlying damage, surgical exploration to determine the extent of involvement may be necessary. Local anaesthetics or hot soaks should be avoided because they can contribute to swelling, vasospasm and ischaemia. Prompt surgical decompression, debridement and evacuation of foreign material should be performed under general anaesthetics, and wide exploration is essential.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

AeroShell Grease 6

Version 2.3		Revision Date 17.12.2024	Print Date 18.12.2024
Unsuitable extinguishing media	:	Do not use water in a jet.	
Specific hazards during firefighting	:	Hazardous combustion products may in A complex mixture of airborne solid and gases (smoke). Carbon monoxide may be evolved if in occurs. Unidentified organic and inorganic com	d liquid particulates and complete combustion
Specific extinguishing methods	:	Use extinguishing measures that are a circumstances and the surrounding en-	
Special protective equipment for firefighters	:	Proper protective equipment including gloves are to be worn; chemical resista large contact with spilled product is exp Breathing Apparatus must be worn who a confined space. Select fire fighter's c relevant Standards (e.g. Europe: EN4	Int suit is indicated if Dected. Self-Contained en approaching a fire in lothing approved to
Hazchem Code	:	NONE	
SECTION 6. ACCIDENTAL RELEA	٩S	E MEASURES	
Personal precautions, protective equipment and emergency procedures		Avoid contact with skin and eyes.	
Environmental precautions	:	Use appropriate containment to prever Prevent from spreading or entering dra	

SECTION 7. HANDLING AND STORAGE

Methods and materials for

Additional advice

containment and cleaning up

General Precautions	 Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
Advice on safe handling	: Avoid prolonged or repeated contact with skin.

this Safety Data Sheet.

using sand, earth, or other appropriate barriers.

see Section 8 of this Safety Data Sheet.

: Prevent from spreading or entering into drains, ditches or rivers by using sand, earth, or other appropriate barriers.

: For guidance on selection of personal protective equipment

For guidance on disposal of spilled material see Section 13 of

AeroShell Grease 6

Version 2.3	Revision Date 17.12.2024	Print Date 18.12.2024
	Avoid inhaling vapour and/or mist When handling product in drums, worn and proper handling equipm Properly dispose of any contamin materials in order to prevent fires	safety footwear should be nent should be used. ated rags or cleaning
Avoidance of contact	: Strong oxidising agents.	
Storage		
Other data	: Keep container tightly closed and place. Use properly labeled and closable	
	Store at ambient temperature.	
Packaging material	: Suitable material: For containers steel or high density polyethylene Unsuitable material: PVC.	e .
Container Advice	: Polyethylene containers should n temperatures because of possible	

SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m3	AU OEL
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m3	Australia. Workplace Exposure Standards for Airborne Contaminant s.
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m3	OSHA Z-1
Oil mist, mineral	Not Assigned	TWA (Inhalable particulate matter)	5 mg/m3	ACGIH

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

AeroShell Grease 6

sion 2.3	Revision Date 17.12.2024	Print Date 18.12.20		
Validated exposure measure samples analysed by an ac	rement methods should be applied by a credited laboratory.	competent person and		
Examples of sources of rec	commended exposure measurement me	thods are given below or		
	er national methods may be available.	Manual of Analytical Math		
http://www.cdc.gov/niosh/	ational Safety and Health (NIOSH), USA	. Manual of Analytical Meth		
Occupational Safety and He	ealth Administration (OSHA), USA: Sam	pling and Analytical Method		
http://www.osha.gov/	e (HSE), UK: Methods for the Determina	ation of Hazardous Substan		
http://www.hse.gov.uk/		alion of Hazaruous Substan		
	eutschen Gesetzlichen Unfallversicherur	ng (IFA) , Germany		
http://www.dguv.de/inhalt/ir	ndex.jsp erche et de Securité, (INRS), France http	o://www.inrs.fr/accueil		
Engineering measures	: The level of protection and types	of controls necessary will		
	vary depending upon potential e			
	controls based on a risk assessn Appropriate measures include:	nent of local circumstances		
	Adequate ventilation to control a	irborne concentrations.		
	Where material is heated, spraw	ad ar mist formed there is		
	Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.			
	General Information:			
	Define procedures for safe hand	ling and maintenance of		
	controls. Educate and train workers in the	hazards and control		
	measures relevant to normal act product.			
	Ensure appropriate selection, tes			
	equipment used to control expose equipment, local exhaust ventilat			
	Drain down system prior to equip			
	maintenance.			
	Retain drain downs in sealed sto subsequent recycle.	rage pending disposal or		
	Always observe good personal h	ygiene measures, such as		
	washing hands after handling the			
	drinking, and/or smoking. Routir protective equipment to remove			
	contaminated clothing and footw			
	Practice good housekeeping.			
	Due to the product's semi-solid of			
	mists and dusts is unlikely to occ	cur.		
Personal protective equip	oment			
Protective measures				

Respiratory protection : No respiratory protection is ordinarily required under normal

AeroShell Grease 6

sion 2.3	Revision Date 17.12.2024	Print Date 18.12.2
	conditions of use. In accordance with good industria precautions should be taken to av If engineering controls do not mai concentrations to a level which is health, select respiratory protection specific conditions of use and me Check with respiratory protective Where air-filtering respirators are appropriate combination of mask Select a filter suitable for the com and vapours and particles [Type A (149°F)].	roid breathing of material. ntain airborne adequate to protect work on equipment suitable for eting relevant legislation. equipment suppliers. suitable, select an and filter. bination of organic gases
Hand protection Remarks	: Where hand contact with the proc gloves approved to relevant stand US: F739) made from the followin suitable chemical protection. PVC gloves Suitability and durability of usage, e.g. frequency and duratio resistance of glove material, dexte from glove suppliers. Contaminate replaced. Personal hygiene is a k care. Gloves must only be worn o gloves, hands should be washed Application of a non-perfumed mo	lards (e.g. Europe: EN374 g materials may provide c, neoprene or nitrile rubbo a glove is dependent on n of contact, chemical erity. Always seek advice ed gloves should be ey element of effective ha n clean hands. After using and dried thoroughly.
	For continuous contact we recom breakthrough time of more than 2 for > 480 minutes where suitable short-term/splash protection we re recognize that suitable gloves offer may not be available and in this c time maybe acceptable so long as and replacement regimes are follor a good predictor of glove resistan dependent on the exact composit Glove thickness should be typical depending on the glove make and	40 minutes with preference gloves can be identified. If ecommend the same but ering this level of protection ase a lower breakthrough a appropriate maintenance bwed. Glove thickness is ice to a chemical as it is ion of the glove material. Ily greater than 0.35 mm
Eye protection	: If material is handled such that it of protective eyewear is recommend	
Skin and body protection	: Skin protection is not ordinarily re work clothes. It is good practice to wear chemic	
Thermal hazards	: Not applicable	

Environmental exposure controls

General advice :	Take appropriate measures to fulfill the requirements of
------------------	--

AeroShell Grease 6

Version 2.3	Revision Date 17.12.2024Print Date 18.12.2024relevant environmental protection legislation. Avoid contamination of the environment by following advice given in Section 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant before discharge to surface water. Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing
	vapour.
SECTION 9. PHYSICAL AND CHE	MICAL PROPERTIES
Appearance	: Semi-solid.
Colour	: brown
Odour	: Slight hydrocarbon
Odour Threshold	: Data not available
рН	: Not applicable
Drop point	: >= 300 °C / >= 572 °F Method: ASTM D2265
Melting point/freezing point	Data not available
Initial boiling point and boiling range	: Data not available
Flash point	: 170 °C / 338 °F Method: ASTM D93 (PMCC)
Evaporation rate	: Data not available
Flammability (solid, gas)	: Not applicable
Flammability (liquids)	: Not classified as flammable but will burn.
Upper explosion limit	: Typical 10 %(V)
Lower explosion limit	: Typical 1 %(V)
Vapour pressure	: < 0.5 Pa (20 °C / 68 °F) estimated value(s)
Relative vapour density	: > 1estimated value(s)
Relative density	: 0.943 (15 °C / 59 °F)
Density	: 938 kg/m3 (15.0 °C / 59.0 °F) Method: Unspecified
Solubility(ies)	

Solubility(ies)

AeroShell Grease 6

Version 2.3	Revision Date 17.12.2024	Print Date 18.12.2024
Water solubility	: negligible	
Solubility in other solvents	: Data not available	
Partition coefficient: n- octanol/water	: log Pow: > 6 (based on information on similar proc	ducts)
Auto-ignition temperature	: > 320 °C / 608 °F	
Decomposition temperature	: Data not available	
Viscosity		
Viscosity, dynamic	: Data not available	
Viscosity, kinematic	: 35 mm2/s (40 °C / 104 °F) Method: Unspecified	
	5.5 mm2/s (100 °C / 212 °F) Method: Unspecified	
Particle characteristics Particle size	: Data not available	
Explosive properties	: Classification Code: Not classified	
Oxidizing properties	: Data not available	
Conductivity	: This material is not expected to be a	static accumulator.

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.
Chemical stability	: Stable.
Possibility of hazardous reactions	: Reacts with strong oxidising agents.
Conditions to avoid	: Extremes of temperature and direct sunlight.
Incompatible materials	: Strong oxidising agents.
Hazardous decomposition products	: No decomposition if stored and applied as directed.

AeroShell Grease 6

Version 2.3	Revision Date 17.12.2024	Print Date 18.12.2024
SECTION 11. TOXICOLOGICAL	INFORMATION	
Basis for assessment	: Information given is based on data the toxicology of similar products.U the data presented is representativ whole, rather than for individual con	Jnless indicated otherwise, ve of the product as a
Exposure routes	: Skin and eye contact are the prima although exposure may occur follo	
Acute toxicity		
Product:		
Acute oral toxicity	: LD50 rat: > 5,000 mg/kg Remarks: Low toxicity Based on available data, the classi	ification criteria are not met.
Acute inhalation toxicity	: Remarks: Based on available data are not met.	, the classification criteria
Acute dermal toxicity	: LD50 Rabbit: > 5,000 mg/kg Remarks: Low toxicity Based on available data, the classi	ification criteria are not met.

Skin corrosion/irritation

Product:

Remarks: Slightly irritating to skin., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis., Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Product:

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Product:

Remarks: Not a skin sensitiser. Based on available data, the classification criteria are not met.

Chronic toxicity

Germ cell mutagenicity

Product:

: Remarks: Non mutagenic, Based on available data, the classification criteria are not met.

Carcinogenicity

10/16

AeroShell Grease 6

Version 2.3	Revision Date 17.12.2024	Print Date 18.12.2024
Product:		

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

Remarks: Product contains mineral oils of types shown to be non-carcinogenic in animal skinpainting studies., Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC).

Material	GHS/CLP Carcinogenicity Classification
Highly refined mineral oil	No carcinogenicity classification.

Reproductive toxicity

Product:

Remarks: Based on available data, the classification criteria are not met., Not a developmental toxicant., Does not impair fertility.

STOT - single exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

2

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

Aspiration toxicity

Product:

Not an aspiration hazard.

Further information

Product:

Remarks: Used grease may contain harmful impurities that have accumulated during use. The concentration of such harmful impurities will depend on use and they may present risks to health and the environment on disposal., ALL used grease should be handled with caution and skin contact avoided as far as possible.

Remarks: High pressure injection of product into the skin may lead to local necrosis if the product is not surgically removed.

AeroShell Grease 6

Version 2.3

Revision Date 17.12.2024

Print Date 18.12.2024

Remarks: Slightly irritating to respiratory system.

SECTION 12. ECOLOGICAL INFO	RMATION
Basis for assessment	 Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).
Ecotoxicity	
Product:	
Toxicity to fish (Acute toxicity)	: Remarks: LL/EL/IL50 > 100 mg/l Practically non toxic: Based on available data, the classification criteria are not met
Toxicity to crustacean (Acute toxicity)	: Remarks: LL/EL/IL50 > 100 mg/I Practically non toxic: Based on available data, the classification criteria are not met
Toxicity to algae/aquatic plants (Acute toxicity)	: Remarks: LL/EL/IL50 > 100 mg/I Practically non toxic: Based on available data, the classification criteria are not met
Toxicity to fish (Chronic toxicity)	: Remarks: Based on available data, the classification criteria are not met.
Toxicity to crustacean (Chronic toxicity)	: Remarks: Based on available data, the classification criteria are not met.
Toxicity to microorganisms (Acute toxicity)	: Remarks: Based on available data, the classification criteria are not met.
Persistence and degradability	
Product:	
Biodegradability	: Remarks: Not readily biodegradable., Major constituents are inherently biodegradable, but contains components that may persist in the environment.
Bioaccumulative potential	
Product:	
Bioaccumulation	: Remarks: Contains components with the potential to

AeroShell Grease 6

Version 2.3	Revision Date 17.12.2024	Print Date 18.12.2024
	bioaccumulate.	
Partition coefficient: n- octanol/water	: log Pow: > 6Remarks: (based on i products)	nformation on similar
Mobility in soil		
Product:		
Mobility	 Remarks: Semi-solid under most e it enters soil, it will adsorb to soil p mobile. Remarks: Floats on water. 	
Other adverse effects		
no data available <u>Product:</u>		
Additional ecological information	 Does not have ozone depletion por ozone creation potential or global is a mixture of non-volatile compor released to air in any significant que conditions of use. Poorly soluble mixture., Causes ple organisms. Mineral oil does not cause chronic organisms at concentrations less to 	warming potential., Product nents, which will not be uantities under normal nysical fouling of aquatic toxicity to aquatic

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal	methods
----------	---------

Waste from residues	 Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Do not dispose into the environment, in drains or in water courses. Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination. Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand. MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides tablight on a spitting a pollution provides tablight.
Contaminated packaging	technical aspects at controlling pollutions from ships. : Dispose in accordance with prevailing regulations, preferably

AeroShell Grease 6

Version 2.3	Revision Date 17.12.2024	Print Date 18.12.2024
	to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.	
Local legislation Remarks	: Disposal should be in accordance v national, and local laws and regulat	

SECTION 14. TRANSPORT INFORMATION

National Regulations

ADG

Not regulated as a dangerous good

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Maritime transport in bulk according to IMO instruments

MARPOL Annex 1 rules apply for bulk shipments by sea.

Special precautions for user

Remarks

: Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Therapeutic Goods (Poisons : No poison schedule number allocated Standard) Instrument

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Product classified as per Work Health Safety Regulations – Implementation of the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) 2012 and SDS prepared as per national model code of practice for preparation of safety data sheet for Hazardous chemicals 2020 based on Globally Harmonized Classification version 7.

National Model Code of Practice for the Labelling of Workplace Hazardous Chemicals (2011).

AeroShell Grease 6

Version 2.3Revision Date 17.12.2024Print Date 18.12.2024Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG code). Standard
for the Uniform Scheduling of Medicines and Poisons (SUSMP).Print Date 18.12.2024

Other international regulations

The components of this product are reported in the following inventories:

TSCA AIIC

: All components listed.: Listed introduction

SECTION 16. OTHER INFORMATION

Full text of H-Statements

H319Causes serious eye irritation.H361fSuspected of damaging fertility. (Causing atrophy of the testes)Full text of other abbreviations

Eye Irrit.	Eye irritation
Repr.	Reproductive toxicity

Abbreviations and Acronyms

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil: ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant: DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC -New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance: PICCS - Philippines Inventory of Chemicals and Chemical Substances: (Q)SAR - (Quantitative) Structure Activity Relationship: REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG -Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Date of preparation or review : 17.12.2024

AeroShell Grease 6

Version 2.3	Revision Date 17.12.2024	Print Date 18.12.2024
Further information		
Other information	: A vertical bar () in the left margin indicates an amendment from the previous version.	

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

AU / EN