Shell Turbo Oil T 32

Version 2.9		Revision Date 24.06.2024	Print Date 25.06.2024
SECTION 1. PRODUCT AND C	OMP	ANY IDENTIFICATION	
Product name	:	Shell Turbo Oil T 32	
Product code	:	001A9782	
Manufacturer or supplier's Supplier Telephone Telefax Emergency telephone number	:	ails Viva Energy Australia Pty Ltd (Formerly: The Shell Company of Aust (ABN 46 004 610 459) 720 Bourke Street Docklands Victoria 3008 Australia +61 (0)3 8823 4444 +61 (0)3 8823 4800 1800 651 818 (Australia). ; POISONS INFORMATION CENTRE	
Recommended use of the Recommended use Restrictions on use	cher : :	nical and restrictions on use Turbine oil. This product must not be used in appli listed in Section 1 without first seeking	
		supplier.	

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Based on available data this substance / mixture does not meet the classification criteria.

GHS label elements

Hazard pictograms	:	No Hazard Symbol required
Signal word	:	No signal word
Hazard statements	:	PHYSICAL HAZARDS: Not classified as a physical hazard under GHS criteria. HEALTH HAZARDS: Not classified as a health hazard under GHS criteria. ENVIRONMENTAL HAZARDS: Not classified as an environmental hazard under GHS criteria.

Precautionary statements

:

Shell Turbo Oil T 32

Version 2.9

Revision Date 24.06.2024

Print Date 25.06.2024

Prevention:

No precautionary phrases.

Response: No precautionary phrases.

Storage: No precautionary phrases.

Disposal: No precautionary phrases.

Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.Used oil may contain harmful impurities.Not classified as flammable but will burn.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture	:	Mixture
Chemical nature	:	Highly refined mineral oils and additives. The highly refined mineral oil contains <3% (w/w) DMSO- extract, according to IP346. Classification based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L).
	:	* contains one or more of the following CAS-numbers: 64742- 53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-65-0, 68037-01-4, 72623-86-0, 72623-87-1, 8042-47-5, 848301-69- 9, 68649-12-7, 151006-60-9, 163149-28-8, 64741-88-4, 64741-89-5.

Chemical name	CAS-No.	Classification	Concentration (% w/w)
Interchangeable low viscosity base oil (<20,5 cSt @40°C) *	Not Assigned	Asp. Tox.1; H304	0 - 99
N-phenyl-1- naphthylamine	90-30-2	Acute Tox.4; H302 Skin Sens.1B; H317 STOT RE2; H373 Aquatic Acute1; H400 Aquatic Chronic1; H410	0.1 - 0.24
(4- nonylphenoxy)acetic acid	3115-49-9	Acute Tox.4; H302 Skin Corr.1B; H314 Skin Sens.1A; H317	0 - < 0.099

Hazardous components

Shell Turbo Oil T 32

Version 2.9	Revision Date 24.06.2024	Print Date 25.06.2024
	Aquatic Acute1; H400 Aquatic Chronic1; H410	

For explanation of abbreviations see section 16.

SECTION 4. FIRST-AID MEASURES			
If inhaled	: No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.		
In case of skin contact	 Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention. 		
In case of eye contact	 Flush eye with copious quantities of water. Remove contact lenses, if present and easy to do. Continue rinsing. If persistent irritation occurs, obtain medical attention. 		
If swallowed	: In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.		
Most important symptoms and effects, both acute and delayed	: Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea.		
Protection of first-aiders	: When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.		
Notes to physician	: Treat symptomatically.		

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	: Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	: Do not use water in a jet.
Specific hazards during firefighting	 Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds.
Specific extinguishing	: Use extinguishing measures that are appropriate to local

Shell Turbo Oil T 32

Version 2.9		Revision Date 24.06.2024 Print Date 25.06.2024
methods		circumstances and the surrounding environment.
Special protective equipment for firefighters	:	Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).
Hazchem Code	:	NONE
SECTION 6. ACCIDENTAL RELEA	٩SI	E MEASURES
Personal precautions, protective equipment and emergency procedures	:	Avoid contact with skin and eyes.
Environmental precautions	:	Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.
		Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	:	Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly.
Additional advice	:	For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet. For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

SECTION 7. HANDLING AND STORAGE

General Precautions	: Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal this material.	of
Advice on safe handling	 Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. 	

Shell Turbo Oil T 32

Version 2.9	Revision Date 24.06.2024	Print Date 25.06.2024
Avoidance of contact	: Strong oxidising agents.	
Product Transfer	: Proper grounding and bonding proc during all bulk transfer operations to	
Storage		
Other data	: Keep container tightly closed and in place. Use properly labeled and closable c	·
	Store at ambient temperature.	
Packaging material	: Suitable material: For containers or steel or high density polyethylene. Unsuitable material: PVC.	container linings, use mild
Container Advice	: Polyethylene containers should not temperatures because of possible ri	

SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m3	AU OEL
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m3	Australia. Workplace Exposure Standards for Airborne Contaminant s.
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m3	OSHA Z-1
Oil mist, mineral	Not Assigned	TWA (Inhalable particulate matter)	5 mg/m3	ACGIH

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate. Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Shell Turbo Oil T 32

ersion 2.9	Revision Date 24.06.2024	Print Data 25.06.202
	mmended exposure measurement met	Print Date 25.06.2024 hods are given below or
	national methods may be available.	
	ional Safety and Health (NIOSH), USA:	Manual of Analytical Method
http://www.cdc.gov/niosh/		
	alth Administration (OSHA), USA: Sam	pling and Analytical Methods
http://www.osha.gov/		
http://www.hse.gov.uk/	(HSE), UK: Methods for the Determina	tion of Hazardous Substance
	utschen Gesetzlichen Unfallversicherun	g (IFA) , Germany
http://www.dguv.de/inhalt/inc		
L'Institut National de Recher	che et de Securité, (INRS), France http	://www.inrs.fr/accueil
Engineering measures	: The level of protection and types	of controls necessary will
	vary depending upon potential ex	
	controls based on a risk assessm	
	Appropriate measures include:	
	Adequate ventilation to control ai	rborne concentrations.
	Where material is heated, spraye	d or mist formed, there is
	greater potential for airborne con	centrations to be generated.
	General Information:	
	Define procedures for safe handl	ing and maintenance of
	controls. Educate and train workers in the	bazarda and control
	measures relevant to normal acti	
	product.	
	Ensure appropriate selection, tes	ting and maintenance of
	equipment used to control expos	
	equipment, local exhaust ventilat	
	Drain down system prior to equip	ment break-in or
	maintenance. Retain drain downs in sealed sto	rade pending disposal or
	subsequent recycle.	lage pending disposal of
	Always observe good personal h	voiene measures, such as
	washing hands after handling the	
	drinking, and/or smoking. Routin	
	protective equipment to remove of	
	contaminated clothing and footwe	ear that cannot be cleaned.
	Practice good housekeeping.	
Porconal protoctive occurr	nont	
Personal protective equipr	nent	
Protective measures		
Development of the first state		

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Respiratory protection	 No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker

Shell Turbo Oil T 32

sion 2.9		Date 25.06.202
	health, select respiratory protection equipment specific conditions of use and meeting relevant Check with respiratory protective equipment su Where air-filtering respirators are suitable, select appropriate combination of mask and filter. Select a filter suitable for the combination of org and vapours and particles [Type A/Type P boilin (149°F)].	legislation. ppliers. ct an ganic gases
Hand protection		
Remarks	 Where hand contact with the product may occur gloves approved to relevant standards (e.g. Eur US: F739) made from the following materials m suitable chemical protection. PVC, neoprene or gloves Suitability and durability of a glove is depusage, e.g. frequency and duration of contact, or resistance of glove material, dexterity. Always s from glove suppliers. Contaminated gloves sho replaced. Personal hygiene is a key element of care. Gloves must only be worn on clean hands gloves, hands should be washed and dried thor Application of a non-perfumed moisturizer is reader. For continuous contact we recommend gloves with for > 480 minutes where suitable gloves can be short-term/splash protection we recommend the recognize that suitable gloves offering this level may not be available and in this case a lower by time maybe accentable so long as appropriate. 	rope: EN374, ay provide initrile rubber bendent on chemical seek advice uld be effective hand s. After using roughly. commended. with th preference identified. Fo a same but of protection reakthrough
Eye protection	 time maybe acceptable so long as appropriate and replacement regimes are followed. Glove the a good predictor of glove resistance to a chemic dependent on the exact composition of the glove Glove thickness should be typically greater than depending on the glove make and model. If material is handled such that it could be splase 	hickness is no cal as it is re material. n 0.35 mm
	protective eyewear is recommended.	
Skin and body protection	 Skin protection is not ordinarily required beyond work clothes. It is good practice to wear chemical resistant global 	
Thermal hazards	: Not applicable	
Environmental exposure of	controls	
General advice	: Take appropriate measures to fulfill the requirer relevant environmental protection legislation. A contamination of the environment by following a Section 6. If necessary, prevent undissolved m being discharged to waste water. Waste water treated in a municipal or industrial waste water	void advice given in aterial from should be

Shell Turbo Oil T 32

Version 2.9	Revision Date 24.06.2024	Print Date 25.06.2024
		water. I limits for volatile substances scharge of exhaust air containing
SECTION 9. PHYSICAL AND CHE	MICAL PROPERTIES	
Appearance	: Liquid at room temperature.	
Colour	: Colourless to pale amber	
Odour	: Data not available	
Odour Threshold	: Data not available	
рН	: Not applicable	
pour point	: <= -22 °C / -8 °F Method: ISO 3016	
Melting / freezing point	Data not available	
pour point	<= -33 °C / <= -27 °F Method: ASTM D97	
Initial boiling point and boiling range	: > 280 °C / 536 °Festimated v	value(s)
Flash point	: >= 215 °C / 419 °F Method: ISO 2592	
Evaporation rate	: Data not available	
Flammability (solid, gas)	: Not applicable	
Flammability (liquids)	: Not classified as flammable	but will burn.
Upper explosion limit	: Typical 10 %(V)	
Lower explosion limit	: Typical 1 %(V)	
Vapour pressure	: < 0.5 Pa (20 °C / 68 °F) estimated value(s)	
Relative vapour density	: >5	
Relative density	: 0.840 (15 °C / 59 °F)	
Density	: 840 kg/m3 (15.0 °C / 59.0 °F Method: ISO 12185	·)
	840 kg/m3 (15.0 °C / 59.0 °F Method: ASTM D4052	.)

Shell Turbo Oil T 32

Version 2.9	Revision Date 24.06.2024	Print Date 25.06.2024
Solubility(ies)		
Water solubility	: negligible	
Solubility in other solvents	: Data not available	
Partition coefficient: n- octanol/water	: log Pow: > 6 (based on information on similar produ	cts)
Auto-ignition temperature	: > 320 °C / 608 °F	
Decomposition temperature	: Data not available	
Viscosity		
Viscosity, dynamic	: Data not available	
Viscosity, kinematic	: 32 mm2/s (40.0 °C / 104.0 °F) Method: ISO 3104	
	5.45 mm2/s (100 °C / 212 °F) Method: ISO 3104	
Particle characteristics		
Particle size	: Data not available	
Explosive properties	: Classification Code: Not classified	
Oxidizing properties	: Data not available	
Conductivity	: This material is not expected to be a st	atic accumulator.

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.
Chemical stability	: Stable.
Possibility of hazardous reactions	: Reacts with strong oxidising agents.
Conditions to avoid	: Extremes of temperature and direct sunlight.
Incompatible materials	: Strong oxidising agents.
Hazardous decomposition products	: No decomposition if stored and applied as directed.

Shell Turbo Oil T 32

Version 2.9	Revision Date 24.06.2024	Print Date 25.06.2024			
SECTION 11. TOXICOLOGICA	SECTION 11. TOXICOLOGICAL INFORMATION				
Basis for assessment	: Information given is based on data the toxicology of similar products.U the data presented is representativ whole, rather than for individual cor	Inless indicated otherwise, re of the product as a			
Exposure routes	: Skin and eye contact are the prima although exposure may occur follow				
Acute toxicity					
Product:					
Acute oral toxicity	: LD50 rat: > 5,000 mg/kg Remarks: Low toxicity Based on available data, the classi	fication criteria are not met.			
Acute inhalation toxicity	: Remarks: Based on available data, are not met.	, the classification criteria			
Acute dermal toxicity	: LD50 Rabbit: > 5,000 mg/kg Remarks: Low toxicity Based on available data, the classi	fication criteria are not met.			

Skin corrosion/irritation

Product:

Remarks: Slightly irritating to skin., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis., Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Product:

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Product:

Remarks: Not a skin sensitiser. Based on available data, the classification criteria are not met.

Components:

N-phenyl-1-naphthylamine:

Remarks: May cause an allergic skin reaction in sensitive individuals.

(4-nonylphenoxy)acetic acid:

Remarks: May cause an allergic skin reaction in sensitive individuals.

Shell Turbo Oil T 32

Version 2.9	Revision Date 24.06.2024	Print Date 25.06.2024
Chronic toxicity		
Germ cell mutagenicity		
Product:		

: Remarks: Non mutagenic, Based on available data, the classification criteria are not met.

Carcinogenicity

Product:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

Remarks: Product contains mineral oils of types shown to be non-carcinogenic in animal skinpainting studies., Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC).

Material	GHS/CLP Carcinogenicity Classification
Highly refined mineral oil	No carcinogenicity classification.

Reproductive toxicity

Product:

Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are not met.

STOT - single exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

1

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

Aspiration toxicity

Product:

Not an aspiration hazard.

Further information

Product:

11 / 17

Shell Turbo Oil T 32

Version 2.9

Revision Date 24.06.2024

Print Date 25.06.2024

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Slightly irritating to respiratory system.

SECTION 12. ECOLOGICAL INFORMATION

Basis for assessment	 Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).
Ecotoxicity	
Product:	
Toxicity to fish (Acute toxicity)	: Remarks: Based on available data, the classification criteria are not met. Practically non toxic: LL/EL/IL50 > 100 mg/I
Toxicity to crustacean (Acute toxicity)	: Remarks: Based on available data, the classification criteria are not met. Practically non toxic: LL/EL/IL50 > 100 mg/I
Toxicity to algae/aquatic plants (Acute toxicity)	: Remarks: Based on available data, the classification criteria are not met. Practically non toxic: LL/EL/IL50 > 100 mg/I
Toxicity to fish (Chronic toxicity)	: Remarks: Based on available data, the classification criteria are not met.
Toxicity to crustacean (Chronic toxicity)	: Remarks: Based on available data, the classification criteria are not met.
Toxicity to microorganisms (Acute toxicity)	: Remarks: Based on available data, the classification criteria are not met.
<u>Components:</u> N-phenyl-1-naphthylamine :	
M-Factor (Short-term (acute)	: 1

Shell Turbo Oil T 32

Version 2.9		Revision Date 24.06.2024	Print Date 25.06.2024
aquatic hazard) M-Factor (Long-term (chronic) aquatic hazard) (4-nonylphenoxy)acetic acid	-	1	
M-Factor (Short-term (acute) aquatic hazard)	:	1	
Persistence and degradability			
Product:			
Biodegradability	:	Remarks: Not readily biodegradable., M inherently biodegradable, but contains of persist in the environment., Persistent p International Oil Pollution Compensation definition: "A non-persistent oil is oil, wh shipment, consists of hydrocarbon fract of which, by volume, distills at a temper and (b) at least 95% of which, by volum temperature of 370°C (700°F) when tess Method D-86/78 or any subsequent rev	components that may ber IMO criteria., n (IOPC) Fund hich, at the time of tions, (a) at least 50% rature of 340°C (645°F) he, distils at a sted by the ASTM
Bioaccumulative potential			
Product:			
Bioaccumulation	:	Remarks: Contains components with the bioaccumulate.	e potential to
Partition coefficient: n- octanol/water	:	log Pow: > 6Remarks: (based on inform products)	nation on similar
Mobility in soil			
Product:			
Mobility	:	Remarks: Liquid under most environme enters soil, it will adsorb to soil particles mobile. Remarks: Floats on water.	
Other adverse effects			
no data available <u>Product:</u>			
Additional ecological information	:	Does not have ozone depletion potentia ozone creation potential or global warm is a mixture of non-volatile components released to air in any significant quantit conditions of use. Poorly soluble mixture., Causes physica organisms. Mineral oil does not cause chronic toxic organisms at concentrations less than a	ing potential., Product , which will not be ies under normal al fouling of aquatic sity to aquatic

SECTION 13. DISPOSAL CONSIDERATIONS

Shell Turbo Oil T 32

Version 2.9	Revision Date 24.06.2024	Print Date 25.06.2024	
Disposal methods			
Waste from residues	toxicity and physical properties of determine the proper waste class methods in compliance with appli Waste product should not be allo ground water, or be disposed of i Do not dispose into the environm courses. Do not dispose of tank water bott drain into the ground. This will res contamination. Waste arising from a spillage or to disposed of in accordance with po preferably to a recognised collect	 It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Do not dispose into the environment, in drains or in water courses. Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination. Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be 	
	MARPOL - see International Con Pollution from Ships (MARPOL 7 technical aspects at controlling po	3/78) which provides	
Contaminated packaging	: Dispose in accordance with preva to a recognized collector or contra the collector or contractor should Disposal should be in accordance national, and local laws and regu	actor. The competence of be established beforehand.	
Local legislation Remarks	: Disposal should be in accordance national, and local laws and regu		

SECTION 14. TRANSPORT INFORMATION

National Regulations

ADG

Not regulated as a dangerous good

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Maritime transport in bulk according to IMO instruments

MARPOL Annex 1 rules apply for bulk shipments by sea.

Special precautions for user

14 / 17

Shell Turbo Oil T 32

Version 2.9	Revision Date 24.06.2024	Print Date 25.06.2024
Remarks	 Special Precautions: Refer to Sectio for special precautions which a user needs to comply with in connection v 	needs to be aware of or

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Therapeutic Goods (Poisons : No poison schedule number allocated Standard) Instrument

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Product classified as per Work Health Safety Regulations – Implementation of the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) 2012 and SDS prepared as per national model code of practice for preparation of safety data sheet for Hazardous chemicals 2020 based on Globally Harmonized Classification version 7.

National Model Code of Practice for the Labelling of Workplace Hazardous Chemicals (2011).

Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG code). Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

Other international regulations

The components of this product are reported in the following inventories:

TSCA	:	All components listed.
AIIC	:	Listed introduction

SECTION 16. OTHER INFORMATION

Full text of H-Statements

Harmful if swallowed.			
May be fatal if swallowed and enters airways.			
Causes severe skin burns and eye damage.			
May cause an allergic skin reaction.			
May cause damage to organs through prolonged or repeated exposure if swallowed.			
Very toxic to aquatic life.			
Very toxic to aquatic life with long lasting effects.			
Full text of other abbreviations			
Acute toxicity			
Short-term (acute) aquatic hazard			
Long-term (chronic) aquatic hazard			
Aspiration hazard			
Skin corrosion			
Skin sensitisation			
Specific target organ toxicity - repeated exposure			

Shell Turbo Oil T 32

Version 2.9

Revision Date 24.06.2024

Print Date 25.06.2024

Abbreviations and Acronyms

AIIC - Australian Inventory of Industrial Chemicals: ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC -New Zealand Inventory of Chemicals: OECD - Organization for Economic Co-operation and Development: OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG -Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Date of preparation or review : 24.06.2024

Further information

Training advice	:	Provide adequate information, instruction and training for operators.
Other information	:	A vertical bar () in the left margin indicates an amendment from the previous version.
Sources of key data used to compile the Safety Data Sheet	:	The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is

Shell Turbo Oil T 32

Version 2.9

Revision Date 24.06.2024

Print Date 25.06.2024

not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

AU / EN