

# SAFETY DATA SHEET.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Spirax S4 CX 30

Version	Revision Date.:	SDS Number:	Print Date.:
3.0	03/03/2026	800001004983	03/04/2026
			Date of last issue: 10/29/2025
			Date of first issue: 03/03/2026

---

### SECTION 1. IDENTIFICATION

Product name : Shell Spirax S4 CX 30  
Product code : 001D8250

#### Manufacturer or supplier's details

Manufacturer/Supplier : **Shell Oil Products US**  
PO Box 4427  
Houston TX 77210-4427  
USA

SDS Request : (+1) 877-276-7285  
Customer Service :

#### Emergency telephone number

Spill Information : 877-242-7400  
Health Information : 877-504-9351

#### Recommended use of the chemical and restrictions on use

Recommended use : Transmission oil.

Restrictions on use :  
This product must not be used in applications other than those listed in Section 1 without first seeking the advice of the supplier.

---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Based on available data this substance / mixture does not meet the classification criteria.

#### GHS label elements

Hazard pictograms : No Hazard Symbol required

Signal word : No signal word

Hazard statements : **PHYSICAL HAZARDS:**  
Not classified as a physical hazard under GHS criteria.  
**HEALTH HAZARDS:**  
Not classified as a health hazard under GHS criteria.  
**ENVIRONMENTAL HAZARDS:**

# SAFETY DATA SHEET.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Spirax S4 CX 30

Version 3.0      Revision Date.: 03/03/2026      SDS Number: 800001004983      Print Date.: 03/04/2026  
Date of last issue: 10/29/2025  
Date of first issue: 03/03/2026

Not classified as an environmental hazard under GHS criteria.

Precautionary statements : **Prevention:**  
No precautionary phrases.  
**Response:**  
No precautionary phrases.  
**Storage:**  
No precautionary phrases.  
**Disposal:**  
No precautionary phrases.

### Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.  
Used oil may contain harmful impurities.  
Not classified as flammable but will burn.

The classification of this material is based on OSHA HCS 2024 criteria.

Under normal conditions of use or in a foreseeable emergency, this product does not meet the definition of a hazardous chemical when evaluated according to the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture  
Chemical nature : Highly refined mineral oils and additives.  
The highly refined mineral oil contains <3% (w/w) DMSO-extract, according to IP346.  
Classification based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L).  
\* contains one or more of the following CAS-numbers: 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-65-0, 68037-01-4, 72623-86-0, 72623-87-1, 8042-47-5, 848301-69-9, 68649-12-7, 151006-60-9, 163149-28-8, 64741-88-4, 64741-89-5.

### Components

Chemical name	Synonym	CAS-No.	Concentration (% w/w)
Interchangeable low viscosity base oil (<20,5 cSt @40°C) *	No data available	Not Assigned	0 - 99
Overbased sulphurised calcium phenate	Phenol, dodecyl-, sulfurized, carbonates, calci-	68784-26-9	0 - 3

# SAFETY DATA SHEET.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Spirax S4 CX 30

Version  
3.0

Revision Date.:  
03/03/2026

SDS Number:  
800001004983

Print Date.: 03/04/2026  
Date of last issue: 10/29/2025  
Date of first issue: 03/03/2026

	um salts, over-based		
Zinc dialkyldithiophosphate	Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	68649-42-3	0 - 2.4
Zinc dialkyldithiophosphate	zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)	4259-15-8	0 - 2.4
Alkylphenol	dodecylphenol	27193-86-8	0.1 - 0.24

### SECTION 4. FIRST-AID MEASURES

- In case of skin contact : Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.
- In case of eye contact : Flush eye with copious quantities of water. Remove contact lenses, if present and easy to do. Continue rinsing. If persistent irritation occurs, obtain medical attention.
- If swallowed : In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.
- Most important symptoms and effects, both acute and delayed : Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhea.
- Protection of first-aiders : When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
- Notes to physician : Treat symptomatically.

### SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
- Unsuitable extinguishing media : Do not use water in a jet.
- Specific hazards during fire-fighting : Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds.
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

# SAFETY DATA SHEET.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Spirax S4 CX 30

Version	Revision Date.:	SDS Number:	Print Date.:
3.0	03/03/2026	800001004983	03/04/2026
			Date of last issue: 10/29/2025
			Date of first issue: 03/03/2026

---

Special protective equipment for firefighters : Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Avoid contact with skin and eyes.

Environmental precautions : Use appropriate containment to prevent uncontrolled release. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.

Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly.

Additional advice : For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet. For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

---

### SECTION 7. HANDLING AND STORAGE

Technical measures : Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

Advice on safe handling : Avoid prolonged or repeated contact with skin.

---

# SAFETY DATA SHEET.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Spirax S4 CX 30

Version	Revision Date.:	SDS Number:	Print Date.:
3.0	03/03/2026	800001004983	03/04/2026
			Date of last issue: 10/29/2025
			Date of first issue: 03/03/2026

Avoid inhaling vapour and/or mists.  
When handling product in drums, safety footwear should be worn and proper handling equipment should be used.  
Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.

Avoidance of contact : Strong oxidising agents.  
Product Transfer : Proper grounding and bonding procedures should be used during all bulk transfer operations to avoid static accumulation.

Further information on storage stability : Keep container tightly closed and in a cool, well-ventilated place.  
Use properly labeled and closable containers.  
Store at ambient temperature.

Packaging material : Suitable material: For containers or container linings, use mild steel or high density polyethylene.  
Unsuitable material: PVC.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m <sup>3</sup>	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m <sup>3</sup>	ACGIH

#### Biological occupational exposure limits

No biological limit allocated.

#### Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods <http://www.cdc.gov/niosh/>

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods <http://www.osha.gov/>

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances <http://www.hse.gov.uk/>

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany <http://www.dguv.de/inhalt/index.jsp>

L'Institut National de Recherche et de Sécurité, (INRS), France <http://www.inrs.fr/accueil>

# SAFETY DATA SHEET.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Spirax S4 CX 30

Version  
3.0

Revision Date.:  
03/03/2026

SDS Number:  
800001004983

Print Date.: 03/04/2026  
Date of last issue: 10/29/2025  
Date of first issue: 03/03/2026

**Engineering measures** : The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:  
Adequate ventilation to control airborne concentrations.  
Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.  
General Information  
Define procedures for safe handling and maintenance of controls.  
Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.  
Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.  
Drain down system prior to equipment break-in or maintenance.  
Retain drain downs in sealed storage pending disposal or subsequent recycle.  
Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned.  
Practice good housekeeping.

### Personal protective equipment

Respiratory protection : No respiratory protection is ordinarily required under normal conditions of use.  
In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material.  
If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation.  
Check with respiratory protective equipment suppliers.  
Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.  
Select a filter suitable for the combination of organic gases and vapours and particles [Type A/Type P boiling point >65°C (149°F)].

Hand protection

Remarks : Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide

# SAFETY DATA SHEET.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Spirax S4 CX 30

Version  
3.0

Revision Date.:  
03/03/2026

SDS Number:  
800001004983

Print Date.: 03/04/2026  
Date of last issue: 10/29/2025  
Date of first issue: 03/03/2026

suitable chemical protection. PVC, neoprene or nitrile rubber gloves Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model.

- Eye protection : If material is handled such that it could be splashed into eyes, protective eyewear is recommended.
- Skin and body protection : Skin protection is not ordinarily required beyond standard work clothes.  
It is good practice to wear chemical resistant gloves.
- Protective measures : Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.
- Thermal hazards : Not applicable

### Environmental exposure controls

- General advice : Take appropriate measures to fulfill the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in Section 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant before discharge to surface water.  
Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.

---

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

# SAFETY DATA SHEET.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Spirax S4 CX 30

Version	Revision Date.:	SDS Number:	Print Date.:
3.0	03/03/2026	800001004983	03/04/2026
			Date of last issue: 10/29/2025
			Date of first issue: 03/03/2026

---

Physical state	:	Liquid at room temperature.
Colour	:	amber
Odour	:	Data not available
Odour Threshold	:	Data not available
Pour point	:	-30 °C Method: ISO 3016
Melting / freezing point	:	Data not available
Initial boiling point and boiling range	:	> 280 °C estimated value(s)
Flammability (solid, gas)	:	Not applicable
Flammability (liquids)	:	Not classified as flammable but will burn.
Upper explosion limit / Upper flammability limit	:	Typical 10 %(V)
Lower explosion limit / Lower flammability limit	:	Typical 1 %(V)
Flash point	:	205 °C Method: ISO 2592
Auto-ignition temperature	:	> 320 °C
Decomposition temperature	:	Data not available
pH	:	Not applicable
Viscosity	:	
Viscosity, dynamic	:	Data not available
Viscosity, kinematic	:	93.9 mm <sup>2</sup> /s (40.0 °C) Method: ISO 3104
	:	10.9 mm <sup>2</sup> /s (100 °C) Method: ISO 3104
Solubility(ies)	:	
Water solubility	:	negligible
Solubility in other solvents	:	Data not available

# SAFETY DATA SHEET.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Spirax S4 CX 30

Version	Revision Date.:	SDS Number:	Print Date.:
3.0	03/03/2026	800001004983	03/04/2026
			Date of last issue: 10/29/2025
			Date of first issue: 03/03/2026

---

Partition coefficient: n-octanol/water	:	log Pow: > 6 (based on information on similar products)
Vapour pressure	:	< 0.5 Pa (20 °C) estimated value(s)
Relative density	:	0.899 (15 °C)
Density	:	899 kg/m <sup>3</sup> (15.0 °C) Method: ISO 12185
Particle characteristics Particle size	:	Data not available

### 9.2 Other information

Explosives	:	Classification Code: Not classified
Oxidizing properties	:	Data not available
Evaporation rate	:	Data not available
Conductivity	:	This material is not expected to be a static accumulator.

---

## SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.
Chemical stability	:	Stable.
Possibility of hazardous reactions	:	Reacts with strong oxidising agents.
Conditions to avoid	:	Extremes of temperature and direct sunlight.
Incompatible materials	:	Strong oxidising agents.
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

---

## SECTION 11. TOXICOLOGICAL INFORMATION

Basis for assessment	:	Information given is based on data on the components and the toxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).
----------------------	---	--

# SAFETY DATA SHEET.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Spirax S4 CX 30

Version  
3.0

Revision Date.:  
03/03/2026

SDS Number:  
800001004983

Print Date.: 03/04/2026  
Date of last issue: 10/29/2025  
Date of first issue: 03/03/2026

---

### Information on likely routes of exposure

Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

### Acute toxicity

#### Product:

Acute oral toxicity : LD50 (rat): > 5,000 mg/kg  
Remarks: Low toxicity  
Based on available data, the classification criteria are not met.

Acute inhalation toxicity : Remarks: Based on available data, the classification criteria are not met.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg  
Remarks: Low toxicity  
Based on available data, the classification criteria are not met.

### Skin corrosion/irritation

#### Product:

Remarks : Slightly irritating to skin.  
Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.  
Based on available data, the classification criteria are not met.

### Serious eye damage/eye irritation

#### Product:

Remarks : Slightly irritating to the eye.  
Based on available data, the classification criteria are not met.

### Components:

#### **Zinc dialkyldithiophosphate:**

Remarks : Based on available data, the classification criteria are not met.

#### **Zinc dialkyldithiophosphate:**

Remarks : Based on available data, the classification criteria are not met.

# SAFETY DATA SHEET.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Spirax S4 CX 30

Version  
3.0

Revision Date.:  
03/03/2026

SDS Number:  
800001004983

Print Date.: 03/04/2026  
Date of last issue: 10/29/2025  
Date of first issue: 03/03/2026

---

### Respiratory or skin sensitisation

**Product:**

Remarks : Not a skin sensitiser.  
Based on available data, the classification criteria are not met.

### Germ cell mutagenicity

**Product:**

Genotoxicity in vivo : Remarks: Non mutagenic  
Based on available data, the classification criteria are not met.

### Carcinogenicity

**Product:**

Remarks : Not a carcinogen.  
Based on available data, the classification criteria are not met.

Remarks : Product contains mineral oils of types shown to be non-carcinogenic in animal skin-painting studies.  
Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC).

**IARC** No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA** No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP** No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

### Reproductive toxicity

Remarks : Not a developmental toxicant.  
Does not impair fertility.  
Based on available data, the classification criteria are not met.

### STOT - single exposure

**Product:**

Remarks : Based on available data, the classification criteria are not met.

### STOT - repeated exposure

**Product:**

Remarks : Based on available data, the classification criteria are not met.

# SAFETY DATA SHEET.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Spirax S4 CX 30

Version	Revision Date.:	SDS Number:	Print Date.:
3.0	03/03/2026	800001004983	03/04/2026
			Date of last issue: 10/29/2025
			Date of first issue: 03/03/2026

---

### Aspiration toxicity

**Product:**

Not an aspiration hazard.

### Further information

**Product:**

Remarks : Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal.  
ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks : Slightly irritating to respiratory system.

---

## SECTION 12. ECOLOGICAL INFORMATION

Basis for assessment : Ecotoxicological data have not been determined specifically for this product.  
Information given is based on a knowledge of the components and the ecotoxicology of similar products.  
Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

### Ecotoxicity

**Product:**

Toxicity to fish : Remarks: Based on available data, the classification criteria are not met.  
Practically non toxic:  
LL/EL/IL50 > 100 mg/l

Toxicity to daphnia and other aquatic invertebrates : Remarks: Based on available data, the classification criteria are not met.  
Practically non toxic:  
LL/EL/IL50 > 100 mg/l

Toxicity to algae/aquatic plants : Remarks: Based on available data, the classification criteria are not met.  
Practically non toxic:  
LL/EL/IL50 > 100 mg/l

Toxicity to fish (Chronic tox- : Remarks: Based on available data, the classification criteria

---

# SAFETY DATA SHEET.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Spirax S4 CX 30

Version	Revision Date.:	SDS Number:	Print Date.:
3.0	03/03/2026	800001004983	03/04/2026
			Date of last issue: 10/29/2025
			Date of first issue: 03/03/2026

---

icity) are not met.

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : Remarks: Based on available data, the classification criteria are not met.

Toxicity to microorganisms : Remarks: Based on available data, the classification criteria are not met.

### **Components:**

#### **Alkylphenol:**

M-Factor (Acute aquatic toxicity) : 10

M-Factor (Chronic aquatic toxicity) : 10

#### **Persistence and degradability**

No data available

#### **Bioaccumulative potential**

#### **Product:**

Bioaccumulation : Remarks: Contains components with the potential to bioaccumulate.

#### **Mobility in soil**

#### **Product:**

Mobility : Remarks: Liquid under most environmental conditions. If it enters soil, it will adsorb to soil particles and will not be mobile.

Remarks: Floats on water.

#### **Other adverse effects**

#### **Product:**

Additional ecological information : Does not have ozone depletion potential, photochemical ozone creation potential or global warming potential. Product is a mixture of non-volatile components, which will not be released to air in any significant quantities under normal conditions of use.

Poorly soluble mixture.  
Causes physical fouling of aquatic organisms.

Mineral oil does not cause chronic toxicity to aquatic organisms at concentrations less than 1 mg/l.

# SAFETY DATA SHEET.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Spirax S4 CX 30

Version	Revision Date.:	SDS Number:	Print Date.: 03/04/2026
3.0	03/03/2026	800001004983	Date of last issue: 10/29/2025
			Date of first issue: 03/03/2026

---

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

- Waste from residues : Recover or recycle if possible.  
It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.  
Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment.  
Do not dispose into the environment, in drains or in water courses.  
Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination.  
Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.  
MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides technical aspects at controlling pollutions from ships.
- Contaminated packaging : Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand.  
Disposal should be in accordance with applicable regional, national, and local laws and regulations.
- Local legislation  
Remarks : Disposal should be in accordance with applicable regional, national, and local laws and regulations.
- 

### SECTION 14. TRANSPORT INFORMATION

#### National Regulations

##### 49 CFR

Not regulated as a dangerous good

#### International Regulations

##### IATA-DGR

Not regulated as a dangerous good

##### IMDG-Code

Not regulated as a dangerous good

#### Maritime transport in bulk according to IMO instruments

---

# SAFETY DATA SHEET.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Spirax S4 CX 30

Version	Revision Date.:	SDS Number:	Print Date.:
3.0	03/03/2026	800001004983	03/04/2026
			Date of last issue: 10/29/2025
			Date of first issue: 03/03/2026

---

MARPOL Annex 1 rules apply for bulk shipments by sea.

### Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

---

## SECTION 15. REGULATORY INFORMATION

### Safety, health and environmental regulations/legislation specific for the substance or mixture

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

### CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

### CERCLA Reportable Quantity

Shell classifies this material as an "oil" under the CERCLA Petroleum Exclusion, therefore releases to the environment are not reportable under CERCLA.

### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : No SARA Hazards

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

Zinc dialkyldithiophosphate	68649-42-3	>= 1 - < 5 %
Zinc dialkyldithiophosphate	4259-15-8	>= 1 - < 5 %

### Clean Water Act

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

# SAFETY DATA SHEET.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Spirax S4 CX 30

Version	Revision Date.:	SDS Number:	Print Date.:
3.0	03/03/2026	800001004983	03/04/2026
			Date of last issue: 10/29/2025
			Date of first issue: 03/03/2026

---

### US State Regulations

#### Massachusetts Right To Know

No components are subject to the Massachusetts Right to Know Act.

#### Pennsylvania Right To Know

Distillates (petroleum), solvent-dewaxed light paraffinic;	64742-56-9
Baseoil — unspecified	
Zinc dialkyldithiophosphate	68649-42-3
Zinc dialkyldithiophosphate	4259-15-8
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0
Distillates (petroleum), hydrotreated light	64742-47-8

#### California Prop. 65

WARNING: This product can expose you to chemicals including 2-ethylhexyl acrylate, which is/are known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

#### California List of Hazardous Substances

Distillates (petroleum), solvent-dewaxed light paraffinic;	64742-56-9
Baseoil — unspecified	
Zinc dialkyldithiophosphate	68649-42-3
Zinc dialkyldithiophosphate	4259-15-8

#### The components of this product are reported in the following inventories:

US TSCA : All components listed.

CA. DSL : All components listed.

---

## SECTION 16. OTHER INFORMATION

### Further information

NFPA Rating (Health, Fire, Reactivity) 0, 1, 0

### Full text of other abbreviations

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA	: 8-hour, time-weighted average
OSHA Z-1 / TWA	: 8-hour time weighted average

# SAFETY DATA SHEET.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## Shell Spirax S4 CX 30

Version	Revision Date.:	SDS Number:	Print Date.: 03/04/2026
3.0	03/03/2026	800001004983	Date of last issue: 10/29/2025
			Date of first issue: 03/03/2026

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

A vertical bar (|) in the left margin indicates an amendment from the previous version.

**|| There has been a significant change in California Prop. 65 in section 15**

Sources of key data used to compile the Safety Data Sheet : The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).

Revision Date. : 03/03/2026

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

# **SAFETY DATA SHEET.**

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## **Shell Spirax S4 CX 30**

Version  
3.0

Revision Date.:  
03/03/2026

SDS Number:  
800001004983

Print Date.: 03/04/2026  
Date of last issue: 10/29/2025  
Date of first issue: 03/03/2026

---

US / EN