According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Quaker State Euro 5W-40 Synthetic Motor Oil

| Version | Revision Date: | SDS Number: | Print Date: 05/14/2024 |
|---------|----------------|--------------|--------------------------------|
| 1.3 | 05/13/2024 | 800010033685 | Date of last issue: 10/21/2020 |
| | | | |

SECTION 1. IDENTIFICATION

Product name : Quaker State Euro 5W-40 Synthetic Motor Oil

Product code : 001H1067

| Manufacturer/Supplier | : Shell Oil Products US PO Box 4427 Houston TX 77210-4427 USA |
|---------------------------------|--|
| SDS Request Customer Service | : (+1) 877-276-7285 |
| | • |

Emergency telephone number

| Spill Information | : | 877-242-7400 |
|--------------------|---|--------------|
| Health Information | : | 877-504-9351 |

Recommended use of the chemical and restrictions on use

| Recommended use | : | Engine oil. |
|-----------------------|---|--|
| Restrictions on use : | | This product must not be used in applications other than those listed in Section 1 without first seeking the advice of the supplier. |

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Based on available data this substance / mixture does not meet the classification criteria.

| Precautionary statements | Prevention: | |
|---|--|--|
| Hazard statements | PHYSICAL HAZARDS: Not classified as a physical hazard under GHS criteria. HEALTH HAZARDS: Not classified as a health hazard under GHS criteria. ENVIRONMENTAL HAZARDS: Not classified as an environmental hazard under GHS criteria. | |
| Signal word | : No signal word | |
| GHS label elements Hazard pictograms | : No Hazard Symbol required | |

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Quaker State Euro 5W-40 Synthetic Motor Oil

Version Revision Date: 1.3 05/13/2024

SDS Number: 800010033685

Print Date: 05/14/2024 Date of last issue: 10/21/2020

No precautionary phrases.

Response:

No precautionary phrases.

Storage:

No precautionary phrases.

Disposal:

No precautionary phrases.

Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

Used oil may contain harmful impurities.

Not classified as flammable but will burn.

The classification of this material is based on OSHA HCS 2012 criteria.

Under normal conditions of use or in a foreseeable emergency, this product does not meet the definition of a hazardous chemical when evaluated according to the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

| Substance / Mixture | : | Mixture |
|---------------------|---|--|
| Chemical nature | : | Synthetic base oil and additives. Highly refined mineral oil. The highly refined mineral oil contains <3% (w/w) DMSO- extract, according to IP346. The highly refined mineral oil is only present as additive dilu- ent. Classification based on DMSO extract content < 3% (Regula- tion (EC) 1272/2008, Annex VI, Part 3, Note L). |

Hazardous components

| Chemical name | Synonyms | CAS-No. | Concentration (% w/w) |
|--|----------------------------------|-------------|-----------------------|
| Distillates (Fischer - | Distillates (Fischer- | 848301-69-9 | 70 - 90 |
| Tropsch), heavy, C18-50 – branched, | Tropsch), | | |
| cyclic and linear | heavy, C18-50- | | |
| | branched, cy- clic and linear | | |
| Alkaryl amine | bis(nonylphenyl | 36878-20-3 | 1 - 3 |
| Aikai yi amille |)amine | 50070-20-5 | 1- 5 |

SECTION 4. FIRST-AID MEASURES

| In case of skin contact | : | Remove contaminated clothing. Flush exposed area with wa- ter and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention. |
|-------------------------|---|--|
| In case of eye contact | : | Flush eye with copious quantities of water. |

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Quaker State Euro 5W-40 Synthetic Motor Oil

| Versio 1.3 | n Revision Date: 05/13/2024 | | DS Number: 00010033685 | Print Date: 05/14/2024 Date of last issue: 10/21/2020 |
|---------------|---|---|---------------------------|--|
| | | | rinsing. | enses, if present and easy to do. Continue on occurs, obtain medical attention. |
| If swallowed | | : | 0 | tment is necessary unless large quantities owever, get medical advice. |
| a | lost important symptoms nd effects, both acute and elayed | : | of black pustules | s signs and symptoms may include formation and spots on the skin of exposed areas. ult in nausea, vomiting and/or diarrhoea. |
| Ρ | rotection of first-aiders | : | | ng first aid, ensure that you are wearing the nal protective equipment according to the d surroundings. |
| m | ndication of any immediate nedical attention and special eatment needed | : | Treat symptomati | cally. |

SECTION 5. FIRE-FIGHTING MEASURES

| Suitable extinguishing media : | : | Foam, water spray or fog. Dry chemical powder, carbon diox- ide, sand or earth may be used for small fires only. |
|--|---|---|
| Unsuitable extinguishing : media | : | Do not use water in a jet. |
| Specific hazards during fire- : fighting | : | Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds. |
| Specific extinguishing meth- : ods | : | Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment. |
| Special protective equipment : for firefighters | : | Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469). |

SECTION 6. ACCIDENTAL RELEASE MEASURES

| Personal precautions, protec- tive equipment and emer- gency procedures | : | Avoid contact with skin and eyes. |
|---|---|--|
| Environmental precautions | : | Use appropriate containment to avoid environmental contami- nation. Prevent from spreading or entering drains, ditches or |

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

| Versio 1.3 | on | Revision Date: 05/13/2024 | | 9S Number: 0010033685 | Print Date: 05/14/2024 Date of last issue: 10/21/2020 |
|---------------------------------|----------|---|---|--|---|
| | | | | rivers by using sa | nd, earth, or other appropriate barriers. |
| | | | | Local authorities s cannot be contain | should be advised if significant spillages ed. |
| | | s and materials for ment and cleaning up | : | Prevent from spre or other containm Reclaim liquid dire Soak up residue v | It. Avoid accidents, clean up immediately. ading by making a barrier with sand, earth ent material. ectly or in an absorbent. vith an absorbent such as clay, sand or other and dispose of properly. |
| Д | Additior | nal advice | : | see Section 8 of the | election of personal protective equipment his Safety Data Sheet. lisposal of spilled material see Section 13 of theet. |
| SECTION 7. HANDLING AND STORAGE | | | | | |
| Т | Fechnic | al measures | : | vapours, mists or Use the information sessment of local | ventilation if there is risk of inhalation of aerosols. on in this data sheet as input to a risk as- circumstances to help determine appropri- fe handling, storage and disposal of this |
| ۵ | Advice | on safe handling | : | Avoid inhaling vap When handling pr worn and proper h | oduct in drums, safety footwear should be nandling equipment should be used. of any contaminated rags or cleaning mate- |

| Avoidance of contact | : | Strong oxidising agents. |
|---|---|--|
| Product Transfer | : | Proper grounding and bonding procedures should be used during all bulk transfer operations to avoid static accumulation. |
| Further information on stor- age stability | : | Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closable containers. |
| | | Store at ambient temperature. |
| Packaging material | : | Suitable material: For containers or container linings, use mild steel or high density polyethylene. Unsuitable material: PVC. |
| Container Advice | : | Polyethylene containers should not be exposed to high tem- peratures because of possible risk of distortion. |

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Quaker State Euro 5W-40 Synthetic Motor Oil

| Version | Revision Date: | SDS Number: | |
|---------|----------------|--------------|---|
| 1.3 | 05/13/2024 | 800010033685 | I |

Print Date: 05/14/2024 Date of last issue: 10/21/2020

SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parame- ters / Permissible concentration | Basis |
|-------------------|--------------|-------------------------------------|--|----------|
| Oil mist, mineral | Not Assigned | TWA (Mist) | 5 mg/m3 | OSHA Z-1 |
| Oil mist, mineral | | TWA (Inhal- | 5 mg/m3 | ACGIH |
| | | able particu- | - | |
| | | late matter) | | |

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

| Engineering measures : | The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate ventilation to control airborne concentrations. |
|------------------------|---|
| | Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated. |
| | General Information: Define procedures for safe handling and maintenance of controls. Educate and train workers in the hazards and control measures relevant to normal activities associated with this product. Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation. Drain down system prior to equipment break-in or mainte- |

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

| Version | Revision Date: | SDS Number: | Print Date: 05/14/2024 |
|---------|----------------|--------------|--------------------------------|
| 1.3 | 05/13/2024 | 800010033685 | Date of last issue: 10/21/2020 |

| | nance. Retain drain downs in sealed storage pending disposal or subsequent recycle. Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard con- taminated clothing and footwear that cannot be cleaned. Practice good housekeeping. |
|-------------------------------|---|
| Personal protective equipment | |
| Respiratory protection : | No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for the combination of organic gases and vapours and particles [Type A/Type P boiling point >65°C (149°F)]. |
| Hand protection Remarks : | Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended. For continuous contact we recommend gloves with break-through time of more than 240 minutes with preference for > 480 minutes where suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. |
| Eye protection : | If material is handled such that it could be splashed into eyes, |

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

| protective eyewear is recommended. Skin and body protection : Skin protection is not ordinarily required beyond standard work clothes. It is good practice to wear chemical resistant gloves. Protective measures : Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers. Thermal hazards : Not applicable Environmental exposure controls : Take appropriate measures to fulfill the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in Section 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant before discharge to surface water. Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour. SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES | Version 1.3 | Revision Date: 05/13/2024 | SDS Number: 800010033685 | Print Date: 05/14/2024 Date of last issue: 10/21/2020 | | |
|---|----------------|------------------------------|--|---|--|--|
| work clothes. It is good practice to wear chemical resistant gloves. Protective measures : Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers. Thermal hazards : Not applicable Environmental exposure controls General advice : Take appropriate measures to fulfill the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in Section 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant before discharge to surface water. Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour. | | | protective eye | wear is recommended. | | |
| mended national standards. Check with PPE suppliers. Thermal hazards : Not applicable Environmental exposure controls General advice : Take appropriate measures to fulfill the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in Section 6. If necessary, prevent undissolved material from being discharge to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant before discharge to surface water. Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour. | Skin a | Skin and body protection | | work clothes. | | |
| Environmental exposure controls General advice : Take appropriate measures to fulfill the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in Section 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant before discharge to surface water. Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour. | Prote | ctive measures | | | | |
| General advice : Take appropriate measures to fulfill the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in Section 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant before discharge to surface water. Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour. | Therr | nal hazards | : Not applicable | | | |
| vant environmental protection legislation. Avoid contamination of the environment by following advice given in Section 6. If necessary, prevent undissolved material from being dis- charged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant before discharge to surface water. Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour. | Envir | ronmental exposure of | controls | | | |
| SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES | Gene | ral advice | vant environm of the environm necessary, pre charged to wa municipal or in discharge to s Local guideline must be obser | ental protection legislation. Avoid contamination ment by following advice given in Section 6. If event undissolved material from being dis- ste water. Waste water should be treated in a ndustrial waste water treatment plant before urface water. es on emission limits for volatile substances | | |
| | SECTION | 9. PHYSICAL AND C | HEMICAL PROPER | TIES | | |

| Appearance | : | Clear, bright liquid. |
|---|---|---|
| Colour | : | Pale amber |
| Odour | : | Data not available |
| Odour Threshold | : | Data not available |
| рН | : | Not applicable |
| pour point | : | -36 °C / -33 °F Method: ASTM D97 |
| Melting / freezing point | | Data not available |
| Initial boiling point and boiling range | : | > 280 °C / 536 °F estimated value(s) |
| Flash point | : | 235 °C / 455 °F |
| | | Method: ASTM D92 (COC) 211 °C / 412 °F |
| | | Method: ASTM D93 (PMCC) |
| Evaporation rate | : | Data not available |
| Flammability | | |

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

| Versic 1.3 | on Revision Date: 05/13/2024 | | S Number: 0010033685 | Print Date: 05/14/2024 Date of last issue: 10/21/2020 |
|---------------|---|---|-----------------------------------|--|
| | Flammability (solid, gas) | : | Not applicable | |
| | Flammability (liquids) | : | Not classified as | flammable but will burn. |
| L | ower explosion limit and upp Upper explosion limit / up- per flammability limit | | | nmability limit |
| | Lower explosion limit / Lower flammability limit | : | Typical 1 %(V) | |
| V | apour pressure | : | < 0.5 Pa (20 °C / | 68 °F) |
| | | | estimated value(s | 5) |
| F | elative vapour density | : | > 5 | |
| F | elative density | : | 0.843 (15.0 °C / 5 | 59.0 °F) |
| C | Density | : | 843 kg/m3 (15.0 Method: ASTM D | |
| S | olubility(ies) Water solubility | : | negligible | |
| | Solubility in other solvents | : | Data not available | e |
| | Partition coefficient: n- ctanol/water | : | log Pow: > 6 (based on inform | ation on similar products) |
| А | uto-ignition temperature | : | > 320 °C / 608 °F | : |
| C | ecomposition temperature | : | Data not availabl | e |
| V | ′iscosity Viscosity, dynamic | : | Data not availabl | e |
| | Viscosity, kinematic | : | 12.8 mm2/s (100 | °C / 212 °F) |
| | | | Method: ASTM D | 9445 |
| | | | 75.7 mm2/s (40.0 |) °C / 104.0 °F) |
| | | | Method: ASTM D | 0445 |
| E | xplosive properties | : | Classification Co | de: Not classified |
| C | Dxidizing properties | : | Data not available | e |
| C | Conductivity | : | This material is n | ot expected to be a static accumulator. |
| F | Particle size | : | Data not availabl | e |
| | | | | |

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Quaker State Euro 5W-40 Synthetic Motor Oil

| Version | Revision Date: | SDS Number: | Print Date: 05/14/2024 |
|---------|----------------|--------------|--------------------------------|
| 1.3 | 05/13/2024 | 800010033685 | Date of last issue: 10/21/2020 |

SECTION 10. STABILITY AND REACTIVITY

| Reactivity | : | The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph. |
|---|---|--|
| Chemical stability | : | Stable. |
| Possibility of hazardous reac- tions | : | Reacts with strong oxidising agents. |
| Conditions to avoid | : | Extremes of temperature and direct sunlight. |
| Incompatible materials | : | Strong oxidising agents. |
| Hazardous decomposition products | : | No decomposition if stored and applied as directed. |

SECTION 11. TOXICOLOGICAL INFORMATION

| Basis for assessment | : | Information given is based on data on the components and |
|----------------------|---|--|
| | | the toxicology of similar products.Unless indicated otherwise, |
| | | the data presented is representative of the product as a |
| | | whole, rather than for individual component(s). |

Information on likely routes of exposure

Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

Acute toxicity

Product:

| Acute oral toxicity | LD50 (rat): > 5,000 mg/kg Remarks: Low toxicity Based on available data, the classification criteria are not met. |
|---------------------------|---|
| Acute inhalation toxicity | Remarks: Based on available data, the classification criteria are not met. |
| Acute dermal toxicity | LD50 (Rabbit): > 5,000 mg/kg Remarks: Low toxicity Based on available data, the classification criteria are not met. |

Skin corrosion/irritation

Product:

Remarks: Slightly irritating to skin., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis., Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Product:

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Quaker State Euro 5W-40 Synthetic Motor Oil

| Version | Revision Date: |
|---------|----------------|
| 1.3 | 05/13/2024 |

SDS Number: 800010033685

Print Date: 05/14/2024 Date of last issue: 10/21/2020

met.

Respiratory or skin sensitisation

Product:

Remarks: Not a skin sensitiser. Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Product:

Genotoxicity in vivo : Remarks: Non mutagenic, Based on available data, the classification criteria are not met.

Carcinogenicity

Product:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

| IARC | No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC. |
|------|---|
| OSHA | No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens. |
| NTP | No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP. |

Reproductive toxicity

Product:

Effects on fertility

Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are not met.

STOT - single exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Quaker State Euro 5W-40 Synthetic Motor Oil

Version Re 1.3 05,

Revision Date: 05/13/2024

SDS Number: 800010033685

Print Date: 05/14/2024 Date of last issue: 10/21/2020

Aspiration toxicity

Product:

Not an aspiration hazard.

Further information

Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Continuous contact with used engine oils has caused skin cancer in animal tests.

Remarks: Slightly irritating to respiratory system.

SECTION 12. ECOLOGICAL INFORMATION

| Basis for assessment | : | Ecotoxicological data have not been determined specificall for this product. Information given is based on a knowledge of the compone and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is represen tive of the product as a whole, rather than for individual cor ponent(s). | |
|--|---|---|--|
| Ecotoxicity | | | |
| <u>Product:</u> Toxicity to fish (Acute toxici- ty) | : | Remarks: Based on available data, the classification criteria are not met. Practically non toxic: LL/EL/IL50 > 100 mg/l | |
| Toxicity to daphnia and other aquatic invertebrates (Acute toxicity) | : | Remarks: Based on available data, the classification criteria are not met. Practically non toxic: LL/EL/IL50 > 100 mg/l | |
| Toxicity to algae (Acute tox- icity) | : | Remarks: Based on available data, the classification criteria are not met. Practically non toxic: LL/EL/IL50 > 100 mg/l | |
| Toxicity to fish (Chronic tox- icity) | : | Remarks: Based on available data, the classification criteria are not met. | |

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

| Vers 1.3 | ion | Revision Date: 05/13/2024 | | DS Number: 0010033685 | Print Date: 05/14/2024 Date of last issue: 10/21/2020 |
|-------------|------------------------------|--|-----|--|---|
| | | v to daphnia and other invertebrates (Chron- ty) | : | Remarks: Based of are not met. | on available data, the classification criteria |
| | | v to microorganisms toxicity) | : | Remarks: Based are not met. | on available data, the classification criteria |
| | Persist | ence and degradabil | ity | | |
| | Produc Biodeg | <u>et:</u> radability | : | Major constituents components that in Persistent per IM0 International Oil P tion: "A non-persist consists of hydroo by volume, distills at least 95% of wh | Pollution Compensation (IOPC) Fund defini- stent oil is oil, which, at the time of shipment, carbon fractions, (a) at least 50% of which, at a temperature of 340°C (645°F) and (b) hich, by volume, distils at a temperature of en tested by the ASTM Method D-86/78 or |
| | Bioacc | umulative potential | | | |
| | Produc Bioaccu | <u>et:</u> umulation | : | Remarks: Contair cumulate. | as components with the potential to bioac- |
| | Mobilit | y in soil | | | |
| | Produc Mobility | | : | | under most environmental conditions. vill adsorb to soil particles and will not be on water. |
| | Other a | adverse effects | | | |
| | Produc Addition mation | <u>et:</u> nal ecological infor- | : | ozone creation po Product is a mixtu be released to air conditions of use. Poorly soluble mix | |

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Quaker State Euro 5W-40 Synthetic Motor Oil

| Version | Revision Date: | SDS Number: |
|---------|----------------|--------------|
| 1.3 | 05/13/2024 | 800010033685 |

Print Date: 05/14/2024 Date of last issue: 10/21/2020

SECTION 13. DISPOSAL CONSIDERATIONS

| Disposal methods | | |
|------------------------------|--|---|
| Waste from residues | ity and physica rmine the prop in compliance of te product show nd water, or be ot dispose into ses. to dispose of ta mination. te arising from an of in accorda recognised col | if possible. ty of the waste generator to determine the al properties of the material generated to er waste classification and disposal meth- with applicable regulations. uld not be allowed to contaminate soil or e disposed of into the environment. the environment, in drains or in water ank water bottoms by allowing them to ad. This will result in soil and groundwater a spillage or tank cleaning should be dis- ance with prevailing regulations, preferably lector or contractor. The competence of the tor should be established beforehand. |
| | ition from Ship | ernational Convention for the Prevention of s (MARPOL 73/78) which provides tech- ntrolling pollutions from ships. |
| Contaminated packaging | recognized col collector or con osal should be | nce with prevailing regulations, preferably lector or contractor. The competence of tractor should be established beforehand. in accordance with applicable regional, laws and regulations. |
| Local legislation Remarks | | in accordance with applicable regional, laws and regulations. |

SECTION 14. TRANSPORT INFORMATION

National Regulations

US Department of Transportation Classification (49 CFR Parts 171-180)

Not regulated as a dangerous good

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Maritime transport in bulk according to IMO instruments

MARPOL Annex 1 rules apply for bulk shipments by sea.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Quaker State Euro 5W-40 Synthetic Motor Oil

| Version | Revision Date: | SDS Number: | Print Date: 05/14/2024 |
|---------|----------------|--------------|--------------------------------|
| 1.3 | 05/13/2024 | 800010033685 | Date of last issue: 10/21/2020 |

Special precautions for user

Remarks

: Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

| Components | CAS-No. | Component RQ | Calculated product RQ |
|---------------|----------|--------------|-----------------------|
| | | (lbs) | (lbs) |
| Cyclohexane | 110-82-7 | 1000 | * |
| vinyl acetate | 108-05-4 | 5000 | * |

*: Calculated RQ exceeds reasonably attainable upper limit.

Calculated RQ exceeds reasonably attainable upper limit., Shell classifies this material as an "oil" under the CERCLA Petroleum Exclusion, therefore releases to the environment are not reportable under CERCLA., The components with RQs are given for information.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

| : | No SARA Hazards | | | |
|---|---|--|--|--|
| : | The following components are subject to reporting levels es- tablished by SARA Title III, Section 313: | | | |
| | Zinc dialkyldithiophos- phate | 28629-66-5 | >= 0.1 - < 1 % | |
| | Zinc dialkyldithiophos- phate | 113706-15-3 | >= 0.1 - < 1 % | |
| | | The following components tablished by SARA Title III Zinc dialkyldithiophos- phate Zinc dialkyldithiophos- | The following components are subject to reportablished by SARA Title III, Section 313: Zinc dialkyldithiophos-28629-66-5 phate Zinc dialkyldithiophos-113706-15-3 | |

Clean Water Act

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3: Cyclohexane 110-82-7 0.0024 %

| Cyclohexane | 110-82-7 | 0.0024 % |
|---------------|----------|----------|
| vinyl acetate | 108-05-4 | 0.0002 % |

US State Regulations

Pennsylvania Right To Know

| Zinc dialkyldithiophosphate2Zinc dialkyldithiophosphate1Diphenylamine1 |
|--|
|--|

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Quaker State Euro 5W-40 Synthetic Motor Oil

| Version | Revision Date: | SDS Number: | Print Date: 05/14/2024 |
|---------|----------------|--------------|--------------------------------|
| 1.3 | 05/13/2024 | 800010033685 | Date of last issue: 10/21/2020 |

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

| The components of this product are reported in the following inventories: | | | |
|---|--------------------------|--|--|
| TSCA | : All components listed. | | |
| DSL | : All components listed. | | |

SECTION 16. OTHER INFORMATION

Further information

NFPA Rating (Health, Fire, Reac- 0, 1, 0 tivity)

Full text of other abbreviations

| ACGIH OSHA Z-1 ACGIH / TWA OSHA Z-1 / TWA Abbreviations and Acronyms | | USA. ACGIH Threshold Limit Values (TLV) USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim- its for Air Contaminants 8-hour, time-weighted average 8-hour time weighted average The standard abbreviations and acronyms used in this docu- ment can be looked up in reference literature (e.g. scientific dictionaries) and/or websites. |
|--|--|--|
| | | ACGIH = American Conference of Governmental Industrial Hygienists ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road AICS = Australian Inventory of Chemical Substances ASTM = American Society for Testing and Materials BEL = Biological exposure limits BTEX = Benzene, Toluene, Ethylbenzene, Xylenes CAS = Chemical Abstracts Service CEFIC = European Chemical Industry Council CLP = Classification Packaging and Labelling COC = Cleveland Open-Cup DIN = Deutsches Institut fur Normung DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level DSL = Canada Domestic Substance List EC = European Commission EC50 = Effective Concentration fifty ECETOC = European Center on Ecotoxicology and Toxicolo- gy Of Chemicals |

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

| Version 1.3 | Revision Date: 05/13/2024 | SDS Number: 800010033685 | Print Date: 05/14/2024 Date of last issue: 10/21/2020 |
|----------------|------------------------------|---|---|
| | | EINECS = The Chemical Subs EL50 = Effectiv ENCS = Japan Inventory EWC = Europe GHS = Globally Labelling of Ch IARC = Interna IATA = Interna IC50 = Inhibitor IMDG = Interna INV = Chinese IP346 = Institu determination of KECI = Korea LC50 = Lethal LD50 = Lethal LD50 = Lethal LL/EL/IL = Leth LL50 = Lethal IL/EL/IL = Leth DS0 = Lethal INV = Oci PBT = Persiste PICCS = Philip Substances PNEC = Predic REACH = Reg Chemicals RID = Regulati gerous Goods SKIN_DES = S STEL = Short t TRA = Targete TSCA = US To TWA = Time-W | ve Loading fifty ese Existing and New Chemical Substances an Waste Code y Harmonised System of Classification and emicals tional Agency for Research on Cancer tional Air Transport Association ry Concentration fifty y Level fifty ational Maritime Dangerous Goods Chemicals Inventory the of Petroleum test method N° 346 for the of polycyclic aromatics DMSO-extractables Existing Chemicals Inventory Concentration fifty Dose fifty per cent. hal Loading/Effective Loading/Inhibitory loading Loading fifty ernational Convention for the Prevention of Ships No Observed Effect Concentration / No Ob- evel cupational Exposure - High Production Volume ent, Bioaccumulative and Toxic pine Inventory of Chemicals and Chemical eted No Effect Concentration istration Evaluation And Authorisation Of ons Relating to International Carriage of Dan- |
| A ver | tical bar () in the left ma | argin indicates an am | endment from the previous version. |
| Sourc | ces of key data used to | : The quoted dat | ta are from, but not limited to, one or more |

| Sources of key data used to compile the Safety Data Sheet | : | The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc). |
|---|---|--|
| Revision Date | : | 05/13/2024 |

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Quaker State Euro 5W-40 Synthetic Motor Oil

| Version | Revision Date: | SDS Number: | Print D |
|---------|----------------|--------------|---------|
| 1.3 | 05/13/2024 | 800010033685 | Date of |

Print Date: 05/14/2024 Date of last issue: 10/21/2020

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN