

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AeroShell Fluid 41 (EU)

Version	Revision Date.:	SDS Number:	Date of last issue: 04.07.2024
1.5	10.09.2025	800010059915	Print Date. 16.04.2026

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name	:	AeroShell Fluid 41 (EU)
Product code	:	007A0188
Unique Formula Identifier	:	11C3-S07N-200N-SAVR

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture	:	Mineral hydraulic fluid for aircraft., For further details consult the AeroShell Book on <a href="http://www.shell.com/aviation">www.shell.com/aviation</a> .
Uses advised against	:	This product must be used, handled, and applied in accordance with the requirements of the equipment manufacturer's manuals, bulletins and other documentation. This product must not be used in applications other than those listed in Section 1 without first seeking the advice of the supplier. This product must not be used for combustion or carburization.

#### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier	:	<b>Shell UK Oil Products Limited</b> Shell Centre London SE1 7NA United Kingdom
Telephone	:	(+44) 08007318888
Telefax	:	
Contact for Safety Data Sheet	:	If you have any enquiries about the content of this SDS please email <a href="mailto:lubricantSDS@shell.com">lubricantSDS@shell.com</a>

#### 1.4 Emergency telephone number

: +44 (0) 20 7934 7778 (This telephone number is available 24 hours per day, 7 days per week)

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AeroShell Fluid 41 (EU)

Version 1.5      Revision Date.: 10.09.2025      SDS Number: 800010059915      Date of last issue: 04.07.2024  
Print Date. 16.04.2026

---

### SECTION 2: Hazards identification


#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Aspiration hazard, Category 1      H304: May be fatal if swallowed and enters airways.  
Long-term (chronic) aquatic hazard, Category 3      H412: Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms : 

Signal word : Danger

Hazard statements :  
PHYSICAL HAZARDS:  
Not classified as a physical hazard according to CLP criteria.  
HEALTH HAZARDS:  
H304 May be fatal if swallowed and enters airways.  
ENVIRONMENTAL HAZARDS:  
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**  
P273 Avoid release to the environment.  
**Response:**  
P331 Do NOT induce vomiting.  
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
**Storage:**  
P405 Store locked up.  
**Disposal:**  
P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label:  
Contains Hydrocarbons, C12-C18, isoalkanes, cyclics, 2-30% aromatics

#### 2.3 Other hazards

This mixture does not contain any REACH registered substances that are assessed to be a PBT or a vPvB.

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AeroShell Fluid 41 (EU)

Version 1.5      Revision Date.: 10.09.2025      SDS Number: 800010059915      Date of last issue: 04.07.2024  
Print Date. 16.04.2026

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.  
Used oil may contain harmful impurities.  
High-pressure injection under the skin may cause serious damage including local necrosis.  
Not classified as flammable but will burn.

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

Chemical nature : Blend of petroleum distillates and additives.

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Hydrocarbons, C12-C18, isoalkanes, cyclics, 2-30% aromatics	Not Assigned 954-225-2 01-2120920648-49	Asp. Tox. 1; H304	80 - 90
Petroleum distillate	Not Assigned 934-954-2 01-2119826592-36	Asp. Tox. 1; H304	1 - 10
Butylated hydroxytoluene	128-37-0 204-881-4 01-2119565113-46	Aquatic Chronic 1; H410 Aquatic Acute 1; H400  M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	0.25 - 0.9

For explanation of abbreviations see section 16.

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AeroShell Fluid 41 (EU)

Version 1.5      Revision Date.: 10.09.2025      SDS Number: 800010059915      Date of last issue: 04.07.2024  
Print Date. 16.04.2026

---

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- Protection of first-aiders : When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
- If inhaled : No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
- In case of skin contact : Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.
- When using high pressure equipment, injection of product under the skin can occur. If high pressure injuries occur, the casualty should be sent immediately to a hospital. Do not wait for symptoms to develop. Obtain medical attention even in the absence of apparent wounds.
- In case of eye contact : Flush eye with copious quantities of water. Remove contact lenses, if present and easy to do. Continue rinsing. If persistent irritation occurs, obtain medical attention.
- If swallowed : Call emergency number for your location / facility. If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever. The onset of respiratory symptoms may be delayed for several hours after exposure. Defatting dermatitis signs and symptoms may include a burning sensation and/or a dried/cracked appearance. Ingestion may result in nausea, vomiting and/or diarrhoea.
- Local necrosis is evidenced by delayed onset of pain and tissue damage a few hours following injection.

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AeroShell Fluid 41 (EU)

Version 1.5      Revision Date.: 10.09.2025      SDS Number: 800010059915      Date of last issue: 04.07.2024  
Print Date. 16.04.2026

---

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Potential for chemical pneumonitis.  
Call a doctor or poison control center for guidance.  
High pressure injection injuries require prompt surgical intervention and possibly steroid therapy, to minimise tissue damage and loss of function.  
Because entry wounds are small and do not reflect the seriousness of the underlying damage, surgical exploration to determine the extent of involvement may be necessary. Local anaesthetics or hot soaks should be avoided because they can contribute to swelling, vasospasm and ischaemia. Prompt surgical decompression, debridement and evacuation of foreign material should be performed under general anaesthetics, and wide exploration is essential.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media : Do not use water in a jet.

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Hazardous combustion products may include:  
A complex mixture of airborne solid and liquid particulates and gases (smoke).  
Carbon monoxide may be evolved if incomplete combustion occurs.  
Unidentified organic and inorganic compounds.

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AeroShell Fluid 41 (EU)

Version	Revision Date.:	SDS Number:	Date of last issue: 04.07.2024
1.5	10.09.2025	800010059915	Print Date. 16.04.2026

---

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

- Personal precautions : 6.1.1 For non emergency personnel:  
Avoid contact with skin and eyes.  
6.1.2 For emergency responders:  
Avoid contact with skin and eyes.

#### 6.2 Environmental precautions

- Environmental precautions : Use appropriate containment to prevent uncontrolled release.  
Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.

#### 6.3 Methods and material for containment and cleaning up

- Methods for cleaning up : Slippery when spilt. Avoid accidents, clean up immediately.  
Prevent from spreading by making a barrier with sand, earth or other containment material.  
Reclaim liquid directly or in an absorbent.  
Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly.

#### 6.4 Reference to other sections

For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.,  
For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

---

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

- Technical measures : Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols.  
Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
- Advice on safe handling : Avoid prolonged or repeated contact with skin.  
Avoid inhaling vapour and/or mists.  
When handling product in drums, safety footwear should be worn and proper handling equipment should be used.  
Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.
- Product Transfer : Proper grounding and bonding procedures should be used during all bulk transfer operations to avoid static accumulation.
- Hygiene measures : Exposure to this product should be reduced as low as reasonably practicable. Reference should be made to the Health and Safety Executive's publication "COSHH Essentials".

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AeroShell Fluid 41 (EU)

Version 1.5      Revision Date.: 10.09.2025      SDS Number: 800010059915      Date of last issue: 04.07.2024  
Print Date. 16.04.2026

### 7.2 Conditions for safe storage, including any incompatibilities

- Further information on storage stability : Keep container tightly closed and in a cool, well-ventilated place.  
Use properly labeled and closable containers.  
Store at ambient temperature.  
Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.  
The storage of this product may be subject to the Control of Pollution (Oil Storage) (England) Regulations. Further guidance may be obtained from the local environmental agency office.
- Packaging material : Suitable material: For containers or container linings, use mild steel or high density polyethylene.  
Unsuitable material: PVC.
- Container Advice : Polyethylene containers should not be exposed to high temperatures because of possible risk of distortion.

### 7.3 Specific end use(s)

- Specific use(s) : Not applicable

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Oil mist, mineral	Not Assigned	TWA (inhalable fraction)	5 mg/m <sup>3</sup>	US. ACGIH Threshold Limit Values
Oil mist, mineral		TWA (Inhalable particulate matter)	5 mg/m <sup>3</sup>	ACGIH

#### Biological occupational exposure limits

No biological limit allocated.

### 8.2 Exposure controls

#### Engineering measures

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Adequate ventilation to control airborne concentrations.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AeroShell Fluid 41 (EU)

Version 1.5      Revision Date.: 10.09.2025      SDS Number: 800010059915      Date of last issue: 04.07.2024  
Print Date. 16.04.2026

---

### General Information

Define procedures for safe handling and maintenance of controls.  
Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.  
Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.  
Drain down system prior to equipment break-in or maintenance.  
Retain drain downs in sealed storage pending disposal or subsequent recycle.  
Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.  
Do not ingest. If swallowed, then seek immediate medical assistance

### Personal protective equipment

The provided information is made in consideration of the PPE directive (Council Directive 89/686/EEC) and the CEN European Committee for Standardisation (CEN) standards.

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye protection : If material is handled such that it could be splashed into eyes, protective eyewear is recommended.  
Approved to EU Standard EN166.

Hand protection

Remarks : Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material.

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AeroShell Fluid 41 (EU)

Version 1.5      Revision Date.: 10.09.2025      SDS Number: 800010059915      Date of last issue: 04.07.2024  
Print Date. 16.04.2026

---

Skin and body protection	:	Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Skin protection is not ordinarily required beyond standard work clothes. It is good practice to wear chemical resistant gloves.
Respiratory protection	:	No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for combined particulate/organic gases and vapours [Type A/Type P boiling point > 65°C (149°F)] meeting EN14387 and EN143.
Thermal hazards	:	Not applicable

---

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Physical state	:	liquid
Colour	:	red
Odour	:	Slight hydrocarbon
Odour Threshold	:	Data not available
Pour point	:	<= -60 °C Method: ASTM D97
Melting / freezing point	:	Data not available
Flammability		
Flammability (solid, gas)	:	Not applicable
Flammability (liquids)	:	Not classified as flammable but will burn.
Lower explosion limit and upper explosion limit / flammability limit		
Upper explosion limit / Upper flammability limit	:	Typical 10 %(V)
Lower explosion limit / Lower flammability limit	:	Typical 1 %(V)

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AeroShell Fluid 41 (EU)

Version 1.5      Revision Date.: 10.09.2025      SDS Number: 800010059915      Date of last issue: 04.07.2024  
Print Date. 16.04.2026

---

Flash point	:	95 °C Method: ASTM D93 (PMCC)
Auto-ignition temperature	:	> 320 °C
Decomposition temperature	:	Data not available
Decomposition temperature	:	Data not available
pH	:	Not applicable
Viscosity	:	
Viscosity, dynamic	:	Data not available
Viscosity, kinematic	:	14.3 mm <sup>2</sup> /s (40.0 °C) Method: ASTM D445
		5.3 mm <sup>2</sup> /s (100 °C) Method: ASTM D445
		460 mm <sup>2</sup> /s (-40 °C) Method: ASTM D445
		2200 mm <sup>2</sup> /s (-54 °C) Method: ASTM D445
Solubility(ies)	:	
Water solubility	:	negligible
Solubility in other solvents	:	Data not available
Partition coefficient: n-octanol/water	:	log Pow: > 6 (based on information on similar products)
Vapour pressure	:	< 0.5 Pa (20 °C) estimated value(s)
Density	:	873 kg/m <sup>3</sup> (15.0 °C) Method: ASTM D4052
Particle characteristics	:	
Particle size	:	Data not available

### 9.2 Other information

Explosive properties	:	Classification Code: Not classified.
Oxidizing properties	:	Data not available
Flammability (liquids)	:	Not classified as flammable but will burn.

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AeroShell Fluid 41 (EU)

Version	Revision Date.:	SDS Number:	Date of last issue: 04.07.2024
1.5	10.09.2025	800010059915	Print Date. 16.04.2026

---

Evaporation rate	:	Data not available
Conductivity	:	This material is not expected to be a static accumulator.

---

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

#### 10.2 Chemical stability

Stable.

No hazardous reaction is expected when handled and stored according to provisions

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with strong oxidising agents.

#### 10.4 Conditions to avoid

Conditions to avoid : Extremes of temperature and direct sunlight.

#### 10.5 Incompatible materials

Materials to avoid : Strong oxidising agents.

#### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

---

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

#### Acute toxicity

##### Product:

Acute oral toxicity : LD50 (rat): > 5,000 mg/kg  
Remarks: Low toxicity  
Based on available data, the classification criteria are not met.

Remarks: Aspiration into the lungs may cause chemical pneumonitis which can be fatal.

Acute inhalation toxicity : Remarks: Based on available data, the classification criteria

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AeroShell Fluid 41 (EU)

Version 1.5      Revision Date.: 10.09.2025      SDS Number: 800010059915      Date of last issue: 04.07.2024  
Print Date. 16.04.2026

---

are not met.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg  
Remarks: Low toxicity  
Based on available data, the classification criteria are not met.

### Skin corrosion/irritation

**Product:**

Remarks : Slightly irritating to skin.  
Prolonged/repeated contact may cause defatting of the skin which can lead to dermatitis.  
Based on available data, the classification criteria are not met.

### Serious eye damage/eye irritation

**Product:**

Remarks : Slightly irritating to the eye.  
Based on available data, the classification criteria are not met.

### Respiratory or skin sensitisation

**Product:**

Remarks : For respiratory and skin sensitisation:  
Not a sensitiser.  
Based on available data, the classification criteria are not met.

### Germ cell mutagenicity

**Product:**

Genotoxicity in vivo : Remarks: Non mutagenic  
Based on available data, the classification criteria are not met.

Germ cell mutagenicity- Assessment : This product does not meet the criteria for classification in categories 1A/1B.

### Carcinogenicity

**Product:**

Remarks : Not a carcinogen.  
Based on available data, the classification criteria are not met.

Remarks : Product contains mineral oils of types shown to be non-carcinogenic in animal skin-painting studies.  
Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC).

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AeroShell Fluid 41 (EU)

Version 1.5      Revision Date.: 10.09.2025      SDS Number: 800010059915      Date of last issue: 04.07.2024  
Print Date. 16.04.2026

Carcinogenicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

Material	GHS/CLP Carcinogenicity Classification
Highly refined mineral oil	No carcinogenicity classification.

### Reproductive toxicity

**Product:**

Effects on fertility :  
Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are not met.

Reproductive toxicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

### STOT - single exposure

**Product:**

Remarks : Based on available data, the classification criteria are not met.

### STOT - repeated exposure

**Product:**

Remarks : Based on available data, the classification criteria are not met.

### Aspiration toxicity

**Product:**

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

## 11.2 Information on other hazards

### Endocrine disrupting properties

**Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AeroShell Fluid 41 (EU)

Version 1.5      Revision Date.: 10.09.2025      SDS Number: 800010059915      Date of last issue: 04.07.2024  
Print Date. 16.04.2026

---

### Further information

#### Product:

- Remarks : Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal.  
ALL used oil should be handled with caution and skin contact avoided as far as possible.
- Remarks : High pressure injection of product into the skin may lead to local necrosis if the product is not surgically removed.
- Remarks : Slightly irritating to respiratory system.
- Remarks : Classifications by other authorities under varying regulatory frameworks may exist.
- Remarks : Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).
- 

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Product:

- Toxicity to fish : Remarks: LL/EL/IL50 10-100 mg/l  
Harmful
- Toxicity to daphnia and other aquatic invertebrates : Remarks: LL/EL/IL50 10-100 mg/l  
Harmful
- Toxicity to algae/aquatic plants : Remarks: LL/EL/IL50 10-100 mg/l  
Harmful
- Toxicity to fish (Chronic toxicity) : Remarks: Data not available
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : Remarks: Data not available
- Toxicity to microorganisms :  
Remarks: Data not available

#### Components:

**Butylated hydroxytoluene:**

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AeroShell Fluid 41 (EU)

Version 1.5      Revision Date.: 10.09.2025      SDS Number: 800010059915      Date of last issue: 04.07.2024  
Print Date. 16.04.2026

---

Toxicity to fish	:	LL50 (Oryzias latipes (Orange-red killifish)): 1.1 mg/l Exposure time: 96 h Method: Regulation (EC) No. 440/2008, Annex, C.1
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 0.48 mg/l Exposure time: 48 h Method: Test(s) equivalent or similar to OECD Guideline 202
M-Factor (Acute aquatic toxicity)	:	1
Toxicity to fish (Chronic toxicity)	:	NOEC: 0.53 mg/l Exposure time: 30 d Species: Oryzias latipes (Orange-red killifish) Method: Test(s) equivalent or similar to OECD Guideline 210
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC: 0.069 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea) Method: Test(s) equivalent or similar to OECD Guideline 211
M-Factor (Chronic aquatic toxicity)	:	1

### 12.2 Persistence and degradability

#### **Product:**

Biodegradability : Remarks: Not readily biodegradable.  
Major constituents are inherently biodegradable, but contains components that may persist in the environment.

#### **Components:**

##### **Butylated hydroxytoluene:**

Biodegradability : Exposure time: 62 d  
Method: OECD Test Guideline 309  
Remarks: Degradation half life  
5.65 days

### 12.3 Bioaccumulative potential

#### **Product:**

Bioaccumulation : Remarks: Contains components with the potential to bioaccumulate.

### 12.4 Mobility in soil

#### **Product:**

Mobility : Remarks: Liquid under most environmental conditions., If it

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AeroShell Fluid 41 (EU)

Version 1.5	Revision Date.: 10.09.2025	SDS Number: 800010059915	Date of last issue: 04.07.2024 Print Date. 16.04.2026
----------------	-------------------------------	-----------------------------	--

---

enters soil, it will adsorb to soil particles and will not be mobile.

Remarks: Floats on water.

### 12.5 Results of PBT and vPvB assessment

**Product:**

Assessment : This mixture does not contain any REACH registered substances that are assessed to be a PBT or a vPvB..

### 12.6 Endocrine disrupting properties

**Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

**Product:**

Additional ecological information : Does not have ozone depletion potential, photochemical ozone creation potential or global warming potential.  
Product is a mixture of non-volatile components, which will not be released to air in any significant quantities under normal conditions of use.

Poorly soluble mixture.

Causes physical fouling of aquatic organisms.

Mineral oil does not cause chronic toxicity to aquatic organisms at concentrations less than 1 mg/l.

Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : Recover or recycle if possible.  
It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.  
Do not dispose into the environment, in drains or in water

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AeroShell Fluid 41 (EU)

Version 1.5      Revision Date.: 10.09.2025      SDS Number: 800010059915      Date of last issue: 04.07.2024  
Print Date. 16.04.2026

---

courses.

Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment.  
Waste, spills or used product is dangerous waste.  
Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.  
Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination.

MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides technical aspects at controlling pollutions from ships.

Contaminated packaging : Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.

Local legislation

Waste catalogue :

EU Waste Disposal Code (EWC):

Waste Code :

13 01 10\*

Remarks

: Disposal should be in accordance with applicable regional, national, and local laws and regulations.

Classification of waste is always the responsibility of the end user.

Hazardous Waste (England and Wales) Regulations 2005.

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AeroShell Fluid 41 (EU)

Version 1.5      Revision Date.: 10.09.2025      SDS Number: 800010059915      Date of last issue: 04.07.2024  
Print Date. 16.04.2026

---

### SECTION 14: Transport information

#### 14.1 UN number or ID number

ADR : Not regulated as a dangerous good  
RID : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not regulated as a dangerous good

#### 14.2 UN proper shipping name

ADR : Not regulated as a dangerous good  
RID : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not regulated as a dangerous good

#### 14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good  
RID : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not regulated as a dangerous good

#### 14.4 Packing group

ADR : Not regulated as a dangerous good  
RID : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not regulated as a dangerous good

#### 14.5 Environmental hazards

ADR : Not regulated as a dangerous good  
RID : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good

#### 14.6 Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

#### 14.7 Maritime transport in bulk according to IMO instruments

MARPOL Annex 1 rules apply for bulk shipments by sea.

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AeroShell Fluid 41 (EU)

Version	Revision Date.:	SDS Number:	Date of last issue: 04.07.2024
1.5	10.09.2025	800010059915	Print Date. 16.04.2026

---

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Product is not subject to Authorisation under REACH.

Volatile organic compounds : Volatile organic compounds (VOC) content: 0 %

#### Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Environmental Protection Act 1990 (as amended). Health and Safety at Work etc. Act 1974. Consumers Protection Act 1987. Pollution Prevention and Control Act 1999. Environment Act 1995. Factories Act 1961. The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment (Amendment) Regulations 2011. Chemicals (Hazard Information and Packaging for Supply) Regulations 2009. Control of Substances Hazardous to Health Regulations 2002 (as amended). Merchant Shipping (Dangerous Goods and Marine Pollutants) Regulations 1997. Reporting of Injuries, Diseases and Dangerous Occurrences Regulations 1995 (as amended). Personal Protective Equipment Regulations 2002. Personal Protective Equipment at Work Regulations 1992. Hazardous Waste (England and Wales) Regulations 2005(as amended). Control of Major Accident Hazards Regulations 1999 (as amended). Renewable Transport Fuel Obligations Order 2007 (as amended). Energy Act 2011. Environmental Permitting (England and Wales) Regulations 2010 (as amended). Waste (England and Wales) Regulations 2011 (as amended). Planning (Hazardous Substances) Act 1990 and associated regulations. The Environmental Protection (Controls on Ozone-Depleting Substances) Regulations 2011.

#### The components of this product are reported in the following inventories:

REACH : All components listed or polymer exempt.

TSCA : All components listed.

#### 15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

---

### SECTION 16: Other information

#### Full text of H-Statements

H304 : May be fatal if swallowed and enters airways.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AeroShell Fluid 41 (EU)

Version	Revision Date.:	SDS Number:	Date of last issue: 04.07.2024
1.5	10.09.2025	800010059915	Print Date. 16.04.2026

### Full text of other abbreviations

Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH / TWA	:	8-hour, time-weighted average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

Training advice : Provide adequate information, instruction and training for operators.

Other information : Under Article 31 of REACH, a SDS is not required for this product. Therefore, this SDS has been created on a voluntary basis to pass on potentially relevant information required under Article 32.

A vertical bar (|) in the left margin indicates an amendment

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AeroShell Fluid 41 (EU)

Version 1.5	Revision Date.: 10.09.2025	SDS Number: 800010059915	Date of last issue: 04.07.2024 Print Date. 16.04.2026
----------------	-------------------------------	-----------------------------	--

---

Sources of key data used to compile the Safety Data Sheet : from the previous version.  
The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).

### Identified Uses according to the Use Descriptor System

#### Uses - Worker

Title : General use of lubricants and greases in vehicles or machinery.  
- Industrial

#### Uses - Worker

Title : General use of lubricants and greases in vehicles or machinery.  
- Professional

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AeroShell Fluid 41 (EU)

Version 1.5      Revision Date.: 10.09.2025      SDS Number: 800010059915      Date of last issue: 04.07.2024  
Print Date. 16.04.2026

### Exposure Scenario - Worker

<b>300000000190</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	General use of lubricants and greases in vehicles or machinery.- Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU3 <b>Process Categories:</b> PROC1, PROC2, PROC8b, PROC9 <b>Environmental Release Categories:</b> ERC4, ERC7, ATIEL-ATC SPERC 4.Bi.v1
<b>Scope of process</b>	Covers general use of lubricants and greases in vehicles or machinery in closed systems. Includes filling and draining of containers and operation of enclosed machinery (including engines) and associated maintenance and storage activities.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>	
<b>Additional Information</b>	No exposure assessment presented for human health.	
<b>Section 2.1</b>	<b>Control of Worker Exposure</b>	
<b>Product Characteristics</b>		
<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>	
<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>	
<b>Amounts Used</b>		
EU tonnage (tonnes per year):		2,631.1
Fraction of EU tonnage used in region:		0.1
Fraction of Regional tonnage used locally:		0.1
<b>Frequency and Duration of Use</b>		
Emission Days (days/year):		300
<b>Environmental factors not influenced by risk management</b>		
Local freshwater dilution factor:		10
Local marine water dilution factor:		100
<b>Other Operational Conditions affecting Environmental Exposure</b>		
Negligible wastewater emissions as process operates without water contact.		
Release fraction to air from process (after typical onsite RMMs) :		5.00E-05
Release fraction to wastewater from process (after typical onsite RMMs and before (municipal) sewage treatment plant):		2.00E-11
Release fraction to soil from process (after typical onsite RMMs):		0
<b>Technical conditions and measures at process level (source) to prevent release</b>		
Common practices vary across sites thus conservative process re-release estimates used.		
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>		
Treat air emission to provide a typical removal efficiency of (%)		70

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AeroShell Fluid 41 (EU)

Version 1.5      Revision Date.: 10.09.2025      SDS Number: 800010059915      Date of last issue: 04.07.2024  
Print Date. 16.04.2026

Prevent discharge of undissolved substance to or recover from onsite wastewater.	
User sites are assumed to be provided with oil/water separators or equivalent and for waste water to be discharged via public sewer system.	
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	6.9E+01
Assumed domestic sewage treatment plant flow (m3/d)	2.00E+03
Maximum allowable site quantity (MSafe) based on OCs and RMMs as above (kg/day) :	1.687567E+05
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
<b>Conditions and measures related to external recovery of waste</b>	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
No exposure assessment presented for human health.	

<b>Section 3.2 -Environment</b>	
Used ECETOC TRA model.	

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
No exposure assessment presented for human health.	

<b>Section 4.2 -Environment</b>	
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.	
Further details on scaling and control technologies are provided in SpERC factsheet ( <a href="http://cefic.org">http://cefic.org</a> ).	
If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.	
For further information see <a href="http://www.ATIEL.org/REACH_GES">www.ATIEL.org/REACH_GES</a> .	

# **SAFETY DATA SHEET.**

According to EC No 1907/2006 as amended as at the date of this SDS

## **AeroShell Fluid 41 (EU)**

Version  
1.5

Revision Date.:  
10.09.2025

SDS Number:  
800010059915

Date of last issue: 04.07.2024  
Print Date. 16.04.2026

---

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AeroShell Fluid 41 (EU)

Version 1.5      Revision Date.: 10.09.2025      SDS Number: 800010059915      Date of last issue: 04.07.2024  
Print Date. 16.04.2026

### Exposure Scenario - Worker

<b>300000000191</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	General use of lubricants and greases in vehicles or machinery.- Professional
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU22 <b>Process Categories:</b> PROC1, PROC2, PROC8a, PROC8b, PROC20 <b>Environmental Release Categories:</b> ERC9a, ERC9b, ATIEL-ATC SPERC 9.Bp.v1
<b>Scope of process</b>	Covers general use of lubricants and greases in vehicles or machinery in closed systems. Includes filling and draining of containers and operation of enclosed machinery (including engines) and associated maintenance and storage activities.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>	
<b>Additional Information</b>	No exposure assessment presented for human health.	
<b>Section 2.1</b>	<b>Control of Worker Exposure</b>	
<b>Product Characteristics</b>		
<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>	
<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>	
<b>Amounts Used</b>		
EU tonnage (tonnes per year):		5,387.2
Fraction of EU tonnage used in region:		0.1
Fraction of Regional tonnage used locally:		0.1
<b>Frequency and Duration of Use</b>		
Emission Days (days/year):		365
<b>Environmental factors not influenced by risk management</b>		
Local freshwater dilution factor:		10
Local marine water dilution factor:		100
<b>Other Operational Conditions affecting Environmental Exposure</b>		
Negligible wastewater emissions as process operates without water contact.		
Release fraction to air from process (after typical onsite RMMs) :		1.00E-04
Release fraction to wastewater from process (after typical onsite RMMs and before (municipal) sewage treatment plant):		5.00E-04
Release fraction to soil from process (after typical onsite RMMs):		1E-03
<b>Technical conditions and measures at process level (source) to prevent release</b>		
Common practices vary across sites thus conservative process re-release estimates used.		
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>		

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AeroShell Fluid 41 (EU)

Version 1.5      Revision Date.: 10.09.2025      SDS Number: 800010059915      Date of last issue: 04.07.2024  
Print Date. 16.04.2026

Prevent discharge of undissolved substance to or recover from onsite wastewater.	
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	69.1
Assumed domestic sewage treatment plant flow (m3/d)	2.00E+03
Maximum allowable site quantity (MSafe) based on OCs and RMMs as above (kg/day) :	424.7
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
<b>Conditions and measures related to external recovery of waste</b>	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
No exposure assessment presented for human health.	

<b>Section 3.2 -Environment</b>	
Used ECETOC TRA model.	

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
No exposure assessment presented for human health.	

<b>Section 4.2 -Environment</b>	
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.	
Further details on scaling and control technologies are provided in SpERC factsheet ( <a href="http://cefic.org">http://cefic.org</a> ).	
If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.	
For further information see <a href="http://www.ATIEL.org/REACH_GES">www.ATIEL.org/REACH_GES</a> .	

# **SAFETY DATA SHEET.**

According to EC No 1907/2006 as amended as at the date of this SDS

## **AeroShell Fluid 41 (EU)**

Version  
1.5

Revision Date.:  
10.09.2025

SDS Number:  
800010059915

Date of last issue: 04.07.2024  
Print Date. 16.04.2026

---