

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version	Revision Date.:	SDS Number:	Date of last issue: 10.05.2024
10.0	04.03.2026	800001001508	Print Date. 05.03.2026

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name	:	AVGAS 100LL
Product code	:	002C0199
Unique Formula Identifier	:	8JP0-C0X4-R002-38VR

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture	:	Aviation Fuel, Low lead content aviation gasoline fuel for piston engined aircraft Please refer to section 16 and/or the annexes for the registered uses under REACH.
------------------------------	---	--

Uses advised against	:	This product must not be used in applications other than those listed in Section 1 without first seeking the advice of the supplier.
----------------------	---	--

#### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier	:	<b>Shell UK Oil Products Limited</b> Shell Centre London SE1 7NA United Kingdom
Telephone	:	(+44) 08007318888
Telefax	:	
Contact for Safety Data Sheet	:	If you have any enquiries about the content of this SDS please email <a href="mailto:fuelSDS@shell.com">fuelSDS@shell.com</a>

#### 1.4 Emergency telephone number

: +44 (0) 20 7934 7778 (This telephone number is available 24 hours per day, 7 days per week)

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Classification (REGULATION (EC) No 1272/2008)**

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
Print Date. 05.03.2026

Flammable liquids, Category 1 Aspiration hazard, Category 1	H224: Extremely flammable liquid and vapour. H304: May be fatal if swallowed and enters air-ways.
Skin irritation, Category 2 Specific target organ toxicity - single exposure, Category 3, Inhalation, Narcotic effects	H315: Causes skin irritation. H336: May cause drowsiness or dizziness.
Carcinogenicity, Category 1B Reproductive toxicity, Category 2 Specific target organ toxicity - repeated exposure, Category 2, Liver , Kidney , Brain	H350: May cause cancer. H361d: Suspected of damaging the unborn child. H373: May cause damage to organs through prolonged or repeated exposure.
Long-term (chronic) aquatic hazard, Category 2	H411: Toxic to aquatic life with long lasting effects.

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements :

PHYSICAL HAZARDS:  
H224 Extremely flammable liquid and vapour.  
HEALTH HAZARDS:  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H336 May cause drowsiness or dizziness.  
H350 May cause cancer.  
H361d Suspected of damaging the unborn child.  
H373 May cause damage to organs through prolonged or repeated exposure.  
ENVIRONMENTAL HAZARDS:  
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements :

**Prevention:**  
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
**Response:**  
P331 Do NOT induce vomiting.  
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
Print Date. 05.03.2026

### Storage:

P403 Store in a well-ventilated place.

### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

### 2.3 Other hazards

This mixture does not contain any REACH registered substances that are assessed to be a PBT or a vPvB.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Liquid evaporates quickly and can ignite leading to a flash fire, or an explosion in a confined space.

This material is a static accumulator.

Even with proper grounding and bonding, this material can still accumulate an electrostatic charge.

If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur.

This product contains tetraethyl lead which is known to accumulate in the human body. There are indications from human epidemiological studies that exposure to tetraethyl lead may cause developmental and neurobehavioral effects in the unborn child.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : Complex mixture of hydrocarbons consisting of paraffins, cycloparaffins, aromatic and olefinic hydrocarbons with carbon numbers predominantly in the C4 to C12 range.  
May also contain several additives at <0.1% v/v each.  
This product is dyed for grade identification.  
Contains Tetraethyl lead, CAS # 78-00-2

### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Gasoline	86290-81-5 289-220-8	Flam. Liq. 1; H224 Asp. Tox. 1; H304	99.88 - <= 99.94

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
Print Date. 05.03.2026

	649-378-00-4 01-2119471335-39, UK-01-4615601157-2	Carc. 1B; H350 Skin Irrit. 2; H315 STOT SE 3; H336 Repr. 2; H361d Aquatic Chronic 2; H411	
Tetraethyl lead	78-00-2 201-075-4 082-002-00-1 01-2119622080-57	Repr. 1A; H360Df Acute Tox. 2; H330 Acute Tox. 1; H310 Acute Tox. 2; H300 STOT RE 2; H373 (Liver, Kidney, Brain) Aquatic Acute 1; H400 Aquatic Chronic 1; H410  <u>M-Factor (Acute aquatic toxicity): 1</u>  specific concentration limit Repr. 1A; H360D > 0.1 % STOT RE 2; H373 > 0.05 %	$\geq 0.06 - \leq 0.12$

For explanation of abbreviations see section 16.

### Further information

Contains:

Chemical name	Identification number	Classification	Concentration (% w/w)
Toluene	108-88-3, 203-625-9	Flam. Liq.2; H225 Asp. Tox.1; H304 Skin Irrit.2; H315 STOT SE3; H336 Repr.2; H361d STOT RE2; H373 Aquatic Chronic3; H412	$\geq 12 - \leq 15$
Trimethylbenzene (all isomers)	25551-13-7, 247-099-9	Flam. Liq.3; H226 STOT SE3; H335 Aquatic Chronic2; H411	$\geq 0 - \leq 0.5$

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
Print Date. 05.03.2026

Xylene, mixed isomers	1330-20-7, 215-535-7	Flam. Liq.3; H226 Asp. Tox.1; H304 Acute Tox.4; H312 Skin Irrit.2; H315 Eye Irrit.2; H319 Acute Tox.4; H332 STOT SE3; H335 STOT RE2; H373 Aquatic Chronic3; H412	$\geq 12 - \leq 15$
n-Hexane	110-54-3, 203-777-6	Flam. Liq.2; H225 Asp. Tox.1; H304 Skin Irrit.2; H315 STOT SE3; H336 Repr.2; H361f STOT RE1; H372 Aquatic Chronic2; H411	$\geq 0 - \leq 0.5$
Naphthalene	91-20-3, 202-049-5	Acute Tox.4; H302 Carc.2; H351 Aquatic Acute1; H400 Aquatic Chronic1; H410  M-Factor (Acute aquatic toxicity): 1	$\geq 0 - \leq 0.05$
Ethylbenzene	100-41-4, 202-849-4	Flam. Liq.2; H225 Asp. Tox.1; H304 Skin Irrit.2; H315 Eye Irrit.2; H319 Acute Tox.4; H332 STOT SE3; H335 STOT RE2; H373 Aquatic Chronic3; H412	$\geq 0 - \leq 2.5$
Cyclohexane	110-82-7, 203-806-2	Flam. Liq.2; H225 Asp. Tox.1; H304 Skin Irrit.2; H315 STOT SE3; H336 Aquatic Chronic1; H410 Aquatic Acute1; H400	$\geq 0 - \leq 0.05$

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
Print Date. 05.03.2026

		M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	
Cumene	98-82-8, 202-704-5	Flam. Liq.3; H226 Asp. Tox.1; H304 STOT SE3; H335 Carc.1B; H350 Aquatic Chronic2; H411	$\geq 0 - \leq 0.25$
Benzene	71-43-2, 200-753-7	Flam. Liq.2; H225 Asp. Tox.1; H304 Skin Irrit.2; H315 Eye Irrit.2; H319 Muta.1B; H340 Carc.1A; H350 STOT RE1; H372 Aquatic Chronic3; H412	$\geq 0 - \leq 0.09$

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- Protection of first-aiders : When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
- If inhaled : Remove to fresh air. If rapid recovery does not occur, transport to nearest medical facility for additional treatment.
- In case of skin contact : Remove contaminated clothing.
- In case of eye contact : Immediately flush eye(s) with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Transport to the nearest medical facility for additional treatment.
- If swallowed : If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0	Revision Date.: 04.03.2026	SDS Number: 800001001508	Date of last issue: 10.05.2024 Print Date. 05.03.2026
-----------------	-------------------------------	-----------------------------	--

---

Rinse mouth.  
Call emergency number for your location / facility.  
If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Skin irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blisters.  
Eye irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blurred vision.  
If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever.  
The onset of respiratory symptoms may be delayed for several hours after exposure.  
Breathing of high vapour concentrations may cause central nervous system (CNS) depression resulting in dizziness, light-headedness, headache and nausea.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.  
Persons on disulfiram (Antabuse®) therapy should be aware that the ethyl alcohol in this product is hazardous to them just as is alcohol from any source. Disulfiram reactions (vomiting, headache and even collapse) may follow ingestion of small amounts of alcohol and have also been described from skin contact.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media : Do not use direct water jets on the burning product as they could cause a steam explosion and spread of the fire.  
Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Hazardous combustion products may include:  
A complex mixture of airborne solid and liquid particulates and gases (smoke).  
Carbon monoxide may be evolved if incomplete combustion

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0	Revision Date.: 04.03.2026	SDS Number: 800001001508	Date of last issue: 10.05.2024 Print Date. 05.03.2026
-----------------	-------------------------------	-----------------------------	--

---

occurs.  
Unidentified organic and inorganic compounds.  
The vapour is heavier than air, spreads along the ground and distant ignition is possible.  
Will float and can be reignited on surface water.

### 5.3 Advice for firefighters

- Special protective equipment for firefighters : Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Further information : Keep adjacent containers cool by spraying with water. If possible remove containers from the danger zone. If the fire cannot be extinguished the only course of action is to evacuate immediately.  
Contain residual material at affected sites to prevent material from entering drains (sewers), ditches, and waterways.
- 

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- Personal precautions : 6.1.1 For non emergency personnel:  
Do not breathe fumes, vapour.  
Do not operate electrical equipment.  
6.1.2 For emergency responders:  
Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area and evacuate all personnel. Attempt to disperse the gas or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment. Monitor area with combustible gas meter.  
Vapour can travel for considerable distances both above and below the ground surface. Underground services (drains, pipelines, cable ducts) can provide preferential flow paths.

### 6.2 Environmental precautions

- Environmental precautions : Take measures to minimise the effects on groundwater.  
Contain residual material at affected sites to prevent material from entering drains (sewers), ditches, and waterways.  
Prevent from spreading or entering into drains, ditches or riv-

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version	Revision Date.:	SDS Number:	Date of last issue: 10.05.2024
10.0	04.03.2026	800001001508	Print Date. 05.03.2026

---

ers by using sand, earth, or other appropriate barriers.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely. For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely. Take precautionary measures against static discharges.

### 6.4 Reference to other sections

For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet., Notify authorities if any exposure to the general public or the environment occurs or is likely to occur., For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet., Local authorities should be advised if significant spillages cannot be contained., Maritime spillages should be dealt with using a Shipboard Oil Pollution Emergency Plan (SOPEP), as required by MARPOL Annex 1 Regulation 26.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Technical measures : Avoid breathing of or direct contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material. Air-dry contaminated clothing in a well-ventilated area before laundering. Prevent spillages. Turn off all battery operated portable electronic devices (examples include: cellular phones, pagers and CD players) before operating gasoline pump. Contaminated leather articles including shoes cannot be decontaminated and should be destroyed to prevent reuse. Do not use as a cleaning solvent or other non-motor fuel uses. Ensure that all local regulations regarding handling and storage facilities are followed. Maintenance and Fuelling Activities - Avoid inhalation of va-

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0	Revision Date.: 04.03.2026	SDS Number: 800001001508	Date of last issue: 10.05.2024 Print Date. 05.03.2026
-----------------	-------------------------------	-----------------------------	--

- 
- Advice on safe handling : pours and contact with skin.  
: Ensure that all local regulations regarding handling and storage facilities are followed.  
When using do not eat or drink.  
Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks.  
Never siphon by mouth.  
The vapour is heavier than air, spreads along the ground and distant ignition is possible.  
Avoid exposure. Obtain special instructions before use.  
Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.  
Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols.  
The following activities have been associated with high levels of exposure to gasoline vapours: Top-loading of tankers, open ship loading by deck crew, drum filling/emptying and laboratory testing (particularly sample bottle washing).  
In the interests of air safety, aviation fuels are subject to strict quality requirements and product integrity is of paramount importance. For one source of information on international standards for the quality assurance of aviation fuels, see [www.jigonline.com](http://www.jigonline.com).
- Product Transfer : Wait 2 minutes after tank filling (for tanks such as those on road tanker vehicles) before opening hatches or manholes.  
Wait 30 minutes after tank filling ( for large storage tanks) before opening hatches or manholes. Even with proper grounding and bonding, this material can still accumulate an electrostatic charge. If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur. Be aware of handling operations that may give rise to additional hazards that result from the accumulation of static charges. These include but are not limited to pumping (especially turbulent flow), mixing, filtering, splash filling, cleaning and filling of tanks and containers, sampling, switch loading, gauging, vacuum truck operations, and mechanical movements. These activities may lead to static discharge e.g. spark formation. Restrict line velocity during pumping in order to avoid generation of electrostatic discharge ( $\leq 1$  m/s until fill pipe submerged to twice its diameter, then  $\leq 7$  m/s). Avoid splash filling. Do NOT use compressed air for filling, discharging, or handling operations.
- Hygiene measures : Read in conjunction with the Exposure Scenario for your specific use contained in the Annex.  
Exposure to this product should be reduced as low as reasonably practicable. Reference should be made to the Health and Safety Executive's publication "COSHH Essentials".

### 7.2 Conditions for safe storage, including any incompatibilities

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version	Revision Date.:	SDS Number:	Date of last issue: 10.05.2024
10.0	04.03.2026	800001001508	Print Date. 05.03.2026

- 
- Further information on storage stability : Drum and small container storage:  
Keep containers closed when not in use.  
Drums should be stacked to a maximum of 3 high.  
Use properly labeled and closable containers.  
Take suitable precautions when opening sealed containers, as pressure can build up during storage.  
Tank storage:  
Tanks must be specifically designed for use with this product.  
Bulk storage tanks should be diked (bunded).  
Locate tanks away from heat and other sources of ignition.  
Cleaning, inspection and maintenance of storage tanks is a specialist operation, which requires the implementation of strict procedures and precautions.  
In the interests of air safety, aviation fuels are subject to strict quality requirements and product integrity is of paramount importance. For one source of information on international standards for the quality assurance of aviation fuels, see [www.jjgonline.com](http://www.jjgonline.com).
- Electrostatic charges will be generated during pumping.  
Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to reduce the risk.  
The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flammable.  
Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.  
The storage of this product may be subject to the Control of Pollution (Oil Storage) (England) Regulations. Further guidance may be obtained from the local environmental agency office.
- Packaging material : Suitable material: For containers, or container linings use mild steel, stainless steel., Aluminium may also be used for applications where it does not present an unnecessary fire hazard., Examples of suitable materials are: high density polyethylene (HDPE), polypropylene (PP), and Viton (FKM), which have been specifically tested for compatibility with this product., For container linings, use amine-adduct cured epoxy paint., For seals and gaskets use: graphite, PTFE, Viton A, Viton B.  
Unsuitable material: Some synthetic materials may be unsuitable for containers or container linings depending on the material specification and intended use. Examples of materials to avoid are: natural rubber (NR), nitrile rubber (NBR), ethylene propylene rubber (EPDM), polymethyl methacrylate (PMMA), polystyrene, polyvinyl chloride (PVC), polyisobutylene., However, some may be suitable for glove materials.
- Container Advice : Containers, even those that have been emptied, can contain explosive vapours. Do not cut, drill, grind, weld or perform

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
Print Date. 05.03.2026

similar operations on or near containers. Gasoline containers must not be used for storage of other products.

### 7.3 Specific end use(s)

Specific use(s) : Please refer to section 16 and/or the annexes for the registered uses under REACH.

See additional references that provide safe handling practices for liquids that are determined to be static accumulators: American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practices on Static Electricity).  
IEC/TS 60079-32-1: Electrostatic hazards, guidance

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Gasoline	86290-81-5	TWA	300 ppm	ACGIH
Gasoline		STEL	500 ppm	ACGIH
Toluene	108-88-3	TWA	50 ppm 191 mg/m <sup>3</sup>	GB EH40
		Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		
Toluene		STEL	100 ppm 384 mg/m <sup>3</sup>	GB EH40
		Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		
Toluene		TWA	50 ppm 192 mg/m <sup>3</sup>	2006/15/EC
		Further information: Indicative, Identifies the possibility of significant uptake through the skin		
Toluene		STEL	100 ppm 384 mg/m <sup>3</sup>	2006/15/EC
		Further information: Indicative, Identifies the possibility of significant uptake through the skin		
Toluene		TWA	20 ppm	ACGIH
Tetraethyl lead	78-00-2	TWA	0.1 mg/m <sup>3</sup> (Lead)	ACGIH
Trimethylbenzene	25551-13-7	TWA	25 ppm	GB EH40

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
Print Date. 05.03.2026

(all isomers)			125 mg/m <sup>3</sup>	
Trimethylbenzene (all isomers)		TWA	10 ppm	ACGIH
Xylene, mixed isomers	1330-20-7	TWA	50 ppm 220 mg/m <sup>3</sup>	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
Xylene, mixed isomers		STEL	100 ppm 441 mg/m <sup>3</sup>	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
Xylene, mixed isomers		TWA	20 ppm	ACGIH
n-Hexane	110-54-3	TWA	20 ppm 72 mg/m <sup>3</sup>	GB EH40
n-Hexane		TWA	20 ppm 72 mg/m <sup>3</sup>	2006/15/EC
	Further information: Indicative			
n-Hexane		TWA	50 ppm	ACGIH
Naphthalene	91-20-3	TWA	10 ppm 50 mg/m <sup>3</sup>	91/322/EEC
	Further information: Indicative			
Naphthalene		TWA	10 ppm	ACGIH
Ethylbenzene	100-41-4	TWA	100 ppm 441 mg/m <sup>3</sup>	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
Ethylbenzene		STEL	125 ppm 552 mg/m <sup>3</sup>	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
Ethylbenzene		TWA	20 ppm	ACGIH
Cyclohexane	110-82-7	TWA	100 ppm 350 mg/m <sup>3</sup>	GB EH40
Cyclohexane		STEL	300 ppm 1,050 mg/m <sup>3</sup>	GB EH40
Cyclohexane		TWA	200 ppm 700 mg/m <sup>3</sup>	2006/15/EC
	Further information: Indicative			
Cyclohexane		TWA	100 ppm	ACGIH
Cumene	98-82-8	TWA	25 ppm 125 mg/m <sup>3</sup>	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will			

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
 Print Date. 05.03.2026

		lead to systemic toxicity.		
Cumene		STEL	50 ppm 250 mg/m <sup>3</sup>	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
Cumene		TWA	10 ppm 50 mg/m <sup>3</sup>	2019/1831/E U
	Further information: A skin notation assigned to the occupational exposure limit value indicates the possibility of significant uptake through the skin., Indicative			
Cumene		STEL	50 ppm 250 mg/m <sup>3</sup>	2019/1831/E U
	Further information: A skin notation assigned to the occupational exposure limit value indicates the possibility of significant uptake through the skin., Indicative			
Cumene		TWA	5 ppm	ACGIH
Benzene	71-43-2	TWA	1 ppm 3.25 mg/m <sup>3</sup>	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity., Capable of causing cancer and/or heritable genetic damage.			
Benzene		TWA	0.25 ppm 0.8 mg/m <sup>3</sup>	Shell Internal Standard (SIS) for 8-12 hour TWA.
Benzene		STEL	2.5 ppm 8 mg/m <sup>3</sup>	Shell Internal Standard (SIS) for 15 min (STEL)
Benzene		TWA	0.02 ppm	ACGIH
Benzene		STEL	2.5 ppm	ACGIH

### Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
Toluene	108-88-3	Toluene: 0.02 mg/l (In blood)	Prior to last shift of workweek	ACGIH BEI
		Toluene: 0.03 mg/l (Urine)	End of shift (As soon as possible after exposure ceases)	ACGIH BEI
		o-Cresol: 0.3 mg/g creatinine (Urine)	End of shift (As soon as possible after exposure ceases)	ACGIH BEI
Xylene, mixed isomers	1330-20-7	methyl hippuric acid: 650 Millimo-	After shift	GB EH40 BAT

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version  
10.0

Revision Date.:  
04.03.2026

SDS Number:  
800001001508

Date of last issue: 10.05.2024  
Print Date. 05.03.2026

		les per mole creatinine (Urine)		
		Methylhippuric acids: 0.3 g/g creatinine (Urine)	End of shift (As soon as possible after exposure ceases)	ACGIH BEI
n-Hexane	110-54-3	2,5-Hexanedione: 0.5 mg/l (Urine)	End of shift	ACGIH BEI
Naphthalene	91-20-3	1-hydroxypyrene: 4 µmol/mol creatinine (Urine)	After shift	GB EH40 BAT
		1-Naphthol + 2-Naphthol:	End of shift (As soon as possible after exposure ceases)	ACGIH BEI
Ethylbenzene	100-41-4	Sum of mandelic acid and phenyl glyoxylic acid: 0.15 g/g creatinine (Urine)	End of shift (As soon as possible after exposure ceases)	ACGIH BEI
Cyclohexane	110-82-7	1,2-Cyclohexanediol: 50 mg/g creatinine (Urine)	End of shift at end of workweek	ACGIH BEI
Benzene	71-43-2	S-Phenylmercapturic acid: 25 µg/g creatinine (Urine)	End of shift (As soon as possible after exposure ceases)	ACGIH BEI
		t,t-Muconic acid: 500 µg/g creatinine (Urine)	End of shift (As soon as possible after exposure ceases)	ACGIH BEI

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Toluene	Workers	Inhalation	Acute systemic effects	384 mg/m <sup>3</sup>
Toluene	Workers	Inhalation	Long-term systemic effects	192 mg/m <sup>3</sup>
Toluene	Workers	Dermal	Long-term systemic effects	180 mg/kg bw/day
Toluene	Consumers	Inhalation	Acute systemic effects	226 mg/m <sup>3</sup>
Toluene	Consumers	Inhalation	Long-term systemic	56.5 mg/m <sup>3</sup>

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version  
10.0

Revision Date.:  
04.03.2026

SDS Number:  
800001001508

Date of last issue: 10.05.2024  
Print Date. 05.03.2026

			effects	
Toluene	Consumers	Dermal	Long-term systemic effects	226 mg/kg bw/day
Toluene	Consumers	Oral	Long-term systemic effects	8.13 mg/kg bw/day
Gasoline	Workers	Inhalation		840 mg/m <sup>3</sup> / 8h
Remarks:	long term, local effects			
Gasoline	Consumers	Inhalation		180 mg/m <sup>3</sup> / 24h
Remarks:	long term, local effects			
Naphthalene	Consumers	Oral	Long-term systemic effects	4.23 mg/kg
Ethylbenzene	Workers	Inhalation	Acute local effects	293 mg/m <sup>3</sup>
Ethylbenzene	Workers	Inhalation	Long-term systemic effects	77 mg/m <sup>3</sup>
Ethylbenzene	Workers	Dermal	Long-term systemic effects	180 mg/kg bw/day
Ethylbenzene	Consumers	Inhalation	Long-term systemic effects	15 mg/m <sup>3</sup>
Ethylbenzene	Consumers	Oral	Long-term systemic effects	1.6 mg/kg bw/day
Benzene	Workers	Inhalation	Long-term systemic effects	0.8 mg/m <sup>3</sup> / 8h

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Remarks:	Substance is a hydrocarbon with a complex, unknown or variable composition. Conventional methods of deriving PNECs are not appropriate and it is not possible to identify a single representative PNEC for such substances.	

## 8.2 Exposure controls

### Engineering measures

Read in conjunction with the Exposure Scenario for your specific use contained in the Annex. The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Use sealed systems as far as possible.

Firewater monitors and deluge systems are recommended.

Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits.

Local exhaust ventilation is recommended.

Eye washes and showers for emergency use.

### General Information

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version	Revision Date.:	SDS Number:	Date of last issue: 10.05.2024
10.0	04.03.2026	800001001508	Print Date. 05.03.2026

equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or for subsequent recycle.

Do not ingest. If swallowed, then seek immediate medical assistance

### Personal protective equipment

Read in conjunction with the Exposure Scenario for your specific use contained in the Annex.

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

The provided information is made in consideration of the PPE directive (Council Directive 89/686/EEC) and the CEN European Committee for Standardisation (CEN) standards.

Eye protection : If material is handled such that it could be splashed into eyes, protective eyewear is recommended.  
Approved to EU Standard EN166.

Hand protection

Remarks : Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Select gloves tested to a relevant standard (e.g. Europe EN374, US F739). When prolonged or frequent repeated contact occurs, Nitrile gloves may be suitable. (Breakthrough time of > 240 minutes.) For incidental contact/splash protection Neoprene, PVC gloves may be suitable.

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version	Revision Date.:	SDS Number:	Date of last issue: 10.05.2024
10.0	04.03.2026	800001001508	Print Date. 05.03.2026

---

Skin and body protection	:	Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. Wear chemical resistant gloves/gauntlets and boots. Where risk of splashing, also wear an apron. Wear antistatic and flame-retardant clothing. Protective clothing approved to EU Standard EN14605.
Respiratory protection	:	No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for combined particulate/organic gases and vapours [Type A/Type P boiling point > 65°C (149°F)] meeting EN14387 and EN143.
Thermal hazards	:	Not applicable

---

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Physical state	:	liquid
Colour	:	blue
Odour	:	Data not available
Odour Threshold	:	Data not available
Melting point/freezing point	:	< -58 °C
Initial boiling point and boiling range	:	Typical 25 - 170 °C
Flammability		
Flammability (solid, gas)	:	Not applicable
Lower explosion limit and upper explosion limit / flammability limit		
Upper explosion limit / Upper flammability limit	:	8 %(V)
Lower explosion limit / Lower flammability limit	:	1 %(V)
Flash point	:	<= -40 °C

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
Print Date. 05.03.2026

---

Auto-ignition temperature : > 250 °C

Decomposition temperature  
Decomposition temperature : Data not available

pH : Data not available

Viscosity  
Viscosity, kinematic : Method: Unspecified  
Not applicable  
  
Method: Unspecified  
Not applicable  
  
0.25 - 0.75 mm<sup>2</sup>/s (40.0 °C)  
Method: Unspecified

Solubility(ies)  
Water solubility : negligible  
Solubility in other solvents : Data not available

Partition coefficient: n-octanol/water : log Pow: 2 - 7

Vapour pressure : 38 - 49 kPa (38.0 °C)  
Method: Unspecified  
  
60 - 90 kPa (50.0 °C)  
Method: Unspecified

Relative density : Data not available

Density : 700 - 730 kg/m<sup>3</sup> (15.0 °C)  
Method: Unspecified

Relative vapour density : Data not available

Particle characteristics  
Particle size : Data not available

### 9.2 Other information

Explosive properties : Classification Code: Not classified.

Oxidizing properties : Not applicable

Evaporation rate : Data not available

Conductivity : Low conductivity: < 100 pS/m, The conductivity of this material makes it a static accumulator., A liquid is typically considered

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0	Revision Date.: 04.03.2026	SDS Number: 800001001508	Date of last issue: 10.05.2024 Print Date. 05.03.2026
-----------------	-------------------------------	-----------------------------	--

---

nonconductive if its conductivity is below 100 pS/m and is considered semi-conductive if its conductivity is below 10,000 pS/m., Whether a liquid is nonconductive or semiconductive, the precautions are the same., A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid

---

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

May oxidise in the presence of air.

#### 10.2 Chemical stability

Stable under normal conditions of use.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : No hazardous reaction is expected when handled and stored according to provisions

#### 10.4 Conditions to avoid

Conditions to avoid : Avoid heat, sparks, open flames and other ignition sources.

In certain circumstances product can ignite due to static electricity.

#### 10.5 Incompatible materials

Materials to avoid : Strong oxidising agents.

#### 10.6 Hazardous decomposition products

Hazardous decomposition products are not expected to form during normal storage. Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

---

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : Exposure may occur via inhalation, ingestion, skin absorption, skin or eye contact, and accidental ingestion.

#### Acute toxicity

##### Product:

Acute oral toxicity : LD50 Oral (Rat): > 2,000 mg/kg

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
Print Date. 05.03.2026

---

- Remarks: Low toxicity  
Based on available data, the classification criteria are not met.
- Acute inhalation toxicity : LC 50 (Rat): > 20 mg/l  
Exposure time: 4 h  
Remarks: Low toxicity
- Remarks: Based on available data, the classification criteria are not met.
- Acute dermal toxicity : LD 50 (Rabbit): > 2,000 mg/kg  
Remarks: Low toxicity  
Based on available data, the classification criteria are not met.
- Acute toxicity (other routes of administration) :  
Remarks: Exposure may occur via inhalation, ingestion, skin absorption, skin or eye contact, and accidental ingestion.

### Components:

#### **Toluene:**

- Acute oral toxicity : LD 50 (Rat, male): > 5,000 mg/kg  
Method: Test(s) equivalent or similar to OECD Test Guideline 401  
Remarks: Based on available data, the classification criteria are not met.
- Acute inhalation toxicity : LC 50 (Rat, male and female): > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Test(s) equivalent or similar to OECD Test Guideline 403  
Remarks: Based on available data, the classification criteria are not met.  
High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea.
- Acute dermal toxicity : LD 50 (Rabbit, male): > 5,000 mg/kg  
Method: Literature data  
Remarks: Based on available data, the classification criteria are not met.

#### **Xylene, mixed isomers:**

- Acute oral toxicity : LD 50 (Rat, male and female): > 2,000 mg/kg  
Method: EC Directive 92/69/EEC B.1 Acute Toxicity (Oral)  
Remarks: Based on available data, the classification criteria are not met.

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
Print Date. 05.03.2026

---

Acute inhalation toxicity : LC 50 (Rat, male): 6350 ppm  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Test(s) equivalent or similar to Directive 67/548/EEC, Annex V, B.2.  
Remarks: Harmful if inhaled.

Acute dermal toxicity : LD 50 (Rabbit, male): > 2,000 mg/kg  
Method: Literature data  
Test substance: m-xylene  
Remarks: Based on available data, the classification criteria are not met.  
Information given is based on data obtained from similar substances.

### **n-Hexane:**

Acute oral toxicity : LD50 (Rat, male and female): 16,000 mg/kg  
Method: OECD Test Guideline 401  
Remarks: Low toxicity

Acute inhalation toxicity : LC50 (Rat): > 17600 mg/m<sup>3</sup>  
Exposure time: 24 h  
Remarks: Low toxicity by inhalation.

Acute dermal toxicity : LD50 (Rabbit): > 5 mg/kg bw  
Method: OECD Test Guideline 402  
Remarks: Low toxicity

### **Ethylbenzene:**

Acute oral toxicity : LD50 (Rat): > 2000 - 5000 mg/kg  
Remarks: May be harmful if swallowed.

Acute inhalation toxicity : LC50: > 10 - 20 mg/l  
Remarks: Harmful if inhaled.

Acute dermal toxicity : LD50 (Rabbit): > 5000 mg/kg  
Remarks: Low toxicity

### **Cyclohexane:**

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg  
Assessment: The component/mixture is minimally toxic after single ingestion.  
Remarks: Based on available data, the classification criteria are not met.

Acute inhalation toxicity : LC 50 (Rat): > 20 mg/l  
Assessment: The component/mixture is minimally toxic after

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
Print Date. 05.03.2026

---

short term inhalation.

Remarks: Based on available data, the classification criteria are not met.

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2,000 mg/kg  
Assessment: The component/mixture is minimally toxic after single contact with skin.  
Remarks: Based on available data, the classification criteria are not met.

### **Cumene:**

Acute oral toxicity : LD50 (Rat): 2,000 - 5,000 mg/kg  
Method: Test(s) equivalent or similar to OECD Test Guideline 401  
Remarks: Based on available data, the classification criteria are not met.

Acute inhalation toxicity : LC50 (Rat, male): > 20 mg/l  
Exposure time: 1 h  
Method: Acceptable non-standard method.  
Remarks: Based on available data, the classification criteria are not met.

Acute dermal toxicity : LD50 (Rabbit, male and female): 2,000 - 5,000 mg/kg  
Method: Acceptable non-standard method.  
Remarks: Based on available data, the classification criteria are not met.

### **Benzene:**

Acute oral toxicity : LD 50 (Rat, male): > 2,000 mg/kg  
Method: Test(s) equivalent or similar to OECD Test Guideline 401  
Remarks: Based on available data, the classification criteria are not met.

Acute inhalation toxicity : LC 50 (Rat, female): > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Test(s) equivalent or similar to OECD Test Guideline 403  
Remarks: Based on available data, the classification criteria are not met.  
High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea; continued inhalation may result in unconsciousness and/or death.

Acute dermal toxicity : LD 50 (Rabbit): > 2,000 mg/kg  
Method: Test(s) equivalent or similar to OECD Test Guideline

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
Print Date. 05.03.2026

---

402

Remarks: Based on available data, the classification criteria are not met.

### Skin corrosion/irritation

#### Product:

Remarks : Irritating to skin.

#### Components:

##### **Toluene:**

Species : Rabbit  
Method : Test(s) equivalent or similar to OECD Test Guideline 404  
Remarks : Causes skin irritation.

##### **Xylene, mixed isomers:**

Species : Rabbit  
Method : Literature data  
Remarks : Causes skin irritation.

##### **n-Hexane:**

Species : Rabbit  
Exposure time : 24 h  
Method : OECD Test Guideline 404  
Result : Skin irritation  
Remarks : Causes skin irritation.  
Repeated exposure may cause skin dryness or cracking.

##### **Ethylbenzene:**

Remarks : Causes skin irritation.

##### **Cyclohexane:**

Remarks : Causes skin irritation.

##### **Cumene:**

Species : Rabbit  
Method : Test(s) equivalent or similar to OECD Test Guideline 404  
Remarks : Slightly irritating to skin.  
Insufficient to classify.

##### **Benzene:**

Species : Rabbit  
Method : OECD Test Guideline 404

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
Print Date. 05.03.2026

---

Remarks : Causes skin irritation.

### Serious eye damage/eye irritation

#### Product:

Remarks : Not irritating to eye.  
Based on available data, the classification criteria are not met.

#### Components:

##### **Toluene:**

Species : Rabbit  
Method : OECD Test Guideline 405  
Remarks : Slightly irritating.  
Insufficient to classify.

##### **Xylene, mixed isomers:**

Species : Rabbit  
Method : Acceptable non-standard method.  
Remarks : Causes serious eye irritation.

##### **n-Hexane:**

Species : Rabbit  
Method : OECD Test Guideline 405  
Result : No eye irritation

##### **Ethylbenzene:**

Remarks : Causes serious eye irritation.

##### **Cyclohexane:**

Remarks : Based on available data, the classification criteria are not met.

##### **Cumene:**

Species : Rabbit  
Method : Test(s) equivalent or similar to OECD Test Guideline 405  
Remarks : Slightly irritating to the eye.  
Insufficient to classify.

##### **Benzene:**

Species : Rabbit  
Method : Literature data  
Remarks : Causes serious eye irritation.

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
Print Date. 05.03.2026

---

### Respiratory or skin sensitisation

#### Product:

Remarks : Not a sensitiser.  
Based on available data, the classification criteria are not met.

#### Components:

##### **Toluene:**

Species : Guinea pig  
Method : Test(s) equivalent or similar to OECD Test Guideline 406  
Remarks : Based on available data, the classification criteria are not met.

##### **Xylene, mixed isomers:**

Species : Mouse  
Method : Test(s) equivalent or similar to OECD Test Guideline 429  
Remarks : Based on available data, the classification criteria are not met.

##### **n-Hexane:**

Test Type : Local lymph node assay (LLNA)  
Species : Mouse  
Method : OECD Test Guideline 429  
Result : negative

##### **Ethylbenzene:**

Remarks : Not a sensitiser.  
Based on available data, the classification criteria are not met.

##### **Cyclohexane:**

Remarks : Based on available data, the classification criteria are not met.

##### **Cumene:**

Species : Guinea pig  
Method : Test(s) equivalent or similar to OECD Test Guideline 406  
Remarks : Not a sensitiser.  
Based on available data, the classification criteria are not met.

##### **Benzene:**

Species : Mouse  
Method : Literature data  
Remarks : Based on available data, the classification criteria are not met.

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
Print Date. 05.03.2026

---

### **Germ cell mutagenicity**

#### **Product:**

Genotoxicity in vivo : Remarks: Non mutagenic  
Based on available data, the classification criteria are not met.

Germ cell mutagenicity- Assessment : This product does not meet the criteria for classification in categories 1A/1B.

#### **Components:**

#### **Toluene:**

Genotoxicity in vitro : Method: Test(s) equivalent or similar to OECD Guideline 471  
Remarks: Based on available data, the classification criteria are not met.

Method: Test(s) equivalent or similar to OECD Test Guideline 476

Remarks: Based on available data, the classification criteria are not met.

Genotoxicity in vivo : Species: Rat  
Method: Acceptable non-standard method.  
Remarks: Based on available data, the classification criteria are not met.

Germ cell mutagenicity- Assessment : This product does not meet the criteria for classification in categories 1A/1B.

#### **Xylene, mixed isomers:**

Genotoxicity in vitro : Method: Test(s) equivalent or similar to Directive 67/548/EEC, Annex V, B.10  
Remarks: Based on available data, the classification criteria are not met.

Method: Test(s) equivalent or similar to Directive 67/548/EEC, Annex V, B.19

Remarks: Based on available data, the classification criteria are not met.

Genotoxicity in vivo : Species: Mouse  
Method: OECD Test Guideline 478  
Remarks: Based on available data, the classification criteria are not met.

Germ cell mutagenicity- Assessment : This product does not meet the criteria for classification in categories 1A/1B.

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
Print Date. 05.03.2026

---

### **n-Hexane:**

Genotoxicity in vitro : Test Type: Ames test  
Test system: Salmonella typhimurium  
Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 471  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Test system: mouse lymphoma cells  
Metabolic activation: with and without metabolic activation  
Method: OECD Test Guideline 476  
Result: negative

Genotoxicity in vivo : Test Type: Chromosome aberration test in vitro  
Species: Rat  
Cell type: Bone marrow  
Application Route: oral (gavage)  
Method: OECD Test Guideline 475  
Result: negative

Test Type: dominant lethal test  
Species: Mouse  
Application Route: inhalation (vapour)  
Method: OECD Test Guideline 478  
Result: negative

Germ cell mutagenicity- Assessment : This product does not meet the criteria for classification in categories 1A/1B.

### **Ethylbenzene:**

Genotoxicity in vivo : Remarks: Not mutagenic.

Germ cell mutagenicity- Assessment : This product does not meet the criteria for classification in categories 1A/1B.

### **Cyclohexane:**

Genotoxicity in vitro : Remarks: Non mutagenic  
Based on available data, the classification criteria are not met.

### **Cumene:**

Genotoxicity in vitro : Method: Test(s) equivalent or similar to OECD Test Guideline 476  
Remarks: Based on available data, the classification criteria are not met.

Genotoxicity in vivo : Species: Mouse  
Method: OECD Test Guideline 474

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
Print Date. 05.03.2026

---

Remarks: Based on available data, the classification criteria are not met.

Germ cell mutagenicity- Assessment : This product does not meet the criteria for classification in categories 1A/1B.

### **Benzene:**

Genotoxicity in vitro : Method: OECD Test Guideline 471  
Remarks: May cause genetic defects.

Method: Other guideline method.  
Remarks: May cause genetic defects.

Method: Literature data  
Remarks: May cause genetic defects.

Genotoxicity in vivo : Species: Mouse  
Method: Test(s) equivalent or similar to OECD Test Guideline 474  
Remarks: May cause genetic defects.

Germ cell mutagenicity- Assessment : May cause genetic defects.

### **Carcinogenicity**

#### **Product:**

Remarks : Contains Cumene, CAS# 98-82-8.  
An increased tumour incidence has been observed in experimental animals; the significance of this finding to man is unknown.  
Not classified as a carcinogen.

Carcinogenicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

#### **Components:**

##### **Gasoline:**

Remarks : Contains Cumene, CAS# 98-82-8.  
An increased tumour incidence has been observed in experimental animals; the significance of this finding to man is unknown.

#### **Components:**

##### **Toluene:**

Species : Rat, male and female

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
Print Date. 05.03.2026

---

Application Route : Inhalation  
Method : OECD Test Guideline 453  
Remarks : Based on available data, the classification criteria are not met.

Carcinogenicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

### **Xylene, mixed isomers:**

Species : Rat, male and female  
Application Route : Oral  
Method : Test(s) equivalent or similar to Directive 67/548/EEC, Annex V, B.32  
Remarks : Based on available data, the classification criteria are not met.

Carcinogenicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

### **n-Hexane:**

Remarks : No data available

Carcinogenicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

### **Ethylbenzene:**

Remarks : Limited evidence of carcinogenic effect  
Causes cancer in laboratory animals.

Carcinogenicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

### **Cyclohexane:**

Remarks : Not a carcinogen.  
Based on available data, the classification criteria are not met.

### **Cumene:**

Species : Mouse, male and female  
Application Route : Inhalation  
Method : Test(s) equivalent or similar to OECD Test Guideline 451  
Remarks : An increased tumour incidence has been observed in experimental animals; the significance of this finding to man is unknown.

Carcinogenicity - Assessment : May cause cancer.

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
Print Date. 05.03.2026

### Benzene:

Species : Rat, male and female  
Application Route : Oral  
Method : Other guideline method.  
Remarks : May cause cancer.  
Known human carcinogen.  
May cause leukaemia (AML - acute myelogenous leukaemia).

Species : Mouse, male and female  
Application Route : Inhalation  
Method : Literature data  
Remarks : May cause cancer.  
Known human carcinogen.  
May cause leukaemia (AML - acute myelogenous leukaemia).

Carcinogenicity - Assessment : May cause cancer.

Material	GHS/CLP Carcinogenicity Classification
Toluene	No carcinogenicity classification.
Tetraethyl lead	No carcinogenicity classification.
Gasoline	Carcinogenicity Category 1B
Trimethylbenzene (all isomers)	No carcinogenicity classification.
Xylene, mixed isomers	No carcinogenicity classification.
n-Hexane	No carcinogenicity classification.
Naphthalene	Carcinogenicity Category 2
Ethylbenzene	No carcinogenicity classification.
Cyclohexane	No carcinogenicity classification.
Cumene	Carcinogenicity Category 1B
Benzene	Carcinogenicity Category 1A

Material	Other Carcinogenicity Classification
Toluene	IARC: Group 3: Not classifiable as to its carcinogenicity to humans
Tetraethyl lead	IARC: Group 3: Not classifiable as to its carcinogenicity to humans
Gasoline	IARC: Group 2B: Possibly carcinogenic to humans
Xylene, mixed isomers	IARC: Group 3: Not classifiable as to its carcinogenicity to humans

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
Print Date. 05.03.2026

	humans
Naphthalene	IARC: Group 2B: Possibly carcinogenic to humans
Ethylbenzene	IARC: Group 2B: Possibly carcinogenic to humans
Cumene	IARC: Group 2B: Possibly carcinogenic to humans
Benzene	IARC: Group 1: Carcinogenic to humans

### Reproductive toxicity

#### Product:

Effects on fertility :  
Remarks: Does not impair fertility.  
Remarks: Contains n-Hexane, CAS # 110-54-3.  
Remarks: Contains Toluene, CAS # 108-88-3., Many case studies involving abuse during pregnancy indicate that toluene can cause birth defects, growth retardation and learning difficulties.

Reproductive toxicity - Assessment : Category 1B

#### Components:

##### **Toluene:**

Effects on fertility : Species: Rat  
Sex: male and female  
Application Route: Inhalation  
Method: OECD Test Guideline 416  
Remarks: Based on available data, the classification criteria are not met.

Reproductive toxicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

##### **Xylene, mixed isomers:**

Effects on fertility : Species: Rat  
Sex: male and female  
Application Route: Inhalation  
Method: Acceptable non-standard method.  
Remarks: Based on available data, the classification criteria are not met.

Reproductive toxicity - Assessment : This product does not meet the criteria for classification in

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
Print Date. 05.03.2026

---

assessment categories 1A/1B.

### **n-Hexane:**

Effects on fertility :  
Remarks: Suspected of damaging fertility or the unborn child.

Reproductive toxicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

### **Ethylbenzene:**

Effects on fertility :  
Remarks: Not a developmental toxicant., Based on available data, the classification criteria are not met., Does not impair fertility.

Reproductive toxicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

### **Cyclohexane:**

Effects on fertility :  
Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are not met.

### **Cumene:**

Effects on fertility : Species: Rat  
Sex: male and female  
Application Route: Inhalation  
  
Method: Test(s) equivalent or similar to OECD Test Guideline 413  
Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are not met.

Reproductive toxicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

### **Benzene:**

Effects on fertility : Species: Rat  
Sex: male and female  
Application Route: Inhalation  
  
Method: Test(s) equivalent or similar to OECD Test Guideline 415.  
Remarks: Based on available data, the classification criteria

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
Print Date. 05.03.2026

---

are not met.

Reproductive toxicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

### STOT - single exposure

#### Product:

Remarks : High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea.

#### Components:

##### **Toluene:**

Exposure routes : Inhalation  
Target Organs : Central nervous system  
Remarks : May cause drowsiness or dizziness.  
Vapours may cause drowsiness and dizziness.  
Inhalation of vapours or mists may cause irritation to the respiratory system.

##### **Xylene, mixed isomers:**

Exposure routes : Inhalation  
Target Organs : Respiratory Tract  
Remarks : High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea; continued inhalation may result in unconsciousness.  
Inhalation of vapours or mists may cause irritation to the respiratory system.  
May cause respiratory irritation.

##### **n-Hexane:**

Remarks : May cause drowsiness and dizziness.  
Central nervous system (CNS)

##### **Ethylbenzene:**

Remarks : Inhalation of vapours or mists may cause irritation to the respiratory system.

##### **Cyclohexane:**

Remarks : May cause drowsiness and dizziness.

##### **Cumene:**

Exposure routes : Inhalation

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
Print Date. 05.03.2026

---

Target Organs : Respiratory Tract  
Remarks : High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea; continued inhalation may result in unconsciousness.  
May cause respiratory irritation.

### **Benzene:**

Remarks : Based on available data, the classification criteria are not met. Inhalation of vapours or mists may cause irritation to the respiratory system.

### **STOT - repeated exposure**

#### **Product:**

Remarks : May cause damage to organs or organ systems through prolonged or repeated exposure.

Exposure routes : Inhalation  
Target Organs : Liver, Kidney, Brain

### **Components:**

#### **Toluene:**

Exposure routes : Inhalation  
Target Organs : Central nervous system  
Remarks : May cause damage to organs or organ systems through prolonged or repeated exposure.  
May cause damage to central nervous system, respiratory system, visual system, and auditory system through prolonged or repeated exposure.  
Effects were seen at high doses only.  
Visual system: may cause decreased color perception.  
These subtle changes have not been found to lead to functional colour vision deficits.  
Auditory system: prolonged and repeated exposures to high concentrations have resulted in hearing loss in rats.  
Solvent abuse and noise interaction in the work environment may cause hearing loss.  
Exposure to very high concentrations of similar materials has been associated with irregular heart rhythms and cardiac arrest.  
Abuse of vapours has been associated with organ damage and death.

#### **Xylene, mixed isomers:**

Exposure routes : Inhalation  
Target Organs : Auditory system

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
Print Date. 05.03.2026

---

Remarks : May cause damage to organs or organ systems through prolonged or repeated exposure.  
Harmful: danger of serious damage to health by prolonged exposure through inhalation.  
Solvent abuse and noise interaction in the work environment may cause hearing loss.

### **n-Hexane:**

Remarks : Central nervous system: repeated exposure affects the nervous system.  
Peripheral nervous system: causes peripheral neuropathy which can be potentiated by ketones.  
Kidney: caused kidney effects in male rats which are not considered relevant to humans

### **Ethylbenzene:**

Remarks : Harmful: danger of serious damage to health by prolonged exposure through inhalation.  
Auditory system: prolonged and repeated exposures to high concentrations have resulted in hearing loss in rats. Solvent abuse and noise interaction in the work environment may cause hearing loss.  
Kidney: can cause kidney damage.  
Liver: can cause liver damage.  
Central nervous system: repeated exposure affects the nervous system.

### **Cyclohexane:**

Remarks : Based on available data, the classification criteria are not met.

### **Cumene:**

Remarks : Kidney: caused kidney effects in male rats which are not considered relevant to humans  
Based on available data, the classification criteria are not met.

### **Benzene:**

Exposure routes : Oral, Inhalation  
Target Organs : hematopoietic system  
Remarks : Causes damage to organs through prolonged or repeated exposure.  
Blood-forming organs: repeated exposure affects the bone marrow.  
Blood: may cause haemolysis of red blood cells and/or anaemia.  
Immune System: animal studies on this material or its components have demonstrated immunotoxicity.

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
Print Date. 05.03.2026

---

May cause MDS (Myelodysplastic Syndrome).  
Exposure to very high concentrations of similar materials has been associated with irregular heart rhythms and cardiac arrest.  
Myelodysplastic syndrome (MDS) was observed in individuals exposed to very high levels (50 ppm to 300 ppm range) of benzene over a long period of time in the workplace. The relevance of these results to lower levels of exposure is not known.

### Components:

#### **Toluene:**

Species : Rat, male and female  
Application Route : Oral  
Method : Test(s) equivalent or similar to Directive 67/548/EEC, Annex V, B.26  
Target Organs : No specific target organs noted

Species : Rat, male and female  
Application Route : Inhalation  
Test atmosphere : vapour  
Method : Test(s) equivalent or similar to OECD Test Guideline 453  
Target Organs : Central nervous system

#### **Xylene, mixed isomers:**

Species : Rat, male and female  
Application Route : Oral  
Method : Test(s) equivalent or similar to OECD Test Guideline 408  
Target Organs : No specific target organs noted  
Remarks : Over exposures of humans to xylene or xylene solvent mixtures produced predominately central nervous system (CNS) effects with less common effects reported to the lung, gastrointestinal tract, liver, kidney and heart.  
Available animal and human results in auditory system provide limited evidence that xylenes may induce decrements in human hearing, and it was unclear if these changes were temporary or permanent.

Species : Rat, male  
Application Route : Inhalation  
Test atmosphere : vapour  
Method : Literature data  
Target Organs : Auditory system  
Remarks : Over exposures of humans to xylene or xylene solvent mixtures produced predominately central nervous system (CNS) effects with less common effects reported to the lung, gastrointestinal tract, liver, kidney and heart.

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
Print Date. 05.03.2026

---

Available animal and human results in auditory system provide limited evidence that xylenes may induce decrements in human hearing, and it was unclear if these changes were temporary or permanent.

### **Cumene:**

Species : Rat, male  
Application Route : Oral  
Method : Acceptable non-standard method.  
Target Organs : No specific target organs noted

Species : Rat, male and female  
Application Route : Inhalation  
Test atmosphere : vapour  
Method : OECD Test Guideline 413  
Target Organs : No specific target organs noted

### **Benzene:**

Species : Rat, male and female  
Application Route : Oral  
Method : Test(s) equivalent or similar to OECD Test Guideline 408  
Target Organs : hematopoietic system

Species : Mouse, male and female  
Application Route : Inhalation  
Test atmosphere : vapour  
Method : Literature data  
Target Organs : hematopoietic system

### **Aspiration toxicity**

#### **Product:**

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

#### **Components:**

##### **Toluene:**

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

##### **Xylene, mixed isomers:**

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0	Revision Date.: 04.03.2026	SDS Number: 800001001508	Date of last issue: 10.05.2024 Print Date. 05.03.2026
-----------------	-------------------------------	-----------------------------	--

---

### **n-Hexane:**

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

### **Ethylbenzene:**

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

### **Cyclohexane:**

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

### **Cumene:**

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

### **Benzene:**

May be fatal if swallowed and enters airways.

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

## 11.2 Information on other hazards

### **Endocrine disrupting properties**

#### **Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### **Further information**

#### **Product:**

Remarks : Exposure to very high concentrations of similar materials has been associated with irregular heart rhythms and cardiac arrest.

Remarks : Classifications by other authorities under varying regulatory frameworks may exist.

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
Print Date. 05.03.2026

---

### Components:

#### **Toluene:**

Remarks : Classifications by other authorities under varying regulatory frameworks may exist.

#### **Xylene, mixed isomers:**

Remarks : Classifications by other authorities under varying regulatory frameworks may exist.

#### **n-Hexane:**

Remarks : Classifications by other authorities under varying regulatory frameworks may exist.

#### **Ethylbenzene:**

Remarks : Classifications by other authorities under varying regulatory frameworks may exist.

#### **Cyclohexane:**

Remarks : Exposure to very high concentrations of similar materials has been associated with irregular heart rhythms and cardiac arrest.

#### **Cumene:**

Remarks : Classifications by other authorities under varying regulatory frameworks may exist.

#### **Benzene:**

Remarks : Classifications by other authorities under varying regulatory frameworks may exist.

---

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Product:

Toxicity to fish : Remarks: LL/EL/IL50 > 1 <= 10 mg/l  
Toxic

Toxicity to daphnia and other : Remarks: LL/EL/IL50 > 1 <= 10 mg/l

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
Print Date. 05.03.2026

---

aquatic invertebrates      Toxic

Toxicity to algae/aquatic plants      :      Remarks: LL/EL/IL50 > 1 <= 10 mg/l  
Toxic

Toxicity to fish (Chronic toxicity)      :      Remarks: NOEC/NOEL/EL10 > 1.0 - <= 10 mg/l

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)      :      Remarks: NOEC/NOEL/EL10 > 1.0 - <= 10 mg/l

Toxicity to microorganisms      :      Remarks: LL/EL/IL50 >10 <= 100 mg/l  
Harmful

### Components:

#### **Tetraethyl lead:**

M-Factor (Acute aquatic toxicity)      :      1

### Components:

#### **Toluene:**

Toxicity to fish      :      LC50 (Oncorhynchus kisutch (coho salmon)): 4.02 mg/l  
Exposure time: 96 h  
Method: Literature data.  
Remarks: Toxic  
LC/EC/IC50 >1 - <=10 mg/l

Toxicity to daphnia and other aquatic invertebrates      :      LC50 (Ceriodaphnia dubia (water flea)): 3.78 mg/l  
Exposure time: 48 h  
Method: Other guideline method.  
Remarks: Toxic  
LC/EC/IC50 >1 - <=10 mg/l

Toxicity to algae/aquatic plants      :      EC50 (Chlorella vulgaris (Fresh water algae)): 134 mg/l  
Exposure time: 3 h  
Method: Literature data.  
Remarks: Practically non toxic:  
LC/EC/IC50 > 100 mg/l

Toxicity to microorganisms      :      EC50 (Nitrosomonas): 84 mg/l  
Exposure time: 24 h  
Method: Literature data.  
Remarks: Harmful  
LL/EL/IL50 10-100 mg/l

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
Print Date. 05.03.2026

---

Toxicity to fish (Chronic toxicity) : NOEC: 1.4 mg/l  
Exposure time: 40 d  
Species: Oncorhynchus kisutch (coho salmon)  
Method: Literature data.  
Remarks: NOEC/NOEL/EL10 > 1.0 - <= 10 mg/l

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0.74 mg/l  
Exposure time: 7 d  
Species: Ceriodaphnia dubia (Water flea)  
Method: Other guideline method.  
Remarks: NOEC/NOEL/EL10 > 0.1 - <=1.0 mg/l

### Xylene, mixed isomers:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2.6 mg/l  
Exposure time: 96 h  
Method: Information given is based on data obtained from similar substances.  
Remarks: Toxic  
LL/EL/IL50 > 1 <= 10 mg/l

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 3.82 mg/l  
Exposure time: 48 h  
Method: Information given is based on data obtained from similar substances.  
Remarks: Toxic  
LC/EC/IC50 >1 - <=10 mg/l

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (algae)): 2.2 mg/l  
Exposure time: 72 h  
Method: Information given is based on data obtained from similar substances.  
Remarks: Toxic  
LC/EC/IC50 >1 - <=10 mg/l

Toxicity to microorganisms : EC50 (Activated sludge): > 157 mg/l  
Exposure time: 3 h  
Method: Information given is based on data obtained from similar substances.  
Remarks: Practically non toxic:  
LL/EL/IL50 > 100 mg/l

Toxicity to fish (Chronic toxicity) : NOEC: > 1.3 mg/l  
Exposure time: 56 d  
Species: Oncorhynchus mykiss (rainbow trout)  
Method: Literature data.  
Remarks: NOEC/NOEL/EL10 > 1.0 - <= 10 mg/l

Toxicity to daphnia and other : NOEC: 0.96 mg/l

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
Print Date. 05.03.2026

aquatic invertebrates (Chronic toxicity)

Exposure time: 7 d  
Species: Ceriodaphnia dubia (Water flea)  
Method: Other guideline method.  
Remarks: NOEC/NOEL/EL10 > 0.1 - <=1.0 mg/l

### n-Hexane:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 2.5 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : NOELR (Daphnia magna Straus): > 100 mg/l  
Exposure time: 72 h  
Method: Test(s) equivalent or similar to OECD Guideline 202  
Remarks: Toxic

Toxicity to algae/aquatic plants : LOELR (Raphidocelis subcapitata (freshwater green alga)): <= 21.3 mg/l  
Exposure time: 72 h  
Method: Test(s) equivalent or similar to OECD Test Guideline 201

NOELR (Raphidocelis subcapitata (freshwater green alga)): < 21.3 mg/l  
Exposure time: 72 h  
Method: Test(s) equivalent or similar to OECD Test Guideline 201

Toxicity to microorganisms :  
Remarks: Data not available

Toxicity to fish (Chronic toxicity) : Remarks: Data not available

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : Remarks: Data not available

### Naphthalene:

M-Factor (Acute aquatic toxicity) : 1

### Ethylbenzene:

Toxicity to fish : Remarks: Toxic  
LC/EC/IC50 >1 - <=10 mg/l

Toxicity to daphnia and other aquatic invertebrates : Remarks: Toxic  
LC/EC/IC50 >1 - <=10 mg/l

Toxicity to algae/aquatic plants : EC50 : Remarks: Toxic  
LC/EC/IC50 >1 - <=10 mg/l

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
Print Date. 05.03.2026

---

- Toxicity to microorganisms :  
Remarks: Harmful  
LC/EC/IC50 >10 - <=100 mg/l
- Toxicity to fish (Chronic toxicity) : Remarks: NOEC/NOEL/EL10 > 0.1 - <=1.0 mg/l
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : Remarks: NOEC/NOEL/EL10 > 0.1 - <=1.0 mg/l
- Cyclohexane:**
- Toxicity to fish : LC50 : 1 - 10 mg/l  
Remarks: Toxic to fish.
- Toxicity to daphnia and other aquatic invertebrates : LC50 : < 1 mg/l  
Remarks: Very toxic.
- M-Factor (Acute aquatic toxicity) : 1
- Toxicity to microorganisms : LL50 : 10 - 100 mg/l  
Remarks: Harmful
- Toxicity to fish (Chronic toxicity) : Remarks: Data not available
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : Remarks: Data not available
- M-Factor (Chronic aquatic toxicity) : 1
- Cumene:**
- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 4.8 mg/l  
Remarks: Toxic
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 2.14 mg/l  
Exposure time: 48 h  
Method: Test(s) equivalent or similar to OECD Guideline 202  
Remarks: Toxic
- Toxicity to algae/aquatic plants : EC50 (green algae): 2.01 mg/l  
Exposure time: 72 h  
Method: Test(s) equivalent or similar to OECD Test Guideline 201  
Remarks: Toxic
- Toxicity to microorganisms : EC50 : > 2,000 mg/l  
Exposure time: 3 h  
Method: Test(s) equivalent or similar to OECD Guideline 209

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
Print Date. 05.03.2026

---

Toxicity to fish (Chronic toxicity) : NOEC: 0.38 mg/l  
Exposure time: 30 d  
Species: Danio rerio (zebra fish)  
Method: Based on quantitative structure-activity relationship (QSAR) modelling

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0.35 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Method: Test(s) equivalent or similar to OECD Guideline 211

### **Benzene:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 5.3 mg/l  
Exposure time: 96 h  
Method: Test(s) equivalent or similar to OECD Guideline 203  
Remarks: Toxic  
LL/EL/IL50 > 1 <= 10 mg/l

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 10 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202  
Remarks: Toxic  
LL/EL/IL50 > 1 <= 10 mg/l

Toxicity to algae/aquatic plants : ErC50 (Selenastrum capricornutum (green algae)): 100 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201  
Remarks: Harmful  
LL/EL/IL50 >10 <= 100 mg/l

Toxicity to microorganisms : IC50 (Nitrosomonas): 13 mg/l  
Exposure time: 24 h  
Method: Literature data.  
Remarks: Harmful  
LL/EL/IL50 >10 <= 100 mg/l

Toxicity to fish (Chronic toxicity) : NOEC: 0.8 mg/l  
Exposure time: 32 d  
Species: Pimephales promelas (fathead minnow)  
Method: Other guideline method.  
Remarks: NOEC/NOEL/EL10 > 0.1 - <=1.0 mg/l

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 3 mg/l  
Exposure time: 7 d  
Species: Ceriodaphnia dubia (Water flea)  
Method: Other guideline method.  
Remarks: NOEC/NOEL/EL10 > 1.0 - <= 10 mg/l

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
Print Date. 05.03.2026

---

### 12.2 Persistence and degradability

#### Product:

Biodegradability : Remarks: Oxidises rapidly by photo-chemical reactions in air.  
Major constituents are inherently biodegradable, but contains components that may persist in the environment.  
Based on available data, the classification criteria are not met.  
Not Persistent per IMO criteria.  
International Oil Pollution Compensation (IOPC) Fund definition:  
"A non-persistent oil is oil, which, at the time of shipment, consists of hydrocarbon fractions, (a) at least 50% of which, by volume, distills at a temperature of 340°C (645°F) and (b) at least 95% of which, by volume, distils at a temperature of 370°C (700°F) when tested by the ASTM Method D-86/78 or any subsequent revision thereof."

#### Components:

##### **Toluene:**

Biodegradability : Biodegradation: 81 %  
Exposure time: 5 d  
Method: ASTM D1252-67  
Remarks: Readily biodegradable.  
  
Remarks: Not Persistent per IMO criteria.  
International Oil Pollution Compensation (IOPC) Fund definition:  
"A non-persistent oil is oil, which, at the time of shipment, consists of hydrocarbon fractions, (a) at least 50% of which, by volume, distills at a temperature of 340°C (645°F) and (b) at least 95% of which, by volume, distils at a temperature of 370°C (700°F) when tested by the ASTM Method D-86/78 or any subsequent revision thereof."

##### **Xylene, mixed isomers:**

Biodegradability : Biodegradation: 87.8 %  
Exposure time: 28 d  
Method: Information given is based on data obtained from similar substances.  
Remarks: Readily biodegradable.

##### **n-Hexane:**

Biodegradability : Remarks: Readily biodegradable.  
Oxidises rapidly by photo-chemical reactions in air.

##### **Ethylbenzene:**

Biodegradability : Remarks: Readily biodegradable.  
Oxidises rapidly by photo-chemical reactions in air.

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
Print Date. 05.03.2026

---

Not Persistent per IMO criteria.  
International Oil Pollution Compensation (IOPC) Fund definition:  
"A non-persistent oil is oil, which, at the time of shipment, consists of hydrocarbon fractions, (a) at least 50% of which, by volume, distills at a temperature of 340°C (645°F) and (b) at least 95% of which, by volume, distils at a temperature of 370°C (700°F) when tested by the ASTM Method D-86/78 or any subsequent revision thereof."

### **Cyclohexane:**

Biodegradability : Remarks: Readily biodegradable.

### **Cumene:**

Biodegradability : Remarks: Rapidly biodegradable under aerobic conditions.  
Oxidises rapidly by photo-chemical reactions in air.

### **Benzene:**

Biodegradability : Biodegradation: 96 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F  
Remarks: Readily biodegradable.  
Not Persistent per IMO criteria.  
International Oil Pollution Compensation (IOPC) Fund definition:  
"A non-persistent oil is oil, which, at the time of shipment, consists of hydrocarbon fractions, (a) at least 50% of which, by volume, distills at a temperature of 340°C (645°F) and (b) at least 95% of which, by volume, distils at a temperature of 370°C (700°F) when tested by the ASTM Method D-86/78 or any subsequent revision thereof."

## 12.3 Bioaccumulative potential

### **Product:**

Bioaccumulation : Remarks: Contains constituents with the potential to bioaccumulate.

### **Components:**

#### **Toluene:**

Bioaccumulation : Remarks: Does not bioaccumulate significantly.

#### **Xylene, mixed isomers:**

Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)  
Exposure time: 56 d  
Bioconcentration factor (BCF): 29  
Method: Literature data.

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
Print Date. 05.03.2026

---

Remarks: Does not bioaccumulate significantly.

Partition coefficient: n-octanol/water : log Pow: 3.16  
Method: Literature data.

### **n-Hexane:**

Bioaccumulation : Remarks: Has the potential to bioaccumulate.

### **Ethylbenzene:**

Bioaccumulation : Remarks: Does not bioaccumulate significantly.

### **Cyclohexane:**

Bioaccumulation : Remarks: Does not significantly accumulate in organisms.

### **Cumene:**

Bioaccumulation : Remarks: Does not bioaccumulate significantly.

### **Benzene:**

Bioaccumulation : Species: Leuciscus idus (Golden orfe)  
Exposure time: 3 d  
Bioconcentration factor (BCF): < 10  
Method: Test(s) equivalent or similar to OECD Test Guideline 305  
Remarks: Does not bioaccumulate significantly.

## 12.4 Mobility in soil

### **Product:**

Mobility : Remarks: If the product enters soil, one or more constituents will or may be mobile and may contaminate groundwater., Floats on water.

### **Components:**

#### **Toluene:**

Mobility : Remarks: Floats on water., If the product enters soil, one or more constituents will or may be mobile and may contaminate groundwater.

#### **Xylene, mixed isomers:**

Mobility : Remarks: Floats on water., If it enters soil, it will adsorb to soil particles and will not be mobile.

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
Print Date. 05.03.2026

---

### **n-Hexane:**

Mobility : Remarks: Floats on water., If it enters soil, it will adsorb to soil particles and will not be mobile.

### **Ethylbenzene:**

Mobility : Remarks: If the product enters soil, one or more constituents will or may be mobile and may contaminate groundwater., Floats on water.

### **Cyclohexane:**

Mobility : Remarks: Floats on water., Adsorbs to soil and has low mobility

### **Cumene:**

Mobility : Remarks: Floats on water., If the product enters soil, one or more constituents will or may be mobile and may contaminate groundwater.

### **Benzene:**

Mobility : Remarks: Floats on water.

## 12.5 Results of PBT and vPvB assessment

### **Product:**

Assessment : This mixture does not contain any REACH registered substances that are assessed to be a PBT or a vPvB..

### **Components:**

#### **Toluene:**

Assessment : The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB..

#### **Xylene, mixed isomers:**

Assessment : The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB..

#### **n-Hexane:**

Assessment : The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB..

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
Print Date. 05.03.2026

---

### **Ethylbenzene:**

Assessment : The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB..

### **Cyclohexane:**

Assessment : The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB..

### **Cumene:**

Assessment : The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB..

### **Benzene:**

Assessment : The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB..

## 12.6 Endocrine disrupting properties

### **Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## 12.7 Other adverse effects

### **Product:**

Additional ecological information : Films formed on water may affect oxygen transfer and damage organisms.

### **Components:**

#### **n-Hexane:**

Additional ecological information : Does not have ozone depletion potential.

#### **Ethylbenzene:**

Additional ecological information : In view of the high rate of loss from solution, the product is unlikely to pose a significant hazard to aquatic life.

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version	Revision Date.:	SDS Number:	Date of last issue: 10.05.2024
10.0	04.03.2026	800001001508	Print Date. 05.03.2026

---

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

- Product : Recover or recycle if possible.  
It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.  
Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment.  
Do not dispose into the environment, in drains or in water courses.  
Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination.  
Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.  
MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides technical aspects at controlling pollutions from ships.
- Contaminated packaging : Drain container thoroughly.  
After draining, vent in a safe place away from sparks and fire.  
Residues may cause an explosion hazard.  
Do not puncture, cut, or weld uncleaned drums.  
Send to drum recoverer or metal reclaimer.  
Do not pollute the soil, water or environment with the waste container.
- Local legislation
- Remarks : EU Waste Disposal Code (EWC):  
13 07 02\* petrol.  
The number given to waste is associated with the appropriate usage. The user must decide if their particular use results in another waste code being assigned.  
  
Disposal should be in accordance with applicable regional, national, and local laws and regulations.  
Local regulations may be more stringent than regional or national requirements and must be complied with.  
  
Hazardous Waste (England and Wales) Regulations 2005.

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version            Revision Date.:            SDS Number:            Date of last issue: 10.05.2024  
10.0                04.03.2026                800001001508            Print Date. 05.03.2026

---

---

### SECTION 14: Transport information

#### 14.1 UN number or ID number

**ADR**                                : 1203  
**RID**                                : 1203  
**IMDG**                              : 1203  
**IATA**                              : 1203

#### 14.2 UN proper shipping name

**ADR**                                : GASOLINE  
**RID**                                : GASOLINE  
**IMDG**                              : GASOLINE  
**IATA**                              : GASOLINE

#### 14.3 Transport hazard class(es)

**ADR**                                : 3  
**RID**                                : 3  
**IMDG**                              : 3  
**IATA**                              : 3

#### 14.4 Packing group

**ADR**  
Packing group                    : II  
Classification Code             : F1  
Hazard Identification Number : 33  
Labels                             : 3

**RID**  
Packing group                    : II  
Classification Code             : F1  
Hazard Identification Number : 33  
Labels                             : 3

**IMDG**  
Packing group                    : II  
Labels                             : 3

**IATA**  
Packing group                    : II  
Labels                             : 3

#### 14.5 Environmental hazards

**ADR**

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
Print Date. 05.03.2026

Environmentally hazardous : yes

### RID

Environmentally hazardous : yes

### IMDG

Marine pollutant : yes

#### 14.6 Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

#### 14.7 Maritime transport in bulk according to IMO instruments

Pollution category : Not applicable  
Ship type : Not applicable  
Product name : Not applicable  
Special precautions : Not applicable

**Additional Information** : MARPOL Annex 1 rules apply for bulk shipments by sea.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:  
Gasoline (Number on list 29, 28)  
Toluene (Number on list 48)  
Tetraethyl lead (Number on list 72, 63, 30)  
Cumene (Number on list 28)  
Benzene (Number on list 72, 5, 29, 28)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. 34a Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version	Revision Date.:	SDS Number:	Date of last issue: 10.05.2024
10.0	04.03.2026	800001001508	Print Date. 05.03.2026

### Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Environmental Protection Act 1990 (as amended). Health and Safety at Work etc. Act 1974. Consumers Protection Act 1987. Pollution Prevention and Control Act 1999. Environment Act 1995. Factories Act 1961. The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment (Amendment) Regulations 2011. Chemicals (Hazard Information and Packaging for Supply) Regulations 2009. Control of Substances Hazardous to Health Regulations 2002 (as amended). Merchant Shipping (Dangerous Goods and Marine Pollutants) Regulations 1997. Reporting of Injuries, Diseases and Dangerous Occurrences Regulations 1995 (as amended). Personal Protective Equipment Regulations 2002. Personal Protective Equipment at Work Regulations 1992. Hazardous Waste (England and Wales) Regulations 2005(as amended). Control of Major Accident Hazards Regulations 1999 (as amended). Renewable Transport Fuel Obligations Order 2007 (as amended). Energy Act 2011. Environmental Permitting (England and Wales) Regulations 2010 (as amended). Waste (England and Wales) Regulations 2011 (as amended). Planning (Hazardous Substances) Act 1990 and associated regulations. The Environmental Protection (Controls on Ozone-Depleting Substances) Regulations 2011.

Product is subject to the Control of Major Accident Hazards Regulations 2015 (2015 No. 483) based on Seveso III directive (2012/18/EU).

**REACH - List of substances subject to authorisation (Annex XIV) - Tetraethyl Lead**  
**Authorisation holder and number: Shell Nederland Raffinaderij B.V. - REACH/25/37/0.**  
**Authorised use: formulation of Avgas**  
**Expires: 30th April 2032.**

### 15.2 Chemical safety assessment.

A Chemical Safety Assessment was performed for all substances of this product.

## SECTION 16: Other information

### Full text of H-Statements

H224	: Extremely flammable liquid and vapour.
H225	: Highly flammable liquid and vapour.
H226	: Flammable liquid and vapour.
H300	: Fatal if swallowed.
H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H310	: Fatal in contact with skin.
H312	: Harmful in contact with skin.
H315	: Causes skin irritation.
H319	: Causes serious eye irritation.
H330	: Fatal if inhaled.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version            Revision Date.:            SDS Number:            Date of last issue: 10.05.2024  
10.0                04.03.2026                800001001508            Print Date. 05.03.2026

### Full text of other abbreviations

Acute Tox.	:	Acute toxicity
Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Carc.	:	Carcinogenicity
Flam. Liq.	:	Flammable liquids
Repr.	:	Reproductive toxicity
Skin Irrit.	:	Skin irritation
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
2006/15/EC	:	Europe. Indicative occupational exposure limit values
2019/1831/EU	:	Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
91/322/EEC	:	Europe. Commission Directive 91/322/EEC on establishing indicative limit values
ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT	:	UK. Biological monitoring guidance values
2006/15/EC / TWA	:	Limit Value - eight hours
2006/15/EC / STEL	:	Short term exposure limit
2019/1831/EU / TWA	:	Limit Value - eight hours
2019/1831/EU / STEL	:	Short term exposure limit
91/322/EEC / TWA	:	Limit Value - eight hours
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	:	Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECl - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified;

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
Print Date. 05.03.2026

NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

Other information : This mixture does not contain any REACH registered substances that are assessed to be a PBT or a vPvB.  
A vertical bar (|) in the left margin indicates an amendment from the previous version.

#### Classification of the mixture:

Flam. Liq. 1	H224
Asp. Tox. 1	H304
Skin Irrit. 2	H315
STOT SE 3	H336
Carc. 1B	H350
Repr. 2	H361d
STOT RE 2	H373
Aquatic Chronic 2	H411

#### Classification procedure:

On basis of test data.  
Expert judgement and weight of evidence determination.  
Expert judgement and weight of evidence determination.  
Expert judgement and weight of evidence determination.  
Expert judgement and weight of evidence determination.  
Expert judgement and weight of evidence determination.  
Expert judgement and weight of evidence determination.  
Expert judgement and weight of evidence determination.

### Identified Uses according to the Use Descriptor System

#### Uses - Worker

Title : Manufacture of substance  
- Industrial

#### Uses - Worker

Title : Use as an intermediate  
- Industrial

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0	Revision Date.: 04.03.2026	SDS Number: 800001001508	Date of last issue: 10.05.2024 Print Date. 05.03.2026
-----------------	-------------------------------	-----------------------------	--

---

### Uses - Worker

Title : Distribution of substance  
- Industrial

### Uses - Worker

Title : Formulation & (re)packing of substances and mixtures  
- Industrial

### Uses - Worker

Title : Use as a fuel  
- Industrial

### Uses - Worker

Title : Use as a fuel  
- Professional

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
Print Date. 05.03.2026

### Exposure Scenario - Worker

<b>300000000028</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Manufacture of substance- Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU3, SU9 <b>Process Categories:</b> PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15 <b>Environmental Release Categories:</b> ERC1, ERC4, ESVOC SpERC 1.1.v1
<b>Scope of process</b>	Manufacture of the substance or use as a process chemical or extraction agent. Includes recycling/ recovery, material transfers, storage, maintenance and loading (including marine vessel/barge, road/rail car and bulk container), sampling and associated laboratory activities.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
<b>Section 2.1</b>	<b>Control of Worker Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure > 10 kPa at STP
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).,
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented.	
<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>
General measures (skin irritants).	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.
General exposures (closed systems)	No other specific measures identified.
General exposures (closed systems)with sample collection	No other specific measures identified.
General exposures (open	Provide extraction ventilation at points where emissions oc-

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
Print Date. 05.03.2026

systems)	cur.
Mixing operations (closed systems)	No other specific measures identified.
Process sampling	No other specific measures identified.
Laboratory activities	Handle in a fume cupboard or under extract ventilation.
Bulk transfers	No other specific measures identified.
Drum/batch transfers	No other specific measures identified.
Equipment maintenance	No other specific measures identified.
Storage.	Store substance within a closed system.
<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Substance is complex UVCB.	
Predominantly hydrophobic.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0.1
Regional use tonnage (tonnes/year):	1.87E+07
Fraction of Regional tonnage used locally:	0.032
Annual site tonnage (tonnes/year):	6.0E+05
Maximum daily site tonnage (kg/day):	2.0E+06
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	300
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from process (initial release prior to RMM):	0.05
Release fraction to wastewater from process (initial release prior to RMM):	3.0E-03
Release fraction to soil from process (initial release prior to RMM):	1.0E-04
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process re-lease estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Prevent discharge of undissolved substance to or recover from onsite wastewater.	
Risk from environmental exposure is driven by humans via indirect exposure (primarily inhalation).	
Onsite waste water treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	99.0
Treat onsite wastewater (prior to receiving water discharge) to provide	99.1

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
Print Date. 05.03.2026

the required removal efficiency of $\geq$ (%)	
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	80.4
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	95.5
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	99.1
STP10	2.0E+06
Assumed domestic sewage treatment plant flow (m3/d)	10,000
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
During manufacturing no waste of the substance is generated.	
<b>Conditions and measures related to external recovery of waste</b>	
During manufacturing no waste of the substance is generated.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

<b>Section 3.2 -Environment</b>	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Available hazard data do not enable the derivation of a DNEL for dermal irritant effects. Risk Management Measures are based on qualitative risk characterisation.	

<b>Section 4.2 -Environment</b>	
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.	
Required removal efficiency for wastewater can be achieved using onsite/offsite technolo-	

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version  
10.0

Revision Date.:  
04.03.2026

SDS Number:  
800001001508

Date of last issue: 10.05.2024  
Print Date. 05.03.2026

---

gies, either alone or in combination.
---------------------------------------

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.
---

Further details on scaling and control technologies are provided in SpERC factsheet ( <a href="http://cefic.org">http://cefic.org</a> ).
--

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
Print Date. 05.03.2026

### Exposure Scenario - Worker

<b>300000000029</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Use as an intermediate- Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU3, SU9 <b>Process Categories:</b> PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC15 <b>Environmental Release Categories:</b> ERC6a, ESVOC SpERC 6.1a.v1
<b>Scope of process</b>	Use of substance as an intermediate (not related to Strictly Controlled Conditions). Includes recycling/ recovery, material transfers, storage, sampling, associated laboratory activities, maintenance and loading (including marine vessel/barge, road/rail car and bulk container).

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
<b>Section 2.1</b>	<b>Control of Worker Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure > 10 kPa at STP
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).,
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented.	
<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>
General measures (skin irritants).	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.
General exposures (closed systems)	No other specific measures identified.
General exposures (closed systems)with sample collection	No other specific measures identified.
General exposures (open	Provide extraction ventilation at points where emissions oc-

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
Print Date. 05.03.2026

systems)	cur.
Mixing operations (closed systems)	No other specific measures identified.
Process sampling	No other specific measures identified.
Laboratory activities	Handle in a fume cupboard or under extract ventilation.
Bulk transfers	No other specific measures identified.
Drum/batch transfers	No other specific measures identified.
Equipment maintenance	No other specific measures identified.
Storage.	Store substance within a closed system.
<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Substance is complex UVCB.	
Predominantly hydrophobic.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0.1
Regional use tonnage (tonnes/year):	2.21E+06
Fraction of Regional tonnage used locally:	0.0068
Annual site tonnage (tonnes/year):	1.5E+04
Maximum daily site tonnage (kg/day):	5.0E+04
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	300
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from process (initial release prior to RMM):	0.025
Release fraction to wastewater from process (initial release prior to RMM):	3.0E-03
Release fraction to soil from process (initial release prior to RMM):	1.0E-03
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process re-lease estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Prevent discharge of undissolved substance to or recover from onsite wastewater.	
Risk from environmental exposure is driven by freshwater sediment.	
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	80
Treat onsite wastewater (prior to receiving water discharge) to provide	92.9

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
Print Date. 05.03.2026

the required removal efficiency of $\geq$ (%)	
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	95.5
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	95.5
STP10	7.8E+04
Assumed domestic sewage treatment plant flow (m3/d)	2,000
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
This substance is consumed during use and no waste of substance is generated.	
<b>Conditions and measures related to external recovery of waste</b>	
This substance is consumed during use and no waste of substance is generated.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

<b>Section 3.2 -Environment</b>	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Available hazard data do not enable the derivation of a DNEL for dermal irritant effects. Risk Management Measures are based on qualitative risk characterisation.	

<b>Section 4.2 -Environment</b>	
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.	
Required removal efficiency for wastewater can be achieved using onsite/offsite technolo-	

## SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

### AVGAS 100LL

Version            Revision Date.:            SDS Number:            Date of last issue: 10.05.2024  
10.0                04.03.2026                800001001508            Print Date. 05.03.2026

---

gies, either alone or in combination.
---------------------------------------

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.
---

Further details on scaling and control technologies are provided in SpERC factsheet ( <a href="http://cefic.org">http://cefic.org</a> ).
--

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
Print Date. 05.03.2026

### Exposure Scenario - Worker

<b>300000000030</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Distribution of substance- Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU3 <b>Process Categories:</b> PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC15 <b>Environmental Release Categories:</b> ERC1, ERC2, ERC3, ERC4, ERC5, ERC6a, ERC6b, ERC6c, ERC6d, ERC7, ESVOC SpERC 1.1b.v1
<b>Scope of process</b>	Loading (including marine vessel/barge, rail/road car and IBC loading) and repacking (including drums and small packs) of substance, including its sampling, storage, unloading distribution and associated laboratory activities.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
<b>Section 2.1</b>	<b>Control of Worker Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure > 10 kPa at STP
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).,
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.	
<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>
General measures (skin irritants).	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.
General exposures (closed systems)	No other specific measures identified.
General exposures (closed systems)with sample collection	No other specific measures identified.
General exposures (open	Provide extraction ventilation at points where emissions oc-

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
 Print Date. 05.03.2026

systems)	cur.
Process sampling	No other specific measures identified.
Laboratory activities	Handle in a fume cupboard or under extract ventilation.
Bulk closed loading and unloading.	No other specific measures identified.
Drum and small package filling	Fill containers/cans at dedicated filling points supplied with local extract ventilation.
Equipment cleaning and maintenance	No other specific measures identified.
Storage.	Store substance within a closed system.
<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Substance is complex UVCB.	
Predominantly hydrophobic.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0.1
Regional use tonnage (tonnes/year):	1.87E+07
Fraction of Regional tonnage used locally:	0.002
Annual site tonnage (tonnes/year):	3.75E+04
Maximum daily site tonnage (kg/day):	1.2E+05
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	100
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from process (initial release prior to RMM):	1.0E-03
Release fraction to wastewater from process (initial release prior to RMM):	1.0E-05
Release fraction to soil from process (initial release prior to RMM):	1.0E-05
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process re-lease estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Risk from environmental exposure is driven by humans via indirect exposure (primarily inhalation).	
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	90
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	12
If discharging to domestic sewage treatment plant, no secondary	0

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
Print Date. 05.03.2026

wastewater treatment required.	
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	95.5
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	95.5
STP10	1.1E+06
Assumed domestic sewage treatment plant flow (m3/d)	2,000
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
<b>Conditions and measures related to external recovery of waste</b>	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

<b>Section 3.2 -Environment</b>	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Available hazard data do not enable the derivation of a DNEL for dermal irritant effects. Risk Management Measures are based on qualitative risk characterisation.	

<b>Section 4.2 -Environment</b>	
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.	
Required removal efficiency for wastewater can be achieved using onsite/offsite technolo-	

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version  
10.0

Revision Date.:  
04.03.2026

SDS Number:  
800001001508

Date of last issue: 10.05.2024  
Print Date. 05.03.2026

---

gies, either alone or in combination.
Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.
Further details on scaling and control technologies are provided in SpERC factsheet ( <a href="http://cefic.org">http://cefic.org</a> ).

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version  
10.0

Revision Date.:  
04.03.2026

SDS Number:  
800001001508

Date of last issue: 10.05.2024  
Print Date. 05.03.2026

### Exposure Scenario - Worker

<b>30000000031</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Formulation & (re)packing of substances and mixtures- Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU3, SU10 <b>Process Categories:</b> PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC14, PROC15 <b>Environmental Release Categories:</b> ERC2, ESVOC SpERC 2.2.v1
<b>Scope of process</b>	Formulation, packing and re-packing of the substance and its mixtures in batch or continuous operations, including storage, materials transfers, mixing, tableting, compression, pelletisation, extrusion, large and small scale packing, sampling, maintenance and associated laboratory activities.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
<b>Section 2.1</b>	<b>Control of Worker Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure > 10 kPa at STP
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently),,
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.	
<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>
General measures (skin irritants).	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.
General exposures (closed systems)	No other specific measures identified.
General exposures (closed systems)with sample collection	No other specific measures identified.

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version  
10.0

Revision Date.:  
04.03.2026

SDS Number:  
800001001508

Date of last issue: 10.05.2024  
Print Date. 05.03.2026

General exposures (open systems)	Provide extraction ventilation at points where emissions occur.
Process sampling	No other specific measures identified.
Mixing operations (closed systems)	Provide extraction ventilation at points where emissions occur.
Laboratory activities	Handle in a fume cupboard or under extract ventilation.
Bulk transfers	Ensure material transfers are under containment or extract ventilation.
Manual Transfer from/pouring from containers	Ensure material transfers are under containment or extract ventilation.
Drum/batch transfers	Ensure material transfers are under containment or extract ventilation.
Drum and small package filling	Fill containers/cans at dedicated filling points supplied with local extract ventilation.
Equipment cleaning and maintenance	No other specific measures identified.
Storage.	Store substance within a closed system.
<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Substance is complex UVCB.	
Predominantly hydrophobic.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0.1
Regional use tonnage (tonnes/year):	1.65E+07
Fraction of Regional tonnage used locally:	0.0018
Annual site tonnage (tonnes/year):	3.0E+04
Maximum daily site tonnage (kg/day):	1.0E+05
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	300
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from process (initial release prior to RMM):	0.025
Release fraction to wastewater from process (initial release prior to RMM):	2.0E-03
Release fraction to soil from process (initial release prior to RMM):	1.0E-04
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process re-	

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
Print Date. 05.03.2026

lease estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Prevent discharge of undissolved substance to or recover from onsite wastewater.	
Risk from environmental exposure is driven by humans via indirect exposure (primarily inhalation).	
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	56.5
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	94.7
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	95.5
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	95.5
STP10	1.0E+05
Assumed domestic sewage treatment plant flow (m3/d)	2,000
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
<b>Conditions and measures related to external recovery of waste</b>	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

<b>Section 3.2 -Environment</b>	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0	Revision Date.: 04.03.2026	SDS Number: 800001001508	Date of last issue: 10.05.2024 Print Date. 05.03.2026
-----------------	-------------------------------	-----------------------------	--

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Available hazard data do not enable the derivation of a DNEL for dermal irritant effects. Risk Management Measures are based on qualitative risk characterisation.

### Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org>).

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version  
10.0

Revision Date.:  
04.03.2026

SDS Number:  
800001001508

Date of last issue: 10.05.2024  
Print Date. 05.03.2026

### Exposure Scenario - Worker

<b>300000000032</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Use as a fuel- Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU3 <b>Process Categories:</b> PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC16 <b>Environmental Release Categories:</b> ERC7, ESVOC SpERC 7.12a.v1
<b>Scope of process</b>	Covers the use as a fuel (or fuel additive) and includes activities associated with its transfer, use, equipment maintenance and handling of waste.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
<b>Section 2.1</b>	<b>Control of Worker Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure > 10 kPa at STP
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).,
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.	
<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>
General measures (skin irritants).	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.
General exposures (closed systems)	No other specific measures identified.
Bulk closed unloading.	No other specific measures identified.
Drum/batch transfers	No other specific measures identified.
Refueling.	No other specific measures identified.

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
 Print Date. 05.03.2026

Refuelling aircraft.	Ensure material transfers are under containment or extract ventilation.
Use as a fuel(closed systems)	No other specific measures identified.
Equipment maintenance	No other specific measures identified.
Storage.	Store substance within a closed system.
<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Substance is complex UVCB.	
Predominantly hydrophobic.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0.1
Regional use tonnage (tonnes/year):	1.4E+06
Fraction of Regional tonnage used locally:	1
Annual site tonnage (tonnes/year):	1.4E+06
Maximum daily site tonnage (kg/day):	4.6E+06
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	300
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from process (initial release prior to RMM):	2.5E-03
Release fraction to wastewater from process (initial release prior to RMM):	1.0E-05
Release fraction to soil from process (initial release prior to RMM):	0
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process re-release estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Risk from environmental exposure is driven by humans via indirect exposure (primarily inhalation).	
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	99.4
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	76.9
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
Print Date. 05.03.2026

Estimated substance removal from wastewater via domestic sewage treatment (%)	95.5
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	95.5
STP10	4.6E+06
Assumed domestic sewage treatment plant flow (m3/d)	2,000
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
Combustion emissions limited by required exhaust emission controls. Waste combustion emissions considered in regional exposure assessment.	
<b>Conditions and measures related to external recovery of waste</b>	
This substance is consumed during use and no waste of substance is generated.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

<b>Section 3.2 -Environment</b>	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Available hazard data do not enable the derivation of a DNEL for dermal irritant effects. Risk Management Measures are based on qualitative risk characterisation.	

<b>Section 4.2 -Environment</b>	
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.	
Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.	
Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.	
Further details on scaling and control technologies are provided in SpERC factsheet ( <a href="http://cefic.org">http://cefic.org</a> ).	

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
Print Date. 05.03.2026

### Exposure Scenario - Worker

<b>300000000033</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Use as a fuel- Professional
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU22 <b>Process Categories:</b> PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC16 <b>Environmental Release Categories:</b> ERC9a, ERC9b, ESVOC SpERC 9.12b.v1
<b>Scope of process</b>	Covers the use as a fuel (or fuel additives and additive components) within closed or contained systems, including incidental exposures during activities associated with its transfer, use, equipment maintenance and handling of waste.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
<b>Section 2.1</b>	<b>Control of Worker Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure > 10 kPa at STP
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).
<b>Frequency and Duration of Use</b>	
Covers daily exposures up to 8 hours (unless stated differently).	
<b>Other Operational Conditions affecting Exposure</b>	
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.	
<b>Contributing Scenarios</b>	<b>Risk Management Measures</b>
General measures (skin irritants).	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.
General exposures (closed systems)	No other specific measures identified.
Preparation of material for application Mixing operations (closed systems)	No other specific measures identified.
Bulk closed unloading.	No other specific measures identified.

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
 Print Date. 05.03.2026

Drum/batch transfers	No other specific measures identified.
Refueling.	No other specific measures identified.
Use as a fuel(closed systems)	No other specific measures identified.
Equipment maintenance	Drain down system prior to equipment opening or maintenance. Wear chemically resistant gloves (tested to EN374) in combination with intensive management supervision controls.
Storage.	No other specific measures identified.
<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Substance is complex UVCB.	
Predominantly hydrophobic.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	0.1
Regional use tonnage (tonnes/year):	1.19E+06
Fraction of Regional tonnage used locally:	5.0E-04
Annual site tonnage (tonnes/year):	5.9E+02
Maximum daily site tonnage (kg/day):	1.6E+03
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	365
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from process (initial release prior to RMM):	0.01
Release fraction to wastewater from process (initial release prior to RMM):	1.0E-05
Release fraction to soil from process (initial release prior to RMM):	1.0E-05
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process release estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Risk from environmental exposure is driven by humans via indirect exposure (primarily inhalation).	
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	3.4
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	
<b>Organisational measures to prevent/limit release from site</b>	

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## AVGAS 100LL

Version 10.0      Revision Date.: 04.03.2026      SDS Number: 800001001508      Date of last issue: 10.05.2024  
Print Date. 05.03.2026

Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	95.5
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	95.5
STP10	1.5E+04
Assumed domestic sewage treatment plant flow (m3/d)	2,000
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
Combustion emissions limited by required exhaust emission controls. Waste combustion emissions considered in regional exposure assessment.	
<b>Conditions and measures related to external recovery of waste</b>	
This substance is consumed during use and no waste of substance is generated.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

<b>Section 3.2 -Environment</b>	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. Available hazard data do not enable the derivation of a DNEL for dermal irritant effects. Risk Management Measures are based on qualitative risk characterisation.	

<b>Section 4.2 -Environment</b>	
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.	
Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.	
Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.	

## **SAFETY DATA SHEET.**

According to EC No 1907/2006 as amended as at the date of this SDS

### **AVGAS 100LL**

Version	Revision Date.:	SDS Number:	Date of last issue: 10.05.2024
10.0	04.03.2026	800001001508	Print Date. 05.03.2026

---

Further details on scaling and control technologies are provided in SpERC factsheet ( <a href="http://cefic.org">http://cefic.org</a> ).
--