

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version	Revision Date:	SDS Number:	Date of last issue: 25.03.2024
7.2	13.06.2024	800001002191	Print Date 14.06.2024

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name	:	F-34 / AVTUR/FSII
Product code	:	002C0944
Unique Formula Identifier (UFI)	:	J344-G0GS-U006-0X1T

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture	:	Fuel for aviation turbine engines fitted to aircraft. Please refer to section 16 and/or the annexes for the registered uses under REACH.
Uses advised against	:	This product must not be used in applications other than those listed in Section 1 without first seeking the advice of the supplier., This product is not to be used as a solvent or cleaning agent; for lighting or brightening fires; as a skin cleanser. Not to be used as a fuel for automotive vehicles., Not to be used to prevent waxing in diesel fuel.

#### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier	:	<b>Shell UK Oil Products Limited</b> Shell Centre London SE1 7NA United Kingdom
Telephone	:	(+44) 08007318888
Telefax	:	
Contact for Safety Data Sheet	:	If you have any enquiries about the content of this SDS please email <a href="mailto:fuelSDS@shell.com">fuelSDS@shell.com</a>

#### 1.4 Emergency telephone number

: +44 (0) 20 7934 7778 (This telephone number is available 24 hours per day, 7 days per week)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Classification (REGULATION (EC) No 1272/2008)**

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version	Revision Date:	SDS Number:	Date of last issue: 25.03.2024
7.2	13.06.2024	800001002191	Print Date 14.06.2024

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters air-ways.
Skin irritation, Category 2	H315: Causes skin irritation.
Acute toxicity, Category 4, Inhalation	H332: Harmful if inhaled.
Carcinogenicity, Category 1B	H350: May cause cancer.
Specific target organ toxicity - single exposure, Category 3, Inhalation, Narcotic effects	H336: May cause drowsiness or dizziness.
Specific target organ toxicity - repeated exposure, Category 2, Blood, thymus, Liver	H373: May cause damage to organs through prolonged or repeated exposure.
Long-term (chronic) aquatic hazard, Category 2	H411: Toxic to aquatic life with long lasting effects.

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements :

PHYSICAL HAZARDS:

H226 Flammable liquid and vapour.

HEALTH HAZARDS:

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H350 May cause cancer.

H373 May cause damage to organs ( ) through prolonged or repeated exposure.

ENVIRONMENTAL HAZARDS:

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P273 Avoid release to the environment.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version	Revision Date:	SDS Number:	Date of last issue: 25.03.2024
7.2	13.06.2024	800001002191	Print Date 14.06.2024

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

### Response:

P331 Do NOT induce vomiting.

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

### 2.3 Other hazards

This mixture does not contain any REACH registered substances that are assessed to be a PBT or a vPvB.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Hydrogen sulphide (H<sub>2</sub>S), an extremely flammable and toxic gas, and other hazardous vapours may evolve and collect in the headspace of storage tanks, transport vessels and other enclosed containers.

Slightly irritating to respiratory system.

Liquid evaporates quickly and can ignite leading to a flash fire, or an explosion in a confined space.

Vapour in the headspace of tanks and containers may ignite and explode at temperatures exceeding auto-ignition temperature, where vapour concentrations are within the flammability range. May ignite on surfaces at temperatures above auto-ignition temperature.

This material is a static accumulator.

Even with proper grounding and bonding, this material can still accumulate an electrostatic charge.

If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : Complex mixture of hydrocarbons consisting of paraffins, cycloparaffins, aromatic and olefinic hydrocarbons with carbon numbers predominantly in the C<sub>9</sub> to C<sub>16</sub> range.  
May also contain several additives at <0.1% v/v each.

#### Components

Chemical name	CAS-No. EC-No. Index-No.	Classification	Concentration (% w/w)

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version 7.2      Revision Date: 13.06.2024      SDS Number: 800001002191      Date of last issue: 25.03.2024  
Print Date 14.06.2024

	Registration number		
Distillates (petroleum), light hydrocracked	64741-77-1 265-078-2 649-437-00-4 01-2119474208-35	Asp. Tox. 1; H304 Acute Tox. 4; H332 Skin Irrit. 2; H315 Carc. 2; H351 STOT RE 2; H373 Aquatic Chronic 2; H411	>= 0 - <= 100
kerosine (petroleum), sweetened	91770-15-9 294-799-5 649-427-00-X 01-2119502385-46, UK-01-0698716160-8	Flam. Liq. 3; H226 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Carc. 1B; H350 Aquatic Chronic 2; H411	>= 0 - <= 100
Kerosine (petroleum)	8008-20-6 232-366-4 649-404-00-4 01-2119485517-27, UK-01-5382718756-7	Flam. Liq. 3; H226 Skin Irrit. 2; H315 Asp. Tox. 1; H304 Carc. 1B; H350 STOT SE 3; H336 (Narcotic effects) Aquatic Chronic 2; H411	>= 0 - <= 100
kerosine (petroleum), hydrodesulfurized	64742-81-0 265-184-9 649-423-00-8 01-2119462828-25, UK-01-3269319310-7	Flam. Liq. 3; H226 Skin Irrit. 2; H315 Asp. Tox. 1; H304 STOT SE 3; H336 (Narcotic effects) Carc. 1B; H350 Aquatic Chronic 2; H411	>= 0 - <= 100
Distillates (petroleum), hydrotreated light	64742-47-8 265-149-8 649-422-00-2 01-2119484819-18, UK-01-9161676197-8	Asp. Tox. 1; H304 Carc. 1B; H350 Skin Irrit. 2; H315 STOT SE 3; H336	>= 0 - <= 100
2-(2-methoxyethoxy)ethanol	111-77-3 203-906-6 603-107-00-6 01-2119475100-52	Repr. 2; H361	>= 0.09 - <= 0.19

For explanation of abbreviations see section 16.

### Further information

Contains:

Chemical name	Identification number	Classification	Concentration (% w/w)
Naphthalene	91-20-3, 202-049-5	Acute Tox.4; H302 Carc.2; H351 Aquatic Acute1; H400	>= 0 - <= 0.9

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version 7.2      Revision Date: 13.06.2024      SDS Number: 800001002191      Date of last issue: 25.03.2024  
Print Date 14.06.2024

		Aquatic Chronic1; H410	
Toluene	108-88-3, 203-625-9	Flam. Liq.2; H225 Asp. Tox.1; H304 Skin Irrit.2; H315 STOT SE3; H336 Repr.2; H361d STOT RE2; H373 Aquatic Chronic3; H412	$\geq 0 - \leq 0.4$
Ethylbenzene	100-41-4, 202-849-4	Flam. Liq.2; H225 Asp. Tox.1; H304 Skin Irrit.2; H315 Eye Irrit.2; H319 Acute Tox.4; H332 STOT SE3; H335 STOT RE2; H373 Aquatic Chronic3; H412	$\geq 0 - \leq 2$
Xylene, mixed isomers	1330-20-7, 215-535-7	Flam. Liq.3; H226 Asp. Tox.1; H304 Acute Tox.4; H312 Skin Irrit.2; H315 Eye Irrit.2; H319 Acute Tox.4; H332 STOT SE3; H335 STOT RE2; H373 Aquatic Chronic3; H412	$\geq 0 - \leq 2$
Trimethylbenzene (all isomers)	25551-13-7, 247-099-9	Flam. Liq.3; H226 STOT SE3; H335 Aquatic Chronic2; H411	$\geq 0 - \leq 1$
Cumene	98-82-8, 202-704-5	Flam. Liq.3; H226 Asp. Tox.1; H304 STOT SE3; H335 Carc.1B; H350 Aquatic Chronic2; H411	$\geq 0 - \leq 0.2$

For explanation of abbreviations see section 16.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version	Revision Date:	SDS Number:	Date of last issue: 25.03.2024
7.2	13.06.2024	800001002191	Print Date 14.06.2024

---

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- |                            |   |  |
|----------------------------|---|--|
| General advice             | : | Not expected to be a health hazard when used under normal conditions.  |
| Protection of first-aiders | : | When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.  |
| If inhaled                 | : | Call emergency number for your location / facility.<br>Remove to fresh air. Do not attempt to rescue the victim unless proper respiratory protection is worn. If the victim has difficulty breathing or tightness of the chest, is dizzy, vomiting, or unresponsive, give 100% oxygen with rescue breathing or Cardio-Pulmonary Resuscitation as required and transport to the nearest medical facility.   |
| In case of skin contact    | : | Remove contaminated clothing. Immediately flush skin with large amounts of water for at least 15 minutes, and follow by washing with soap and water if available. If redness, swelling, pain and/or blisters occur, transport to the nearest medical facility for additional treatment.<br>When using high pressure equipment, injection of product under the skin can occur. If high pressure injuries occur, the casualty should be sent immediately to a hospital. Do not wait for symptoms to develop.<br>Obtain medical attention even in the absence of apparent wounds. |
| In case of eye contact     | : | Flush eye with copious quantities of water.<br>Remove contact lenses, if present and easy to do. Continue rinsing.<br>If persistent irritation occurs, obtain medical attention.   |
| If swallowed               | : | Call emergency number for your location / facility.<br>If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.<br>If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.   |

#### 4.2 Most important symptoms and effects, both acute and delayed

- |          |   |  |
|----------|---|--|
| Symptoms | : | Respiratory irritation signs and symptoms may include a temporary burning sensation of the nose and throat, coughing, and/or difficulty breathing.<br>Breathing of high vapour concentrations may cause central nervous system (CNS) depression resulting in dizziness, light-headedness, headache, nausea and loss of coordination. |
|----------|---|--|

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version	Revision Date:	SDS Number:	Date of last issue: 25.03.2024
7.2	13.06.2024	800001002191	Print Date 14.06.2024

Continued inhalation may result in unconsciousness and death.  
Skin irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blisters.  
Local necrosis is evidenced by delayed onset of pain and tissue damage a few hours following injection.  
Eye irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blurred vision.  
If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever.  
If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : IMMEDIATE TREATMENT IS EXTREMELY IMPORTANT!  
Call a doctor or poison control center for guidance.  
Treat symptomatically.  
Potential for chemical pneumonitis.  
Do not induce vomiting.  
High pressure injection injuries require prompt surgical intervention and possibly steroid therapy, to minimise tissue damage and loss of function.  
Because entry wounds are small and do not reflect the seriousness of the underlying damage, surgical exploration to determine the extent of involvement may be necessary. Local anaesthetics or hot soaks should be avoided because they can contribute to swelling, vasospasm and ischaemia. Prompt surgical decompression, debridement and evacuation of foreign material should be performed under general anaesthetics, and wide exploration is essential.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media : Do not use direct water jets on the burning product as they could cause a steam explosion and spread of the fire.  
Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Hazardous combustion products may include:  
A complex mixture of airborne solid and liquid particulates and gases (smoke).  
Oxides of sulphur.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version	Revision Date:	SDS Number:	Date of last issue: 25.03.2024
7.2	13.06.2024	800001002191	Print Date 14.06.2024

---

Unidentified organic and inorganic compounds.  
Carbon monoxide may be evolved if incomplete combustion occurs.  
Will float and can be reignited on surface water.  
Flammable vapours may be present even at temperatures below the flash point.  
The vapour is heavier than air, spreads along the ground and distant ignition is possible.

### 5.3 Advice for firefighters

- Special protective equipment for firefighters : Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Further information : Keep adjacent containers cool by spraying with water.  
If possible remove containers from the danger zone.  
If the fire cannot be extinguished the only course of action is to evacuate immediately.  
Prevent fire extinguishing water from contaminating surface water or the ground water system.  
Contain residual material at affected sites to prevent material from entering drains (sewers), ditches, and waterways.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- Personal precautions : 6.1.1 For non emergency personnel:  
Do not breathe fumes, vapour.  
Do not operate electrical equipment.  
6.1.2 For emergency responders:  
Shut off leaks, if possible without personal risks.  
Remove all possible sources of ignition in the surrounding area.  
Evacuate all personnel.  
Attempt to disperse vapour or to direct its flow to a safe location for example using fog sprays.  
Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.

### 6.2 Environmental precautions

- Environmental precautions : Prevent from spreading or entering into drains, ditches or rivers by using sand, earth, or other appropriate barriers.



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version	Revision Date:	SDS Number:	Date of last issue: 25.03.2024
7.2	13.06.2024	800001002191	Print Date 14.06.2024

---

Take measures to minimise the effects on groundwater.  
Contain residual material at affected sites to prevent material from entering drains (sewers), ditches, and waterways.  
Do not allow contact with soil, surface or ground water.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Take precautionary measures against static discharges.  
For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.  
For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.

### 6.4 Reference to other sections

For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.,  
Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.,  
For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet., Local authorities should be advised if significant spillages cannot be contained., Maritime spillages should be dealt with using a Shipboard Oil Pollution Emergency Plan (SOPEP), as required by MARPOL Annex 1 Regulation 26.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Technical measures : Avoid breathing of or direct contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.  
Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.  
Air-dry contaminated clothing in a well-ventilated area before laundering.  
Contaminated leather articles including shoes cannot be decontaminated and should be destroyed to prevent reuse.  
Prevent spillages.  
Never siphon by mouth.

Maintenance and Fuelling Activities - Avoid inhalation of vapours and contact with skin.

Advice on safe handling : Ensure that all local regulations regarding handling and storage facilities are followed.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version	Revision Date:	SDS Number:	Date of last issue: 25.03.2024
7.2	13.06.2024	800001002191	Print Date 14.06.2024

Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks.  
Avoid inhaling vapour and/or mists.  
Avoid prolonged or repeated contact with skin.  
When using do not eat or drink.  
When handling product in drums, safety footwear should be worn and proper handling equipment should be used.  
The vapour is heavier than air, spreads along the ground and distant ignition is possible.  
Earth all equipment.  
Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols.  
Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.

### Product Transfer

: Avoid splash filling Wait 2 minutes after tank filling (for tanks such as those on road tanker vehicles) before opening hatches or manholes. Wait 30 minutes after tank filling ( for large storage tanks) before opening hatches or manholes. Keep containers closed when not in use. Conditions, such as filling empty Filter Water Separator vessels, that lead to the formation of hydrocarbon mists are also particularly hazardous. Contamination resulting from product transfer may give rise to light hydrocarbon vapour in the headspace of tanks that have previously contained gasoline. This vapour may explode if there is a source of ignition. Partly filled containers present a greater hazard than those that are full, therefore handling, transfer and sampling activities need special care. Even with proper grounding and bonding, this material can still accumulate an electrostatic charge. If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur. Be aware of handling operations that may give rise to additional hazards that result from the accumulation of static charges. These include but are not limited to pumping (especially turbulent flow), mixing, filtering, splash filling, cleaning and filling of tanks and containers, sampling, switch loading, gauging, vacuum truck operations, and mechanical movements. These activities may lead to static discharge e.g. spark formation. Restrict line velocity during pumping in order to avoid generation of electrostatic discharge ( $\leq 1$  m/s until fill pipe submerged to twice its diameter, then  $\leq 7$  m/s). Avoid splash filling. Do NOT use compressed air for filling, discharging, or handling operations.

### Hygiene measures

: Exposure to this product should be reduced as low as reasonably practicable. Reference should be made to the Health and Safety Executive's publication "COSHH Essentials".

In the interests of air safety, aviation fuels are subject to strict quality requirements and product integrity is of paramount importance. For one source of information on international standards for the quality assurance of aviation fuels, see [www.jigonline.com](http://www.jigonline.com).

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version	Revision Date:	SDS Number:	Date of last issue: 25.03.2024
7.2	13.06.2024	800001002191	Print Date 14.06.2024

---

### 7.2 Conditions for safe storage, including any incompatibilities

- Further information on storage stability : Drum and small container storage:  
Drums should be stacked to a maximum of 3 high.  
Use properly labeled and closable containers.  
Take suitable precautions when opening sealed containers, as pressure can build up during storage.  
Tank storage:  
Tanks must be specifically designed for use with this product.  
Bulk storage tanks should be diked (bunded).  
Locate tanks away from heat and other sources of ignition.  
The vapour is heavier than air. Beware of accumulation in pits and confined spaces.  
Electrostatic charges will be generated during pumping.  
Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to reduce the risk.  
The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flammable.  
Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.  
The storage of this product may be subject to the Control of Pollution (Oil Storage) (England) Regulations. Further guidance may be obtained from the local environmental agency office.
- Packaging material : Suitable material: For containers, or container linings use carbon steel and low alloy steel. Aluminium may also be used for applications where it does not present an unnecessary fire hazard. For container linings the following may also be used: Unplasticized polyvinyl chloride (U-PVC), Fluoropolymers (PTFE), Polyvinylidene fluoride (PVDF), Polyetheretherketone (PEEK), Polyamide (PA-11). For seals and gaskets use: Fluoroelastomer (FKM), Viton A, and Viton B, Nitrile butadiene (NBR), Buna-N. For coating (paint) materials use: High build, amine adduct-cured epoxy.  
Unsuitable material: For containers or container linings, examples of materials to avoid are: Polyethylene (PE, HDPE), Polypropylene (PP), Polymethyl methacrylate (PMMA), Acrylonitrile butadiene styrene (ABS). For seals and gaskets, examples of materials to avoid are: Natural rubber (NR), Ethylene Propylene (EPDM), Polychloroprene (CR) - Neoprene, Butyl (IIR), Chlorosulphonated polyethylene (CSM), e.g. Hypalon.
- Container Advice : Containers, even those that have been emptied, can contain explosive vapours. Do not cut, drill, grind, weld or perform similar operations on or near containers.

### 7.3 Specific end use(s)

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version 7.2      Revision Date: 13.06.2024      SDS Number: 800001002191      Date of last issue: 25.03.2024  
Print Date 14.06.2024

Specific use(s) : Please refer to section 16 and/or the annexes for the registered uses under REACH.

See additional references that provide safe handling practices for liquids that are determined to be static accumulators: American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practices on Static Electricity).

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

##### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Toluene	108-88-3	TWA	50 ppm 191 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
Toluene		STEL	100 ppm 384 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
Toluene		TWA	50 ppm 192 mg/m3	2006/15/EC
	Further information: Indicative, Identifies the possibility of significant uptake through the skin			
Toluene		STEL	100 ppm 384 mg/m3	2006/15/EC
	Further information: Indicative, Identifies the possibility of significant uptake through the skin			
Toluene		TWA	20 ppm	ACGIH
Naphthalene	91-20-3	TWA	10 ppm 50 mg/m3	91/322/EEC
	Further information: Indicative			
Naphthalene		TWA	10 ppm	ACGIH
Ethylbenzene	100-41-4	TWA	100 ppm 441 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
Ethylbenzene		STEL	125 ppm 552 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version  
7.2

Revision Date:  
13.06.2024

SDS Number:  
800001002191

Date of last issue: 25.03.2024  
Print Date 14.06.2024

Ethylbenzene		TWA	20 ppm	ACGIH
2-(2-methoxyethoxy)ethanol	111-77-3	TWA	10 ppm 50.1 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
2-(2-methoxyethoxy)ethanol		TWA	10 ppm 50.1 mg/m3	2006/15/EC
	Further information: Indicative, Identifies the possibility of significant uptake through the skin			
Distillates (petroleum), light hydrocracked	64741-77-1	TWA	200 mg/m3 (total hydrocarbon vapor)	ACGIH
kerosine (petroleum), sweetened	91770-15-9	TWA	200 mg/m3 (total hydrocarbon vapor)	ACGIH
Xylene, mixed isomers	1330-20-7	TWA	50 ppm 220 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
Xylene, mixed isomers		STEL	100 ppm 441 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
Xylene, mixed isomers		TWA	20 ppm	ACGIH
Kerosine (petroleum)	8008-20-6	TWA	200 mg/m3 (total hydrocarbon vapor)	ACGIH
Trimethylbenzene (all isomers)	25551-13-7	TWA	25 ppm 125 mg/m3	GB EH40
Trimethylbenzene (all isomers)		TWA	10 ppm	ACGIH
kerosine (petroleum), hydrodesulfurized	64742-81-0	TWA	200 mg/m3 (total hydrocarbon vapor)	ACGIH
Cumene	98-82-8	TWA	25 ppm 125 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
Cumene		STEL	50 ppm 250 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
Cumene		TWA	10 ppm 50 mg/m3	2019/1831/EU
	Further information: A skin notation assigned to the occupational exposure			

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version 7.2      Revision Date: 13.06.2024      SDS Number: 800001002191      Date of last issue: 25.03.2024  
Print Date 14.06.2024

	limit value indicates the possibility of significant uptake through the skin., Indicative			
Cumene		STEL	50 ppm 250 mg/m3	2019/1831/EU
	Further information: A skin notation assigned to the occupational exposure limit value indicates the possibility of significant uptake through the skin., Indicative			
Cumene		TWA	5 ppm	ACGIH
Distillates (petroleum), hydrotreated light	64742-47-8	TWA	200 mg/m3 (total hydrocarbon vapor)	ACGIH

### Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
Ethylbenzene	100-41-4	Sum of mandelic acid and phenyl glyoxylic acid: 0.15 g/g creatinine (Urine)	End of shift (As soon as possible after exposure ceases)	ACGIH BEI
Naphthalene	91-20-3	1-hydroxypyrene: 4 µmol/mol creatinine (Urine)	After shift	GB EH40 BAT
		1-Naphthol + 2-Naphthol:	End of shift (As soon as possible after exposure ceases)	ACGIH BEI
Toluene	108-88-3	Toluene: 0.02 mg/l (In blood)	Prior to last shift of workweek	ACGIH BEI
		Toluene: 0.03 mg/l (Urine)	End of shift (As soon as possible after exposure ceases)	ACGIH BEI
		o-Cresol: 0.3 mg/g creatinine (Urine)	End of shift (As soon as possible after exposure ceases)	ACGIH BEI
Xylene, mixed isomers	1330-20-7	methyl hippuric acid: 650 Millimoles per mole creatinine (Urine)	After shift	GB EH40 BAT
		Methylhippuric acids: 1.5 g/g creatinine (Urine)	End of shift (As soon as possible after exposure ceases)	ACGIH BEI

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Ethylbenzene	Workers	Inhalation	Acute local effects	293 mg/m3
Ethylbenzene	Workers	Inhalation	Long-term systemic	77 mg/m3

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version 7.2      Revision Date: 13.06.2024      SDS Number: 800001002191      Date of last issue: 25.03.2024  
Print Date 14.06.2024

			effects	
Ethylbenzene	Workers	Dermal	Long-term systemic effects	180 mg/kg bw/day
Ethylbenzene	Consumers	Inhalation	Long-term systemic effects	15 mg/m3
Ethylbenzene	Consumers	Oral	Long-term systemic effects	1.6 mg/kg bw/day
Naphthalene	Consumers	Oral	Long-term systemic effects	4.23 mg/kg
Toluene	Workers	Inhalation	Acute systemic effects	384 mg/m3
Toluene	Workers	Inhalation	Long-term systemic effects	192 mg/m3
Toluene	Workers	Dermal	Long-term systemic effects	180 mg/kg bw/day
Toluene	Consumers	Inhalation	Acute systemic effects	226 mg/m3
Toluene	Consumers	Inhalation	Long-term systemic effects	56.5 mg/m3
Toluene	Consumers	Dermal	Long-term systemic effects	226 mg/kg bw/day
Toluene	Consumers	Oral	Long-term systemic effects	8.13 mg/kg bw/day
Kerosine (petroleum)	Consumers	Oral		19 mg/kg 24h
Remarks:	long term, systemic effects			
kerosine (petroleum), hydrodesulfurized	Consumers	Oral		19 mg/kg 24h
Remarks:	long term, systemic effects			

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Remarks:	Substance is a hydrocarbon with a complex, unknown or variable composition. Conventional methods of deriving PNECs are not appropriate and it is not possible to identify a single representative PNEC for such substances.	

## 8.2 Exposure controls

### Engineering measures

Read in conjunction with the Exposure Scenario for your specific use contained in the Annex. The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Use sealed systems as far as possible.

Firewater monitors and deluge systems are recommended.

Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits.

Local exhaust ventilation is recommended.

Eye washes and showers for emergency use.

### General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version	Revision Date:	SDS Number:	Date of last issue: 25.03.2024
7.2	13.06.2024	800001002191	Print Date 14.06.2024

equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or for subsequent recycle.

Do not ingest. If swallowed, then seek immediate medical assistance.

### Personal protective equipment

Read in conjunction with the Exposure Scenario for your specific use contained in the Annex.

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

The provided information is made in consideration of the PPE directive (Council Directive 89/686/EEC) and the CEN European Committee for Standardisation (CEN) standards.

Eye protection : Wear goggles for use against liquids and gas.  
If a local risk assessment deems it so then chemical splash goggles may not be required and safety glasses may provide adequate eye protection.

Approved to EU Standard EN166.

Hand protection

Remarks : Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. When prolonged or frequent repeated contact occurs. Nitrile rubber. For incidental contact/splash protection Neoprene, PVC gloves may be suitable. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version	Revision Date:	SDS Number:	Date of last issue: 25.03.2024
7.2	13.06.2024	800001002191	Print Date 14.06.2024

---

	perfumed moisturizer is recommended. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model.
Skin and body protection	: Wear chemical resistant gloves/gauntlets and boots. Where risk of splashing, also wear an apron. Wear antistatic and flame-retardant clothing, if a local risk assessment deems it so.  Protective clothing approved to EU Standard EN14605.
Respiratory protection	: If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.  Select a filter suitable for the combination of organic gases and vapours and particles meeting EN14387 and EN143 [Filter type A/P for use against certain organic gases and vapours with a boiling point >65°C (149°F) and for use against particles].
Thermal hazards	: Not applicable

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state	: liquid
Colour	: Colourless to light coloured
Odour	: Not applicable
Odour Threshold	: Data not available
Freezing point	: -47 °C
Boiling point/boiling range	: 150 - 300 °CMethod: Unspecified
Flammability	
Flammability (solid, gas)	: Not applicable

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version	Revision Date:	SDS Number:	Date of last issue: 25.03.2024
7.2	13.06.2024	800001002191	Print Date 14.06.2024

---

Lower explosion limit and upper explosion limit / flammability limit

Upper explosion limit /  
upper flammability limit : Typical 6 %(V)

Typical 5 %(V)

Lower explosion limit /  
Lower flammability limit : Typical 0.7 %(V)

Typical 1 %(V)

Flash point : 38 - 60 °C  
Method: Unspecified

Auto-ignition temperature : > 220 °C

Decomposition temperature  
Decomposition temperature : Data not available

pH : Not applicable

Viscosity  
Viscosity, dynamic : Data not available

Viscosity, kinematic : 1 - 2.5 mm<sup>2</sup>/s (40 °C)

Solubility(ies)  
Water solubility : negligible

Solubility in other solvents : Data not available

Partition coefficient: n-  
octanol/water : log Pow: 2 - 10

Vapour pressure : 1 - 3.7 kPa (38.0 °C)  
Method: Unspecified  
1.6 - 7 kPa (50.0 °C)  
Method: Unspecified

Relative density : Data not available

Density : 775 - 840 kg/m<sup>3</sup> (15.0 °C)  
Method: Unspecified

Relative vapour density : Data not available

Particle characteristics  
Particle size : Data not available

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version	Revision Date:	SDS Number:	Date of last issue: 25.03.2024
7.2	13.06.2024	800001002191	Print Date 14.06.2024

Data not available

### 9.2 Other information

Explosive properties	:	Classification Code: Not classified
Oxidizing properties	:	Not applicable
Evaporation rate	:	Data not available
Conductivity	:	Low conductivity: < 100 pS/m, The conductivity of this material makes it a static accumulator., A liquid is typically considered nonconductive if its conductivity is below 100 pS/m and is considered semi-conductive if its conductivity is below 10,000 pS/m., Whether a liquid is nonconductive or semiconductive, the precautions are the same., A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Oxidises on contact with air.

### 10.2 Chemical stability

No hazardous reaction is expected when handled and stored according to provisions

### 10.3 Possibility of hazardous reactions

Hazardous reactions	:	No hazardous reaction is expected when handled and stored according to provisions
---------------------	---	---

### 10.4 Conditions to avoid

Conditions to avoid	:	Avoid heat, sparks, open flames and other ignition sources.  In certain circumstances product can ignite due to static electricity.
---------------------	---	---

### 10.5 Incompatible materials

Materials to avoid	:	Strong oxidising agents.
--------------------	---	--------------------------

### 10.6 Hazardous decomposition products

Hazardous decomposition products are not expected to form during normal storage.  
Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version	Revision Date:	SDS Number:	Date of last issue: 25.03.2024
7.2	13.06.2024	800001002191	Print Date 14.06.2024

---

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : Exposure may occur via inhalation, ingestion, skin absorption, skin or eye contact, and accidental ingestion.

##### Acute toxicity

###### Product:

Acute oral toxicity	: LD50 (rat): > 5,000 mg/kg Remarks: Low toxicity
Acute inhalation toxicity	: LC 50 (rat): >1-<=5 mg/l Exposure time: 4 h Remarks: Low toxicity LC50 >20 mg/l
Acute dermal toxicity	: LD 50 (Rabbit): > 2,000 mg/kg Remarks: Low toxicity

###### Components:

###### **Kerosine (petroleum):**

Acute oral toxicity	: LD 50 (Rat): > 5,000 mg/kg Remarks: Low toxicity
Acute inhalation toxicity	: LC 50 (Rat): > 5 mg/l Exposure time: 4 h Remarks: Low toxicity
Acute dermal toxicity	: LD 50 (Rabbit): > 2,000 mg/kg Remarks: Low toxicity

###### **kerosine (petroleum), hydrodesulfurized:**

Acute oral toxicity	: LD 50 (Rat): > 5,000 mg/kg Remarks: Low toxicity
Acute inhalation toxicity	: LC 50 (Rat): > 5 mg/l Exposure time: 4 h Remarks: Low toxicity
Acute dermal toxicity	: LD 50 (Rabbit): > 2,000 mg/kg Remarks: Low toxicity

###### **Distillates (petroleum), hydrotreated light:**

Acute oral toxicity	: LD50 (Rat): > 5000 mg/kg Remarks: Low toxicity
---------------------	---

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version	Revision Date:	SDS Number:	Date of last issue: 25.03.2024
7.2	13.06.2024	800001002191	Print Date 14.06.2024

---

Acute inhalation toxicity : LC50 (Rat): 5 mg/l  
Exposure time: 4 h  
Remarks: Low toxicity

Acute dermal toxicity : LD50 (Rabbit): > 5000 mg/kg  
Remarks: Low toxicity

### Skin corrosion/irritation

#### Product:

Remarks : Irritating to skin.

#### Components:

##### **Kerosine (petroleum):**

Remarks : Irritating to skin.

##### **kerosine (petroleum), hydrodesulfurized:**

Remarks : Irritating to skin.

##### **Distillates (petroleum), hydrotreated light:**

Remarks : Irritating to skin.

### Serious eye damage/eye irritation

#### Product:

Remarks : Slightly irritating to the eye.  
Based on available data, the classification criteria are not met.

#### Components:

##### **Kerosine (petroleum):**

Remarks : Slightly irritating to the eye.  
Based on available data, the classification criteria are not met.

##### **kerosine (petroleum), hydrodesulfurized:**

Remarks : Slightly irritating to the eye.  
Based on available data, the classification criteria are not met.

##### **Distillates (petroleum), hydrotreated light:**

Remarks : Not irritating to eye.

### Respiratory or skin sensitisation

#### Product:

Remarks : Not a sensitiser.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version	Revision Date:	SDS Number:	Date of last issue: 25.03.2024
7.2	13.06.2024	800001002191	Print Date 14.06.2024

Based on available data, the classification criteria are not met.

### Components:

#### **Kerosine (petroleum):**

Remarks : Not a sensitiser.  
Based on available data, the classification criteria are not met.

#### **kerosine (petroleum), hydrodesulfurized:**

Remarks : Not a sensitiser.  
Based on available data, the classification criteria are not met.

#### **Distillates (petroleum), hydrotreated light:**

Remarks : Not a sensitiser.  
Based on available data, the classification criteria are not met.

### **Germ cell mutagenicity**

#### Product:

Genotoxicity in vivo : Remarks: Positive in in-vitro, but negative in in-vivo mutagenicity assays.

Germ cell mutagenicity- Assessment : This product does not meet the criteria for classification in categories 1A/1B.

### Components:

#### **Kerosine (petroleum):**

Genotoxicity in vivo : Remarks: Non mutagenic  
Based on available data, the classification criteria are not met.

#### **kerosine (petroleum), hydrodesulfurized:**

Genotoxicity in vivo : Remarks: Non mutagenic  
Based on available data, the classification criteria are not met.

#### **Distillates (petroleum), hydrotreated light:**

Genotoxicity in vivo : Remarks: Not mutagenic.

Germ cell mutagenicity- Assessment : This product does not meet the criteria for classification in categories 1A/1B.

### **Carcinogenicity**

#### Product:

Remarks : Causes cancer in laboratory animals.  
Repeated skin contact may result in irritation and skin cancer.  
Contains Cumene, CAS# 98-82-8.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version 7.2      Revision Date: 13.06.2024      SDS Number: 800001002191      Date of last issue: 25.03.2024  
Print Date 14.06.2024

An increased tumour incidence has been observed in experimental animals; the significance of this finding to man is unknown.

Carcinogenicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

### Components:

#### **kerosine (petroleum), sweetened:**

Remarks : Contains Cumene, CAS# 98-82-8.  
An increased tumour incidence has been observed in experimental animals; the significance of this finding to man is unknown.

#### **Kerosine (petroleum):**

Remarks : Contains Cumene, CAS# 98-82-8.  
An increased tumour incidence has been observed in experimental animals; the significance of this finding to man is unknown.

#### **kerosine (petroleum), hydrodesulfurized:**

Remarks : Contains Cumene, CAS# 98-82-8.  
An increased tumour incidence has been observed in experimental animals; the significance of this finding to man is unknown.

#### **Distillates (petroleum), hydrotreated light:**

Remarks : May cause cancer.

Remarks : Contains Cumene, CAS# 98-82-8.  
An increased tumour incidence has been observed in experimental animals; the significance of this finding to man is unknown.

Carcinogenicity - Assessment : Category 1B

Material	GHS/CLP Carcinogenicity Classification
Toluene	No carcinogenicity classification.
2-(2-methoxyethoxy)ethanol	No carcinogenicity classification.
Naphthalene	Carcinogenicity Category 2
Ethylbenzene	No carcinogenicity classification.
kerosine (petroleum), sweetened	Carcinogenicity Category 1B

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version 7.2      Revision Date: 13.06.2024      SDS Number: 800001002191      Date of last issue: 25.03.2024  
Print Date 14.06.2024

Distillates (petroleum), light hydrocracked	Carcinogenicity Category 2
Xylene, mixed isomers	No carcinogenicity classification.
Kerosine (petroleum)	Carcinogenicity Category 1B
Trimethylbenzene (all isomers)	No carcinogenicity classification.
kerosine (petroleum), hydrodesulfurized	Carcinogenicity Category 1B
Cumene	Carcinogenicity Category 1B
Distillates (petroleum), hydrotreated light	Carcinogenicity Category 1B

Material	Other Carcinogenicity Classification
Toluene	IARC: Group 3: Not classifiable as to its carcinogenicity to humans
Naphthalene	IARC: Group 2B: Possibly carcinogenic to humans
Ethylbenzene	IARC: Group 2B: Possibly carcinogenic to humans
kerosine (petroleum), sweetened	IARC: Group 3: Not classifiable as to its carcinogenicity to humans
Distillates (petroleum), light hydrocracked	IARC: Group 3: Not classifiable as to its carcinogenicity to humans
Xylene, mixed isomers	IARC: Group 3: Not classifiable as to its carcinogenicity to humans
Kerosine (petroleum)	IARC: Group 3: Not classifiable as to its carcinogenicity to humans
kerosine (petroleum), hydrodesulfurized	IARC: Group 3: Not classifiable as to its carcinogenicity to humans
Cumene	IARC: Group 2B: Possibly carcinogenic to humans
Distillates (petroleum), hydrotreated light	IARC: Group 3: Not classifiable as to its carcinogenicity to humans

### Reproductive toxicity

#### Product:

Reproductive toxicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

#### Components:

##### **Kerosine (petroleum):**

Effects on fertility :



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version	Revision Date:	SDS Number:	Date of last issue: 25.03.2024
7.2	13.06.2024	800001002191	Print Date 14.06.2024

Remarks: Does not impair fertility., Not a developmental toxicant., Based on available data, the classification criteria are not met.

### **kerosine (petroleum), hydrodesulfurized:**

Effects on fertility : Remarks: Does not impair fertility., Not a developmental toxicant., Based on available data, the classification criteria are not met.

### **Distillates (petroleum), hydrotreated light:**

Effects on fertility : Remarks: Does not impair fertility., Not a developmental toxicant., Based on available data, the classification criteria are not met.

Reproductive toxicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

### **STOT - single exposure**

#### **Product:**

Remarks : High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea; continued inhalation may result in unconsciousness and/or death.

#### **Components:**

##### **Kerosine (petroleum):**

Remarks : High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea; continued inhalation may result in unconsciousness.

##### **kerosine (petroleum), hydrodesulfurized:**

Remarks : High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea; continued inhalation may result in unconsciousness.

##### **Distillates (petroleum), hydrotreated light:**

Remarks : High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea; continued inhalation may result in unconsciousness.

### **STOT - repeated exposure**

#### **Product:**

Target Organs : Blood, thymus, Liver  
Remarks : May cause damage to organs or organ systems through pro-

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version	Revision Date:	SDS Number:	Date of last issue: 25.03.2024
7.2	13.06.2024	800001002191	Print Date 14.06.2024

longed or repeated exposure.

### **Components:**

#### **Kerosine (petroleum):**

Remarks : Kidney: caused kidney effects in male rats which are not considered relevant to humans

#### **kerosine (petroleum), hydrodesulfurized:**

Remarks : Kidney: caused kidney effects in male rats which are not considered relevant to humans

#### **Distillates (petroleum), hydrotreated light:**

Remarks : Kidney: caused kidney effects in male rats which are not considered relevant to humans

### **Aspiration toxicity**

#### **Product:**

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

### **Components:**

#### **Kerosine (petroleum):**

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

#### **kerosine (petroleum), hydrodesulfurized:**

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

#### **Distillates (petroleum), hydrotreated light:**

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

## **11.2 Information on other hazards**

### **Endocrine disrupting properties**

#### **Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version	Revision Date:	SDS Number:	Date of last issue: 25.03.2024
7.2	13.06.2024	800001002191	Print Date 14.06.2024

### Further information

#### Product:

Remarks : Classifications by other authorities under varying regulatory frameworks may exist.

#### Components:

##### **Kerosine (petroleum):**

Remarks : Classifications by other authorities under varying regulatory frameworks may exist.

##### **kerosine (petroleum), hydrodesulfurized:**

Remarks : Classifications by other authorities under varying regulatory frameworks may exist.

##### **Distillates (petroleum), hydrotreated light:**

Remarks : Classifications by other authorities under varying regulatory frameworks may exist.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Product:

Toxicity to fish : Remarks: Toxic  
LL/EL/IL50 > 1 <= 10 mg/l

Toxicity to daphnia and other aquatic invertebrates : Remarks: Toxic  
LL/EL/IL50 > 1 <= 10 mg/l

Toxicity to algae/aquatic plants : Remarks: Toxic  
LL/EL/IL50 > 1 <= 10 mg/l

Toxicity to fish (Chronic toxicity) : Remarks: NOEC/NOEL > 0.01 - <=0.1 mg/l

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : Remarks: NOEC/NOEL > 0.1 - <=1.0 mg/l

Toxicity to microorganisms :  
Remarks: Practically non toxic:  
LL/EL/IL50 > 100 mg/l

#### Components:

##### **Kerosine (petroleum):**

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version	Revision Date:	SDS Number:	Date of last issue: 25.03.2024
7.2	13.06.2024	800001002191	Print Date 14.06.2024

---

Toxicity to fish	:	Remarks: Toxic LL/EL/IL50 > 1 <= 10 mg/l
Toxicity to daphnia and other aquatic invertebrates	:	Remarks: Toxic LL/EL/IL50 > 1 <= 10 mg/l
Toxicity to algae/aquatic plants	:	Remarks: Toxic LL/EL/IL50 > 1 <= 10 mg/l
Toxicity to microorganisms	:	Remarks: Practically non toxic: LL/EL/IL50 > 100 mg/l
Toxicity to fish (Chronic toxicity)	:	Remarks: NOEC/NOEL > 0.01 - <=0.1 mg/l
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	Remarks: NOEC/NOEL > 0.1 - <=1.0 mg/l

### kerosine (petroleum), hydrodesulfurized:

Toxicity to fish	:	Remarks: Toxic LL/EL/IL50 > 1 <= 10 mg/l
Toxicity to daphnia and other aquatic invertebrates	:	Remarks: Toxic LL/EL/IL50 > 1 <= 10 mg/l
Toxicity to algae/aquatic plants	:	Remarks: Toxic LL/EL/IL50 > 1 <= 10 mg/l
Toxicity to microorganisms	:	Remarks: Practically non toxic: LL/EL/IL50 > 100 mg/l
Toxicity to fish (Chronic toxicity)	:	Remarks: NOEC/NOEL > 0.01 - <=0.1 mg/l
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	Remarks: NOEC/NOEL > 0.1 - <=1.0 mg/l

### Distillates (petroleum), hydrotreated light:

Toxicity to fish	:	Remarks: Practically non toxic: LL/EL/IL50 > 100 mg/l
Toxicity to daphnia and other aquatic invertebrates	:	Remarks: Practically non toxic: LL/EL/IL50 > 100 mg/l
Toxicity to algae/aquatic plants	:	Remarks: Practically non toxic: LL/EL/IL50 > 100 mg/l

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version	Revision Date:	SDS Number:	Date of last issue: 25.03.2024
7.2	13.06.2024	800001002191	Print Date 14.06.2024

---

Toxicity to microorganisms	:	Remarks: Data not available
Toxicity to fish (Chronic toxicity)	:	Remarks: Data not available
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	Remarks: Data not available

### 12.2 Persistence and degradability

#### Product:

Biodegradability	:	Remarks: Major constituents are inherently biodegradable, but contains components that may persist in the environment. The volatile constituents will oxidize rapidly by photochemical reactions in air. Based on available data, the classification criteria are not met. Not Persistent per IMO criteria. International Oil Pollution Compensation (IOPC) Fund definition: "A non-persistent oil is oil, which, at the time of shipment, consists of hydrocarbon fractions, (a) at least 50% of which, by volume, distills at a temperature of 340°C (645°F) and (b) at least 95% of which, by volume, distils at a temperature of 370°C (700°F) when tested by the ASTM Method D-86/78 or any subsequent revision thereof."
------------------	---	--

#### Components:

##### **Kerosine (petroleum):**

Biodegradability	:	Remarks: Major constituents are inherently biodegradable, but contains components that may persist in the environment. The volatile constituents will oxidize rapidly by photochemical reactions in air. Based on available data, the classification criteria are not met. Not Persistent per IMO criteria. International Oil Pollution Compensation (IOPC) Fund definition: "A non-persistent oil is oil, which, at the time of shipment, consists of hydrocarbon fractions, (a) at least 50% of which, by volume, distills at a temperature of 340°C (645°F) and (b) at least 95% of which, by volume, distils at a temperature of 370°C (700°F) when tested by the ASTM Method D-86/78 or any subsequent revision thereof."
------------------	---	--

##### **kerosine (petroleum), hydrodesulfurized:**

Biodegradability	:	Remarks: Major constituents are inherently biodegradable, but contains components that may persist in the environment. The volatile constituents will oxidize rapidly by photochemical reactions in air. Based on available data, the classification criteria are not met. Not Persistent per IMO criteria.
------------------	---	--

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version	Revision Date:	SDS Number:	Date of last issue: 25.03.2024
7.2	13.06.2024	800001002191	Print Date 14.06.2024

International Oil Pollution Compensation (IOPC) Fund definition:  
"A non-persistent oil is oil, which, at the time of shipment, consists of hydrocarbon fractions, (a) at least 50% of which, by volume, distills at a temperature of 340°C (645°F) and (b) at least 95% of which, by volume, distils at a temperature of 370°C (700°F) when tested by the ASTM Method D-86/78 or any subsequent revision thereof."

### Distillates (petroleum), hydrotreated light:

Biodegradability : Remarks: Readily biodegradable.  
Oxidises rapidly by photo-chemical reactions in air.  
Not Persistent per IMO criteria.  
International Oil Pollution Compensation (IOPC) Fund definition:  
"A non-persistent oil is oil, which, at the time of shipment, consists of hydrocarbon fractions, (a) at least 50% of which, by volume, distills at a temperature of 340°C (645°F) and (b) at least 95% of which, by volume, distils at a temperature of 370°C (700°F) when tested by the ASTM Method D-86/78 or any subsequent revision thereof."

## 12.3 Bioaccumulative potential

### Product:

Bioaccumulation : Remarks: Contains constituents with the potential to bioaccumulate.

### Components:

#### Kerosine (petroleum):

Bioaccumulation : Remarks: Contains constituents with the potential to bioaccumulate.

#### kerosine (petroleum), hydrodesulfurized:

Bioaccumulation : Remarks: Contains constituents with the potential to bioaccumulate.

### Distillates (petroleum), hydrotreated light:

Bioaccumulation : Remarks: Has the potential to bioaccumulate.

## 12.4 Mobility in soil

### Product:

Mobility : Remarks: Evaporates within a day from water or soil surfaces., Large volumes may penetrate soil and could contaminate groundwater., Contains volatile components., Floats on water.

### Components:

#### Kerosine (petroleum):

Mobility : Remarks: Evaporates within a day from water or soil surfaces., Large volumes may penetrate soil and could contaminate

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version	Revision Date:	SDS Number:	Date of last issue: 25.03.2024
7.2	13.06.2024	800001002191	Print Date 14.06.2024

groundwater., Contains volatile components., Floats on water.

### **kerosine (petroleum), hydrodesulfurized:**

Mobility : Remarks: Evaporates within a day from water or soil surfaces., Large volumes may penetrate soil and could contaminate groundwater., Contains volatile components., Floats on water.

### **Distillates (petroleum), hydrotreated light:**

Mobility : Remarks: Floats on water., If it enters soil, it will adsorb to soil particles and will not be mobile.

## 12.5 Results of PBT and vPvB assessment

### **Product:**

Assessment : This mixture does not contain any REACH registered substances that are assessed to be a PBT or a vPvB..

### **Components:**

#### **Kerosine (petroleum):**

Assessment : This mixture does not contain any REACH registered substances that are assessed to be a PBT or a vPvB..

#### **kerosine (petroleum), hydrodesulfurized:**

Assessment : This mixture does not contain any REACH registered substances that are assessed to be a PBT or a vPvB..

#### **Distillates (petroleum), hydrotreated light:**

Assessment : The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB..

## 12.6 Endocrine disrupting properties

### **Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## 12.7 Other adverse effects

### **Product:**

Additional ecological information : Films formed on water may affect oxygen transfer and damage organisms.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version	Revision Date:	SDS Number:	Date of last issue: 25.03.2024
7.2	13.06.2024	800001002191	Print Date 14.06.2024

### Components:

#### **Kerosine (petroleum):**

Additional ecological information : Films formed on water may affect oxygen transfer and damage organisms.

#### **kerosine (petroleum), hydrodesulfurized:**

Additional ecological information : Films formed on water may affect oxygen transfer and damage organisms.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : Recover or recycle if possible.  
It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.  
Do not dispose into the environment, in drains or in water courses.  
Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination.  
Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.

MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides technical aspects at controlling pollutions from ships.

Contaminated packaging : Send to drum recoverer or metal reclaimers.  
Drain container thoroughly.  
After draining, vent in a safe place away from sparks and fire.  
Residues may cause an explosion hazard if heated above the flash point. Do not puncture, cut or weld uncleaned drums.  
Do not pollute the soil, water or environment with the waste container.  
Comply with any local recovery or waste disposal regulations.

Local legislation

Remarks : EU Waste Disposal Code (EWC):  
13 07 03\* wastes of liquid fuels, other fuels (including mixtures).  
The number given to waste is associated with the appropriate usage. The user must decide if their particular use results in another waste code being assigned.



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version	Revision Date:	SDS Number:	Date of last issue: 25.03.2024
7.2	13.06.2024	800001002191	Print Date 14.06.2024

Disposal should be in accordance with applicable regional, national, and local laws and regulations.  
Local regulations may be more stringent than regional or national requirements and must be complied with.

Hazardous Waste (England and Wales) Regulations 2005.

### SECTION 14: Transport information

#### 14.1 UN number or ID number

ADR	:	1863
RID	:	1863
IMDG	:	1863
IATA	:	1863

#### 14.2 UN proper shipping name

ADR	:	FUEL, AVIATION, TURBINE ENGINE
RID	:	FUEL, AVIATION, TURBINE ENGINE
IMDG	:	FUEL, AVIATION, TURBINE ENGINE
IATA	:	FUEL, AVIATION, TURBINE ENGINE

#### 14.3 Transport hazard class(es)

ADR	:	3
RID	:	3
IMDG	:	3
IATA	:	3

#### 14.4 Packing group

<b>ADR</b>	
Packing group	: III
Classification Code	: F1
Hazard Identification Number	: 30
Labels	: 3
<b>RID</b>	
Packing group	: III
Classification Code	: F1
Hazard Identification Number	: 30
Labels	: 3
<b>IMDG</b>	
Packing group	: III
Labels	: 3
<b>IATA</b>	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version	Revision Date:	SDS Number:	Date of last issue: 25.03.2024
7.2	13.06.2024	800001002191	Print Date 14.06.2024

Packing group : III  
Labels : 3

### 14.5 Environmental hazards

#### ADR

Environmentally hazardous : yes

#### RID

Environmentally hazardous : yes

#### IMDG

Marine pollutant : yes

### 14.6 Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

### 14.7 Maritime transport in bulk according to IMO instruments

MARPOL Annex 1 rules apply for bulk shipments by sea.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:  
2-(2-methoxyethoxy)ethanol (Number on list 54)  
Toluene (Number on list 48)  
kerosine (petroleum), sweetened (Number on list 28)  
Kerosine (petroleum) (Number on list 28)  
kerosine (petroleum), hydrodesulfurized (Number on list 28)  
Distillates (petroleum), hydrotreated light (Number on list 28)  
Cumene (Number on list 28)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

34b Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version	Revision Date:	SDS Number:	Date of last issue: 25.03.2024
7.2	13.06.2024	800001002191	Print Date 14.06.2024

environmental hazards as the products referred to in points (a) to (d)

### Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Environmental Protection Act 1990 (as amended). Health and Safety at Work etc. Act 1974. Consumers Protection Act 1987. Pollution Prevention and Control Act 1999. Environment Act 1995. Factories Act 1961. The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment (Amendment) Regulations 2011. Chemicals (Hazard Information and Packaging for Supply) Regulations 2009. Control of Substances Hazardous to Health Regulations 2002 (as amended). Merchant Shipping (Dangerous Goods and Marine Pollutants) Regulations 1997. Reporting of Injuries, Diseases and Dangerous Occurrences Regulations 1995 (as amended). Personal Protective Equipment Regulations 2002. Personal Protective Equipment at Work Regulations 1992. Hazardous Waste (England and Wales) Regulations 2005(as amended). Control of Major Accident Hazards Regulations 1999 (as amended). Renewable Transport Fuel Obligations Order 2007 (as amended). Energy Act 2011. Environmental Permitting (England and Wales) Regulations 2010 (as amended). Waste (England and Wales) Regulations 2011 (as amended). Planning (Hazardous Substances) Act 1990 and associated regulations. The Environmental Protection (Controls on Ozone-Depleting Substances) Regulations 2011.

Product is subject to the Control of Major Accident Hazards Regulations 2015 (2015 No. 483) based on Seveso III directive (2012/18/EU).

### 15.2 Chemical safety assessment

A Chemical Safety Assessment was performed for all substances of this product.

## SECTION 16: Other information

### Full text of H-Statements

H225	: Highly flammable liquid and vapour.
H226	: Flammable liquid and vapour.
H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H312	: Harmful in contact with skin.
H315	: Causes skin irritation.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H350	: May cause cancer.
H351	: Suspected of causing cancer.
H361	: Suspected of damaging fertility or the unborn child.
H361d	: Suspected of damaging the unborn child.
H373	: May cause damage to organs through prolonged or repeated

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version	Revision Date:	SDS Number:	Date of last issue: 25.03.2024
7.2	13.06.2024	800001002191	Print Date 14.06.2024

exposure.

H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H411	: Toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.

### Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Carc.	: Carcinogenicity
Flam. Liq.	: Flammable liquids
Repr.	: Reproductive toxicity
Skin Irrit.	: Skin irritation
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure
2006/15/EC	: Europe. Indicative occupational exposure limit values
2019/1831/EU	: Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
91/322/EEC	: Europe. Commission Directive 91/322/EEC on establishing indicative limit values
ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	: ACGIH - Biological Exposure Indices (BEI)
GB EH40	: UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT	: UK. Biological monitoring guidance values
2006/15/EC / TWA	: Limit Value - eight hours
2006/15/EC / STEL	: Short term exposure limit
2019/1831/EU / TWA	: Limit Value - eight hours
2019/1831/EU / STEL	: Short term exposure limit
91/322/EEC / TWA	: Limit Value - eight hours
ACGIH / TWA	: 8-hour, time-weighted average
GB EH40 / TWA	: Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	: Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - Interna-

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version	Revision Date:	SDS Number:	Date of last issue: 25.03.2024
7.2	13.06.2024	800001002191	Print Date 14.06.2024

tional Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

Training advice : Provide adequate information, instruction and training for operators.

Other information : This product is intended for use in closed systems only.

This mixture does not contain any REACH registered substances that are assessed to be a PBT or a vPvB.

A vertical bar (|) in the left margin indicates an amendment from the previous version.

There has been a significant change in compositional information in section 2 & 3.

There has been an increase in the Health Hazard classification of this product in section 2. Ensure that the related sections (particularly sections 4, 8 & 11) are carefully studied.

Due to a change in detail in Section 15, this document has been released as a significant change.

Sources of key data used to compile the Safety Data Sheet : The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID data base, EC 1272 regulation, etc).

### Classification of the mixture:

Flam. Liq. 3	H226
Asp. Tox. 1	H304
Skin Irrit. 2	H315
Acute Tox. 4	H332

### Classification procedure:

On basis of test data.  
Expert judgement and weight of evidence determination.  
Expert judgement and weight of evidence determination.  
Expert judgement and weight of evidence determination.

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version	Revision Date:	SDS Number:	Date of last issue: 25.03.2024
7.2	13.06.2024	800001002191	Print Date 14.06.2024

---

Carc. 1B	H350	Expert judgement and weight of evidence determination.
STOT SE 3	H336	Expert judgement and weight of evidence determination.
STOT RE 2	H373	Expert judgement and weight of evidence determination.
Aquatic Chronic 2	H411	Expert judgement and weight of evidence determination.

### Identified Uses according to the Use Descriptor System

#### Uses - Worker

Title : Manufacture of substance  
- Industrial

#### Uses - Worker

Title : Use as an intermediate  
- Industrial

#### Uses - Worker

Title : Formulation & (re)packing of substances and mixtures  
- Industrial

#### Uses - Worker

Title : Use as a fuel  
- Industrial

#### Uses - Worker

Title : Use as a fuel  
- Professional

### Identified Uses according to the Use Descriptor System

#### Uses - Consumer

Title : Use as a fuel  
- Consumer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version 7.2      Revision Date: 13.06.2024      SDS Number: 800001002191      Date of last issue: 25.03.2024  
Print Date 14.06.2024

### Exposure Scenario - Worker

<b>300000000012</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Manufacture of substance- Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU3, SU8, SU9 <b>Process Categories:</b> PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC15 <b>Environmental Release Categories:</b> ERC1, ESVOC SpERC 1.1.v1
<b>Scope of process</b>	Manufacture of the substance or use as a process chemical or extraction agent. Includes recycling/ recovery, material transfers, storage, maintenance and loading (including marine vessel/barge, road/rail car and bulk container), sampling and associated laboratory activities.

SECTION 2		OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Section 2.1		Control of Worker Exposure	
Product Characteristics			
Physical form of product		Liquid, vapour pressure < 0.5 kPa at STP	
Concentration of the Substance in Mixture/Article		Covers use of substance/product up to 100% (unless stated differently).,	
Frequency and Duration of Use			
Covers daily exposures up to 8 hours (unless stated differently).			
Other Operational Conditions affecting Exposure			
Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented.			
Contributing Scenarios		Risk Management Measures	
General measures (skin irritants).		Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.	
General measures (carcinogens).		Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance. Where there is potential for exposure: restrict access to authorised persons; provide specific activity training	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version 7.2      Revision Date: 13.06.2024      SDS Number: 800001002191      Date of last issue: 25.03.2024  
Print Date 14.06.2024

	to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when there is potential for inhalation; clear up spills immediately and dispose of wastes safely. Ensure safe systems of work or equivalent arrangements are in place to manage risks. Regularly inspect, test and maintain all control measures. Consider the need for risk based health surveillance.
<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Substance is complex UVCB.	
Predominantly hydrophobic.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	1
Regional use tonnage (tonnes/year):	1.6E+07
Fraction of Regional tonnage used locally:	9.5E-01
Annual site tonnage (tonnes/year):	1.8E+06
Maximum daily site tonnage (kg/day):	6.0E+06
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	300
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from process (initial release prior to RMM):	1.0E-02
Release fraction to wastewater from process (initial release prior to RMM):	7.5E-08
Release fraction to soil from process (initial release prior to RMM):	1.0E-04
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process release estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Risk from environmental exposure is driven by freshwater sediment.	
Prevent discharge of undissolved substance to or recover from onsite wastewater.	
Onsite waste water treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	90
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	94.3
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils.	
Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	95



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version 7.2      Revision Date: 13.06.2024      SDS Number: 800001002191      Date of last issue: 25.03.2024  
Print Date 14.06.2024

Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	95
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	6.7E+06
Assumed domestic sewage treatment plant flow (m3/d)	10,000
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
During manufacturing no waste of the substance is generated.	
<b>Conditions and measures related to external recovery of waste</b>	
During manufacturing no waste of the substance is generated.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

<b>Section 3.2 -Environment</b>	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Available hazard data do not enable the derivation of a DNEL for dermal irritant effects. Risk Management Measures are based on qualitative risk characterisation. Users are advised to consider national Occupational Exposure Limits or other equivalent values. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.	

<b>Section 4.2 -Environment</b>	
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.	
Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.	
Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.	
Further details on scaling and control technologies are provided in SpERC factsheet ( <a href="http://cefic.org">http://cefic.org</a> ).	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version 7.2      Revision Date: 13.06.2024      SDS Number: 800001002191      Date of last issue: 25.03.2024  
Print Date 14.06.2024

### Exposure Scenario - Worker

<b>300000000013</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Use as an intermediate- Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU3, SU8, SU9 <b>Process Categories:</b> PROC1, PROC2, PROC3, PROC4, PROC8a, PROC8b, PROC9, PROC15 <b>Environmental Release Categories:</b> ERC6a, ESVOC SpERC 6.1a.v1
<b>Scope of process</b>	Use of substance as an intermediate within closed or contained systems (not related to Strictly Controlled Conditions). Includes incidental exposures during recycling/recovery, material transfers, storage, sampling, associated laboratory activities, maintenance and loading (including marine vessel/barge, road/rail car and bulk container).

SECTION 2		OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Section 2.1		Control of Worker Exposure	
Product Characteristics			
Physical form of product		Liquid, vapour pressure < 0.5 kPa at STP	
Concentration of the Substance in Mixture/Article		Covers use of substance/product up to 100% (unless stated differently).,	
Frequency and Duration of Use			
Covers daily exposures up to 8 hours (unless stated differently).			
Other Operational Conditions affecting Exposure			
Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented.			
Contributing Scenarios		Risk Management Measures	
General measures (skin irritants).		Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.	
General measures (carcinogens).		Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance. Where there is potential for exposure: restrict	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version 7.2      Revision Date: 13.06.2024      SDS Number: 800001002191      Date of last issue: 25.03.2024  
Print Date 14.06.2024

	access to authorised persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when there is potential for inhalation; clear up spills immediately and dispose of wastes safely. Ensure safe systems of work or equivalent arrangements are in place to manage risks. Regularly inspect, test and maintain all control measures. Consider the need for risk based health surveillance.
<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Substance is complex UVCB.	
Predominantly hydrophobic.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	1.0
Regional use tonnage (tonnes/year):	2.8E+06
Fraction of Regional tonnage used locally:	5.5E-02
Annual site tonnage (tonnes/year):	1.5E+04
Maximum daily site tonnage (kg/day):	5.0E+04
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	300
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from process (initial release prior to RMM):	1.0E-03
Release fraction to wastewater from process (initial release prior to RMM):	3.0E-04
Release fraction to soil from process (initial release prior to RMM):	1.0E-03
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process release estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Risk from environmental exposure is driven by freshwater sediment.	
Prevent discharge of undissolved substance to or recover from onsite wastewater.	
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	80
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	93.2
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils.	
Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version 7.2      Revision Date: 13.06.2024      SDS Number: 800001002191      Date of last issue: 25.03.2024  
Print Date 14.06.2024

Estimated substance removal from wastewater via domestic sewage treatment (%)	95
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	95
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	6.7E+04
Assumed domestic sewage treatment plant flow (m3/d)	2,000
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
This substance is consumed during use and no waste of substance is generated.	
<b>Conditions and measures related to external recovery of waste</b>	
This substance is consumed during use and no waste of substance is generated.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

<b>Section 3.2 -Environment</b>	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Available hazard data do not enable the derivation of a DNEL for dermal irritant effects. Risk Management Measures are based on qualitative risk characterisation. Users are advised to consider national Occupational Exposure Limits or other equivalent values. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.	

<b>Section 4.2 -Environment</b>	
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.	
Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.	
Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.	
Further details on scaling and control technologies are provided in SpERC factsheet ( <a href="http://cefic.org">http://cefic.org</a> ).	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version  
7.2

Revision Date:  
13.06.2024

SDS Number:  
800001002191

Date of last issue: 25.03.2024  
Print Date 14.06.2024

### Exposure Scenario - Worker

**300000000015**

SECTION 1	EXPOSURE SCENARIO TITLE
Title	Formulation & (re)packing of substances and mixtures- Industrial
Use Descriptor	<b>Sector of Use:</b> SU3, SU10 <b>Process Categories:</b> PROC1, PROC2, PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC9, PROC14, PROC15 <b>Environmental Release Categories:</b> ERC2, ESVOC SpERC 2.2.v1
Scope of process	Formulation, packing and re-packing of the substance and its mixtures in batch or continuous operations, including storage, materials transfers, mixing, tableting, compression, pelletisation, extrusion, large and small scale packing, sampling, maintenance and associated laboratory activities.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Section 2.1	Control of Worker Exposure
Product Characteristics	
Physical form of product	Liquid, vapour pressure < 0.5 kPa at STP
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).,
Frequency and Duration of Use	
Covers daily exposures up to 8 hours (unless stated differently).	
Other Operational Conditions affecting Exposure	
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.	
Contributing Scenarios	Risk Management Measures
General measures (skin irritants).	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.
General measures (carcinogens).	Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance. Where there is potential for exposure: restrict

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version  
7.2

Revision Date:  
13.06.2024

SDS Number:  
800001002191

Date of last issue: 25.03.2024  
Print Date 14.06.2024

	access to authorised persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when there is potential for inhalation; clear up spills immediately and dispose of wastes safely. Ensure safe systems of work or equivalent arrangements are in place to manage risks. Regularly inspect, test and maintain all control measures. Consider the need for risk based health surveillance.
<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Substance is complex UVCB.	
Predominantly hydrophobic.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	1.0
Regional use tonnage (tonnes/year):	6.2E+07
Fraction of Regional tonnage used locally:	2.0E-03
Annual site tonnage (tonnes/year):	3.7E+03
Maximum daily site tonnage (kg/day):	1.2E+04
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	300
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from process (after typical onsite RMMs consistent with EU Solvent Emissions Directive requirements):	1.0E-02
Release fraction to wastewater from process (initial release prior to RMM):	2.0E-04
Release fraction to soil from process (initial release prior to RMM):	1.0E-04
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process release estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Risk from environmental exposure is driven by freshwater sediment.	
Prevent discharge of undissolved substance to or recover from onsite wastewater.	
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	0
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	79.3
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils.	
Sludge should be incinerated, contained or reclaimed.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version 7.2      Revision Date: 13.06.2024      SDS Number: 800001002191      Date of last issue: 25.03.2024  
Print Date 14.06.2024

<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	95
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	95
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	5.1E+04
Assumed domestic sewage treatment plant flow (m3/d)	2,000
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
<b>Conditions and measures related to external recovery of waste</b>	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

<b>Section 3.2 -Environment</b>
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Available hazard data do not enable the derivation of a DNEL for dermal irritant effects. Risk Management Measures are based on qualitative risk characterisation. Users are advised to consider national Occupational Exposure Limits or other equivalent values. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.	

<b>Section 4.2 -Environment</b>
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.
Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.
Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.
Further details on scaling and control technologies are provided in SpERC factsheet ( <a href="http://cefic.org">http://cefic.org</a> ).

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version 7.2      Revision Date: 13.06.2024      SDS Number: 800001002191      Date of last issue: 25.03.2024  
Print Date 14.06.2024

### Exposure Scenario - Worker

<b>300000000016</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Use as a fuel- Industrial
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU3 <b>Process Categories:</b> PROC1, PROC2, PROC8a, PROC8b, PROC16 <b>Environmental Release Categories:</b> ERC7, ESVOC SpERC 7.12a.v1
<b>Scope of process</b>	Covers the use as a fuel (or fuel additive) and includes activities associated with its transfer, use, equipment maintenance and handling of waste.

SECTION 2		OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Section 2.1		Control of Worker Exposure	
Product Characteristics			
Physical form of product		Liquid, vapour pressure < 0.5 kPa at STP	
Concentration of the Substance in Mixture/Article		Covers use of substance/product up to 100% (unless stated differently).,	
Frequency and Duration of Use			
Covers daily exposures up to 8 hours (unless stated differently).			
Other Operational Conditions affecting Exposure			
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.			
Contributing Scenarios		Risk Management Measures	
General measures (skin irritants).		Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.	
General measures (carcinogens).		Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance. Where there is potential for exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory pro-	



# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version 7.2      Revision Date: 13.06.2024      SDS Number: 800001002191      Date of last issue: 25.03.2024  
Print Date 14.06.2024

	tection when there is potential for inhalation; clear up spills immediately and dispose of wastes safely. Ensure safe systems of work or equivalent arrangements are in place to manage risks. Regularly inspect, test and maintain all control measures. Consider the need for risk based health surveillance.
<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Substance is complex UVCB.	
Predominantly hydrophobic.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	1.0
Regional use tonnage (tonnes/year):	3.8E+06
Fraction of Regional tonnage used locally:	5.0E+04
Annual site tonnage (tonnes/year):	1.6E+02
Maximum daily site tonnage (kg/day):	8.1E+03
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	20
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from process (initial release prior to RMM):	5.0E-03
Release fraction to wastewater from process (initial release prior to RMM):	1.0E-05
Release fraction to soil from process (initial release prior to RMM):	0
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process release estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Risk from environmental exposure is driven by freshwater sediment.	
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	95
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	0
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils.	
Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	95
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	95
Maximum allowable site tonnage (MSafe) based on release following	5.0E+05

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version 7.2      Revision Date: 13.06.2024      SDS Number: 800001002191      Date of last issue: 25.03.2024  
Print Date 14.06.2024

total wastewater treatment removal (kg/d)	
Assumed domestic sewage treatment plant flow (m3/d)	2,000
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
Combustion emissions limited by required exhaust emission controls.	
Waste combustion emissions considered in regional exposure assessment.	
<b>Conditions and measures related to external recovery of waste</b>	
This substance is consumed during use and no waste of substance is generated.	

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

<b>Section 3.2 -Environment</b>	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	

<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Available hazard data do not enable the derivation of a DNEL for dermal irritant effects. Risk Management Measures are based on qualitative risk characterisation. Users are advised to consider national Occupational Exposure Limits or other equivalent values. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.	

<b>Section 4.2 -Environment</b>	
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.	
Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.	
Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.	
Further details on scaling and control technologies are provided in SpERC factsheet ( <a href="http://cefic.org">http://cefic.org</a> ).	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version 7.2      Revision Date: 13.06.2024      SDS Number: 800001002191      Date of last issue: 25.03.2024  
Print Date 14.06.2024

### Exposure Scenario - Worker

<b>300000000017</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Use as a fuel- Professional
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU22 <b>Process Categories:</b> PROC1, PROC2, PROC8a, PROC8b, PROC16 <b>Environmental Release Categories:</b> ERC9a, ERC9b, ESVOC SpERC 9.12b.v1
<b>Scope of process</b>	Covers the use as a fuel (or fuel additive) and includes activities associated with its transfer, use, equipment maintenance and handling of waste.

SECTION 2		OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Section 2.1		Control of Worker Exposure	
Product Characteristics			
Physical form of product		Liquid, vapour pressure < 0.5 kPa at STP	
Concentration of the Substance in Mixture/Article		Covers use of substance/product up to 100% (unless stated differently).,	
Frequency and Duration of Use			
Covers daily exposures up to 8 hours (unless stated differently).			
Other Operational Conditions affecting Exposure			
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.			
Contributing Scenarios		Risk Management Measures	
General measures (skin irritants).		Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop. No other specific measures identified.	
General measures (carcinogens).		Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance. Where there is potential for exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory pro-	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version 7.2      Revision Date: 13.06.2024      SDS Number: 800001002191      Date of last issue: 25.03.2024  
Print Date 14.06.2024

	tection when there is potential for inhalation; clear up spills immediately and dispose of wastes safely.Ensure safe systems of work or equivalent arrangements are in place to manage risks. Regularly inspect, test and maintain all control measures. Consider the need for risk based health surveillance.
<b>Section 2.2</b>	<b>Control of Environmental Exposure</b>
Substance is complex UVCB.	
Predominantly hydrophobic.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	1.0
Regional use tonnage (tonnes/year):	1.4E+07
Fraction of Regional tonnage used locally:	2.0E-03
Annual site tonnage (tonnes/year):	2.9E+03
Maximum daily site tonnage (kg/day):	7.9E+03
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	365
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from wide dispersive use (regional only):	5.0E-03
Release fraction to wastewater from wide dispersive use:	1.0E-06
Release fraction to soil from wide dispersive use (regional only):	2.5E-04
<b>Technical conditions and measures at process level (source) to prevent release</b>	
Common practices vary across sites thus conservative process release estimates used.	
<b>Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil</b>	
Risk from environmental exposure is driven by freshwater.	
No wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	0
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
<b>Organisational measures to prevent/limit release from site</b>	
Do not apply industrial sludge to natural soils.	
Sludge should be incinerated, contained or reclaimed.	
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Estimated substance removal from wastewater via domestic sewage treatment (%)	95
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	95
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	7.7E+05
Assumed domestic sewage treatment plant flow (m3/d)	2,000

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version 7.2      Revision Date: 13.06.2024      SDS Number: 800001002191      Date of last issue: 25.03.2024  
Print Date 14.06.2024

### Conditions and Measures related to external treatment of waste for disposal

Combustion emissions limited by required exhaust emission controls.

Waste combustion emissions considered in regional exposure assessment.

### Conditions and measures related to external recovery of waste

This substance is consumed during use and no waste of substance is generated.

## SECTION 3

### EXPOSURE ESTIMATION

#### Section 3.1 - Health

The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

#### Section 3.2 -Environment

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

## SECTION 4

### GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

#### Section 4.1 - Health

Available hazard data do not enable the derivation of a DNEL for dermal irritant effects.

Risk Management Measures are based on qualitative risk characterisation.

Users are advised to consider national Occupational Exposure Limits or other equivalent values.

Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

#### Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org>).

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version 7.2      Revision Date: 13.06.2024      SDS Number: 800001002191      Date of last issue: 25.03.2024  
Print Date 14.06.2024

### Exposure Scenario - Consumer

<b>300000000209</b>	
<b>SECTION 1</b>	<b>EXPOSURE SCENARIO TITLE</b>
<b>Title</b>	Use as a fuel - Consumer
<b>Use Descriptor</b>	<b>Sector of Use:</b> SU21 <b>Product Categories:</b> PC13 <b>Environmental Release Categories:</b> ERC9a, ERC9b, ESVOC SpERC 9.12c.v1
<b>Scope of process</b>	Covers use for automotive, home heating appliances and garden equipment.

<b>SECTION 2</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
<b>Section 2.1</b>	<b>Control of Consumer Exposure</b>
<b>Product Characteristics</b>	
Physical form of product	Liquid, vapour pressure > 10 Pa
Concentration of the Substance in Mixture/Article	Unless stated otherwise.
	Covers concentration up to (%): 100 %
<b>Amounts Used</b>	
Unless stated otherwise.	
for each use event, covers amount up to (g):	37,500
covers skin contact area (cm2):	420
<b>Frequency and Duration of Use</b>	
covers use up to (times/day of use):	1
Exposure (hours/event): Unless stated otherwise.	0.05
<b>Other Operational Conditions affecting Exposure</b>	
Covers use at ambient temperatures. Covers use in room size of 20m3 Covers use under typical household ventilation. Unless stated otherwise.	
<b>Product Categories</b>	<b>OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES</b>
Fuels Liquid: Automotive Refuelling.	Covers concentrations up to 100 %
	covers use up to 52 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 210.00 cm2
	For each use event, covers amount up to 37,500 g
	Covers outdoor use.
	Covers use in room size of 100 m3
	Covers exposure up to 0.05 hours/event
Fuels Liquid: Home space heater fuel.	Covers concentrations up to 100 %
	covers use up to 180 day/year

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version 7.2      Revision Date: 13.06.2024      SDS Number: 800001002191      Date of last issue: 25.03.2024  
Print Date 14.06.2024

	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 210.00 cm2
	For each use event, covers amount up to 3,320 g
	Covers use under typical household ventilation.
	Covers use in room size of 20 m3
	Covers exposure up to 0.03 hours/event
Fuels Liquid: Garden Equipment - Refuelling.	Covers concentrations up to 100 %
	covers use up to 26 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 420.00 cm2
	For each use event, covers amount up to 750 g
	Covers use in a one car garage (34 m3) under typical ventilation.
	Covers exposure up to 0.03 hours/event

Section 2.2	Control of Environmental Exposure
Substance is complex UVCB.	
Predominantly hydrophobic.	
<b>Amounts Used</b>	
Fraction of EU tonnage used in region:	1.0
Regional use tonnage (tonnes/year):	4.4E+07
Fraction of Regional tonnage used locally:	2.0E-03
Annual site tonnage (tonnes/year):	1.5E+02
Maximum daily site tonnage (kg/day):	4.2E+02
<b>Frequency and Duration of Use</b>	
Continuous release.	
Emission Days (days/year):	365
<b>Environmental factors not influenced by risk management</b>	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
<b>Other Operational Conditions affecting Environmental Exposure</b>	
Release fraction to air from wide dispersive use (regional only):	1.0E-04
Release fraction to wastewater from wide dispersive use:	2.0E-07
Release fraction to soil from wide dispersive use (regional only):	5.0E-05
<b>Conditions and Measures related to municipal sewage treatment plant</b>	
Risk from environmental exposure is driven by freshwater.	
Estimated substance removal from wastewater via domestic sewage treatment (%)	95.0
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	4.4E+04
Assumed domestic sewage treatment plant flow (m3/d)	2,000
<b>Conditions and Measures related to external treatment of waste for disposal</b>	
Combustion emissions limited by required exhaust emission controls.	
Waste combustion emissions considered in regional exposure assessment.	
<b>Conditions and measures related to external recovery of waste</b>	
This substance is consumed during use and no waste of substance is generated.	

# SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

## F-34 / AVTUR/FSII

Version 7.2      Revision Date: 13.06.2024      SDS Number: 800001002191      Date of last issue: 25.03.2024  
Print Date 14.06.2024

<b>SECTION 3</b>	<b>EXPOSURE ESTIMATION</b>
<b>Section 3.1 - Health</b>	
The ECETOC TRA tool has been used to estimate consumer exposures unless otherwise indicated.	
<b>Section 3.2 -Environment</b>	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	
<b>SECTION 4</b>	<b>GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO</b>
<b>Section 4.1 - Health</b>	
Predicted exposures are not expected to exceed the applicable consumer reference values when the operational conditions/risk management measures given in section 2 are implemented. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.	
<b>Section 4.2 -Environment</b>	
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.	
Further details on scaling and control technologies are provided in SpERC factsheet ( <a href="http://cefic.org">http://cefic.org</a> ).	