

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version	Revision Date.:	SDS Number:	Date of last issue: 05.09.2025
8.3	09.03.2026	800001004187	Print Date. 10.03.2026

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name	:	Shell FuelSave Unleaded
Product code	:	002D1843
Unique Formula Identifier	:	W2R3-M0V6-X00X-D4FS

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture	:	Fuel for use in suitably designed motor vehicles. Please refer to section 16 and/or the annexes for the registered uses under REACH.
Uses advised against	:	This product must not be used in applications other than those listed in Section 1 without first seeking the advice of the supplier., This product is not to be used as a solvent or cleaning agent; for lighting or brightening fires; as a skin cleanser., This product is designed only to suit automotive applications and no provision is made for the requirements of aviation applications.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier	:	Shell UK Oil Products Limited Shell Centre London SE1 7NA United Kingdom
Telephone	:	(+44) 08007318888
Telefax	:	
Contact for Safety Data Sheet	:	If you have any enquiries about the content of this SDS please email fuelSDS@shell.com

1.4 Emergency telephone number

: +44 (0) 20 7934 7778 (This telephone number is available 24 hours per day, 7 days per week)

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

SECTION 2: Hazards identification


2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 1	H224: Extremely flammable liquid and vapour.
Skin irritation, Category 2	H315: Causes skin irritation.
Carcinogenicity, Category 1B	H350: May cause cancer.
Germ cell mutagenicity, Category 1B	H340: May cause genetic defects.
Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters airways.
Specific target organ toxicity - single exposure, Category 3, Inhalation, Narcotic effects	H336: May cause drowsiness or dizziness.
Reproductive toxicity, Category 2	H361fd: Suspected of damaging fertility. Suspected of damaging the unborn child.
Long-term (chronic) aquatic hazard, Category 2	H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms : 

Signal word : Danger

Hazard statements :
PHYSICAL HAZARDS:
H224 Extremely flammable liquid and vapour.
HEALTH HAZARDS:
H315 Causes skin irritation.
H340 May cause genetic defects.
H350 May cause cancer.
H304 May be fatal if swallowed and enters airways.
H336 May cause drowsiness or dizziness.
H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.
ENVIRONMENTAL HAZARDS:
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3	Revision Date.: 09.03.2026	SDS Number: 800001004187	Date of last issue: 05.09.2025 Print Date. 10.03.2026
----------------	-------------------------------	-----------------------------	--

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

2.3 Other hazards

This mixture does not contain any REACH registered substances that are assessed to be a PBT or a vPvB.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Liquid evaporates quickly and can ignite leading to a flash fire, or an explosion in a confined space.

A component or components of this material may cause cancer.

This product contains benzene which may cause leukaemia (AML - acute myelogenous leukaemia).

This material is a static accumulator.

Even with proper grounding and bonding, this material can still accumulate an electrostatic charge.

If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur.

Ether oxygenates are significantly more water soluble and less biodegradable than benzene, toluene, ethyl benzene and xylenes (BTEX)

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Complex mixture of hydrocarbons consisting of paraffins, cycloparaffins, aromatic and olefinic hydrocarbons with carbon numbers predominantly in the C4 to C12 range.
Contains oxygenated hydrocarbons, including ethanol or other alcohols.
Contains oxygenated hydrocarbons which may include methyl tertiary butyl ether (MTBE) and other ethers.

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version
8.3

Revision Date.:
09.03.2026

SDS Number:
800001004187

Date of last issue: 05.09.2025
Print Date. 10.03.2026

May also contain several additives at <0.1% v/v each.

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Gasoline; Low boiling point naphtha -unspecified	86290-81-5 289-220-8 649-378-00-4 01-2119471335-39, UK-01-4615601157-2	Flam. Liq. 1; H224 Skin Irrit. 2; H315 Carc. 1B; H350 Muta. 1B; H340 Asp. Tox. 1; H304 STOT SE 3; H336 (Narcotic effects) Repr. 2; H361fd Aquatic Chronic 2; H411	>= 80 - <= 100
tert-butyl methyl ether	1634-04-4 216-653-1 603-181-00-X 01-2119452786-27, UK-01-8863475017-3	Flam. Liq. 2; H225 Skin Irrit. 2; H315	>= 0 - <= 15
2-methoxy-2-methylbutane	994-05-8 213-611-4 603-213-00-2 01-2119453236-41, UK-01-4696622180-9	Flam. Liq. 2; H225 Acute Tox. 4; H302 STOT SE 3; H336	>= 0 - <= 15
Ethyl tertiary butyl ether	637-92-3 211-309-7 01-2119452785-29, UK-01-3710149740-4	Flam. Liq. 2; H225 STOT SE 3; H336 (Narcotic effects)	>= 0 - <= 15
Renewable hydrocarbons (naphtha type fraction) obtained from the catalytic transformation of ethanol	Not Assigned 701-193-0 01-2120790169-43	Flam. Liq. 1; H224 Skin Irrit. 2; H315 Asp. Tox. 1; H304 Repr. 2; H361d Carc. 1B; H350 Muta. 1B; H340 STOT SE 3; H336 Aquatic Chronic 2; H411	>= 0 - <= 5
Ethanol	64-17-5 200-578-6 603-002-00-5 01-2119457610-43, UK-01-8186404962-2	Flam. Liq. 2; H225 Eye Irrit. 2; H319 specific concentration limit Eye Irrit. 2 50 %	>= 0 - <= 5
Methanol	67-56-1	Flam. Liq. 2; H225	>= 0 - <= 3

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version
8.3

Revision Date.:
09.03.2026

SDS Number:
800001004187

Date of last issue: 05.09.2025
Print Date. 10.03.2026

	200-659-6 603-001-00-X 01-2119433307-44, UK-01-8636477472-8	Acute Tox. 3; H331 Acute Tox. 3; H311 Acute Tox. 3; H301 STOT SE 1; H370 (Visual system, Nervous system) specific concentration limit STOT SE 1; H370 ≥ 10 % STOT SE 2; H371 3 - < 10 % Acute oral toxicity: Acute toxicity esti- mate 100 mg/kg bw Acute inhalation tox- icity: Acute toxicity estimate 3 mg/l Acute dermal toxicity: Acute toxicity esti- mate 300 mg/kg bw	
--	--	--	--

Remarks : Dyes and markers can be used to indicate tax status and prevent fraud.

For explanation of abbreviations see section 16.

Further information

Contains:

Chemical name	Identification number	Classification	Concentration (% w/w)
Xylene, mixed isomers	1330-20-7, 215-535-7	Flam. Liq.3; H226 Asp. Tox.1; H304 Acute Tox.4; H312 Skin Irrit.2; H315 Eye Irrit.2; H319 Acute Tox.4; H332 STOT SE3; H335 STOT RE2; H373 Aquatic Chronic3; H412	5 - 25

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version
8.3

Revision Date.:
09.03.2026

SDS Number:
800001004187

Date of last issue: 05.09.2025
Print Date. 10.03.2026

Ethylbenzene	100-41-4, 202-849-4	Flam. Liq.2; H225 Asp. Tox.1; H304 Skin Irrit.2; H315 Eye Irrit.2; H319 Acute Tox.4; H332 STOT SE3; H335 STOT RE2; H373 Aquatic Chronic3; H412	1 - 5
Cyclohexane	110-82-7, 203-806-2	Flam. Liq.2; H225 Asp. Tox.1; H304 Skin Irrit.2; H315 STOT SE3; H336 Aquatic Chronic1; H410 Aquatic Acute1; H400 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	1 - 5
Cumene	98-82-8, 202-704-5	Flam. Liq.3; H226 Asp. Tox.1; H304 STOT SE3; H335 Carc.1B; H350 Aquatic Chronic2; H411	0 - 0.5
n-Hexane	110-54-3, 203-777-6	Flam. Liq.2; H225 Asp. Tox.1; H304 Skin Irrit.2; H315 STOT SE3; H336 Repr.2; H361f STOT RE1; H372 Aquatic Chronic2; H411	0 - 5
Toluene	108-88-3, 203-625-9	Flam. Liq.2; H225 Asp. Tox.1; H304 Skin Irrit.2; H315 STOT SE3; H336 Repr.2; H361d STOT RE2; H373 Aquatic Chronic3; H412	5 - 25

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version
8.3

Revision Date.:
09.03.2026

SDS Number:
800001004187

Date of last issue: 05.09.2025
Print Date. 10.03.2026

Trimethylbenzene (all isomers)	25551-13-7, 247-099-9	Flam. Liq.3; H226 STOT SE3; H335 Aquatic Chronic2; H411	0 - 5
Naphthalene	91-20-3, 202-049-5	Acute Tox.4; H302 Carc.2; H351 Aquatic Acute1; H400 Aquatic Chronic1; H410 M-Factor (Acute aquatic toxicity): 1	0 - 0.5
Benzene	71-43-2, 200-753-7	Flam. Liq.2; H225 Asp. Tox.1; H304 Skin Irrit.2; H315 Eye Irrit.2; H319 Muta.1B; H340 Carc.1A; H350 STOT RE1; H372 Aquatic Chronic3; H412	0 - 1

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Not expected to be a health hazard when used under normal conditions.
- Protection of first-aiders : When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
- If inhaled : Remove to fresh air. If rapid recovery does not occur, transport to nearest medical facility for additional treatment.
- In case of skin contact : Remove contaminated clothing. Immediately flush skin with large amounts of water for at least 15 minutes, and follow by washing with soap and water if available. If redness, swelling, pain and/or blisters occur, transport to the nearest medical

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

facility for additional treatment.
When using high pressure equipment, injection of product under the skin can occur. If high pressure injuries occur, the casualty should be sent immediately to a hospital. Do not wait for symptoms to develop.
Obtain medical attention even in the absence of apparent wounds.

In case of eye contact : Flush eye with copious quantities of water.
Remove contact lenses, if present and easy to do. Continue rinsing.
If persistent irritation occurs, obtain medical attention.

If swallowed : Call emergency number for your location / facility.
If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.
If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Breathing of high vapour concentrations may cause central nervous system (CNS) depression resulting in dizziness, light-headedness, headache and nausea.
The onset of respiratory symptoms may be delayed for several hours after exposure.
Skin irritation signs and symptoms may include a burning sensation, redness, or swelling.
Local necrosis is evidenced by delayed onset of pain and tissue damage a few hours following injection.
Eye irritation signs and symptoms may include a burning sensation and a temporary redness of the eye.
If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever.
If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : IMMEDIATE TREATMENT IS EXTREMELY IMPORTANT!
Treat symptomatically.
Call a doctor or poison control center for guidance.
High pressure injection injuries require prompt surgical intervention and possibly steroid therapy, to minimise tissue dam-

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3	Revision Date.: 09.03.2026	SDS Number: 800001004187	Date of last issue: 05.09.2025 Print Date. 10.03.2026
----------------	-------------------------------	-----------------------------	--

age and loss of function.
Because entry wounds are small and do not reflect the seriousness of the underlying damage, surgical exploration to determine the extent of involvement may be necessary. Local anaesthetics or hot soaks should be avoided because they can contribute to swelling, vasospasm and ischaemia. Prompt surgical decompression, debridement and evacuation of foreign material should be performed under general anaesthetics, and wide exploration is essential.
Potential for chemical pneumonitis.
Do not induce vomiting.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Alcohol-resistant foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
- Unsuitable extinguishing media : Do not use direct water jets on the burning product as they could cause a steam explosion and spread of the fire. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.

5.2 Special hazards arising from the substance or mixture

- Specific hazards during fire-fighting : Hazardous combustion products may include:
A complex mixture of airborne solid and liquid particulates and gases (smoke).
Carbon monoxide may be evolved if incomplete combustion occurs.
Unidentified organic and inorganic compounds.
The vapour is heavier than air, spreads along the ground and distant ignition is possible.
Will float and can be reignited on surface water.

5.3 Advice for firefighters

- Special protective equipment for firefighters : Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).
- Further information : Keep adjacent containers cool by spraying with water. If possible remove containers from the danger zone. If the fire cannot be extinguished the only course of action is to evacuate immediately.

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3	Revision Date.: 09.03.2026	SDS Number: 800001004187	Date of last issue: 05.09.2025 Print Date. 10.03.2026
----------------	-------------------------------	-----------------------------	--

Contain residual material at affected sites to prevent material from entering drains (sewers), ditches, and waterways.

Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : 6.1.1 For non emergency personnel:
Do not breathe fumes, vapour.
Do not operate electrical equipment.
6.1.2 For emergency responders:
Shut off leaks, if possible without personal risks.
Evacuate all personnel.
Vapour can travel for considerable distances both above and below the ground surface. Underground services (drains, pipelines, cable ducts) can provide preferential flow paths. Remove all possible sources of ignition in the surrounding area.
Attempt to disperse vapour or to direct its flow to a safe location for example using fog sprays.

6.2 Environmental precautions

Environmental precautions : Take measures to minimise the effects on groundwater.
Contain residual material at affected sites to prevent material from entering drains (sewers), ditches, and waterways.
Prevent from spreading or entering into drains, ditches or rivers by using sand, earth, or other appropriate barriers.

Do not allow contact with soil, surface or ground water.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Take precautionary measures against static discharges.
For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.
For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version	Revision Date.:	SDS Number:	Date of last issue: 05.09.2025
8.3	09.03.2026	800001004187	Print Date. 10.03.2026

6.4 Reference to other sections

For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet., Notify authorities if any exposure to the general public or the environment occurs or is likely to occur., For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet., Local authorities should be advised if significant spillages cannot be contained., Maritime spillages should be dealt with using a Shipboard Oil Pollution Emergency Plan (SOPEP), as required by MARPOL Annex 1 Regulation 26.

To the extent that this product, including its chemical components (e.g. Methyl tertiary butyl ether) may impact surface or groundwater, appropriate assessment and remediation (if necessary) should be implemented.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- | | | |
|-------------------------|---|--|
| Technical measures | : | Avoid breathing of or direct contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.
Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
Air-dry contaminated clothing in a well-ventilated area before laundering.
Prevent spillages.
Turn off all battery operated portable electronic devices (examples include: cellular phones, pagers and CD players) before operating gasoline pump.
Contaminated leather articles including shoes cannot be decontaminated and should be destroyed to prevent reuse.
Do not use as a cleaning solvent or other non-motor fuel uses.
Ensure that all local regulations regarding handling and storage facilities are followed.
Vehicle fueling and vehicle workshop areas - Avoid inhalation of vapours and contact with skin, when filling or emptying a vehicle. |
| Advice on safe handling | : | Ensure that all local regulations regarding handling and storage facilities are followed.
When using do not eat or drink.
Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks.
Never siphon by mouth.
The vapour is heavier than air, spreads along the ground and distant ignition is possible.
Avoid exposure. Obtain special instructions before use.
Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols.
Properly dispose of any contaminated rags or cleaning mate- |

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

- Product Transfer : rials in order to prevent fires.
: Wait 2 minutes after tank filling (for tanks such as those on road tanker vehicles) before opening hatches or manholes. Wait 30 minutes after tank filling (for large storage tanks) before opening hatches or manholes. Even with proper grounding and bonding, this material can still accumulate an electrostatic charge. If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur. Be aware of handling operations that may give rise to additional hazards that result from the accumulation of static charges. These include but are not limited to pumping (especially turbulent flow), mixing, filtering, splash filling, cleaning and filling of tanks and containers, sampling, switch loading, gauging, vacuum truck operations, and mechanical movements. These activities may lead to static discharge e.g. spark formation. Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (≤ 1 m/s until fill pipe submerged to twice its diameter, then ≤ 7 m/s). Avoid splash filling. Do NOT use compressed air for filling, discharging, or handling operations.
- Hygiene measures : Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping. Define procedures for safe handling and maintenance of controls. Educate and train workers in the hazards and control measures relevant to normal activities associated with this product. Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation. Drain down system prior to equipment break-in or maintenance. Retain drain downs in sealed storage pending disposal or subsequent recycle. Do not ingest. If swallowed, then seek immediate medical assistance.
Exposure to this product should be reduced as low as reasonably practicable. Reference should be made to the Health and Safety Executive's publication "COSHH Essentials".

7.2 Conditions for safe storage, including any incompatibilities

- Further information on storage stability : Drum and small container storage:
Keep containers closed when not in use.
Drums should be stacked to a maximum of 3 high.
Use properly labeled and closable containers.
Packaged product must be kept tightly closed and stored in a diked (bunded) well-ventilated area, away from, ignition sources and other sources of heat.
Take suitable precautions when opening sealed containers, as pressure can build up during storage.
Tank storage:

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

Tanks must be specifically designed for use with this product. Bulk storage tanks should be diked (bunded). Locate tanks away from heat and other sources of ignition. Cleaning, inspection and maintenance of storage tanks is a specialist operation, which requires the implementation of strict procedures and precautions. Keep in a cool place. Electrostatic charges will be generated during pumping. Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to reduce the risk. The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flammable. Refer to section 15 for any additional specific legislation covering the packaging and storage of this product. The storage of this product may be subject to the Control of Pollution (Oil Storage) (England) Regulations. Further guidance may be obtained from the local environmental agency office.

- Packaging material : Suitable material: For containers, or container linings use mild steel, stainless steel., Aluminium may also be used for applications where it does not present an unnecessary fire hazard., Examples of suitable materials are: high density polyethylene (HDPE), polypropylene (PP), and Viton (FKM), which have been specifically tested for compatibility with this product., For container linings, use amine-adduct cured epoxy paint., For seals and gaskets use: graphite, PTFE, Viton A, Viton B. Unsuitable material: Some synthetic materials may be unsuitable for containers or container linings depending on the material specification and intended use. Examples of materials to avoid are: natural rubber (NR), nitrile rubber (NBR), ethylene propylene rubber (EPDM), polymethyl methacrylate (PMMA), polystyrene, polyvinyl chloride (PVC), polyisobutylene., However, some may be suitable for glove materials.
- Container Advice : Containers, even those that have been emptied, can contain explosive vapours. Do not cut, drill, grind, weld or perform similar operations on or near containers. Gasoline containers must not be used for storage of other products.

7.3 Specific end use(s)

- Specific use(s) : Please refer to section 16 and/or the annexes for the registered uses under REACH.

See additional references that provide safe handling practices for liquids that are determined to be static accumulators: American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practices

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version
8.3

Revision Date.:
09.03.2026

SDS Number:
800001004187

Date of last issue: 05.09.2025
Print Date. 10.03.2026

on Static Electricity).
IEC/TS 60079-32-1: Electrostatic hazards, guidance

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Gasoline; Low boiling point naphtha -unspecified	86290-81-5	TWA	300 ppm	ACGIH
Gasoline; Low boiling point naphtha -unspecified		STEL	500 ppm	ACGIH
2-methoxy-2-methylbutane	994-05-8	TWA	20 ppm	ACGIH
Ethyl tertiary butyl ether	637-92-3	TWA	25 ppm	ACGIH
tert-butyl methyl ether	1634-04-4	TWA	50 ppm 183.5 mg/m ³	GB EH40
tert-butyl methyl ether		STEL	100 ppm 367 mg/m ³	GB EH40
tert-butyl methyl ether		TWA	50 ppm	ACGIH
Ethanol	64-17-5	TWA	1,000 ppm 1,920 mg/m ³	GB EH40
	Further information: Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.			
Ethanol		STEL	1,000 ppm	ACGIH
Methanol	67-56-1	TWA	200 ppm 266 mg/m ³	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
Methanol		STEL	250 ppm 333 mg/m ³	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
Methanol		TWA	200 ppm 260 mg/m ³	2006/15/EC
	Further information: Indicative, Identifies the possibility of significant uptake through the skin			
Methanol		TWA	200 ppm	ACGIH
Methanol		STEL	250 ppm	ACGIH

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version
8.3

Revision Date.:
09.03.2026

SDS Number:
800001004187

Date of last issue: 05.09.2025
Print Date. 10.03.2026

Xylene, mixed isomers	1330-20-7	TWA	50 ppm 220 mg/m ³	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
Xylene, mixed isomers		STEL	100 ppm 441 mg/m ³	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
Xylene, mixed isomers		TWA	20 ppm	ACGIH
Ethylbenzene	100-41-4	TWA	100 ppm 441 mg/m ³	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
Ethylbenzene		STEL	125 ppm 552 mg/m ³	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
Ethylbenzene		TWA	20 ppm	ACGIH
Cyclohexane	110-82-7	TWA	100 ppm 350 mg/m ³	GB EH40
Cyclohexane		STEL	300 ppm 1,050 mg/m ³	GB EH40
Cyclohexane		TWA	200 ppm 700 mg/m ³	2006/15/EC
	Further information: Indicative			
Cyclohexane		TWA	100 ppm	ACGIH
Cumene	98-82-8	TWA	25 ppm 125 mg/m ³	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
Cumene		STEL	50 ppm 250 mg/m ³	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
Cumene		TWA	10 ppm 50 mg/m ³	2019/1831/E U
	Further information: A skin notation assigned to the occupational exposure limit value indicates the possibility of significant uptake through the skin., Indicative			
Cumene		STEL	50 ppm 250 mg/m ³	2019/1831/E U

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version
8.3

Revision Date.:
09.03.2026

SDS Number:
800001004187

Date of last issue: 05.09.2025
Print Date. 10.03.2026

		Further information: A skin notation assigned to the occupational exposure limit value indicates the possibility of significant uptake through the skin., Indicative		
Cumene		TWA	5 ppm	ACGIH
n-Hexane	110-54-3	TWA	20 ppm 72 mg/m ³	GB EH40
n-Hexane		TWA	20 ppm 72 mg/m ³	2006/15/EC
		Further information: Indicative		
n-Hexane		TWA	50 ppm	ACGIH
Toluene	108-88-3	TWA	50 ppm 191 mg/m ³	GB EH40
		Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		
Toluene		STEL	100 ppm 384 mg/m ³	GB EH40
		Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		
Toluene		TWA	50 ppm 192 mg/m ³	2006/15/EC
		Further information: Indicative, Identifies the possibility of significant uptake through the skin		
Toluene		STEL	100 ppm 384 mg/m ³	2006/15/EC
		Further information: Indicative, Identifies the possibility of significant uptake through the skin		
Toluene		TWA	20 ppm	ACGIH
Trimethylbenzene (all isomers)	25551-13-7	TWA	25 ppm 125 mg/m ³	GB EH40
Trimethylbenzene (all isomers)		TWA	10 ppm	ACGIH
Naphthalene	91-20-3	TWA	10 ppm 50 mg/m ³	91/322/EEC
		Further information: Indicative		
Naphthalene		TWA	10 ppm	ACGIH
Benzene	71-43-2	TWA	1 ppm 3.25 mg/m ³	GB EH40
		Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity., Capable of causing cancer and/or heritable genetic damage.		
Benzene		TWA	0.25 ppm 0.8 mg/m ³	Shell Internal Standard (SIS) for 8-12 hour TWA.
Benzene		STEL	2.5 ppm	Shell Internal

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version
8.3

Revision Date.:
09.03.2026

SDS Number:
800001004187

Date of last issue: 05.09.2025
Print Date. 10.03.2026

			8 mg/m ³	Standard (SIS) for 15 min (STEL)
Benzene		TWA	0.02 ppm	ACGIH
Benzene		STEL	2.5 ppm	ACGIH

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
Methanol	67-56-1	Methanol: 15 mg/l (Urine)	End of shift (As soon as possible after exposure ceases)	ACGIH BEI
Xylene, mixed isomers	1330-20-7	methyl hippuric acid: 650 Millimoles per mole creatinine (Urine)	After shift	GB EH40 BAT
		Methylhippuric acids: 0.3 g/g creatinine (Urine)	End of shift (As soon as possible after exposure ceases)	ACGIH BEI
Ethylbenzene	100-41-4	Sum of mandelic acid and phenyl glyoxylic acid: 0.15 g/g creatinine (Urine)	End of shift (As soon as possible after exposure ceases)	ACGIH BEI
Cyclohexane	110-82-7	1,2-Cyclohexanediol: 50 mg/g creatinine (Urine)	End of shift at end of workweek	ACGIH BEI
n-Hexane	110-54-3	2,5-Hexanedione: 0.5 mg/l (Urine)	End of shift	ACGIH BEI
Toluene	108-88-3	Toluene: 0.02 mg/l (In blood)	Prior to last shift of workweek	ACGIH BEI
		Toluene: 0.03 mg/l (Urine)	End of shift (As soon as possible after exposure ceases)	ACGIH BEI
		o-Cresol: 0.3 mg/g creatinine (Urine)	End of shift (As soon as possible after exposure ceases)	ACGIH BEI
Naphthalene	91-20-3	1-hydroxypyrene: 4 µmol/mol creatinine (Urine)	After shift	GB EH40 BAT
		1-Naphthol + 2-Naphthol:	End of shift (As soon as possible)	ACGIH BEI

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version
8.3

Revision Date.:
09.03.2026

SDS Number:
800001004187

Date of last issue: 05.09.2025
Print Date. 10.03.2026

			after exposure ceases)	
Benzene	71-43-2	S-Phenylmercapturic acid: 25 µg/g creatinine (Urine)	End of shift (As soon as possible after exposure ceases)	ACGIH BEI
		t,t-Muconic acid: 500 µg/g creatinine (Urine)	End of shift (As soon as possible after exposure ceases)	ACGIH BEI

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Gasoline; Low boiling point naphtha - unspecified	Workers	Inhalation		840 mg/m3/8h
Remarks:	long term, local effects			
Gasoline; Low boiling point naphtha - unspecified	Consumers	Inhalation		180 mg/m3/24h
Remarks:	long term, local effects			
2-methoxy-2-methylbutane	Workers	Inhalation	Long-term systemic effects	88 mg/m3
2-methoxy-2-methylbutane	Workers	Inhalation	Acute systemic effects	353.3 mg/m3
2-methoxy-2-methylbutane	Workers	Dermal	Long-term systemic effects	1601 mg/kg bw/day
2-methoxy-2-methylbutane	Consumers	Inhalation	Long-term systemic effects	26.5 mg/m3
2-methoxy-2-methylbutane	Consumers	Inhalation	Acute systemic effects	212 mg/m3
2-methoxy-2-methylbutane	Consumers	Dermal	Long-term systemic effects	961 mg/kg bw/day
2-methoxy-2-methylbutane	Consumers	Oral	Long-term systemic effects	1 mg/kg bw/day
tert-butyl methyl ether	Workers	Inhalation	Acute local effects	357 mg/m3
tert-butyl methyl ether	Workers	Dermal	Long-term systemic effects	5100 mg/kg bw/day
tert-butyl methyl ether	Workers	Inhalation	Long-term systemic effects	178.5 mg/m3
tert-butyl methyl ether	Consumers	Inhalation	Acute local effects	214 mg/m3
tert-butyl methyl ether	Consumers	Oral	Long-term systemic effects	7.1 mg/kg bw/day
tert-butyl methyl ether	Consumers	Dermal	Long-term systemic effects	3570 mg/kg bw/day
tert-butyl methyl ether	Consumers	Inhalation	Long-term systemic effects	53.6 mg/m3

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version
8.3

Revision Date.:
09.03.2026

SDS Number:
800001004187

Date of last issue: 05.09.2025
Print Date. 10.03.2026

Ethanol	Workers	Inhalation	Long-term systemic effects	380 mg/m3
Ethanol	Workers	Dermal	Long-term systemic effects	343 mg/kg
Ethanol	Consumers	Inhalation	Long-term systemic effects	114 mg/m3
Ethanol	Consumers	Dermal	Long-term systemic effects	206 mg/kg/day
Ethanol	Consumers	Oral	Long-term systemic effects	87 mg/kg/day
Methanol	Workers	Inhalation	Acute systemic effects	260 mg/kg
Methanol	Workers	Dermal	Long-term systemic effects	40 mg/kg/day
Methanol	Workers	Inhalation	Long-term systemic effects	260 mg/kg
Methanol	Consumers	Inhalation	Acute systemic effects	50 mg/kg
Methanol	Consumers	Dermal	Long-term systemic effects	8 mg/kg/day
Methanol	Consumers	Inhalation	Long-term systemic effects	50 mg/kg
Methanol	Consumers	Oral	Long-term systemic effects	8 mg/kg/day
Ethylbenzene	Workers	Inhalation	Acute local effects	293 mg/m3
Ethylbenzene	Workers	Inhalation	Long-term systemic effects	77 mg/m3
Ethylbenzene	Workers	Dermal	Long-term systemic effects	180 mg/kg bw/day
Ethylbenzene	Consumers	Inhalation	Long-term systemic effects	15 mg/m3
Ethylbenzene	Consumers	Oral	Long-term systemic effects	1.6 mg/kg bw/day
Toluene	Workers	Inhalation	Acute systemic effects	384 mg/m3
Toluene	Workers	Inhalation	Long-term systemic effects	192 mg/m3
Toluene	Workers	Dermal	Long-term systemic effects	180 mg/kg bw/day
Toluene	Consumers	Inhalation	Acute systemic effects	226 mg/m3
Toluene	Consumers	Inhalation	Long-term systemic effects	56.5 mg/m3
Toluene	Consumers	Dermal	Long-term systemic effects	226 mg/kg bw/day
Toluene	Consumers	Oral	Long-term systemic effects	8.13 mg/kg bw/day
Naphthalene	Consumers	Oral	Long-term systemic effects	4.23 mg/kg

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

			effects	
Benzene	Workers	Inhalation	Long-term systemic effects	0.8 mg/m ³ / 8h

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Remarks:	Substance is a hydrocarbon with a complex, unknown or variable composition. Conventional methods of deriving PNECs are not appropriate and it is not possible to identify a single representative PNEC for such substances.	

8.2 Exposure controls

Engineering measures

Read in conjunction with the Exposure Scenario for your specific use contained in the Annex. The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Use sealed systems as far as possible.

Firewater monitors and deluge systems are recommended.

Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits.

Local exhaust ventilation is recommended.

Eye washes and showers for emergency use.

Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance. Where there is potential for exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when there is potential for inhalation; clear up spills immediately and dispose of wastes safely. Ensure safe systems of work or equivalent arrangements are in place to manage risks. Regularly inspect, test and maintain all control measures. Consider the need for risk based health surveillance.

Prevent unauthorised persons entering the zone.

Personal protective equipment

Read in conjunction with the Exposure Scenario for your specific use contained in the Annex.

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

The provided information is made in consideration of the PPE directive (Council Directive 89/686/EEC) and the CEN European Committee for Standardisation (CEN) standards.

Eye protection : Wear goggles for use against liquids and gas.
If a local risk assessment deems it so then chemical splash goggles may not be required and safety glasses may provide adequate eye protection.
Approved to EU Standard EN166.

Hand protection

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

- Remarks : Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Select gloves tested to a relevant standard (e.g. Europe EN374, US F739). When prolonged or frequent repeated contact occurs, Nitrile gloves may be suitable. (Breakthrough time of > 240 minutes.) For incidental contact/splash protection Neoprene, PVC gloves may be suitable. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model.
- Skin and body protection : Wear chemical resistant gloves/gauntlets and boots. Where risk of splashing, also wear an apron. Protective clothing approved to EU Standard EN14605.
- Respiratory protection : If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus. All respiratory protection equipment and use must be in accordance with local regulations. Select a filter suitable for combined particulate/organic gases and vapours [Type A/Type P boiling point > 65°C (149°F)] meeting EN14387 and EN143.
- Thermal hazards : Not applicable

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid
Colour : Undyed
Odour : Not applicable
Odour Threshold : Data not available

Melting point/freezing point : Data not available

Initial boiling point and boiling range : 25 - 170 °C Method: Unspecified

Flammability

Flammability (solid, gas) : Not applicable

Lower explosion limit and upper explosion limit / flammability limit

Upper explosion limit / Upper flammability limit : 8 %(V)

Lower explosion limit / Lower flammability limit : 1 %(V)

Flash point : <= -40 °C
Method: Unspecified

Auto-ignition temperature : > 250 °C

Decomposition temperature

Decomposition temperature : Data not available

pH : Not applicable

Viscosity

Viscosity, dynamic : Data not available

Viscosity, kinematic : 0.25 - 0.75 mm²/s (40 °C)
Method: Unspecified

Solubility(ies)

Water solubility : negligible
Solubility in other solvents : Data not available

Partition coefficient: n-octanol/water : log Pow: ca. -0.3 - 7

Vapour pressure : 45 - 100 kPa (38.0 °C)

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3	Revision Date.: 09.03.2026	SDS Number: 800001004187	Date of last issue: 05.09.2025 Print Date. 10.03.2026
----------------	-------------------------------	-----------------------------	--

	Method: Unspecified
	50 - 160 kPa (50.0 °C) Method: Unspecified
Relative density	: Data not available
Density	: 720 - 775 kg/m ³ (15.0 °C) Method: Unspecified
Relative vapour density	: >= 1.6 Method: No information available.
Particle characteristics Particle size	: Data not available Data not available

9.2 Other information

Explosive properties	: Classification Code: Not classified.
Oxidizing properties	: Not applicable
Evaporation rate	: Data not available
Conductivity	: Low conductivity: < 100 pS/m, The conductivity of this material makes it a static accumulator., A liquid is typically considered nonconductive if its conductivity is below 100 pS/m and is considered semi-conductive if its conductivity is below 10,000 pS/m., Whether a liquid is nonconductive or semiconductive, the precautions are the same., A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid

SECTION 10: Stability and reactivity

10.1 Reactivity

May oxidise in the presence of air.

10.2 Chemical stability

Stable under normal conditions of use.

10.3 Possibility of hazardous reactions

Hazardous reactions	: No hazardous reaction is expected when handled and stored according to provisions
---------------------	---

10.4 Conditions to avoid

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

Conditions to avoid : Avoid heat, sparks, open flames and other ignition sources.
In certain circumstances product can ignite due to static electricity.

10.5 Incompatible materials

Materials to avoid : Strong oxidising agents.

10.6 Hazardous decomposition products

Hazardous decomposition products are not expected to form during normal storage. Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases including carbon monoxide, carbon dioxide, sulphur oxides and unidentified organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : Exposure may occur via inhalation, ingestion, skin absorption, skin or eye contact, and accidental ingestion.

Acute toxicity

Product:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg
Remarks: Low toxicity

Acute inhalation toxicity : LC 50 (Rat): > 5 mg/l
Exposure time: 4 h
Remarks: Low toxicity

Remarks: Based on human experience, breathing of vapours or mists may cause a temporary burning sensation to nose, throat and lungs.

Acute dermal toxicity : LD 50 (Rabbit): > 2,000 mg/kg
Remarks: Low toxicity

Acute toxicity (other routes of administration) : Remarks: Exposure may occur via inhalation, ingestion, skin absorption, skin or eye contact, and accidental ingestion.

Components:

Gasoline; Low boiling point naphtha -unspecified:

Acute oral toxicity : LD 50 (Rat): > 5,000 mg/kg
Remarks: Low toxicity

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

Acute inhalation toxicity : LC 50 (Rat): > 5 mg/l
Exposure time: 4 h
Remarks: Low toxicity

Remarks: Based on human experience, breathing of vapours or mists may cause a temporary burning sensation to nose, throat and lungs.

Acute dermal toxicity : LD 50 (Rabbit): > 2,000 mg/kg
Remarks: Low toxicity

Acute toxicity (other routes of administration) : Remarks: Exposure may occur via inhalation, ingestion, skin absorption, skin or eye contact, and accidental ingestion.

tert-butyl methyl ether:

Acute oral toxicity : LD 50 (Rat, male and female): Method: OECD Test Guideline 401
Remarks: May be harmful if swallowed.

Acute inhalation toxicity : LC 50 (Rat, male and female): > 85 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Test(s) equivalent or similar to OECD Test Guideline 403
Remarks: Based on available data, the classification criteria are not met.

Acute dermal toxicity : LD 50 (Rat, male and female): > 2,000 mg/kg
Method: OECD Test Guideline 402
Remarks: Based on available data, the classification criteria are not met.

2-methoxy-2-methylbutane:

Acute oral toxicity : LD50 Oral (Rat, female): 1,602 mg/kg
Method: Test(s) equivalent or similar to OECD Test Guideline 401
Assessment: The component/mixture is moderately toxic after single ingestion.

Acute inhalation toxicity : LC 50 (Rat, male and female): > 5,400 mg/l
Exposure time: 4 h
Method: Test(s) equivalent or similar to OECD Test Guideline 403
Remarks: Based on available data, the classification criteria are not met.

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

Acute dermal toxicity : LD50 Dermal (Rabbit, male and female): $\geq 2,000$ mg/kg
Method: Test(s) equivalent or similar to OECD Test Guideline 402
Remarks: Based on available data, the classification criteria are not met.

Ethyl tertiary butyl ether:

Acute oral toxicity : LD50 Oral (Rat, male and female): $> 2,000$ mg/kg
Method: Test(s) equivalent or similar to OECD Test Guideline 401
Remarks: Based on available data, the classification criteria are not met.

Acute inhalation toxicity : LC 50 (Rat, male and female): > 5.88 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Test(s) equivalent or similar to OECD Test Guideline 403
Remarks: Based on available data, the classification criteria are not met.

Acute dermal toxicity : LD50 Dermal (Rabbit, male and female): $> 2,000$ mg/kg
Method: Test(s) equivalent or similar to OECD Test Guideline 402
Remarks: Based on available data, the classification criteria are not met.

Ethanol:

Acute oral toxicity : LD50 Oral (Rat, male and female): $> 5,000$ mg/kg
Method: Test(s) equivalent or similar to OECD Test Guideline 401
Remarks: Based on available data, the classification criteria are not met.

Acute inhalation toxicity : LC 50 (Rat, male and female): > 124.7 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Test(s) equivalent or similar to OECD Test Guideline 403
Remarks: Based on available data, the classification criteria are not met.

Acute dermal toxicity : Remarks: Based on available data, the classification criteria are not met.

Methanol:

Acute oral toxicity : Acute toxicity estimate: 100 mg/kg bw

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

Remarks: Expert judgement

LD 50 (Rat): \geq 1187 - 2769 mg/kg bw
Method: Test(s) equivalent or similar to OECD Test Guideline 401
Remarks: Toxic if swallowed.
There is a marked difference in acute oral toxicity between animals and man, man being more susceptible than animals.
The estimated fatal dose for man is 100 milliliters (1/2 cup).

Acute inhalation toxicity : Acute toxicity estimate: 3 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Remarks: Expert judgement

LC 50 (Cat): 43.7 mg/l
Exposure time: 6 h
Test atmosphere: vapour
Method: Acceptable non-standard method.
Remarks: Toxic if inhaled.

Acute dermal toxicity : Acute toxicity estimate: 300 mg/kg bw
Remarks: Expert judgement

LD50 Dermal (Rabbit): 17100 mg/kg bw
Remarks: Toxic in contact with skin.

Components:

Xylene, mixed isomers:

Acute oral toxicity : LD 50 (Rat, male and female): $>$ 2,000 mg/kg
Method: EC Directive 92/69/EEC B.1 Acute Toxicity (Oral)
Remarks: Based on available data, the classification criteria are not met.

Acute inhalation toxicity : LC 50 (Rat, male): 6350 ppm
Exposure time: 4 h
Test atmosphere: vapour
Method: Test(s) equivalent or similar to Directive 67/548/EEC, Annex V, B.2.
Remarks: Harmful if inhaled.

Acute dermal toxicity : LD 50 (Rabbit, male): $>$ 2,000 mg/kg
Method: Literature data
Test substance: m-xylene
Remarks: Based on available data, the classification criteria are not met.
Information given is based on data obtained from similar substances.

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

Ethylbenzene:

- Acute oral toxicity : LD50 (Rat): > 2000 - 5000 mg/kg
Remarks: May be harmful if swallowed.
- Acute inhalation toxicity : LC50: > 10 - 20 mg/l
Remarks: Harmful if inhaled.
- Acute dermal toxicity : LD50 (Rabbit): > 5000 mg/kg
Remarks: Low toxicity

Cyclohexane:

- Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg
Assessment: The component/mixture is minimally toxic after single ingestion.
Remarks: Based on available data, the classification criteria are not met.
- Acute inhalation toxicity : LC 50 (Rat): > 20 mg/l
Assessment: The component/mixture is minimally toxic after short term inhalation.
Remarks: Based on available data, the classification criteria are not met.
- Acute dermal toxicity : LD50 Dermal (Rabbit): > 2,000 mg/kg
Assessment: The component/mixture is minimally toxic after single contact with skin.
Remarks: Based on available data, the classification criteria are not met.

Cumene:

- Acute oral toxicity : LD50 (Rat): 2,000 - 5,000 mg/kg
Method: Test(s) equivalent or similar to OECD Test Guideline 401
Remarks: Based on available data, the classification criteria are not met.
- Acute inhalation toxicity : LC50 (Rat, male): > 20 mg/l
Exposure time: 1 h
Method: Acceptable non-standard method.
Remarks: Based on available data, the classification criteria are not met.
- Acute dermal toxicity : LD50 (Rabbit, male and female): 2,000 - 5,000 mg/kg
Method: Acceptable non-standard method.
Remarks: Based on available data, the classification criteria are not met.

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

n-Hexane:

Acute oral toxicity : LD50 (Rat, male and female): 16,000 mg/kg
Method: OECD Test Guideline 401
Remarks: Low toxicity

Acute inhalation toxicity : LC50 (Rat): > 17600 mg/m³
Exposure time: 24 h
Remarks: Low toxicity by inhalation.

Acute dermal toxicity : LD50 (Rabbit): > 5 mg/kg bw
Method: OECD Test Guideline 402
Remarks: Low toxicity

Toluene:

Acute oral toxicity : LD 50 (Rat, male): > 5,000 mg/kg
Method: Test(s) equivalent or similar to OECD Test Guideline 401
Remarks: Based on available data, the classification criteria are not met.

Acute inhalation toxicity : LC 50 (Rat, male and female): > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Test(s) equivalent or similar to OECD Test Guideline 403
Remarks: Based on available data, the classification criteria are not met.
High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea.

Acute dermal toxicity : LD 50 (Rabbit, male): > 5,000 mg/kg
Method: Literature data
Remarks: Based on available data, the classification criteria are not met.

Benzene:

Acute oral toxicity : LD 50 (Rat, male): > 2,000 mg/kg
Method: Test(s) equivalent or similar to OECD Test Guideline 401
Remarks: Based on available data, the classification criteria are not met.

Acute inhalation toxicity : LC 50 (Rat, female): > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Test(s) equivalent or similar to OECD Test Guideline

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

403

Remarks: Based on available data, the classification criteria are not met.

High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea; continued inhalation may result in unconsciousness and/or death.

Acute dermal toxicity : LD 50 (Rabbit): > 2,000 mg/kg
Method: Test(s) equivalent or similar to OECD Test Guideline 402
Remarks: Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Product:

Remarks : Irritating to skin.

Components:

Gasoline; Low boiling point naphtha -unspecified:

Remarks : Irritating to skin.

tert-butyl methyl ether:

Species : Rabbit
Method : OECD Test Guideline 404
Remarks : Irritating to skin.

2-methoxy-2-methylbutane:

Species : Rabbit
Exposure time : 4 h
Method : Test(s) equivalent or similar to OECD Test Guideline 404
Remarks : Based on available data, the classification criteria are not met.

Ethyl tertiary butyl ether:

Species : Rabbit
Method : Test(s) equivalent or similar to OECD Test Guideline 404
Remarks : Slightly irritating.
Insufficient to classify.

Ethanol:

Species : Rabbit
Method : Test(s) equivalent or similar to OECD Test Guideline 404
Remarks : Based on data from similar materials
Based on available data, the classification criteria are not met.

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

Methanol:

Species : Rabbit
Method : Acceptable non-standard method.
Remarks : Based on available data, the classification criteria are not met.

Components:

Xylene, mixed isomers:

Species : Rabbit
Method : Literature data
Remarks : Causes skin irritation.

Ethylbenzene:

Remarks : Causes skin irritation.

Cyclohexane:

Remarks : Causes skin irritation.

Cumene:

Species : Rabbit
Method : Test(s) equivalent or similar to OECD Test Guideline 404
Remarks : Slightly irritating to skin.
Insufficient to classify.

n-Hexane:

Species : Rabbit
Exposure time : 24 h
Method : OECD Test Guideline 404
Result : Skin irritation
Remarks : Causes skin irritation.
Repeated exposure may cause skin dryness or cracking.

Toluene:

Species : Rabbit
Method : Test(s) equivalent or similar to OECD Test Guideline 404
Remarks : Causes skin irritation.

Benzene:

Species : Rabbit
Method : OECD Test Guideline 404
Remarks : Causes skin irritation.

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

Serious eye damage/eye irritation

Product:

Remarks : Slightly irritating to the eye.
Based on available data, the classification criteria are not met.

Components:

Gasoline; Low boiling point naphtha -unspecified:

Remarks : Slightly irritating to the eye.
Based on available data, the classification criteria are not met.

tert-butyl methyl ether:

Species : Rabbit
Method : OECD Test Guideline 405
Remarks : Slightly irritating to the eye.
Based on available data, the classification criteria are not met.

2-methoxy-2-methylbutane:

Species : Rabbit
Exposure time : 24 h
Method : Test(s) equivalent or similar to OECD Test Guideline 405
Remarks : Based on available data, the classification criteria are not met.

Ethyl tertiary butyl ether:

Species : Rabbit
Method : Test(s) equivalent or similar to OECD Test Guideline 405
Remarks : Slightly irritating.
Based on available data, the classification criteria are not met.

Ethanol:

Species : Rabbit
Method : Test(s) equivalent or similar to OECD Test Guideline 405
Result : Irritating to eyes.
Remarks : Based on data from similar materials

Methanol:

Species : Rabbit
Method : Acceptable non-standard method.
Remarks : Based on available data, the classification criteria are not met.

Components:

Xylene, mixed isomers:

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

Species : Rabbit
Method : Acceptable non-standard method.
Remarks : Causes serious eye irritation.

Ethylbenzene:

Remarks : Causes serious eye irritation.

Cyclohexane:

Remarks : Based on available data, the classification criteria are not met.

Cumene:

Species : Rabbit
Method : Test(s) equivalent or similar to OECD Test Guideline 405
Remarks : Slightly irritating to the eye.
Insufficient to classify.

n-Hexane:

Species : Rabbit
Method : OECD Test Guideline 405
Result : No eye irritation

Toluene:

Species : Rabbit
Method : OECD Test Guideline 405
Remarks : Slightly irritating.
Insufficient to classify.

Benzene:

Species : Rabbit
Method : Literature data
Remarks : Causes serious eye irritation.

Respiratory or skin sensitisation

Product:

Remarks : Not a sensitiser.
Based on available data, the classification criteria are not met.

Components:

Gasoline; Low boiling point naphtha -unspecified:

Remarks : Not a sensitiser.
Based on available data, the classification criteria are not met.

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

tert-butyl methyl ether:

Species : Guinea pig
Method : Test(s) equivalent or similar to OECD Test Guideline 406
Remarks : Based on available data, the classification criteria are not met.

2-methoxy-2-methylbutane:

Test Type : Buehler Test
Species : Guinea pig
Remarks : Based on available data, the classification criteria are not met.

Ethyl tertiary butyl ether:

Species : Guinea pig
Method : Test(s) equivalent or similar to OECD Test Guideline 406
Remarks : Based on available data, the classification criteria are not met.

Ethanol:

Species : Mouse
Method : Test(s) equivalent or similar to OECD Test Guideline 406
Remarks : Based on data from similar materials
Based on available data, the classification criteria are not met.

Methanol:

Species : Guinea pig
Method : Test(s) equivalent or similar to OECD Test Guideline 406
Remarks : Based on available data, the classification criteria are not met.

Components:

Xylene, mixed isomers:

Species : Mouse
Method : Test(s) equivalent or similar to OECD Test Guideline 429
Remarks : Based on available data, the classification criteria are not met.

Ethylbenzene:

Remarks : Not a sensitiser.
Based on available data, the classification criteria are not met.

Cyclohexane:

Remarks : Based on available data, the classification criteria are not met.

Cumene:

Species : Guinea pig
Method : Test(s) equivalent or similar to OECD Test Guideline 406

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

Remarks : Not a sensitiser.
Based on available data, the classification criteria are not met.

n-Hexane:

Test Type : Local lymph node assay (LLNA)
Species : Mouse
Method : OECD Test Guideline 429
Result : negative

Toluene:

Species : Guinea pig
Method : Test(s) equivalent or similar to OECD Test Guideline 406
Remarks : Based on available data, the classification criteria are not met.

Benzene:

Species : Mouse
Method : Literature data
Remarks : Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Product:

Genotoxicity in vivo : Remarks: Contains Benzene, CAS # 71-43-2.
May cause heritable genetic damage

Remarks: Mutagenicity studies on gasoline and gasoline blending streams have shown predominantly negative results.

Germ cell mutagenicity- Assessment : Category 1B

Components:

Gasoline; Low boiling point naphtha -unspecified:

Genotoxicity in vivo : Remarks: Contains Benzene, CAS # 71-43-2.
May cause heritable genetic damage

Remarks: Mutagenicity studies on gasoline and gasoline blending streams have shown predominantly negative results.

Germ cell mutagenicity- Assessment : Category 1B

tert-butyl methyl ether:

Genotoxicity in vitro : Method: OECD Test Guideline 471
Remarks: Based on available data, the classification criteria are not met.

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

- Genotoxicity in vivo : Method: Test(s) equivalent or similar to OECD Test Guideline 476
Remarks: Based on available data, the classification criteria are not met.
- Genotoxicity in vivo : Species: Mouse
Method: Test(s) equivalent or similar to OECD Test Guideline 486
Remarks: Based on available data, the classification criteria are not met.
- Genotoxicity in vivo : Species: Mouse
Method: Other guideline method.
Remarks: Based on available data, the classification criteria are not met.
- Germ cell mutagenicity- Assessment : This product does not meet the criteria for classification in categories 1A/1B.
- 2-methoxy-2-methylbutane:**
- Genotoxicity in vitro : Test Type: gene mutation test
Test system: mammalian cells
Remarks: Based on available data, the classification criteria are not met.
- Genotoxicity in vivo : Remarks: Based on available data, the classification criteria are not met.
- Germ cell mutagenicity- Assessment : This product does not meet the criteria for classification in categories 1A/1B.
- Ethyl tertiary butyl ether:**
- Genotoxicity in vitro : Method: Test(s) equivalent or similar to OECD Guideline 471
Remarks: Based on available data, the classification criteria are not met.
- Genotoxicity in vitro : Method: OECD Test Guideline 476
Remarks: Based on available data, the classification criteria are not met.
- Genotoxicity in vitro : Method: OECD Test Guideline 473
Remarks: Based on available data, the classification criteria are not met.
- Genotoxicity in vivo : Species: Mouse
Method: OECD Test Guideline 474
Remarks: Based on available data, the classification criteria

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

are not met.

Germ cell mutagenicity- Assessment : This product does not meet the criteria for classification in categories 1A/1B.

Ethanol:

Genotoxicity in vivo : Species: Mouse
Method: OECD Test Guideline 478
Remarks: Based on data from similar materials
Based on available data, the classification criteria are not met.

Germ cell mutagenicity- Assessment : This product does not meet the criteria for classification in categories 1A/1B.

Methanol:

Genotoxicity in vitro : Method: OECD Test Guideline 471
Remarks: Based on available data, the classification criteria are not met.

Method: Test(s) equivalent or similar to OECD Test Guideline 476

Remarks: Based on available data, the classification criteria are not met.

Method: Literature data

Remarks: Based on available data, the classification criteria are not met.

Genotoxicity in vivo : Species: Mouse
Method: Test(s) equivalent or similar to OECD Test Guideline 474
Remarks: Based on available data, the classification criteria are not met.

Species: Mouse

Method: Literature data

Remarks: Based on available data, the classification criteria are not met.

Germ cell mutagenicity- Assessment : This product does not meet the criteria for classification in categories 1A/1B.

Components:

Xylene, mixed isomers:

Genotoxicity in vitro : Method: Test(s) equivalent or similar to Directive 67/548/EEC, Annex V, B.10

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

Remarks: Based on available data, the classification criteria are not met.

Method: Test(s) equivalent or similar to Directive 67/548/EEC, Annex V, B.19

Remarks: Based on available data, the classification criteria are not met.

Genotoxicity in vivo : Species: Mouse
Method: OECD Test Guideline 478
Remarks: Based on available data, the classification criteria are not met.

Germ cell mutagenicity- Assessment : This product does not meet the criteria for classification in categories 1A/1B.

Ethylbenzene:

Genotoxicity in vivo : Remarks: Not mutagenic.

Germ cell mutagenicity- Assessment : This product does not meet the criteria for classification in categories 1A/1B.

Cyclohexane:

Genotoxicity in vitro : Remarks: Non mutagenic
Based on available data, the classification criteria are not met.

Cumene:

Genotoxicity in vitro : Method: Test(s) equivalent or similar to OECD Test Guideline 476
Remarks: Based on available data, the classification criteria are not met.

Genotoxicity in vivo : Species: Mouse
Method: OECD Test Guideline 474
Remarks: Based on available data, the classification criteria are not met.

Germ cell mutagenicity- Assessment : This product does not meet the criteria for classification in categories 1A/1B.

n-Hexane:

Genotoxicity in vitro : Test Type: Ames test
Test system: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

Test Type: In vitro mammalian cell gene mutation test
Test system: mouse lymphoma cells
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: negative

Genotoxicity in vivo : Test Type: Chromosome aberration test in vitro
Species: Rat
Cell type: Bone marrow
Application Route: oral (gavage)
Method: OECD Test Guideline 475
Result: negative

Test Type: dominant lethal test
Species: Mouse
Application Route: inhalation (vapour)
Method: OECD Test Guideline 478
Result: negative

Germ cell mutagenicity- Assessment : This product does not meet the criteria for classification in categories 1A/1B.

Toluene:

Genotoxicity in vitro : Method: Test(s) equivalent or similar to OECD Guideline 471
Remarks: Based on available data, the classification criteria are not met.

Method: Test(s) equivalent or similar to OECD Test Guideline 476
Remarks: Based on available data, the classification criteria are not met.

Genotoxicity in vivo : Species: Rat
Method: Acceptable non-standard method.
Remarks: Based on available data, the classification criteria are not met.

Germ cell mutagenicity- Assessment : This product does not meet the criteria for classification in categories 1A/1B.

Benzene:

Genotoxicity in vitro : Method: OECD Test Guideline 471
Remarks: May cause genetic defects.

Method: Other guideline method.
Remarks: May cause genetic defects.

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

Method: Literature data
Remarks: May cause genetic defects.

Genotoxicity in vivo : Species: Mouse
Method: Test(s) equivalent or similar to OECD Test Guideline 474
Remarks: May cause genetic defects.

Germ cell mutagenicity- Assessment : May cause genetic defects.

Carcinogenicity

Product:

Remarks : Contains Benzene, CAS # 71-43-2.
Known human carcinogen.

Remarks : Contains Benzene, CAS # 71-43-2.
May cause leukaemia (AML - acute myelogenous leukaemia).

Remarks : Inhalation exposure to mice causes liver tumours, which are not considered relevant to humans.

Remarks : Contains Cumene, CAS# 98-82-8.
An increased tumour incidence has been observed in experimental animals; the significance of this finding to man is unknown.

Carcinogenicity - Assessment : Category 1B

Components:

Gasoline; Low boiling point naphtha -unspecified:

Remarks : Contains Benzene, CAS # 71-43-2.
Known human carcinogen.

Remarks : Contains Benzene, CAS # 71-43-2.
May cause leukaemia (AML - acute myelogenous leukaemia).
May cause MDS (Myelodysplastic Syndrome).

Remarks : Inhalation exposure to mice causes liver tumours, which are not considered relevant to humans.

Remarks : An epidemiology study of more than 18,000 petroleum marketing and distribution workers found no significantly increased risk of death from leukemia, multiple myeloma, or kidney cancer associated with gasoline exposure.

Remarks : Contains Cumene, CAS# 98-82-8.

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

An increased tumour incidence has been observed in experimental animals; the significance of this finding to man is unknown.

Carcinogenicity - Assessment : Category 1B

tert-butyl methyl ether:

Species : Rat, male and female
Application Route : Inhalation
Method : Other guideline method.
Remarks : Based on available data, the classification criteria are not met.

Carcinogenicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

2-methoxy-2-methylbutane:

Remarks : Based on available data, the classification criteria are not met.

Carcinogenicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

Ethyl tertiary butyl ether:

Carcinogenicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

Ethanol:

Species : Rat, male and female
Application Route : Oral
Method : Test(s) equivalent or similar to OECD Test Guideline 453
Remarks : Based on available data, the classification criteria are not met.

Carcinogenicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

Methanol:

Species : Mouse, male and female
Application Route : Inhalation
Method : Test(s) equivalent or similar to OECD Test Guideline 453
Remarks : Based on available data, the classification criteria are not met.

Species : Rat, male and female
Application Route : Inhalation
Method : Test(s) equivalent or similar to OECD Test Guideline 453
Remarks : Based on available data, the classification criteria are not met.

Carcinogenicity - Assessment : This product does not meet the criteria for classification in

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

Remarks : Based on available data, the classification criteria are not met.

Carcinogenicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

Benzene:

Species : Rat, male and female
Application Route : Oral
Method : Other guideline method.
Remarks : May cause cancer.
Known human carcinogen.
May cause leukaemia (AML - acute myelogenous leukaemia).

Species : Mouse, male and female
Application Route : Inhalation
Method : Literature data
Remarks : May cause cancer.
Known human carcinogen.
May cause leukaemia (AML - acute myelogenous leukaemia).

Carcinogenicity - Assessment : May cause cancer.

Material	GHS/CLP Carcinogenicity Classification
Gasoline; Low boiling point naphtha -unspecified	Carcinogenicity Category 1B
2-methoxy-2-methylbutane	No carcinogenicity classification.
Ethyl tertiary butyl ether	No carcinogenicity classification.
tert-butyl methyl ether	No carcinogenicity classification.
Ethanol	No carcinogenicity classification.
Renewable hydrocarbons (naphtha type fraction) obtained from the catalytic transformation of ethanol	Carcinogenicity Category 1B
Methanol	No carcinogenicity classification.
Xylene, mixed isomers	No carcinogenicity classification.
Ethylbenzene	No carcinogenicity classification.
Cyclohexane	No carcinogenicity classification.
Cumene	Carcinogenicity Category 1B
n-Hexane	No carcinogenicity classification.
Toluene	No carcinogenicity classification.

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version
8.3

Revision Date.:
09.03.2026

SDS Number:
800001004187

Date of last issue: 05.09.2025
Print Date. 10.03.2026

Trimethylbenzene (all isomers)	No carcinogenicity classification.
Naphthalene	Carcinogenicity Category 2
Benzene	Carcinogenicity Category 1A

Material	Other Carcinogenicity Classification
Gasoline; Low boiling point naphtha -unspecified	IARC: Group 2B: Possibly carcinogenic to humans
tert-butyl methyl ether	IARC: Group 3: Not classifiable as to its carcinogenicity to humans
Ethanol	IARC: Group 1: Carcinogenic to humans
Xylene, mixed isomers	IARC: Group 3: Not classifiable as to its carcinogenicity to humans
Ethylbenzene	IARC: Group 2B: Possibly carcinogenic to humans
Cumene	IARC: Group 2B: Possibly carcinogenic to humans
Toluene	IARC: Group 3: Not classifiable as to its carcinogenicity to humans
Naphthalene	IARC: Group 2B: Possibly carcinogenic to humans
Benzene	IARC: Group 1: Carcinogenic to humans

Reproductive toxicity

Product:

Effects on fertility

:

Remarks: Contains Toluene, CAS # 108-88-3., Causes foetotoxicity at doses which are maternally toxic.

Remarks: Contains Toluene, CAS # 108-88-3., Many case studies involving abuse during pregnancy indicate that toluene can cause birth defects, growth retardation and learning difficulties.

Remarks: Contains n-Hexane, CAS # 110-54-3., May impair fertility at doses which produce other toxic effects.

Remarks: Ethanol, a component of this material, may cause birth defects and/or miscarriages following high oral doses.

Remarks: Inhalation of high concentrations of gasoline vapour containing Methyl tertiary butyl ether produced a very low incidence of rare birth defects (ventral midline closure failure)

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

in mice.

Reproductive toxicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

Components:

Gasoline; Low boiling point naphtha -unspecified:

Effects on fertility :
Remarks: Contains Toluene, CAS # 108-88-3., Causes foetotoxicity at doses which are maternally toxic.
Remarks: Contains n-Hexane, CAS # 110-54-3., May impair fertility at doses which produce other toxic effects.
Remarks: Contains Toluene, CAS # 108-88-3., Many case studies involving abuse during pregnancy indicate that toluene can cause birth defects, growth retardation and learning difficulties.
Remarks: Inhalation of high concentrations of gasoline vapour containing Methyl tertiary butyl ether produced a very low incidence of rare birth defects (ventral midline closure failure) in mice.

Reproductive toxicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

tert-butyl methyl ether:

Effects on fertility : Species: Rat
Sex: male and female
Application Route: Inhalation
Method: Literature data
Remarks: Based on available data, the classification criteria are not met.

Reproductive toxicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

2-methoxy-2-methylbutane:

Effects on fertility : Test Type: Two-generation study
Species: Rat, male and female
Dose: <3000 parts per million
Duration of Single Treatment: 6 h
Frequency of Treatment: 5 days/week
General Toxicity - Parent: NOEC: 250 ppm

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

General Toxicity F1: NOEC: 250 ppm
General Toxicity F2: NOEC: 250 ppm
Result: Animal testing did not show any effects on fertility.

Effects on foetal development : Species: Rabbit, male and female
Remarks: Based on available data, the classification criteria are not met.

Species: Rat, female
Remarks: Based on available data, the classification criteria are not met.

Reproductive toxicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

Ethyl tertiary butyl ether:

Effects on fertility : Species: Rat
Sex: male and female
Application Route: Oral

Method: Equivalent or similar to OECD Test Guideline 416
Remarks: Based on available data, the classification criteria are not met.

Effects on foetal development : Species: Rat, female
Application Route: Oral
Method: OECD Test Guideline 414
Remarks: Based on available data, the classification criteria are not met.

Species: Rabbit, female
Application Route: Oral
Method: OECD Test Guideline 414
Remarks: Based on available data, the classification criteria are not met.

Reproductive toxicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

Ethanol:

Effects on fertility : Species: Mouse
Sex: male and female
Application Route: Oral

Method: Equivalent or similar to OECD Test Guideline 416
Remarks: Based on available data, the classification criteria are not met.

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

Reproductive toxicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

Methanol:

Effects on fertility : Species: Rat
Sex: male and female
Application Route: Inhalation

Method: Equivalent or similar to OECD Test Guideline 416
Remarks: Based on available data, the classification criteria are not met.

Reproductive toxicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

Components:

Xylene, mixed isomers:

Effects on fertility : Species: Rat
Sex: male and female
Application Route: Inhalation

Method: Acceptable non-standard method.
Remarks: Based on available data, the classification criteria are not met.

Reproductive toxicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

Ethylbenzene:

Effects on fertility :

Remarks: Not a developmental toxicant., Based on available data, the classification criteria are not met., Does not impair fertility.

Reproductive toxicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

Cyclohexane:

Effects on fertility :

Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are not met.

Cumene:

Effects on fertility : Species: Rat

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

Sex: male and female
Application Route: Inhalation

Method: Test(s) equivalent or similar to OECD Test Guideline 413

Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are not met.

Reproductive toxicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

n-Hexane:

Effects on fertility :
Remarks: Suspected of damaging fertility or the unborn child.

Reproductive toxicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

Toluene:

Effects on fertility : Species: Rat
Sex: male and female
Application Route: Inhalation

Method: OECD Test Guideline 416
Remarks: Based on available data, the classification criteria are not met.

Reproductive toxicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

Benzene:

Effects on fertility : Species: Rat
Sex: male and female
Application Route: Inhalation

Method: Test(s) equivalent or similar to OECD Test Guideline 415.
Remarks: Based on available data, the classification criteria are not met.

Reproductive toxicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

STOT - single exposure

Product:

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

Remarks : High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea; continued inhalation may result in unconsciousness.

Components:

Gasoline; Low boiling point naphtha -unspecified:

Remarks : High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea; continued inhalation may result in unconsciousness.

tert-butyl methyl ether:

Remarks : Based on available data, the classification criteria are not met. Slightly irritating to respiratory system. Vapours may cause drowsiness and dizziness.

2-methoxy-2-methylbutane:

Exposure routes : Inhalation
Assessment : The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects., May cause drowsiness or dizziness.

Ethyl tertiary butyl ether:

Exposure routes : Inhalation
Target Organs : Central nervous system
Remarks : May cause drowsiness or dizziness.

Ethanol:

Remarks : Based on available data, the classification criteria are not met.

Methanol:

Exposure routes : Oral, Inhalation, Dermal
Target Organs : Central nervous system, optic nerve
Remarks : Causes damage to organs.
High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea; continued inhalation may result in unconsciousness and/or death.
Visual system: may cause marked impairment of vision or blindness.

Components:

Xylene, mixed isomers:

Exposure routes : Inhalation

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

Target Organs : Respiratory Tract
Remarks : High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea; continued inhalation may result in unconsciousness.
Inhalation of vapours or mists may cause irritation to the respiratory system.
May cause respiratory irritation.

Ethylbenzene:

Remarks : Inhalation of vapours or mists may cause irritation to the respiratory system.

Cyclohexane:

Remarks : May cause drowsiness and dizziness.

Cumene:

Exposure routes : Inhalation
Target Organs : Respiratory Tract
Remarks : High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea; continued inhalation may result in unconsciousness.
May cause respiratory irritation.

n-Hexane:

Remarks : May cause drowsiness and dizziness.
Central nervous system (CNS)

Toluene:

Exposure routes : Inhalation
Target Organs : Central nervous system
Remarks : May cause drowsiness or dizziness.
Vapours may cause drowsiness and dizziness.
Inhalation of vapours or mists may cause irritation to the respiratory system.

Benzene:

Remarks : Based on available data, the classification criteria are not met.
Inhalation of vapours or mists may cause irritation to the respiratory system.

STOT - repeated exposure

Product:

Remarks : Kidney: caused kidney effects in male rats which are not con-

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

Remarks : sidered relevant to humans
: Contains n-Hexane, CAS # 110-54-3.
Peripheral nervous system: repeated exposure causes peripheral neuropathy in animals.

Components:

Gasoline; Low boiling point naphtha -unspecified:

Remarks : Kidney: caused kidney effects in male rats which are not considered relevant to humans

tert-butyl methyl ether:

Remarks : Based on available data, the classification criteria are not met.

2-methoxy-2-methylbutane:

Remarks : Based on available data, the classification criteria are not met.

Ethyl tertiary butyl ether:

Remarks : Based on available data, the classification criteria are not met.

Ethanol:

Remarks : Based on available data, the classification criteria are not met.

Methanol:

Remarks : Visual system: may cause decreased color perception.
Based on available data, the classification criteria are not met.

Components:

Xylene, mixed isomers:

Exposure routes : Inhalation
Target Organs : Auditory system
Remarks : May cause damage to organs or organ systems through prolonged or repeated exposure.
Harmful: danger of serious damage to health by prolonged exposure through inhalation.
Solvent abuse and noise interaction in the work environment may cause hearing loss.

Ethylbenzene:

Remarks : Harmful: danger of serious damage to health by prolonged exposure through inhalation.
Auditory system: prolonged and repeated exposures to high

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

concentrations have resulted in hearing loss in rats. Solvent abuse and noise interaction in the work environment may cause hearing loss.
Kidney: can cause kidney damage.
Liver: can cause liver damage.
Central nervous system: repeated exposure affects the nervous system.

Cyclohexane:

Remarks : Based on available data, the classification criteria are not met.

Cumene:

Remarks : Kidney: caused kidney effects in male rats which are not considered relevant to humans
Based on available data, the classification criteria are not met.

n-Hexane:

Remarks : Central nervous system: repeated exposure affects the nervous system.
Peripheral nervous system: causes peripheral neuropathy which can be potentiated by ketones.
Kidney: caused kidney effects in male rats which are not considered relevant to humans

Toluene:

Exposure routes : Inhalation
Target Organs : Central nervous system
Remarks : May cause damage to organs or organ systems through prolonged or repeated exposure.
May cause damage to central nervous system, respiratory system, visual system, and auditory system through prolonged or repeated exposure.
Effects were seen at high doses only.
Visual system: may cause decreased color perception.
These subtle changes have not been found to lead to functional colour vision deficits.
Auditory system: prolonged and repeated exposures to high concentrations have resulted in hearing loss in rats.
Solvent abuse and noise interaction in the work environment may cause hearing loss.
Exposure to very high concentrations of similar materials has been associated with irregular heart rhythms and cardiac arrest.
Abuse of vapours has been associated with organ damage and death.

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

Benzene:

Exposure routes : Oral, Inhalation
Target Organs : hematopoietic system
Remarks : Causes damage to organs through prolonged or repeated exposure.
Blood-forming organs: repeated exposure affects the bone marrow.
Blood: may cause haemolysis of red blood cells and/or anaemia.
Immune System: animal studies on this material or its components have demonstrated immunotoxicity.
May cause MDS (Myelodysplastic Syndrome).
Exposure to very high concentrations of similar materials has been associated with irregular heart rhythms and cardiac arrest.
Myelodysplastic syndrome (MDS) was observed in individuals exposed to very high levels (50 ppm to 300 ppm range) of benzene over a long period of time in the workplace. The relevance of these results to lower levels of exposure is not known.

Repeated dose toxicity

Components:

tert-butyl methyl ether:

Species : Rat, male and female
Application Route : Oral
Method : Test(s) equivalent or similar to OECD Test Guideline 408
Target Organs : No specific target organs noted

Species : Rat, male and female
Application Route : Inhalation
Test atmosphere : vapour
Method : Literature data
Target Organs : No specific target organs noted

Ethyl tertiary butyl ether:

Species : Rat, male and female
Application Route : Oral
Method : Test(s) equivalent or similar to OECD Test Guideline 453
Target Organs : No specific target organs noted

Species : Rat, male and female
Application Route : Inhalation
Test atmosphere : vapour
Method : Test(s) equivalent or similar to OECD Test Guideline 453
Target Organs : No specific target organs noted

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

Ethanol:

Species : Rat, male and female
Method : OECD Test Guideline 408
Remarks : No significant adverse effects were reported

Methanol:

Species : Monkey, male
Application Route : Oral
Method : Literature data
Target Organs : No specific target organs noted

Species : Rat, male and female
Application Route : Inhalation
Test atmosphere : vapour
Method : Test(s) equivalent or similar to OECD Test Guideline 453
Target Organs : No specific target organs noted

Components:

Xylene, mixed isomers:

Species : Rat, male and female
Application Route : Oral
Method : Test(s) equivalent or similar to OECD Test Guideline 408
Target Organs : No specific target organs noted
Remarks : Over exposures of humans to xylene or xylene solvent mixtures produced predominately central nervous system (CNS) effects with less common effects reported to the lung, gastrointestinal tract, liver, kidney and heart.
Available animal and human results in auditory system provide limited evidence that xylenes may induce decrements in human hearing, and it was unclear if these changes were temporary or permanent.

Species : Rat, male
Application Route : Inhalation
Test atmosphere : vapour
Method : Literature data
Target Organs : Auditory system
Remarks : Over exposures of humans to xylene or xylene solvent mixtures produced predominately central nervous system (CNS) effects with less common effects reported to the lung, gastrointestinal tract, liver, kidney and heart.
Available animal and human results in auditory system provide limited evidence that xylenes may induce decrements in human hearing, and it was unclear if these changes were temporary or permanent.

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

Cumene:

Species : Rat, male
Application Route : Oral
Method : Acceptable non-standard method.
Target Organs : No specific target organs noted

Species : Rat, male and female
Application Route : Inhalation
Test atmosphere : vapour
Method : OECD Test Guideline 413
Target Organs : No specific target organs noted

Toluene:

Species : Rat, male and female
Application Route : Oral
Method : Test(s) equivalent or similar to Directive 67/548/EEC, Annex V, B.26
Target Organs : No specific target organs noted

Species : Rat, male and female
Application Route : Inhalation
Test atmosphere : vapour
Method : Test(s) equivalent or similar to OECD Test Guideline 453
Target Organs : Central nervous system

Benzene:

Species : Rat, male and female
Application Route : Oral
Method : Test(s) equivalent or similar to OECD Test Guideline 408
Target Organs : hematopoietic system

Species : Mouse, male and female
Application Route : Inhalation
Test atmosphere : vapour
Method : Literature data
Target Organs : hematopoietic system

Aspiration toxicity

Product:

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3	Revision Date.: 09.03.2026	SDS Number: 800001004187	Date of last issue: 05.09.2025 Print Date. 10.03.2026
----------------	-------------------------------	-----------------------------	--

Components:

Gasoline; Low boiling point naphtha -unspecified:

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

tert-butyl methyl ether:

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

2-methoxy-2-methylbutane:

Based on available data, the classification criteria are not met.

Methanol:

Based on available data, the classification criteria are not met.

Components:

Xylene, mixed isomers:

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

Ethylbenzene:

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

Cyclohexane:

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

Cumene:

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

n-Hexane:

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

Toluene:

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

Benzene:

May be fatal if swallowed and enters airways.

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Further information

Product:

Remarks : Exposure to very high concentrations of similar materials has been associated with irregular heart rhythms and cardiac arrest.

Remarks : Contains Toluene, CAS # 108-88-3.
Prolonged and repeated exposures to high concentrations have resulted in hearing loss in rats. Solvent abuse and noise interaction in the work environment may cause hearing loss.

Remarks : Contains Toluene, CAS # 108-88-3.
Abuse of vapours has been associated with organ damage and death.

Remarks : Contains Benzene, CAS # 71-43-2.
May cause MDS (Myelodysplastic Syndrome).

Remarks : Classifications by other authorities under varying regulatory frameworks may exist.

Components:

Gasoline; Low boiling point naphtha -unspecified:

Remarks : Exposure to very high concentrations of similar materials has been associated with irregular heart rhythms and cardiac arrest.

Remarks : Contains Toluene, CAS # 108-88-3.
Prolonged and repeated exposures to high concentrations

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

Remarks : have resulted in hearing loss in rats. Solvent abuse and noise interaction in the work environment may cause hearing loss.

Remarks : Contains Toluene, CAS # 108-88-3.
Abuse of vapours has been associated with organ damage and death.

Remarks : Contains Benzene, CAS # 71-43-2.
May cause MDS (Myelodysplastic Syndrome).

Remarks : Classifications by other authorities under varying regulatory frameworks may exist.

tert-butyl methyl ether:

Remarks : Classifications by other authorities under varying regulatory frameworks may exist.

2-methoxy-2-methylbutane:

Remarks : Classifications by other authorities under varying regulatory frameworks may exist.

Methanol:

Remarks : Classifications by other authorities under varying regulatory frameworks may exist.

Components:

Xylene, mixed isomers:

Remarks : Classifications by other authorities under varying regulatory frameworks may exist.

Ethylbenzene:

Remarks : Classifications by other authorities under varying regulatory frameworks may exist.

Cyclohexane:

Remarks : Exposure to very high concentrations of similar materials has been associated with irregular heart rhythms and cardiac arrest.

Cumene:

Remarks : Classifications by other authorities under varying regulatory frameworks may exist.

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

n-Hexane:

Remarks : Classifications by other authorities under varying regulatory frameworks may exist.

Toluene:

Remarks : Classifications by other authorities under varying regulatory frameworks may exist.

Benzene:

Remarks : Classifications by other authorities under varying regulatory frameworks may exist.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: LL/EL/IL50 > 1 <= 10 mg/l
Toxic

Toxicity to daphnia and other aquatic invertebrates : Remarks: LL/EL/IL50 > 1 <= 10 mg/l
Toxic

Toxicity to algae/aquatic plants : Remarks: LL/EL/IL50 > 1 <= 10 mg/l
Toxic

Toxicity to fish (Chronic toxicity) : Remarks: NOEC/NOEL/EL10 > 1.0 - <= 10 mg/l

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : Remarks: NOEC/NOEL/EL10 > 1.0 - <= 10 mg/l

Toxicity to microorganisms :
Remarks: LL/EL/IL50 >10 <= 100 mg/l
Harmful

Components:

Gasoline; Low boiling point naphtha -unspecified:

Toxicity to fish : Remarks: LL/EL/IL50 > 1 <= 10 mg/l
Toxic

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

-
- Toxicity to daphnia and other aquatic invertebrates : Remarks: LL/EL/IL50 > 1 <= 10 mg/l
Toxic
- Toxicity to algae/aquatic plants : Remarks: LL/EL/IL50 > 1 <= 10 mg/l
Toxic
- Toxicity to microorganisms :
Remarks: LL/EL/IL50 >10 <= 100 mg/l
Harmful
- Toxicity to fish (Chronic toxicity) : Remarks: NOEC/NOEL/EL10 > 1.0 - <= 10 mg/l
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : Remarks: NOEC/NOEL/EL10 > 1.0 - <= 10 mg/l
- tert-butyl methyl ether:**
- Toxicity to fish : LC50 (Menidia beryllina (Silverside)): 574 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Practically non toxic:
LL/EL/IL50 > 100 mg/l
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Americamysis): 187 mg/l
Exposure time: 96 h
Method: Test(s) equivalent or similar to OECD Guideline 202
Remarks: Practically non toxic:
LL/EL/IL50 > 100 mg/l
- Toxicity to algae/aquatic plants : IC50 (Scenedesmus capricornutum (fresh water algae)): 103 mg/l
Exposure time: 96 h
Method: Test(s) equivalent or similar to OECD Test Guideline 201
Remarks: Practically non toxic:
LL/EL/IL50 > 100 mg/l
- Toxicity to microorganisms : EC10 (Pseudomonas putida): 710 mg/l
Exposure time: 18 h
Method: Test(s) equivalent or similar to OECD Guideline 209
Remarks: Practically non toxic:
LL/EL/IL50 > 100 mg/l
- Toxicity to fish (Chronic toxicity) : NOEC: 299 mg/l
Exposure time: 31 d
Species: Pimephales promelas (fathead minnow)
Method: Test(s) equivalent or similar to OECD Guideline 210
Remarks: NOEC/NOEL/EL10 > 100 mg/l
- Toxicity to daphnia and other : 26 mg/l

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

aquatic invertebrates (Chronic toxicity) Exposure time: 28 d
Species: Americamysis
Method: Test(s) equivalent or similar to OECD Guideline 210
Remarks: NOEC/NOEL/EL10 > 10 - <=100 mg/l

2-methoxy-2-methylbutane:

Toxicity to fish : LC50 (Fish (freshwater)): 580 mg/l
Exposure time: 96 h
Remarks: Based on available data, the classification criteria are not met.

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 100 mg/l
Exposure time: 48 h
Remarks: Based on available data, the classification criteria are not met.

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 780 mg/l
Exposure time: 72 h
Remarks: Based on available data, the classification criteria are not met.

Toxicity to microorganisms : EC10 (Pseudomonas putida): 25 mg/l
Exposure time: 16 h
Remarks: Based on available data, the classification criteria are not met.

Toxicity to fish (Chronic toxicity) : NOEC: 29.9 mg/l
Species: Pimephales promelas (fathead minnow)
Remarks: Based on available data, the classification criteria are not met.

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 5.1 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Remarks: Based on available data, the classification criteria are not met.

Ethyl tertiary butyl ether:

Toxicity to fish : LC50 (Poecilia reticulata (guppy)): > 974 mg/l
Exposure time: 96 h
Method: Test(s) equivalent or similar to OECD Guideline 203
Remarks: Practically non toxic, LC/EC/IC 50 > 100 mg/l .

Toxicity to daphnia and other aquatic invertebrates : EC50 (Americamysis): 37 mg/l
Exposure time: 96 h
Remarks: Harmful
LL/EL/IL50 >10 <= 100 mg/l

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

Toxicity to algae/aquatic plants : EC50 (Selenastrum capricornutum (green algae)): 1,100 mg/l
Exposure time: 72 h
Method: Test(s) equivalent or similar to OECD Test Guideline 201
Remarks: Practically non toxic:
LL/EL/IL50 > 100 mg/l

Toxicity to microorganisms : EC50 (Pseudomonas putida): 510 mg/l
Exposure time: 16 h
Method: Information given is based on data obtained from similar substances.
Remarks: Practically non toxic, LC/EC/IC 50 > 100 mg/l .

Toxicity to fish (Chronic toxicity) : NOEC: 299 mg/l
Exposure time: 31 d
Species: Pimephales promelas (fathead minnow)
Method: Information given is based on data obtained from similar substances.
Remarks: NOEC/NOEL/EL10 > 1.0 - <=10 mg/l

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 3.39 mg/l
Species: Americamysis
Method: Information given is based on data obtained from similar substances.
Remarks: NOEC/NOEL/EL10 > 1.0 - <=10 mg/l

Ethanol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 14,200 mg/l
Exposure time: 96 h
Method: Test(s) equivalent or similar to OECD Guideline 203
Remarks: Based on available data, the classification criteria are not met.

Toxicity to daphnia and other aquatic invertebrates : LC50 (Ceriodaphnia dubia (water flea)): 5,012 mg/l
Exposure time: 48 h
Method: Test(s) equivalent or similar to OECD Guideline 202
Remarks: Based on available data, the classification criteria are not met.

Toxicity to algae/aquatic plants : EC50 (Chlorella vulgaris (Fresh water algae)): 675 mg/l
Exposure time: 72 h
Method: Test(s) equivalent or similar to OECD Test Guideline 201
Remarks: Based on available data, the classification criteria are not met.

Toxicity to microorganisms : Toxic threshold (Pseudomonas putida): 6,500 mg/l
Exposure time: 16 h

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

Toxicity to fish (Chronic toxicity) : NOEC: 245 mg/l
Exposure time: 30 d
Method: Based on quantitative structure-activity relationship (QSAR) modelling
Remarks: NOEC/NOEL/EL10 > 100 mg/l

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 2 mg/l
Exposure time: 10 d
Species: Ceriodaphnia dubia (Water flea)
Method: Test(s) equivalent or similar to OECD Guideline 211
Remarks: NOEC/NOEL/EL10 > 1.0 - <=10 mg/l

Methanol:

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 15,400 mg/l
Exposure time: 96 h
Method: Other guideline method.
Remarks: Practically non toxic:
LL/EL/IL50 > 100 mg/l

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 18,260 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 202
Remarks: Practically non toxic:
LL/EL/IL50 > 100 mg/l

Toxicity to algae/aquatic plants : EC50 (Selenastrum capricornutum (green algae)): 22,000 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 201
Remarks: Practically non toxic:
LL/EL/IL50 > 100 mg/l

Toxicity to microorganisms : IC50 (Activated sludge): > 1,000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: Practically non toxic:
LL/EL/IL50 > 100 mg/l

Toxicity to fish (Chronic toxicity) : NOEC: 7,900 mg/l
Exposure time: 200 d
Species: Oryzias latipes (Japanese medaka)
Method: Other guideline method.
Remarks: NOEC/NOEL/EL10 > 100 mg/l

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 208 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: Based on quantitative structure-activity relationship

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

(QSAR) modelling
Remarks: NOEC/NOEL/EL10 > 100 mg/l

Components:

Xylene, mixed isomers:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2.6 mg/l
Exposure time: 96 h
Method: Information given is based on data obtained from similar substances.
Remarks: Toxic
LL/EL/IL50 > 1 <= 10 mg/l

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 3.82 mg/l
Exposure time: 48 h
Method: Information given is based on data obtained from similar substances.
Remarks: Toxic
LC/EC/IC50 >1 - <=10 mg/l

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (algae)): 2.2 mg/l
Exposure time: 72 h
Method: Information given is based on data obtained from similar substances.
Remarks: Toxic
LC/EC/IC50 >1 - <=10 mg/l

Toxicity to microorganisms : EC50 (Activated sludge): > 157 mg/l
Exposure time: 3 h
Method: Information given is based on data obtained from similar substances.
Remarks: Practically non toxic:
LL/EL/IL50 > 100 mg/l

Toxicity to fish (Chronic toxicity) : NOEC: > 1.3 mg/l
Exposure time: 56 d
Species: Oncorhynchus mykiss (rainbow trout)
Method: Literature data.
Remarks: NOEC/NOEL/EL10 > 1.0 - <= 10 mg/l

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0.96 mg/l
Exposure time: 7 d
Species: Ceriodaphnia dubia (Water flea)
Method: Other guideline method.
Remarks: NOEC/NOEL/EL10 > 0.1 - <=1.0 mg/l

Ethylbenzene:

Toxicity to fish : Remarks: Toxic

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

LC/EC/IC50 >1 - <=10 mg/l

Toxicity to daphnia and other aquatic invertebrates : Remarks: Toxic
LC/EC/IC50 >1 - <=10 mg/l

Toxicity to algae/aquatic plants : EC50 : Remarks: Toxic
LC/EC/IC50 >1 - <=10 mg/l

Toxicity to microorganisms :
Remarks: Harmful
LC/EC/IC50 >10 - <=100 mg/l

Toxicity to fish (Chronic toxicity) : Remarks: NOEC/NOEL/EL10 > 0.1 - <=1.0 mg/l

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : Remarks: NOEC/NOEL/EL10 > 0.1 - <=1.0 mg/l

Cyclohexane:

Toxicity to fish : LC50 : 1 - 10 mg/l
Remarks: Toxic to fish.

Toxicity to daphnia and other aquatic invertebrates : LC50 : < 1 mg/l
Remarks: Very toxic.

M-Factor (Acute aquatic toxicity) : 1

Toxicity to microorganisms : LL50 : 10 - 100 mg/l
Remarks: Harmful

Toxicity to fish (Chronic toxicity) : Remarks: Data not available

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : Remarks: Data not available

M-Factor (Chronic aquatic toxicity) : 1

Cumene:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 4.8 mg/l
Remarks: Toxic

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 2.14 mg/l
Exposure time: 48 h
Method: Test(s) equivalent or similar to OECD Guideline 202
Remarks: Toxic

Toxicity to algae/aquatic plants : EC50 (green algae): 2.01 mg/l
Exposure time: 72 h

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

		Method: Test(s) equivalent or similar to OECD Test Guideline 201 Remarks: Toxic
Toxicity to microorganisms	:	EC50 : > 2,000 mg/l Exposure time: 3 h Method: Test(s) equivalent or similar to OECD Guideline 209
Toxicity to fish (Chronic toxicity)	:	NOEC: 0.38 mg/l Exposure time: 30 d Species: Danio rerio (zebra fish) Method: Based on quantitative structure-activity relationship (QSAR) modelling
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC: 0.35 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea) Method: Test(s) equivalent or similar to OECD Guideline 211
n-Hexane:		
Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): 2.5 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	NOELR (Daphnia magna Straus): > 100 mg/l Exposure time: 72 h Method: Test(s) equivalent or similar to OECD Guideline 202 Remarks: Toxic
Toxicity to algae/aquatic plants	:	LOELR (Raphidocelis subcapitata (freshwater green alga)): <= 21.3 mg/l Exposure time: 72 h Method: Test(s) equivalent or similar to OECD Test Guideline 201
		NOELR (Raphidocelis subcapitata (freshwater green alga)): < 21.3 mg/l Exposure time: 72 h Method: Test(s) equivalent or similar to OECD Test Guideline 201
Toxicity to microorganisms	:	Remarks: Data not available
Toxicity to fish (Chronic toxicity)	:	Remarks: Data not available
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	Remarks: Data not available

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

Toluene:

Toxicity to fish : LC50 (Oncorhynchus kisutch (coho salmon)): 4.02 mg/l
Exposure time: 96 h
Method: Literature data.
Remarks: Toxic
LC/EC/IC50 >1 - <=10 mg/l

Toxicity to daphnia and other aquatic invertebrates :

LC50 (Ceriodaphnia dubia (water flea)): 3.78 mg/l
Exposure time: 48 h
Method: Other guideline method.
Remarks: Toxic
LC/EC/IC50 >1 - <=10 mg/l

Toxicity to algae/aquatic plants : EC50 (Chlorella vulgaris (Fresh water algae)): 134 mg/l
Exposure time: 3 h
Method: Literature data.
Remarks: Practically non toxic:
LC/EC/IC50 > 100 mg/l

Toxicity to microorganisms : EC50 (Nitrosomonas): 84 mg/l
Exposure time: 24 h
Method: Literature data.
Remarks: Harmful
LL/EL/IL50 10-100 mg/l

Toxicity to fish (Chronic toxicity) : NOEC: 1.4 mg/l
Exposure time: 40 d
Species: Oncorhynchus kisutch (coho salmon)
Method: Literature data.
Remarks: NOEC/NOEL/EL10 > 1.0 - <= 10 mg/l

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0.74 mg/l
Exposure time: 7 d
Species: Ceriodaphnia dubia (Water flea)
Method: Other guideline method.
Remarks: NOEC/NOEL/EL10 > 0.1 - <=1.0 mg/l

Naphthalene:

M-Factor (Acute aquatic toxicity) : 1

Benzene:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 5.3 mg/l
Exposure time: 96 h
Method: Test(s) equivalent or similar to OECD Guideline 203
Remarks: Toxic

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

- LL/EL/IL50 > 1 <= 10 mg/l
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 10 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: Toxic
LL/EL/IL50 > 1 <= 10 mg/l
- Toxicity to algae/aquatic plants : ErC50 (Selenastrum capricornutum (green algae)): 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Harmful
LL/EL/IL50 >10 <= 100 mg/l
- Toxicity to microorganisms : IC50 (Nitrosomonas): 13 mg/l
Exposure time: 24 h
Method: Literature data.
Remarks: Harmful
LL/EL/IL50 >10 <= 100 mg/l
- Toxicity to fish (Chronic toxicity) : NOEC: 0.8 mg/l
Exposure time: 32 d
Species: Pimephales promelas (fathead minnow)
Method: Other guideline method.
Remarks: NOEC/NOEL/EL10 > 0.1 - <=1.0 mg/l
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 3 mg/l
Exposure time: 7 d
Species: Ceriodaphnia dubia (Water flea)
Method: Other guideline method.
Remarks: NOEC/NOEL/EL10 > 1.0 - <= 10 mg/l

12.2 Persistence and degradability

Product:

- Biodegradability : Remarks: Major constituents are inherently biodegradable.
The volatile constituents will oxidize rapidly by photochemical reactions in air.
Not Persistent per IMO criteria.
International Oil Pollution Compensation (IOPC) Fund definition:
"A non-persistent oil is oil, which, at the time of shipment, consists of hydrocarbon fractions, (a) at least 50% of which, by volume, distills at a temperature of 340°C (645°F) and (b) at least 95% of which, by volume, distills at a temperature of 370°C (700°F) when tested by the ASTM Method D-86/78 or any subsequent revision thereof."

Remarks: While biodegradation of Methyl tertiary butyl ether has been documented, it is generally less biodegradable than many pe-

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

roleum hydrocarbons and has a potential to migrate relatively longer distances in groundwater.

Components:

Gasoline; Low boiling point naphtha -unspecified:

Biodegradability : Remarks: The volatile constituents will oxidize rapidly by photo-chemical reactions in air.
Major constituents are inherently biodegradable, but contains components that may persist in the environment.
Based on available data, the classification criteria are not met.
Not Persistent per IMO criteria.
International Oil Pollution Compensation (IOPC) Fund definition:
"A non-persistent oil is oil, which, at the time of shipment, consists of hydrocarbon fractions, (a) at least 50% of which, by volume, distills at a temperature of 340°C (645°F) and (b) at least 95% of which, by volume, distills at a temperature of 370°C (700°F) when tested by the ASTM Method D-86/78 or any subsequent revision thereof."

tert-butyl methyl ether:

Biodegradability : Biodegradation: 9.24 %
Exposure time: 28 d
Method: OECD Test Guideline 301D
Remarks: Not readily biodegradable.

2-methoxy-2-methylbutane:

Biodegradability : Remarks: Not readily biodegradable.

Ethyl tertiary butyl ether:

Biodegradability : Biodegradation: 6.6 %
Exposure time: 7 d
Method: Test(s) equivalent or similar to OECD Guideline 301D
Remarks: Not readily biodegradable.

Ethanol:

Biodegradability : Biodegradation: 84 %
Exposure time: 20 d
Method: Test(s) equivalent or similar to OECD Guideline 301 B
Remarks: Readily biodegradable.
Oxidises rapidly by photo-chemical reactions in air.

Methanol:

Biodegradability : Biodegradation: 82.7 %

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

Exposure time: 5 d
Method: Other guideline method.
Remarks: Readily biodegradable.
Oxidises rapidly by photo-chemical reactions in air.

Components:

Xylene, mixed isomers:

Biodegradability : Biodegradation: 87.8 %
Exposure time: 28 d
Method: Information given is based on data obtained from similar substances.
Remarks: Readily biodegradable.

Ethylbenzene:

Biodegradability : Remarks: Readily biodegradable.
Oxidises rapidly by photo-chemical reactions in air.
Not Persistent per IMO criteria.
International Oil Pollution Compensation (IOPC) Fund definition:
"A non-persistent oil is oil, which, at the time of shipment, consists of hydrocarbon fractions, (a) at least 50% of which, by volume, distills at a temperature of 340°C (645°F) and (b) at least 95% of which, by volume, distils at a temperature of 370°C (700°F) when tested by the ASTM Method D-86/78 or any subsequent revision thereof."

Cyclohexane:

Biodegradability : Remarks: Readily biodegradable.

Cumene:

Biodegradability : Remarks: Rapidly biodegradable under aerobic conditions.
Oxidises rapidly by photo-chemical reactions in air.

n-Hexane:

Biodegradability : Remarks: Readily biodegradable.
Oxidises rapidly by photo-chemical reactions in air.

Toluene:

Biodegradability : Biodegradation: 81 %
Exposure time: 5 d
Method: ASTM D1252-67
Remarks: Readily biodegradable.

Remarks: Not Persistent per IMO criteria.
International Oil Pollution Compensation (IOPC) Fund definition:

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

“A non-persistent oil is oil, which, at the time of shipment, consists of hydrocarbon fractions, (a) at least 50% of which, by volume, distills at a temperature of 340°C (645°F) and (b) at least 95% of which, by volume, distills at a temperature of 370°C (700°F) when tested by the ASTM Method D-86/78 or any subsequent revision thereof.”

Benzene:

Biodegradability : Biodegradation: 96 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
Remarks: Readily biodegradable.
Not Persistent per IMO criteria.
International Oil Pollution Compensation (IOPC) Fund definition:
“A non-persistent oil is oil, which, at the time of shipment, consists of hydrocarbon fractions, (a) at least 50% of which, by volume, distills at a temperature of 340°C (645°F) and (b) at least 95% of which, by volume, distills at a temperature of 370°C (700°F) when tested by the ASTM Method D-86/78 or any subsequent revision thereof.”

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: Contains constituents with the potential to bioaccumulate.

Components:

Gasoline; Low boiling point naphtha -unspecified:

Bioaccumulation : Remarks: Contains constituents with the potential to bioaccumulate.

tert-butyl methyl ether:

Bioaccumulation : Species: Cyprinus carpio (Carp)
Exposure time: 28 d
Bioconcentration factor (BCF): 1.5
Method: Test(s) equivalent or similar to OECD Test Guideline 305
Remarks: Does not bioaccumulate significantly.

2-methoxy-2-methylbutane:

Bioaccumulation : Remarks: Not persistent, bioaccumulative, and toxic (PBT).

Ethyl tertiary butyl ether:

Bioaccumulation : Remarks: Does not bioaccumulate significantly.

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

Ethanol:

Bioaccumulation : Remarks: Does not bioaccumulate significantly.

Partition coefficient: n-octanol/water : log Pow: < 1

Methanol:

Bioaccumulation : Species: Cyprinus carpio (Carp)
Exposure time: 72 h
Bioconcentration factor (BCF): 1
Method: Test(s) equivalent or similar to OECD Test Guideline 305
Remarks: Does not bioaccumulate significantly.

Components:

Xylene, mixed isomers:

Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)
Exposure time: 56 d
Bioconcentration factor (BCF): 29
Method: Literature data.
Remarks: Does not bioaccumulate significantly.

Partition coefficient: n-octanol/water : log Pow: 3.16
Method: Literature data.

Ethylbenzene:

Bioaccumulation : Remarks: Does not bioaccumulate significantly.

Cyclohexane:

Bioaccumulation : Remarks: Does not significantly accumulate in organisms.

Cumene:

Bioaccumulation : Remarks: Does not bioaccumulate significantly.

n-Hexane:

Bioaccumulation : Remarks: Has the potential to bioaccumulate.

Toluene:

Bioaccumulation : Remarks: Does not bioaccumulate significantly.

Benzene:

Bioaccumulation : Species: Leuciscus idus (Golden orfe)
Exposure time: 3 d

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

Bioconcentration factor (BCF): < 10
Method: Test(s) equivalent or similar to OECD Test Guideline 305
Remarks: Does not bioaccumulate significantly.

12.4 Mobility in soil

Product:

Mobility : Remarks: Evaporates within a day from water or soil surfaces., Large volumes may penetrate soil and could contaminate groundwater., Contains volatile components., Floats on water., Toxic to aquatic organisms; may cause long-term adverse effects in the aquatic environment. Ether oxygenates are significantly more water soluble and less biodegradable than benzene, toluene, ethyl benzene and xylenes (BTEX). Consequently ether oxygenates have the potential to migrate relatively longer distances than BTEX in groundwater.

Components:

Gasoline; Low boiling point naphtha -unspecified:

Mobility : Remarks: Evaporates within a day from water or soil surfaces., Large volumes may penetrate soil and could contaminate groundwater., Toxic to aquatic organisms; may cause long-term adverse effects in the aquatic environment., Contains volatile components., Floats on water.

tert-butyl methyl ether:

Mobility : Remarks: Floats on water., If product enters soil, it will be highly mobile and may contaminate groundwater.

2-methoxy-2-methylbutane:

Mobility : Remarks: The product is insoluble and floats on water.

Ethyl tertiary butyl ether:

Mobility : Remarks: If the product enters soil, one or more constituents will or may be mobile and may contaminate groundwater.

Ethanol:

Mobility : Remarks: Dissolves in water., If product enters soil, it will be highly mobile and may contaminate groundwater.

Methanol:

Mobility : Remarks: If product enters soil, it will be highly mobile and

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

may contaminate groundwater.

Components:

Xylene, mixed isomers:

Mobility : Remarks: Floats on water., If it enters soil, it will adsorb to soil particles and will not be mobile.

Ethylbenzene:

Mobility : Remarks: If the product enters soil, one or more constituents will or may be mobile and may contaminate groundwater., Floats on water.

Cyclohexane:

Mobility : Remarks: Floats on water., Adsorbs to soil and has low mobility

Cumene:

Mobility : Remarks: Floats on water., If the product enters soil, one or more constituents will or may be mobile and may contaminate groundwater.

n-Hexane:

Mobility : Remarks: Floats on water., If it enters soil, it will adsorb to soil particles and will not be mobile.

Toluene:

Mobility : Remarks: Floats on water., If the product enters soil, one or more constituents will or may be mobile and may contaminate groundwater.

Benzene:

Mobility : Remarks: Floats on water.

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This mixture does not contain any REACH registered substances that are assessed to be a PBT or a vPvB..

Components:

Gasoline; Low boiling point naphtha -unspecified:

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

Assessment : This mixture does not contain any REACH registered substances that are assessed to be a PBT or a vPvB..

tert-butyl methyl ether:

Assessment : The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB..

Ethyl tertiary butyl ether:

Assessment : The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB..

Ethanol:

Assessment : The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB..

Methanol:

Assessment : The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB..

Components:

Xylene, mixed isomers:

Assessment : The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB..

Ethylbenzene:

Assessment : The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB..

Cyclohexane:

Assessment : The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB..

Cumene:

Assessment : The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not consid-

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

ered to be PBT or vPvB..

n-Hexane:

Assessment : The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB..

Toluene:

Assessment : The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB..

Benzene:

Assessment : The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not considered to be PBT or vPvB..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : Films formed on water may affect oxygen transfer and damage organisms.

Components:

Gasoline; Low boiling point naphtha -unspecified:

Additional ecological information : Films formed on water may affect oxygen transfer and damage organisms.

2-methoxy-2-methylbutane:

Additional ecological information : None

Components:

Ethylbenzene:

Additional ecological information : In view of the high rate of loss from solution, the product is unlikely

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3	Revision Date.: 09.03.2026	SDS Number: 800001004187	Date of last issue: 05.09.2025 Print Date. 10.03.2026
----------------	-------------------------------	-----------------------------	--

The number given to waste is associated with the appropriate usage. The user must decide if their particular use results in another waste code being assigned.

Classification of waste is always the responsibility of the end user.

Hazardous Waste (England and Wales) Regulations 2005.

SECTION 14: Transport information

14.1 UN number or ID number

ADR	:	1203
RID	:	1203
IMDG	:	1203
IATA	:	1203

14.2 UN proper shipping name

ADR	:	GASOLINE
RID	:	GASOLINE
IMDG	:	GASOLINE
IATA	:	GASOLINE

14.3 Transport hazard class(es)

ADR	:	3
RID	:	3
IMDG	:	3
IATA	:	3

14.4 Packing group

ADR		
Packing group	:	II
Classification Code	:	F1
Hazard Identification Number	:	33
Labels	:	3

RID		
Packing group	:	II
Classification Code	:	F1
Hazard Identification Number	:	33
Labels	:	3

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

IMDG

Packing group : II

Labels : 3

IATA

Packing group : II

Labels : 3

14.5 Environmental hazards

ADR

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

14.6 Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

14.7 Maritime transport in bulk according to IMO instruments

MARPOL Annex 1 rules apply for bulk shipments by sea.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Methanol (Number on list 75, 69)
Gasoline; Low boiling point naphtha-
unspecified (Number on list 29, 28)
Cyclohexane (Number on list 57)
Cumene (Number on list 28)
Toluene (Number on list 48)
Benzene (Number on list 72, 5, 29, 28)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. 34a Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e)

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3	Revision Date.: 09.03.2026	SDS Number: 800001004187	Date of last issue: 05.09.2025 Print Date. 10.03.2026
----------------	-------------------------------	-----------------------------	--

alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Environmental Protection Act 1990 (as amended). Health and Safety at Work etc. Act 1974. Consumers Protection Act 1987. Pollution Prevention and Control Act 1999. Environment Act 1995. Factories Act 1961. The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment (Amendment) Regulations 2011. Chemicals (Hazard Information and Packaging for Supply) Regulations 2009. Control of Substances Hazardous to Health Regulations 2002 (as amended). Merchant Shipping (Dangerous Goods and Marine Pollutants) Regulations 1997. Reporting of Injuries, Diseases and Dangerous Occurrences Regulations 1995 (as amended). Personal Protective Equipment Regulations 2002. Personal Protective Equipment at Work Regulations 1992. Hazardous Waste (England and Wales) Regulations 2005(as amended). Control of Major Accident Hazards Regulations 1999 (as amended). Renewable Transport Fuel Obligations Order 2007 (as amended). Energy Act 2011. Environmental Permitting (England and Wales) Regulations 2010 (as amended). Waste (England and Wales) Regulations 2011 (as amended). Planning (Hazardous Substances) Act 1990 and associated regulations. The Environmental Protection (Controls on Ozone-Depleting Substances) Regulations 2011.

Product is subject to the Control of Major Accident Hazards Regulations 2015 (2015 No. 483) based on Seveso III directive (2012/18/EU).

15.2 Chemical safety assessment.

A Chemical Safety Assessment was performed for all substances of this product.

SECTION 16: Other information

Full text of H-Statements

H224	: Extremely flammable liquid and vapour.
H225	: Highly flammable liquid and vapour.
H226	: Flammable liquid and vapour.
H301	: Toxic if swallowed.
H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H311	: Toxic in contact with skin.
H312	: Harmful in contact with skin.
H315	: Causes skin irritation.
H319	: Causes serious eye irritation.
H331	: Toxic if inhaled.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

H336	: May cause drowsiness or dizziness.
H340	: May cause genetic defects.
H350	: May cause cancer.
H351	: Suspected of causing cancer.
H361d	: Suspected of damaging the unborn child.
H361f	: Suspected of damaging fertility.
H361fd	: Suspected of damaging fertility. Suspected of damaging the unborn child.
H370	: Causes damage to organs.
H372	: Causes damage to organs through prolonged or repeated exposure.
H373	: May cause damage to organs through prolonged or repeated exposure.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H411	: Toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Carc.	: Carcinogenicity
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Muta.	: Germ cell mutagenicity
Repr.	: Reproductive toxicity
Skin Irrit.	: Skin irritation
STOT SE	: Specific target organ toxicity - single exposure
2006/15/EC	: Europe. Indicative occupational exposure limit values
2019/1831/EU	: Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
91/322/EEC	: Europe. Commission Directive 91/322/EEC on establishing indicative limit values
ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	: ACGIH - Biological Exposure Indices (BEI)
GB EH40	: UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT	: UK. Biological monitoring guidance values
2006/15/EC / TWA	: Limit Value - eight hours
2006/15/EC / STEL	: Short term exposure limit
2019/1831/EU / TWA	: Limit Value - eight hours
2019/1831/EU / STEL	: Short term exposure limit
91/322/EEC / TWA	: Limit Value - eight hours
ACGIH / TWA	: 8-hour, time-weighted average
ACGIH / STEL	: Short-term exposure limit
GB EH40 / TWA	: Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	: Short-term exposure limit (15-minute reference period)

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information : This product is intended for use in closed systems only.
This mixture does not contain any REACH registered substances that are assessed to be a PBT or a vPvB.
A vertical bar (|) in the left margin indicates an amendment from the previous version.

Classification of the mixture:

Flam. Liq. 1	H224
Skin Irrit. 2	H315
Carc. 1B	H350
Muta. 1B	H340

Classification procedure:

On basis of test data.
Expert judgement and weight of evidence determination.
Expert judgement and weight of evidence determination.
Expert judgement and weight of evidence determination.

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

Asp. Tox. 1	H304	Expert judgement and weight of evidence determination.
STOT SE 3	H336	Expert judgement and weight of evidence determination.
Repr. 2	H361fd	Expert judgement and weight of evidence determination.
Aquatic Chronic 2	H411	Expert judgement and weight of evidence determination.

Identified Uses according to the Use Descriptor System

Uses - Worker

Title : Manufacture of substance
- Industrial

Uses - Worker

Title : Use as an intermediate
- Industrial

Uses - Worker

Title : Distribution of substance
- Industrial

Uses - Worker

Title : Formulation & (re)packing of substances and mixtures
- Industrial

Uses - Worker

Title : Use as a fuel
- Industrial

Uses - Worker

Title : Use as a fuel
- Professional

Identified Uses according to the Use Descriptor System

Uses - Consumer

Title : Use as a fuel
- Consumer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guid-

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version	Revision Date.:	SDS Number:	Date of last issue: 05.09.2025
8.3	09.03.2026	800001004187	Print Date. 10.03.2026

ance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version
8.3

Revision Date.:
09.03.2026

SDS Number:
800001004187

Date of last issue: 05.09.2025
Print Date. 10.03.2026

Exposure Scenario - Worker

300000000006	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Manufacture of substance- Industrial
Use Descriptor	Sector of Use: SU 3, SU8, SU9 Process Categories: PROC 1, PROC 2, PROC 3, PROC 8a, PROC 8b, PROC 15 Environmental Release Categories: ERC1, ERC4, ESVOC SpERC 1.1.v1
Scope of process	Loading (including marine vessel/barge, rail/road car and IBC loading) and repacking (including drums and small packs) of substance, including its sampling, storage, unloading distribution and associated laboratory activities.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Section 2.1	Control of Worker Exposure
Product Characteristics	
Physical form of product	Liquid, vapour pressure > 10 kPa at STP
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).
Frequency and Duration of Use	
Covers daily exposures up to 8 hours (unless stated differently).	
Other Operational Conditions affecting Exposure	
Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented.	
Contributing Scenarios	Risk Management Measures
General measures (skin irritants).	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.
General measures (carcinogens).	Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance. Where there is potential for exposure: restrict

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version
8.3

Revision Date.:
09.03.2026

SDS Number:
800001004187

Date of last issue: 05.09.2025
Print Date. 10.03.2026

	access to authorised persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when its use is identified for certain contributing scenarios; clear up spills immediately and maintain all control measures. Consider the need for risk based health surveillance.
General exposures (closed systems)with sample collection	Handle substance within a closed system. Sample via a closed loop or other system to avoid exposure Wear suitable gloves tested to EN374.
General exposures (closed systems)Continuous process	Handle substance within a closed system.
General exposures (closed systems)Batch process	Handle substance within a closed system. Ensure operation is undertaken outdoors.
Laboratory activities	Handle within a fume cupboard or implement suitable equivalent methods to minimise exposure.
Bulk transfers	Ensure material transfers are under containment or extract ventilation.
Equipment cleaning and maintenance	Drain down and flush system prior to equipment opening or maintenance. Retain drain downs in sealed storage pending disposal or for subsequent recycle. Clear spills immediately. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Storage.	Ensure operation is undertaken outdoors. Store substance within a closed system.
Section 2.2	Control of Environmental Exposure
Substance is complex UVCB.	
Predominantly hydrophobic.	
Amounts Used	
Fraction of EU tonnage used in region:	0.1
Regional use tonnage (tonnes/year):	1.87E+07
Fraction of Regional tonnage used locally:	0.03
Annual site tonnage (tonnes/year):	6.0E+05
Maximum daily site tonnage (kg/day):	2.0E+06
Frequency and Duration of Use	
Continuous release.	
Emission Days (days/year):	300
Environmental factors not influenced by risk management	

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
 Print Date. 10.03.2026

Local freshwater dilution factor:	10
Local marine water dilution factor:	100
Other Operational Conditions affecting Environmental Exposure	
Release fraction to air from process (initial release prior to RMM):	5.0E-02
Release fraction to wastewater from process (initial release prior to RMM):	3.0E-03
Release fraction to soil from process (initial release prior to RMM):	1.0E-04
Technical conditions and measures at process level (source) to prevent release	
Common practices vary across sites thus conservative process re-lease estimates used.	
Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil	
Prevent discharge of undissolved substance to or recover from onsite wastewater.	
Risk from environmental exposure is driven by humans via indirect exposure (primarily inhalation).	
Onsite waste water treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	99.0
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	99.1
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	80.4
Organisational measures to prevent/limit release from site	
Do not apply industrial sludge to natural soils.	
Sludge should be incinerated, contained or reclaimed.	
Conditions and Measures related to municipal sewage treatment plant	
Estimated substance removal from wastewater via domestic sewage treatment (%)	95.5
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	99.1
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	2.0E+06
Assumed domestic sewage treatment plant flow (m3/d)	10,000
Conditions and Measures related to external treatment of waste for disposal	
During manufacturing no waste of the substance is generated.	
Conditions and measures related to external recovery of waste	
During manufacturing no waste of the substance is generated.	

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version
8.3

Revision Date.:
09.03.2026

SDS Number:
800001004187

Date of last issue: 05.09.2025
Print Date. 10.03.2026

Section 3.2 -Environment

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

SECTION 4

GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.
Available hazard data do not enable the derivation of a DNEL for dermal irritant effects.
Available hazard data do not enable the derivation of a DNEL for carcinogenic effects.
Risk Management Measures are based on qualitative risk characterisation.
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org>).

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version
8.3

Revision Date.:
09.03.2026

SDS Number:
800001004187

Date of last issue: 05.09.2025
Print Date. 10.03.2026

Exposure Scenario - Worker

300000000007	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use as an intermediate- Industrial
Use Descriptor	Sector of Use: SU3, SU9 Process Categories: PROC1, PROC2, PROC3, PROC8a, PROC8b, PROC15 Environmental Release Categories: ERC6a, ESVOC SpERC 6.1a.v1
Scope of process	Use of substance as an intermediate within closed or contained systems (not related to Strictly Controlled Conditions). Includes incidental exposures during recycling/recovery, material transfers, storage, sampling, associated laboratory activities, maintenance and loading (including marine vessel/barge, road/rail car and bulk container).

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Section 2.1	Control of Worker Exposure
Product Characteristics	
Physical form of product	Liquid, vapour pressure > 10 kPa at STP
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently),,
Frequency and Duration of Use	
Covers daily exposures up to 8 hours (unless stated differently).	
Other Operational Conditions affecting Exposure	
Operation is carried out at elevated temperature (> 20°C above ambient temperature). Assumes a good basic standard of occupational hygiene is implemented.	
Contributing Scenarios	Risk Management Measures
General measures (skin irritants).	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.
General measures (carcinogens).	Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking con-

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version
8.3

Revision Date.:
09.03.2026

SDS Number:
800001004187

Date of last issue: 05.09.2025
Print Date. 10.03.2026

	tainment. Clean/flush equipment, where possible, prior to maintenance. Where there is potential for exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when its use is identified for certain contributing scenarios; clear up spills immediately and maintain all control measures. Consider the need for risk based health surveillance.
General exposures (closed systems)with sample collection	Handle substance within a closed system. Sample via a closed loop or other system to avoid exposure Wear suitable gloves tested to EN374.
General exposures (closed systems)	Handle substance within a closed system. Ensure operation is undertaken outdoors.
Laboratory activities	Handle within a fume cupboard or implement suitable equivalent methods to minimise exposure.
Bulk transfers	Ensure material transfers are under containment or extract ventilation.
Equipment cleaning and maintenance	Drain down and flush system prior to equipment opening or maintenance. Retain drain downs in sealed storage pending disposal or for subsequent recycle. Clear spills immediately. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Storage.	Ensure operation is undertaken outdoors. Store substance within a closed system.
Section 2.2	Control of Environmental Exposure
Substance is complex UVCB.	
Predominantly hydrophobic.	
Amounts Used	
Fraction of EU tonnage used in region:	0.1
Regional use tonnage (tonnes/year):	2.21E+06
Fraction of Regional tonnage used locally:	6.8E-03
Annual site tonnage (tonnes/year):	1.5E+04
Maximum daily site tonnage (kg/day):	5.0E+04
Frequency and Duration of Use	
Continuous release.	
Emission Days (days/year):	300
Environmental factors not influenced by risk management	
Local freshwater dilution factor:	10

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

Local marine water dilution factor:	100
Other Operational Conditions affecting Environmental Exposure	
Release fraction to air from process (initial release prior to RMM):	2.5E-02
Release fraction to wastewater from process (initial release prior to RMM):	3.0E-03
Release fraction to soil from process (initial release prior to RMM):	1.0E-03
Technical conditions and measures at process level (source) to prevent release	
Common practices vary across sites thus conservative process re-release estimates used.	
Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil	
Prevent discharge of undissolved substance to or recover from onsite wastewater.	
Risk from environmental exposure is driven by freshwater sediment.	
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	80
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	92.9
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
Organisational measures to prevent/limit release from site	
Do not apply industrial sludge to natural soils.	
Sludge should be incinerated, contained or reclaimed.	
Conditions and Measures related to municipal sewage treatment plant	
Estimated substance removal from wastewater via domestic sewage treatment (%)	95.5
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	95.5
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	7.8E+04
Assumed domestic sewage treatment plant flow (m3/d)	2,000
Conditions and Measures related to external treatment of waste for disposal	
This substance is consumed during use and no waste of substance is generated.	
Conditions and measures related to external recovery of waste	
This substance is consumed during use and no waste of substance is generated.	

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

Section 3.2 -Environment

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version
8.3

Revision Date.:
09.03.2026

SDS Number:
800001004187

Date of last issue: 05.09.2025
Print Date. 10.03.2026

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

SECTION 4

GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.
Available hazard data do not enable the derivation of a DNEL for dermal irritant effects.
Available hazard data do not enable the derivation of a DNEL for carcinogenic effects.
Risk Management Measures are based on qualitative risk characterisation.
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org>).

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version
8.3

Revision Date.:
09.03.2026

SDS Number:
800001004187

Date of last issue: 05.09.2025
Print Date. 10.03.2026

Exposure Scenario - Worker

300000000008	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Distribution of substance- Industrial
Use Descriptor	Sector of Use: SU 3 Process Categories: PROC 15, PROC 1, PROC 2, PROC 3, PROC 8a, PROC 8b Environmental Release Categories: ERC1, ERC2, ERC3, ERC4, ERC5, ERC6a, ERC6b, ERC 6C, ERC 6D, ERC7, ESVOC SpERC 1.1b.v1
Scope of process	Bulk loading (including marine vessel/barge, rail/road car and IBC loading) of substance within closed or contained systems, including incidental exposures during its sampling, storage, unloading, maintenance and associated laboratory activities.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Section 2.1	Control of Worker Exposure
Product Characteristics	
Physical form of product	Liquid, vapour pressure > 10 kPa at STP
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently),,
Frequency and Duration of Use	
Covers daily exposures up to 8 hours (unless stated differently).	
Other Operational Conditions affecting Exposure	
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.	
Contributing Scenarios	Risk Management Measures
General measures (skin irritants).	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.
General measures (carcinogens).	Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking con-

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version
8.3

Revision Date.:
09.03.2026

SDS Number:
800001004187

Date of last issue: 05.09.2025
Print Date. 10.03.2026

	tainment. Clean/flush equipment, where possible, prior to maintenance. Where there is potential for exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when its use is identified for certain contributing scenarios; clear up spills immediately and maintain all control measures. Consider the need for risk based health surveillance.
General exposures (closed systems)with sample collection	Handle substance within a closed system. Sample via a closed loop or other system to avoid exposure Wear suitable gloves tested to EN374.
General exposures (closed systems)Outdoor	Handle substance within a closed system.
Process sampling	Sample via a closed loop or other system to avoid exposure
Laboratory activities	Handle within a fume cupboard or implement suitable equivalent methods to minimise exposure.
Bulk closed loading and unloading.	Ensure material transfers are under containment or extract ventilation.
Equipment cleaning and maintenance	Drain down and flush system prior to equipment opening or maintenance. Retain drain downs in sealed storage pending disposal or for subsequent recycle. Clear spills immediately. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Storage.	Ensure operation is undertaken outdoors. Store substance within a closed system.
Section 2.2	Control of Environmental Exposure
Substance is complex UVCB.	
Predominantly hydrophobic.	
Amounts Used	
Fraction of EU tonnage used in region:	0.1
Regional use tonnage (tonnes/year):	1.87E+07
Fraction of Regional tonnage used locally:	2.0E-03
Annual site tonnage (tonnes/year):	3.75E+04
Maximum daily site tonnage (kg/day):	1.2E+05
Frequency and Duration of Use	
Continuous release.	
Emission Days (days/year):	300
Environmental factors not influenced by risk management	

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
 Print Date. 10.03.2026

Local freshwater dilution factor:	10
Local marine water dilution factor:	100
Other Operational Conditions affecting Environmental Exposure	
Release fraction to air from process (initial release prior to RMM):	1.0E-03
Release fraction to wastewater from process (initial release prior to RMM):	1.0E-05
Release fraction to soil from process (initial release prior to RMM):	1.0E-05
Technical conditions and measures at process level (source) to prevent release	
Common practices vary across sites thus conservative process re-lease estimates used.	
Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil	
Risk from environmental exposure is driven by humans via indirect exposure (primarily inhalation).	
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	90
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	12
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
Organisational measures to prevent/limit release from site	
Do not apply industrial sludge to natural soils.	
Sludge should be incinerated, contained or reclaimed.	
Conditions and Measures related to municipal sewage treatment plant	
Estimated substance removal from wastewater via domestic sewage treatment (%)	95.5
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	95.5
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	1.1E+06
Assumed domestic sewage treatment plant flow (m3/d)	2,000
Conditions and Measures related to external treatment of waste for disposal	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
Conditions and measures related to external recovery of waste	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version
8.3

Revision Date.:
09.03.2026

SDS Number:
800001004187

Date of last issue: 05.09.2025
Print Date. 10.03.2026

Section 3.2 -Environment

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.

SECTION 4

GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented.
Available hazard data do not enable the derivation of a DNEL for dermal irritant effects.
Available hazard data do not enable the derivation of a DNEL for carcinogenic effects.
Risk Management Measures are based on qualitative risk characterisation.
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.

Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (<http://cefic.org>).

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version
8.3

Revision Date.:
09.03.2026

SDS Number:
800001004187

Date of last issue: 05.09.2025
Print Date. 10.03.2026

Exposure Scenario - Worker

300000000009	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Formulation & (re)packing of substances and mixtures- Industrial
Use Descriptor	Sector of Use: SU 3, SU 10 Process Categories: PROC 1, PROC 2, PROC 3, PROC 8a, PROC 8b, PROC 15 Environmental Release Categories: ERC2, ESVOC SpERC 2.2.v1
Scope of process	Formulation of the substance and its mixtures in batch or continuous operations within closed or contained systems, including incidental exposures during storage, materials transfers, mixing, maintenance, sampling and associated laboratory activities.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Section 2.1	Control of Worker Exposure
Product Characteristics	
Physical form of product	Liquid, vapour pressure > 10 kPa at STP
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently),,
Frequency and Duration of Use	
Covers daily exposures up to 8 hours (unless stated differently).	
Other Operational Conditions affecting Exposure	
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.	
Contributing Scenarios	Risk Management Measures
General measures (skin irritants).	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.
General measures (carcinogens).	Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking con-

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version
8.3

Revision Date.:
09.03.2026

SDS Number:
800001004187

Date of last issue: 05.09.2025
Print Date. 10.03.2026

	tainment. Clean/flush equipment, where possible, prior to maintenance. Where there is potential for exposure: restrict access to authorised persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when its use is identified for certain contributing scenarios; clear up spills immediately and maintain all control measures. Consider the need for risk based health surveillance.
General exposures (closed systems)with sample collection	Handle substance within a closed system. Sample via a closed loop or other system to avoid exposure Wear suitable gloves tested to EN374.
General exposures (closed systems)Outdoor	Handle substance within a closed system.
Process sampling	Sample via a closed loop or other system to avoid exposure
Laboratory activities	Handle within a fume cupboard or implement suitable equivalent methods to minimise exposure.
Bulk transfers	Ensure material transfers are under containment or extract ventilation.
Drum/batch transfers	Ensure material transfers are under containment or extract ventilation.
Equipment cleaning and maintenance	Drain down and flush system prior to equipment opening or maintenance. Retain drain downs in sealed storage pending disposal or for subsequent recycle. Clear spills immediately. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Storage.	Store substance within a closed system. Ensure operation is undertaken outdoors.
Section 2.2	Control of Environmental Exposure
Substance is complex UVCB.	
Predominantly hydrophobic.	
Amounts Used	
Fraction of EU tonnage used in region:	0.1
Regional use tonnage (tonnes/year):	1.65E+07
Fraction of Regional tonnage used locally:	1.8E-03
Annual site tonnage (tonnes/year):	3.0E+04
Maximum daily site tonnage (kg/day):	1.0E+05
Frequency and Duration of Use	

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version
8.3

Revision Date.:
09.03.2026

SDS Number:
800001004187

Date of last issue: 05.09.2025
Print Date. 10.03.2026

Continuous release.	
Emission Days (days/year):	300
Environmental factors not influenced by risk management	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
Other Operational Conditions affecting Environmental Exposure	
Release fraction to air from process (initial release prior to RMM):	2.5E-02
Release fraction to wastewater from process (initial release prior to RMM):	2.0E-03
Release fraction to soil from process (initial release prior to RMM):	1.0E-04
Technical conditions and measures at process level (source) to prevent release	
Common practices vary across sites thus conservative process re-release estimates used.	
Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil	
Prevent discharge of undissolved substance to or recover from onsite wastewater.	
Risk from environmental exposure is driven by humans via indirect exposure (primarily inhalation).	
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	56.5
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	94.7
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
Organisational measures to prevent/limit release from site	
Do not apply industrial sludge to natural soils.	
Sludge should be incinerated, contained or reclaimed.	
Conditions and Measures related to municipal sewage treatment plant	
Estimated substance removal from wastewater via domestic sewage treatment (%)	95.5
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	95.5
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	1.0E+05
Assumed domestic sewage treatment plant flow (m3/d)	2,000
Conditions and Measures related to external treatment of waste for disposal	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
Conditions and measures related to external recovery of waste	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version
8.3

Revision Date.:
09.03.2026

SDS Number:
800001004187

Date of last issue: 05.09.2025
Print Date. 10.03.2026

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

Section 3.2 -Environment	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Available hazard data do not enable the derivation of a DNEL for dermal irritant effects. Available hazard data do not enable the derivation of a DNEL for carcinogenic effects. Risk Management Measures are based on qualitative risk characterisation. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.	

Section 4.2 -Environment	
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.	
Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.	
Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.	
Further details on scaling and control technologies are provided in SpERC factsheet (http://cefic.org).	

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version
8.3

Revision Date.:
09.03.2026

SDS Number:
800001004187

Date of last issue: 05.09.2025
Print Date. 10.03.2026

Exposure Scenario - Worker

30000000010	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use as a fuel- Industrial
Use Descriptor	Sector of Use: SU 3 Process Categories: PROC 1, PROC 2, PROC 3, PROC 8a, PROC 8b, PROC 16 Environmental Release Categories: ERC7, ESVOC SpERC 7.12a.v1
Scope of process	Covers the use as a fuel (or fuel additives and additive components) within closed or contained systems, including incidental exposures during activities associated with its transfer, use, equipment maintenance and handling of waste.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Section 2.1	Control of Worker Exposure
Product Characteristics	
Physical form of product	Liquid, vapour pressure > 10 kPa at STP
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).
Frequency and Duration of Use	
Covers daily exposures up to 8 hours (unless stated differently).	
Other Operational Conditions affecting Exposure	
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.	
Contributing Scenarios	Risk Management Measures
General measures (skin irritants).	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.
General measures (carcinogens).	Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance. Where there is potential for exposure: restrict

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version
8.3

Revision Date.:
09.03.2026

SDS Number:
800001004187

Date of last issue: 05.09.2025
Print Date. 10.03.2026

	access to authorised persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when its use is identified for certain contributing scenarios; clear up spills immediately and maintain all control measures. Consider the need for risk based health surveillance.
Bulk closed unloading.	Ensure material transfers are under containment or extract ventilation.
Drum/batch transfers	Ensure material transfers are under containment or extract ventilation.
Refueling.	Ensure material transfers are under containment or extract ventilation.
Refuelling aircraft.	Ensure material transfers are under containment or extract ventilation.
General exposures (closed systems)	Handle substance within a closed system. Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.
Use as a fuel(closed systems)	Handle substance within a closed system.
Equipment cleaning and maintenance	Drain down system prior to equipment opening or maintenance. Retain drain downs in sealed storage pending disposal or for subsequent recycle. Clear spills immediately. Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.
Storage.	Store substance within a closed system. Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.
Section 2.2	Control of Environmental Exposure
Substance is complex UVCB.	
Predominantly hydrophobic.	
Amounts Used	
Fraction of EU tonnage used in region:	0.1
Regional use tonnage (tonnes/year):	1.4E+06

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

Fraction of Regional tonnage used locally:	1
Annual site tonnage (tonnes/year):	1.4E+06
Maximum daily site tonnage (kg/day):	4.6E+06
Frequency and Duration of Use	
Continuous release.	
Emission Days (days/year):	300
Environmental factors not influenced by risk management	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
Other Operational Conditions affecting Environmental Exposure	
Release fraction to air from process (initial release prior to RMM):	2.5E-03
Release fraction to wastewater from process (initial release prior to RMM):	1.0E-05
Release fraction to soil from process (initial release prior to RMM):	0
Technical conditions and measures at process level (source) to prevent release	
Common practices vary across sites thus conservative process re-release estimates used.	
Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil	
Risk from environmental exposure is driven by humans via indirect exposure (primarily inhalation).	
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	99.4
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	76.9
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	0
Organisational measures to prevent/limit release from site	
Do not apply industrial sludge to natural soils.	
Sludge should be incinerated, contained or reclaimed.	
Conditions and Measures related to municipal sewage treatment plant	
Estimated substance removal from wastewater via domestic sewage treatment (%)	95.5
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	95.5
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	4.6E+06
Assumed domestic sewage treatment plant flow (m3/d)	2,000
Conditions and Measures related to external treatment of waste for disposal	
Combustion emissions limited by required exhaust emission controls.	
Waste combustion emissions considered in regional exposure assessment.	
Conditions and measures related to external recovery of waste	
This substance is consumed during use and no waste of substance is generated.	

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version
8.3

Revision Date.:
09.03.2026

SDS Number:
800001004187

Date of last issue: 05.09.2025
Print Date. 10.03.2026

--

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

Section 3.2 -Environment	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Available hazard data do not enable the derivation of a DNEL for dermal irritant effects. Available hazard data do not enable the derivation of a DNEL for carcinogenic effects. Risk Management Measures are based on qualitative risk characterisation. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.	

Section 4.2 -Environment	
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.	
Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.	
Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.	
Further details on scaling and control technologies are provided in SpERC factsheet (http://cefic.org).	

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version
8.3

Revision Date.:
09.03.2026

SDS Number:
800001004187

Date of last issue: 05.09.2025
Print Date. 10.03.2026

Exposure Scenario - Worker

30000000011	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use as a fuel- Professional
Use Descriptor	Sector of Use: SU 22 Process Categories: PROC 1, PROC 2, PROC 3, PROC 8a, PROC 8b, PROC 16 Environmental Release Categories: ERC9a, ERC9b, ESVOC SpERC 9.12b.v1
Scope of process	Covers the use as a fuel (or fuel additives and additive components) within closed or contained systems, including incidental exposures during activities associated with its transfer, use, equipment maintenance and handling of waste.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Section 2.1	Control of Worker Exposure
Product Characteristics	
Physical form of product	Liquid, vapour pressure > 10 kPa at STP
Concentration of the Substance in Mixture/Article	Covers use of substance/product up to 100% (unless stated differently).,
Frequency and Duration of Use	
Covers daily exposures up to 8 hours (unless stated differently).	
Other Operational Conditions affecting Exposure	
Assumes use at not more than 20°C above ambient temperature (unless stated differently). Assumes a good basic standard of occupational hygiene is implemented.	
Contributing Scenarios	Risk Management Measures
General measures (skin irritants).	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent / minimise exposures and to report any skin problems that may develop.
General measures (carcinogens).	Consider technical advances and process upgrades (including automation) for the elimination of releases. Minimise exposure using measures such as closed systems, dedicated facilities and suitable general/local exhaust ventilation. Drain down systems and clear transfer lines prior to breaking containment. Clean/flush equipment, where possible, prior to maintenance. Where there is potential for exposure: restrict

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version
8.3

Revision Date.:
09.03.2026

SDS Number:
800001004187

Date of last issue: 05.09.2025
Print Date. 10.03.2026

	access to authorised persons; provide specific activity training to operators to minimise exposures; wear suitable gloves and coveralls to prevent skin contamination; wear respiratory protection when its use is identified for certain contributing scenarios; clear up spills immediately and maintain all control measures. Consider the need for risk based health surveillance.
General exposures (closed systems)Outdoor	Handle substance within a closed system.
Bulk closed unloading.	Ensure material transfers are under containment or extract ventilation.
Drum/batch transfers	Ensure material transfers are under containment or extract ventilation.
Refueling.	Ensure material transfers are under containment or extract ventilation.
Use as a fuel(closed systems)	Handle substance within a closed system.
Equipment maintenance	Drain down system prior to equipment opening or maintenance. Retain drain downs in sealed storage pending disposal or for subsequent recycle. Clear spills immediately. Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan. Ensure operatives are trained to minimise exposures.
Storage.	Store substance within a closed system. Provide a good standard of general ventilation. Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.
Section 2.2	Control of Environmental Exposure
Substance is complex UVCB.	
Predominantly hydrophobic.	
Amounts Used	
Fraction of EU tonnage used in region:	0.1
Regional use tonnage (tonnes/year):	1.19E+06
Fraction of Regional tonnage used locally:	5.0E-04
Annual site tonnage (tonnes/year):	5.9E+02
Maximum daily site tonnage (kg/day):	1.6E+03
Frequency and Duration of Use	
Continuous release.	
Emission Days (days/year):	365

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
Print Date. 10.03.2026

Environmental factors not influenced by risk management	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100
Other Operational Conditions affecting Environmental Exposure	
Release fraction to air from process (initial release prior to RMM):	1.0E-02
Release fraction to wastewater from process (initial release prior to RMM):	1.0E-05
Release fraction to soil from process (initial release prior to RMM):	1.0E-05
Technical conditions and measures at process level (source) to prevent release	
Common practices vary across sites thus conservative process re-release estimates used.	
Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil	
Risk from environmental exposure is driven by humans via indirect exposure (primarily inhalation).	
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	
Treat air emission to provide a typical removal efficiency of (%)	0
Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of >= (%)	3.4
If discharging to domestic sewage treatment plant, no secondary wastewater treatment required.	
Organisational measures to prevent/limit release from site	
Do not apply industrial sludge to natural soils.	
Sludge should be incinerated, contained or reclaimed.	
Conditions and Measures related to municipal sewage treatment plant	
Estimated substance removal from wastewater via domestic sewage treatment (%)	95.5
Total efficiency of removal from wastewater after onsite and offsite (domestic treatment plant) RMMs (%)	95.5
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	1.5E+04
Assumed domestic sewage treatment plant flow (m3/d)	2,000
Conditions and Measures related to external treatment of waste for disposal	
Combustion emissions limited by required exhaust emission controls.	
Waste combustion emissions considered in regional exposure assessment.	
Conditions and measures related to external recovery of waste	
This substance is consumed during use and no waste of substance is generated.	

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.	

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version
8.3

Revision Date.:
09.03.2026

SDS Number:
800001004187

Date of last issue: 05.09.2025
Print Date. 10.03.2026

--

Section 3.2 -Environment

The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.
--

SECTION 4

GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
--

Section 4.1 - Health

Predicted exposures are not expected to exceed the DN(M)EL when the Risk Management Measures/Operational Conditions outlined in Section 2 are implemented. Available hazard data do not enable the derivation of a DNEL for dermal irritant effects. Available hazard data do not enable the derivation of a DNEL for carcinogenic effects. Risk Management Measures are based on qualitative risk characterisation. Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.
--

Section 4.2 -Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.
--

Required removal efficiency for wastewater can be achieved using onsite/offsite technologies, either alone or in combination.

Required removal efficiency for air can be achieved using on-site technologies, either alone or in combination.

Further details on scaling and control technologies are provided in SpERC factsheet (http://cefic.org).
--

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version
8.3

Revision Date.:
09.03.2026

SDS Number:
800001004187

Date of last issue: 05.09.2025
Print Date. 10.03.2026

Exposure Scenario - Consumer

30000000208	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use as a fuel - Consumer
Use Descriptor	Sector of Use: SU21 Product Categories: PC13 Environmental Release Categories: ERC9a, ERC9b, ESVOC SpERC 9.12c.v1
Scope of process	Covers consumer uses of automotive fuels only.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Section 2.1	Control of Consumer Exposure
Product Characteristics	
Physical form of product	Liquid, vapour pressure > 10 Pa
Concentration of the Substance in Mixture/Article	Unless stated otherwise.
	Covers concentration up to (%): 100 %
Amounts Used	
Unless stated otherwise.	
for each use event, covers amount up to (g):	37,500
covers skin contact area (cm ²):	420
Frequency and Duration of Use	
Unless stated otherwise.	
covers use up to (times/day of use):	0.143
Exposure (hours/event):	2
Other Operational Conditions affecting Exposure	
Unless stated otherwise.	
Covers use at ambient temperatures.	
Covers use in room size of 20m ³	
Covers use under typical household ventilation.	
Product Categories	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Fuels Liquid: Automotive Refuelling.	Covers concentrations up to 100 %
	covers use up to 52 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm ²): 210.00 cm ²

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version 8.3 Revision Date.: 09.03.2026 SDS Number: 800001004187 Date of last issue: 05.09.2025
 Print Date. 10.03.2026

	For each use event, covers amount up to 37,500 g
	Covers outdoor use.
	Covers use in room size of 100 m3
	Covers exposure up to 0.05 hours/event
Fuels Liquid Scooter Refuelling.	Covers concentrations up to 100 %
	covers use up to 52 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 210.00 cm2
	For each use event, covers amount up to 3,750 g
	Covers outdoor use.
	Covers use in room size of 100 m3
	Covers exposure up to 0.03 hours/event
Fuels Liquid, Garden Equipment - Use.	Covers concentrations up to 100 %
	covers use up to 26 day/year
	covers use up to 1 times/day of use
	For each use event, covers amount up to 750 g
	Covers outdoor use.
	Covers use in room size of 100 m3
	Covers exposure up to 2.00 hours/event
Fuels Liquid: Garden Equipment - Refuelling.	Covers concentrations up to 100 %
	covers use up to 26 day/year
	covers use up to 1 times/day of use
	covers skin contact area up to (cm2): 420.00 cm2
	For each use event, covers amount up to 750 g
	Covers use in a one car garage (34 m3) under typical ventilation.
	Covers use in room size of 34 m3
	Covers exposure up to 0.03 hours/event

Section 2.2	Control of Environmental Exposure
Substance is complex UVCB.	
Predominantly hydrophobic.	
Amounts Used	
Fraction of EU tonnage used in region:	0.1
Regional use tonnage (tonnes/year):	1.39E+07
Fraction of Regional tonnage used locally:	5.0E-04
Annual site tonnage (tonnes/year):	7.0E+03
Maximum daily site tonnage (kg/day):	1.9E+04
Frequency and Duration of Use	
Continuous release.	
Emission Days (days/year):	365
Environmental factors not influenced by risk management	
Local freshwater dilution factor:	10
Local marine water dilution factor:	100

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version
8.3

Revision Date.:
09.03.2026

SDS Number:
800001004187

Date of last issue: 05.09.2025
Print Date. 10.03.2026

Other Operational Conditions affecting Environmental Exposure	
Release fraction to air from process (initial release prior to RMM):	1.0E-02
Release fraction to wastewater from process (initial release prior to RMM):	1.0E-05
Release fraction to soil from process (initial release prior to RMM):	1.0E-05
Conditions and Measures related to municipal sewage treatment plant	
Risk from environmental exposure is driven by humans via indirect exposure (primarily inhalation).	
Estimated substance removal from wastewater via domestic sewage treatment (%)	95.5
Maximum allowable site tonnage (MSafe) based on release following total wastewater treatment removal (kg/d)	1.8E+05
Assumed domestic sewage treatment plant flow (m3/d)	2,000
Conditions and Measures related to external treatment of waste for disposal	
Combustion emissions limited by required exhaust emission controls.	
Waste combustion emissions considered in regional exposure assessment.	
Conditions and measures related to external recovery of waste	
This substance is consumed during use and no waste of substance is generated.	

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
The ECETOC TRA tool has been used to estimate consumer exposures unless otherwise indicated.	

Section 3.2 -Environment	
The Hydrocarbon Block Method has been used to calculate environmental exposure with the Petrorisk model.	

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
Predicted exposures are not expected to exceed the applicable consumer reference values when the operational conditions/risk management measures given in section 2 are implemented.	
Where other Risk Management Measures/Operational Conditions are adopted, then users should ensure that risks are managed to at least equivalent levels.	

Section 4.2 -Environment	
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.	
Further details on scaling and control technologies are provided in SpERC factsheet	

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell FuelSave Unleaded

Version
8.3

Revision Date.:
09.03.2026

SDS Number:
800001004187

Date of last issue: 05.09.2025
Print Date. 10.03.2026

(<http://cefic.org>).