Shell Tegula V 32

Version 2.5	Revision Date 14.10.2022	Print Date 15.10.2022
SECTION 1. PRODUCT AND C	OMPANY IDENTIFICATION	
Product name	: Shell Tegula V 32	
Product code	: 001B1573	
Manufacturer or supplier's	s details	
Supplier	: Viva Energy Australia Pty Ltd (Formerly: The Shell Company (ABN 46 004 610 459) 720 Bourke Street Docklands Victoria 3008 Australia	y of Australia)
Telephone Telefax	: +61 (0)3 8823 4444 : +61 (0)3 8823 4800	
Emergency telephone number	: 1800 651 818 (Australia). ; PC CENTRE: 13 11 26 (Australia)	
Recommended use of the Recommended use	chemical and restrictions on use : Transmission oil.	

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification	
Short-term (acute) aquatic hazard	: Category 2
Long-term (chronic) aquatic hazard	: Category 2
GHS label elements	
Hazard pictograms	
Signal word	: No signal word
Hazard statements	 PHYSICAL HAZARDS: Not classified as a physical hazard under GHS criteria. HEALTH HAZARDS: Not classified as a health hazard under GHS criteria. ENVIRONMENTAL HAZARDS: H401 Toxic to aquatic life. H411 Toxic to aquatic life with long lasting effects.

Precautionary statements :

Shell Tegula V 32

Version 2.5	Revision Date 14.10.2022	Print Date 15.10.2022
	Prevention:	
	P273 Avoid release to the enviror	nment.
	Response:	
	P391 Collect spillage.	
	Storage:	
	No precautionary phrases.	
	Disposal:	
	P501 Dispose of contents/ contai disposal plant.	ner to an approved waste

Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.Used oil may contain harmful impurities.Not classified as flammable but will burn.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture	:	Mixture
Chemical nature	:	Highly refined mineral oils and additives. The highly refined mineral oil contains <3% (w/w) DMSO- extract, according to IP346. Classification based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L).
	:	* contains one or more of the following CAS-numbers: 64742- 53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-65-0, 68037-01-4, 72623-86-0, 72623-87-1, 8042-47-5, 848301-69- 9, 68649-12-7, 151006-60-9, 163149-28-8, 64741-88-4, 64741-89-5.

Chemical name	CAS-No.	Classification	Concentration (% w/w)
Interchangeable low viscosity base oil (<20,5 cSt @40°C) *	Not Assigned	Asp. Tox.1; H304	0 - 90
Alkyl phosphite	Not Assigned	Skin Corr.1B; H314 Aquatic Acute1; H400 Aquatic Chronic1; H410 Acute Tox.5; H303	0.25 - 0.9
Alkylamide alkyleneamine	64051-50-9	Skin Sens.1; H317 Aquatic Chronic3; H412	0.1 - 0.9

Hazardous components

Shell Tegula V 32

ersion 2.5	Revis	sion Date 14.10.2022	Print Date 15.10.2022	
		Aquatic Acute3; H402		
Thioalkyl ester	Not Assigned	Skin Sens.1B; H317 Aquatic Chronic2; H411	0.1 - 0.9	
methyl-1H- benzotriazole	29385-43-1	Repr.2; H361	0.1 - 0.9	

For explanation of abbreviations see section 16.

SECTION 4. FIRST-AID MEASURES

If inhaled	: No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
In case of skin contact	: Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.
In case of eye contact	 Flush eye with copious quantities of water. Remove contact lenses, if present and easy to do. Continue rinsing. If persistent irritation occurs, obtain medical attention.
If swallowed	: In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.
Most important symptoms and effects, both acute and delayed	: Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea.
Protection of first-aiders	: When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
Notes to physician	: Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	: Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.	
Unsuitable extinguishing media	: Do not use water in a jet.	
Specific hazards during firefighting	 Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds. 	Ł

Shell Tegula V 32

Version 2.5		Revision Date 14.10.2022	Print Date 15.10.2022	
Specific extinguishing methods	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.		
Special protective equipment for firefighters	:	Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).		
Hazchem Code	:	•3Z		
SECTION 6. ACCIDENTAL RELEA	SECTION 6. ACCIDENTAL RELEASE MEASURES			
Personal precautions, protective equipment and	:	Avoid contact with skin and eyes.		
emergency procedures Environmental precautions	:	Local authorities should be advised if s cannot be contained.	significant spillages	
Methods and materials for containment and cleaning up	:	Slippery when spilt. Avoid accidents, or Prevent from spreading by making a b or other containment material. Reclaim liquid directly or in an absorber Soak up residue with an absorbent suc suitable material and dispose of prope	arrier with sand, earth ent. ch as clay, sand or other	
Additional advice	:	For guidance on selection of personal see Section 8 of this Safety Data Shee For guidance on disposal of spilled ma this Safety Data Sheet.	et.	

SECTION 7. HANDLING AND STORAGE

General Precautions	 Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
Advice on safe handling	 Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.
Avoidance of contact	: Strong oxidising agents.

Shell Tegula V 32

Version 2.5	Revision Date 14.10.2022	Print Date 15.10.2022
Product Transfer	Proper grounding and bonding procedures should be used during all bulk transfer operations to avoid static accumulation.	
Storage		
Other data	 Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closable containers. 	
	Store at ambient temperature.	
Packaging material	: Suitable material: For containers or consteel or high density polyethylene. Unsuitable material: PVC.	ntainer linings, use mild
Container Advice	: Polyethylene containers should not be temperatures because of possible risk	

SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m3	AU OEL
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m3	Australia. Workplace Exposure Standards for Airborne Contaminant s.
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m3	OSHA Z-1
Oil mist, mineral	Not Assigned	TWA (Inhalable particulate matter)	5 mg/m3	ACGIH

Components with workplace control parameters

Biological occupational exposure limits

Biological Limit Values (BLV) have not been established for this material.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate. Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory. Examples of sources of recommended exposure measurement methods are given below or

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods

Shell Tegula V 32

sion 2.5	Revision Date 14.10.2022	Print Date 15.10.2022
	Ith Administration (OSHA), USA: Sam	oling and Analytical Methods
http://www.osha.gov/ Health and Safety Executive (http://www.hse.gov.uk/	(HSE), UK: Methods for the Determina	tion of Hazardous Substances
Institut für Arbeitsschutz Deut http://www.dguv.de/inhalt/inde		
L'Institut National de Recherc	he et de Securité, (INRS), France http	://www.inrs.fr/accueil
Engineering measures	: The level of protection and types vary depending upon potential ex controls based on a risk assessm Appropriate measures include:	posure conditions. Select nent of local circumstances.
	Adequate ventilation to control ai	rborne concentrations.
	Where material is heated, spraye greater potential for airborne con-	
	General Information:	
	Define procedures for safe handl	ing and maintenance of
	controls. Educate and train workers in the measures relevant to normal acti	
	product. Ensure appropriate selection, tes equipment used to control exposi equipment, local exhaust ventilat	ure, e.g. personal protective
	Drain down system prior to equip maintenance.	
	Retain drain downs in sealed stor subsequent recycle.	rage pending disposal or
	Always observe good personal hy washing hands after handling the drinking, and/or smoking. Routin protective equipment to remove of contaminated clothing and footwe Practice good housekeeping.	material and before eating, ely wash work clothing and contaminants. Discard
Personal protective equipm	ent	
Protective measures		

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Respiratory protection	 No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers.

Shell Tegula V 32

sion 2.5	Revision Date 14.10.2022 Print Date 15.10.202
	Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for the combination of organic gases and vapours and particles [Type A/Type P boiling point >65°C (149°F)].
Hand protection	
Remarks	: Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.
	For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is no a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model.
Eye protection	: If material is handled such that it could be splashed into eyes protective eyewear is recommended.
Skin and body protection	 Skin protection is not ordinarily required beyond standard work clothes. It is good practice to wear chemical resistant gloves.
Thermal hazards	: Not applicable
Environmental exposure c	ontrols
General advice	 Take appropriate measures to fulfill the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in Section 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment pla before discharge to surface water. Local guidelines on emission limits for volatile substances

Shell Tegula V 32

Version 2.5	Revision Date 14.10.2022	Print Date 15.10.2022
	vapour.	
SECTION 9. PHYSICAL AND CHE	MICAL PROPERTIES	
Appearance	: liquid	
Colour	: clear	
Odour	: Slight hydrocarbon	
Odour Threshold	: Data not available	
рН	: Not applicable	
pour point	: -30 °C / -22 °F Method: ISO 3016	
Melting / freezing point	Data not available	
Initial boiling point and boiling range	: > 280 °C / 536 °Festimated value((s)
Flash point	: 211 °C / 412 °F Method: ISO 2592	
Evaporation rate	: Data not available	
Flammability (solid, gas)	: Not applicable	
Flammability (liquids)	: Not classified as flammable but w	ill burn.
Upper explosion limit	: Typical 10 %(V)	
Lower explosion limit	: Typical 1 %(V)	
Vapour pressure	: < 0.5 Pa (20 °C / 68 °F) estimated value(s)	
Relative vapour density	: > 1estimated value(s)	
Relative density	: 0.870 (15 °C / 59 °F)	
Density	: 870 kg/m3 (15.0 °C / 59.0 °F) Method: ISO 12185	
Solubility(ies)		
Water solubility	: negligible	
Solubility in other solvents	: Data not available	
Partition coefficient: n- octanol/water	: log Pow: > 6 (based on information on similar p	products)
Auto-ignition temperature	: > 320 °C / 608 °F	

Shell Tegula V 32

Version 2.5 Decomposition temperature	Revision Date 14.10.2022 : Data not available	Print Date 15.10.2022
Viscosity		
Viscosity, dynamic	: Data not available	
Viscosity, kinematic	: 32 mm2/s (40.0 °C / 104.0 °F) Method: ISO 3104	
	5.6 mm2/s (100 °C / 212 °F) Method: ISO 3104	
Explosive properties	: Classification Code: Not classified	
Oxidizing properties	: Data not available	
Conductivity Particle size	: This material is not expected to be a s : Data not available	tatic accumulator.

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.
Chemical stability	: Stable.
Possibility of hazardous reactions	: Reacts with strong oxidising agents.
Conditions to avoid	: Extremes of temperature and direct sunlight.
Incompatible materials	: Strong oxidising agents.
Hazardous decomposition products	: No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Basis for assessment	: Information given is based on data on the components and the toxicology of similar products.Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).
Exposure routes	: Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.
Acute toxicity	
Product:	

Shell Tegula V 32

Version 2.5	Revision Date 14.10.2022	Print Date 15.10.2022
Acute oral toxicity	: LD50 rat: > 5,000 mg/kg Remarks: Low toxicity: Based on available data, the class	ification criteria are not met.
Acute inhalation toxicity	: Remarks: Based on available data are not met.	, the classification criteria
Acute dermal toxicity	: LD50 Rabbit: > 5,000 mg/kg Remarks: Low toxicity: Based on available data, the class	ification criteria are not met.

Skin corrosion/irritation

Product:

Remarks: Slightly irritating to skin., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis., Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Product:

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Product:

Remarks: Not a skin sensitiser. Based on available data, the classification criteria are not met.

Components:

Alkylamide alkyleneamine:

Remarks: May cause an allergic skin reaction in sensitive individuals.

Chronic toxicity

Germ cell mutagenicity

Product:

: Remarks: Non mutagenic, Based on available data, the classification criteria are not met.

Carcinogenicity

Product:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

Remarks: Product contains mineral oils of types shown to be non-carcinogenic in animal skin-

Shell Tegula V 32

Version 2.5

Revision Date 14.10.2022

Print Date 15.10.2022

painting studies., Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC).

Material	GHS/CLP Carcinogenicity Classification
Highly refined mineral oil	No carcinogenicity classification.

Reproductive toxicity

Product:

Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are not met.

STOT - single exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

1

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

Aspiration toxicity

Product:

Not an aspiration hazard.

Further information

Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Slightly irritating to respiratory system.

SECTION 12. ECOLOGICAL INFORMATION

Basis for assessment	: Ecotoxicological data have not been determined specifically
	for this product.
	Information given is based on a knowledge of the components
	and the ecotoxicology of similar products.

Shell Tegula V 32

Version 2.5	Revision Date 14.10.2022 Print Date 15.10.2022
	Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).
Ecotoxicity	
Product:	
Toxicity to fish (Acute toxicity)	: Remarks: LL/EL/IL50 > 1 <= 10 mg/l Toxic
Toxicity to crustacean (Acute toxicity)	: Remarks: LL/EL/IL50 1-10 mg/I Toxic
Toxicity to algae/aquatic plants (Acute toxicity)	: Remarks: LL/EL/IL50 1-10 mg/I Toxic
Toxicity to fish (Chronic toxicity)	: Remarks: Data not available
Toxicity to crustacean (Chronic toxicity)	: Remarks: Data not available
Toxicity to microorganisms (Acute toxicity)	: Remarks: LL/EL/IL50 > 1 <= 10 mg/l Toxic
<u>Components:</u> Alkyl phosphite :	
M-Factor (Short-term (acute)	: 10
aquatic hazard) M-Factor (Long-term (chronic) aquatic hazard)	: 10
Persistence and degradability	
Product:	
Biodegradability	: Remarks: Not readily biodegradable., Major constituents are inherently biodegradable, but contains components that may persist in the environment.
Bioaccumulative potential	
Product:	
Bioaccumulation	: Remarks: Contains components with the potential to bioaccumulate.
Partition coefficient: n- octanol/water	: log Pow: > 6Remarks: (based on information on similar products)
Mobility in soil	
Product:	
Mobility	: Remarks: Liquid under most environmental conditions., If it enters soil, it will adsorb to soil particles and will not be

Shell Tegula V 32

Version 2.5	Revision Date 14.10.2022	Print Date 15.10.2022	
	mobile. Remarks: Floats on water.		
Other adverse effects			
no data available <u>Product:</u>			
Additional ecological information	ozone creation potential or global v is a mixture of non-volatile compon released to air in any significant qu conditions of use. Poorly soluble mixture., Causes ph organisms. Mineral oil does not cause chronic	Poorly soluble mixture., Causes physical fouling of aquatic	

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues	 Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water courses
	Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Waste, spills or used product is dangerous waste. Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand. Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination.
	MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides technical aspects at controlling pollutions from ships.
Contaminated packaging	: Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.
Local legislation Remarks	: Disposal should be in accordance with applicable regional,
(17	80000100444

Shell Tegula V 32

Version 2.5	Revision Date 14.10.2022	Print Date 15.10.2022
	national, and local laws and regul	ations.
SECTION 14. TRANSPORT INF	ORMATION	
ADG		
UN number	: 3082	
Proper shipping name	 ENVIRONMENTALLY HAZARDC N.O.S. (Alkyl phosphite) 	OUS SUBSTANCE, LIQUID,
Class	: 9	
Packing group	: 111	
Labels	: 9	
Hazchem Code	: •3Z	
ternational Regulations		
IATA-DGR		
UN/ID No.	: UN 3082	
Proper shipping name	: ENVIRONMENTALLY HAZARDC N.O.S.	OUS SUBSTANCE, LIQUID,
Class	(Alkyl phosphite)	
Packing group	: 9 : III	
Labels	: 9	
	. 9	
IMDG-Code UN number	: UN 3082	
Proper shipping name	: ENVIRONMENTALLY HAZARDC N.O.S.	JUS SUBSTAINCE, LIQUID,
	(Alkyl phosphite)	
Class	: 9	
Packing group	: 111	
Labels	: 9	
Marine pollutant	: yes	
laritime transport in bulk acco	ording to IMO instruments	
IARPOL Annex 1 rules apply fo	r bulk shipments by sea.	
Special precautions for user		
Remarks	: Special Precautions: Refer to Se	ction 7. Handling & Storage.

Remarks	: Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.
Additional Information	: Not classified under ADG 7.7 regulations if special provision AU 01 applies

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or

Shell Tegula V 32

vision Date 14.10.2022	Print Date 15.10.2022
poison schedule number allocated	
	poison schedule number allocated

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Product classified as per Work Health Safety Regulations – Implementation of the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) 2012 and SDS prepared as per national model code of practice for preparation of safety data sheet for Hazardous chemicals 2020 based on Globally Harmonized Classification version 7.

National Model Code of Practice for the Labelling of Workplace Hazardous Chemicals (2011). Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG code). Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

Other international regulations

The components of this product are reported in the following inventories:

REACH	:	All components listed.
TSCA	:	All components listed.
AIIC	:	Listed introduction

SECTION 16. OTHER INFORMATION

Full text of H-Statements

H303	May be harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H361	Suspected of damaging fertility or the unborn child.
H400	Very toxic to aquatic life.
H402	Harmful to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Full text of other al	obreviations
Acute Tox.	Acute toxicity
Aquatic Acute	Short term (acute) aquatic bazard

Aquatic Acute	Short-term (acute) aquatic hazard
Aquatic Chroni	c Long-term (chronic) aquatic hazard
Asp. Tox.	Aspiration hazard
Repr.	Reproductive toxicity
Skin Corr.	Skin corrosion
Skin Sens.	Skin sensitisation

Abbreviations and Acronyms

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with

Shell Tegula V 32

Version 2.5

Revision Date 14.10.2022

Print Date 15.10.2022

x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System: GLP - Good Laboratory Practice: IARC - International Agency for Research on Cancer: IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC -New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development: OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG -Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Date of preparation or review : 14.10.2022

Further information

Training advice	:	Provide adequate information, instruction and training for operators.
Other information	:	A vertical bar () in the left margin indicates an amendment from the previous version.
Sources of key data used to compile the Safety Data Sheet	:	The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

AU / EN

Shell Tegula V 32

Version 2.5

Revision Date 14.10.2022

Print Date 15.10.2022