# Helix Ultra Racing 10W-60

ersion 1.9	F	Revision Date 14.10.2022	Print Date 15.10.202			
CTION 1. PRODUCT AND	COMPAN	Y IDENTIFICATION				
Product name	: H	elix Ultra Racing 10W-60				
Product code	: 90	: 901L3254				
Manufacturer or supplie	's details					
Supplier	: V (F (A 72 D V	iva Energy Australia Pty Ltd Formerly: The Shell Company of ABN 46 004 610 459) 20 Bourke Street ocklands ictoria 3008 ustralia	Australia)			
Telephone Telefax		61 (0)3 8823 4444 61 (0)3 8823 4800				
Emergency telephone number		800 651 818 (Australia). ; POIS0 ENTRE: 13 11 26 (Australia).	ONS INFORMATION			
Recommended use of th	e chemic	al and restrictions on use				
		ngine oil.				

#### **GHS Classification**

Based on available data this substance / mixture does not meet the classification criteria.

GHS label elements	
Hazard pictograms	: No Hazard Symbol required
Signal word	: No signal word
Hazard statements	<ul> <li>PHYSICAL HAZARDS: Not classified as a physical hazard under GHS criteria. HEALTH HAZARDS: Not classified as a health hazard under GHS criteria. ENVIRONMENTAL HAZARDS: Not classified as an environmental hazard under GHS criteria.</li> </ul>
Precautionary statements	: <b>Prevention:</b> No precautionary phrases. <b>Response:</b> No precautionary phrases.
	Storage:

## Helix Ultra Racing 10W-60

Version 1.9

Revision Date 14.10.2022 No precautionary phrases. Print Date 15.10.2022

#### Disposal:

No precautionary phrases.

### Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.Used oil may contain harmful impurities.Not classified as flammable but will burn.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture	: Mixture
Chemical nature	<ul> <li>Synthetic base oil and additives. Highly refined mineral oil. The highly refined mineral oil contains &lt;3% (w/w) DMSO- extract, according to IP346. The highly refined mineral oil is only present as additive diluent. Classification based on DMSO extract content &lt; 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L).</li> </ul>
	<ul> <li>* contains one or more of the following CAS-numbers: 64742- 53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-65-0, 68037-01-4, 72623-86-0, 72623-87-1, 8042-47-5, 848301-69- 9, 68649-12-7, 151006-60-9, 163149-28-8, 64741-88-4,</li> </ul>

#### Hazardous components

Chemical name	CAS-No.	Classification	Concentration (% w/w)
Interchangeable low viscosity base oil (<20,5 cSt @40°C) *	Not Assigned	Asp. Tox.1; H304	0 - 90
Alkaryl amine	36878-20-3	Aquatic Chronic4; H413	0 - 3

64741-89-5.

For explanation of abbreviations see section 16.

#### **SECTION 4. FIRST-AID MEASURES**

If inhaled	: No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
In case of skin contact	<ul> <li>Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available.</li> <li>If persistent irritation occurs, obtain medical attention.</li> </ul>

# Helix Ultra Racing 10W-60

Version 1.9	Revision Date 14.10.2022	Print Date 15.10.2022
In case of eye contact	<ul> <li>Flush eye with copious quantitie Remove contact lenses, if prese rinsing.</li> <li>If persistent irritation occurs, obt</li> </ul>	ent and easy to do. Continue
If swallowed	: In general no treatment is neces are swallowed, however, get me	
Most important symptoms and effects, both acute and delayed	: Oil acne/folliculitis signs and symptoms may include formatio of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea.	
Protection of first-aiders	: When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.	
Notes to physician	: Treat symptomatically.	

### SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	:	Do not use water in a jet.
Specific hazards during firefighting	:	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds.
Specific extinguishing methods	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Special protective equipment for firefighters	:	Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).
Hazchem Code	:	NONE

## SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions,	:	Avoid contact with skin and eyes.
protective equipment and		

# Helix Ultra Racing 10W-60

Version 1.9	Revision Date 14.10.2022	Print Date 15.10.2022
emergency procedures Environmental precautions	: Use appropriate containment to a contamination. Prevent from spre ditches or rivers by using sand, e barriers.	eading or entering drains,
	Local authorities should be advise cannot be contained.	ed if significant spillages
Methods and materials for containment and cleaning up	: Slippery when spilt. Avoid accide Prevent from spreading by makin or other containment material. Reclaim liquid directly or in an ab Soak up residue with an absorber suitable material and dispose of p	ng a barrier with sand, earth psorbent. nt such as clay, sand or other
Additional advice	: For guidance on selection of pers see Section 8 of this Safety Data For guidance on disposal of spille this Safety Data Sheet.	Sheet.

#### SECTION 7. HANDLING AND STORAGE

General Precautions	Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal this material.	of
Advice on safe handling	Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.	
Avoidance of contact	Strong oxidising agents.	
Product Transfer	Proper grounding and bonding procedures should be used during all bulk transfer operations to avoid static accumulation	on.
Storage		
Other data	Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closable containers. Store at ambient temperature.	

Version 1.9	Revision Date 14.10.2022	Print Date 15.10.2022
Packaging material	: Suitable material: For containers or steel or high density polyethylene. Unsuitable material: PVC.	container linings, use mild
Container Advice	: Polyethylene containers should not temperatures because of possible ri	

### SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m3	AU OEL
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m3	Australia. Workplace Exposure Standards for Airborne Contaminant s.
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m3	OSHA Z-1
Oil mist, mineral	Not Assigned	TWA (Inhalable particulate matter)	5 mg/m3	ACGIH

#### Components with workplace control parameters

### Biological occupational exposure limits

No biological limit allocated.

#### **Monitoring Methods**

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

Engineering measures : The level of protection and types of controls necessary will

rsion 1.9	Revision Date 14.10.2022	Print Date 15.10.2022
	vary depending upon potential ex controls based on a risk assessm Appropriate measures include: Adequate ventilation to control air	nent of local circumstances.
	Where material is heated, spraye greater potential for airborne con-	
	General Information: Define procedures for safe handli controls.	ing and maintenance of
	Educate and train workers in the measures relevant to normal active product.	
	Ensure appropriate selection, tes equipment used to control exposi equipment, local exhaust ventilati Drain down system prior to equip	ure, e.g. personal protective ion.
	maintenance. Retain drain downs in sealed stor subsequent recycle.	
	Always observe good personal hy washing hands after handling the drinking, and/or smoking. Routin protective equipment to remove of contaminated clothing and footwe Practice good housekeeping.	material and before eating, ely wash work clothing and contaminants. Discard
Personal protective equi	oment	
Protective measures		
Personal protective equipn PPE suppliers.	nent (PPE) should meet recommended n	ational standards. Check wit
Respiratory protection	<ul> <li>No respiratory protection is ordinal conditions of use.</li> <li>In accordance with good industrial precautions should be taken to avail of engineering controls do not man concentrations to a level which is health, select respiratory protection specific conditions of use and men Check with respiratory protective Where air-filtering respirators are appropriate combination of mask</li> </ul>	al hygiene practices, void breathing of material. intain airborne adequate to protect worker on equipment suitable for the eeting relevant legislation. equipment suppliers. suitable, select an

: Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide

Hand protection

Remarks

Version 1.9	Revision Date 14.10.2022	Print Date 15.10.2022
	suitable chemical protection. PVC gloves Suitability and durability of usage, e.g. frequency and duratic resistance of glove material, dext from glove suppliers. Contaminat replaced. Personal hygiene is a k care. Gloves must only be worn of gloves, hands should be washed Application of a non-perfumed mo	f a glove is dependent on on of contact, chemical erity. Always seek advice ed gloves should be ey element of effective hand on clean hands. After using and dried thoroughly.
	For continuous contact we recom breakthrough time of more than 2 for > 480 minutes where suitable short-term/splash protection we re recognize that suitable gloves offer may not be available and in this of time maybe acceptable so long a and replacement regimes are folled a good predictor of glove resistant dependent on the exact composit Glove thickness should be typical depending on the glove make and	240 minutes with preference gloves can be identified. For ecommend the same but ering this level of protection case a lower breakthrough s appropriate maintenance owed. Glove thickness is not ice to a chemical as it is tion of the glove material. Ily greater than 0.35 mm
Eye protection	If material is handled such that it protective eyewear is recommend	
Skin and body protection	<ul> <li>Skin protection is not ordinarily re work clothes.</li> <li>It is good practice to wear chemic</li> </ul>	
Thermal hazards	Not applicable	
Environmental exposure contr	rols	
General advice	Take appropriate measures to ful relevant environmental protection contamination of the environment Section 6. If necessary, prevent being discharged to waste water. treated in a municipal or industria before discharge to surface water Local guidelines on emission limit must be observed for the discharg vapour.	a legislation. Avoid t by following advice given in undissolved material from Waste water should be I waste water treatment plant r. ts for volatile substances
SECTION 9. PHYSICAL AND CHEM	ICAL PROPERTIES	
Appearance	Liquid at room temperature.	
Colour	amber	
Odour	: Data not available	
Odour Threshold	: Data not available	

# Helix Ultra Racing 10W-60

sion 1.9 pH	Revision Date 14.10.2022 : Not applicable	Print Date 15.10.2
pour point	: -42 °C / -44 °F	
	Method: ASTM D97	
Melting / freezing point	Data not available	
Initial boiling point and boiling range	: > 280 °C / 536 °Festimated val	lue(s)
Flash point	: 250 °C / 482 °F Method: ASTM D92 (COC)	
Evaporation rate	: Data not available	
Flammability (solid, gas)	: Not applicable	
Flammability (liquids)	: Not classified as flammable bu	it will burn.
Upper explosion limit	: Typical 10 %(V)	
Lower explosion limit	: Typical 1 %(V)	
Vapour pressure	: < 0.5 Pa (20 °C / 68 °F) estimated value(s)	
Relative vapour density	: >5	
Relative density	: 0.8458 (15 °C / 59 °F)	
Density	: 845.8 kg/m3 (15.0 °C / 59.0 °F Method: ASTM D4052	·)
Solubility(ies)		
Water solubility	: negligible	
Solubility in other solvents	: Data not available	
Partition coefficient: n- octanol/water	: log Pow: > 6 (based on information on simila	ar products)
Auto-ignition temperature	: > 320 °C / 608 °F	
Decomposition temperature	: Data not available	
Viscosity		
Viscosity, dynamic	: Data not available	
Viscosity, kinematic	: 160.1 mm2/s (40.0 °C / 104.0 ° Method: ASTM D445	°F)
	23.1 mm2/s (100 °C / 212 °F) Method: ASTM D445	

# Helix Ultra Racing 10W-60

Version 1.9	Revision Date 14.10.2022	Print Date 15.10.2022
Explosive properties	: Classification Code: Not classified	
Oxidizing properties	: Data not available	
Conductivity Particle size	: This material is not expected to be a : Data not available	a static accumulator.

Reactivity	: The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.
Chemical stability	: Stable.
Possibility of hazardous reactions	: Reacts with strong oxidising agents.
Conditions to avoid	: Extremes of temperature and direct sunlight.
Incompatible materials	: Strong oxidising agents.
Hazardous decomposition products	: No decomposition if stored and applied as directed.

### SECTION 11. TOXICOLOGICAL INFORMATION

SECTION 10. STABILITY AND REACTIVITY

Basis for assessment	: Information given is based on data on the components and the toxicology of similar products.Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).
Exposure routes	: Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.
Acute toxicity	
Product:	
Acute oral toxicity	<ul> <li>LD50 rat: &gt; 5,000 mg/kg</li> <li>Remarks: Low toxicity:</li> <li>Based on available data, the classification criteria are not met.</li> </ul>
Acute inhalation toxicity	: Remarks: Based on available data, the classification criteria are not met.
Acute dermal toxicity	: LD50 Rabbit: > 5,000 mg/kg Remarks: Low toxicity:

## Helix Ultra Racing 10W-60

Version 1.9	Revision Date 14.10.2022	Print Date 15.10.2022
	Based on available data, the classific	cation criteria are not met.

#### Skin corrosion/irritation

#### Product:

Remarks: Slightly irritating to skin., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis., Based on available data, the classification criteria are not met.

#### Serious eye damage/eye irritation

#### Product:

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

#### Respiratory or skin sensitisation

#### Product:

Remarks: Not a skin sensitiser. Based on available data, the classification criteria are not met.

1

#### **Chronic toxicity**

#### Germ cell mutagenicity

#### Product:

: Remarks: Non mutagenic, Based on available data, the classification criteria are not met.

### Carcinogenicity

#### Product:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

Material	GHS/CLP Carcinogenicity Classification
Highly refined mineral oil	No carcinogenicity classification.

#### **Reproductive toxicity**

#### Product:

Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are not met.

### STOT - single exposure

#### Product:

10/16

## Helix Ultra Racing 10W-60

Version 1.9

Revision Date 14.10.2022

Print Date 15.10.2022

Remarks: Based on available data, the classification criteria are not met.

#### STOT - repeated exposure

#### Product:

Remarks: Based on available data, the classification criteria are not met.

#### Aspiration toxicity

#### Product:

Not an aspiration hazard.

#### **Further information**

#### Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Continuous contact with used engine oils has caused skin cancer in animal tests.

Remarks: Slightly irritating to respiratory system.

### **SECTION 12. ECOLOGICAL INFORMATION**

Basis for assessment :	Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).
Ecotoxicity	
Product:	
Toxicity to fish (Acute : toxicity)	Remarks: Based on available data, the classification criteria are not met. Practically non toxic:
Toxicity to crustacean (Acute : toxicity)	LL/EL/IL50 > 100 mg/l Remarks: Based on available data, the classification criteria are not met. Practically non toxic: LL/EL/IL50 > 100 mg/l

Version 1.9	Revision Date 14.10.2022	Print Date 15.10.2022
Toxicity to algae/aquatic plants (Acute toxicity)	: Remarks: Based on available da are not met. Practically non toxic: LL/EL/IL50 > 100 mg/l	ta, the classification criteria
Toxicity to fish (Chronic toxicity)	: Remarks: Based on available da are not met.	ta, the classification criteria
Toxicity to crustacean (Chronic toxicity)	: Remarks: Based on available da are not met.	ta, the classification criteria
Toxicity to microorganisms (Acute toxicity)	: Remarks: Based on available da are not met.	ta, the classification criteria
Persistence and degradability		
Product:		
Biodegradability	: Remarks: Not readily biodegrada inherently biodegradable, but con persist in the environment., Pers International Oil Pollution Compe- definition: "A non-persistent oil is shipment, consists of hydrocarbo of which, by volume, distills at a and (b) at least 95% of which, by temperature of 370°C (700°F) wh Method D-86/78 or any subseque	ntains components that may istent per IMO criteria., ensation (IOPC) Fund oil, which, at the time of on fractions, (a) at least 50% temperature of 340°C (645°F) volume, distils at a nen tested by the ASTM
Bioaccumulative potential		
Product:		
Bioaccumulation	: Remarks: Contains components bioaccumulate.	with the potential to
Partition coefficient: n- octanol/water	: log Pow: > 6Remarks: (based or products)	n information on similar
Mobility in soil		
Product:		
Mobility	<ul> <li>Remarks: Liquid under most env enters soil, it will adsorb to soil p mobile.</li> <li>Remarks: Floats on water.</li> </ul>	
Other adverse effects		
no data available Product:		
Additional ecological information	: Does not have ozone depletion p ozone creation potential or globa is a mixture of non-volatile comp released to air in any significant	I warming potential., Product onents, which will not be

# Helix Ultra Racing 10W-60

Version 1.9	Revision Date 14.10.2022	Print Date 15.10.2022
	conditions of use.	
	Poorly soluble mixture., Causes ph	ysical fouling of aquatic
	organisms.	

### **SECTION 13. DISPOSAL CONSIDERATIONS**

Disposal methods	
Waste from residues	<ul> <li>Recover or recycle if possible.</li> <li>It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.</li> <li>Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Do not dispose into the environment, in drains or in water courses</li> <li>Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination.</li> <li>Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.</li> </ul>
	MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides technical aspects at controlling pollutions from ships.
Contaminated packaging	: Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.
Local legislation Remarks	: Disposal should be in accordance with applicable regional, national, and local laws and regulations.

## SECTION 14. TRANSPORT INFORMATION

### **National Regulations**

#### ADG

Not regulated as a dangerous good

#### International Regulations

#### IATA-DGR

Not regulated as a dangerous good

## Helix Ultra Racing 10W-60

Version 1.9

Revision Date 14.10.2022

Print Date 15.10.2022

IMDG-Code Not regulated as a dangerous good

Maritime transport in bulk according to IMO instruments

MARPOL Annex 1 rules apply for bulk shipments by sea.

#### Special precautions for user

Remarks

: Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

#### **SECTION 15. REGULATORY INFORMATION**

Safety, health and environmental regulations/legislation specific for the substance or mixture

Standard for the Uniform : No poison schedule number allocated Scheduling of Medicines and Poisons

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Product classified as per Work Health Safety Regulations – Implementation of the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) 2012 and SDS prepared as per national model code of practice for preparation of safety data sheet for Hazardous chemicals 2020 based on Globally Harmonized Classification version 7.

National Model Code of Practice for the Labelling of Workplace Hazardous Chemicals (2011).

Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG code). Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

#### Other international regulations

#### The components of this product are reported in the following inventories:

REACH	: Notified with Restrictions.
TSCA	: All components listed.
AIIC	: Listed introduction

#### **SECTION 16. OTHER INFORMATION**

#### Full text of H-Statements

H304 May be fatal if swallowed and enters airways.		
H413 May cause long lasting harmful effects to aquatic		
Full text of other abbreviations		
Aquatic Chronic	Long-term (chronic) aquatic hazard	

Asp. Tox. Aspiration hazard

## Helix Ultra Racing 10W-60

Version 1.9

Revision Date 14.10.2022

Print Date 15.10.2022

#### Abbreviations and Acronyms

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose): MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC -New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development: OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG -Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Date of preparation or review : 14.10.2022

#### Further information

Training advice	:	Provide adequate information, instruction and training for operators.
Other information	:	A vertical bar ( ) in the left margin indicates an amendment from the previous version.
Sources of key data used to compile the Safety Data Sheet	:	The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the

# Helix Ultra Racing 10W-60

 Version 1.9
 Revision Date 14.10.2022
 Print Date 15.10.2022

 specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
 Print Date 15.10.2022

AU / EN