Spirax S6 GME 40

Version 2.1	Revision Date 23.07.2025	Print Date 24.07.2025
SECTION 1. PRODUCT AND	COMPANY IDENTIFICA	TION
Product name	: Spirax S6 GME	40
Product code	: 001F8273	
Manufacturer or supplie	er's details	
Supplier	: Viva Energy Aus (Formerly: The S (ABN 46 004 61 720 Bourke Stre Docklands Victoria 3008 Australia	Shell Company of Australia) 0 459)
Telephone Telefax	: +61 (0)3 8823 4 : +61 (0)3 8823 4	
Emergency telephone number	: 1800 651 818 (<i>/</i> ;POISONS INF	Australia). ORMATION CENTRE: 13 11 26 (Australia).
Recommended use of the	he chemical and restrict	ions on use
Recommended use	: Transmission oil	
Restrictions on use		st not be used in applications other than those 1 without first seeking the advice of the

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification	
Specific target organ toxicity -	: Category 2 (lymph node)
repeated exposure Long-term (chronic) aquatic hazard	: Category 3
GHS label elements	
Hazard pictograms	
Signal word	: Warning

Version 2.1	Revision Date 23.07.2025	Print Date 24.07.2025
Hazard statements	HEALTH HAZA H373 May cause repeated expose ENVIRONMEN	s a physical hazard under GHS criteria. RDS: e damage to organs through prolonged or
Precautionary statements		eathe dust/ fume/ gas/ mist/ vapours/ spray. ase to the environment.
	Response: P314 Get medic	al advice/ attention if you feel unwell.
	Storage: No precautiona	ry phrases.
	Disposal: P501 Dispose or disposal plant.	f contents/ container to an approved waste

Hazardous components which must be listed on the label: Contains amine phosphate.

Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.Used oil may contain harmful impurities.Not classified as flammable but will burn.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture	Mixture

3.2 Mixtures

Chemical nature	:	Blend of polyolefins and additives. The highly refined mineral oil contains <3% (w/w) DMSO- extract, according to IP346. The highly refined mineral oil is only present as additive diluent. Classification based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L).
	:	* contains one or more of the following CAS-numbers: 64742-

Spirax S6 GME 40

Version 2.1 Revision Date Print Date 24.07.2025 23.07.2025 53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-65-0, 68037-01-4, 72623-86-0, 72623-87-1, 8042-47-5, 848301-69-9, 68649-12-7, 151006-60-9, 163149-28-8, 64741-88-4, 64741-89-5.

Components

Chemical name	CAS-No.	Classification	Concentration (% w/w)
Interchangeable low viscosity base oil (<20,5 cSt @40°C) *	Not Assigned	Asp. Tox.1; H304	0 - 10
Amine phosphate	80939-62-4	Skin Irrit.2; H315 Eye Irrit.2; H319 STOT RE1; H372 Aquatic Chronic2; H411	1 - 2.99
2,6-di-tert-butyl phenol	128-39-2	Skin Irrit.2; H315 Aquatic Acute1; H400 Aquatic Chronic1; H410	0.25 - 0.99
Ethoxylated amine	61791-44-4	Acute Tox.4; H302 Skin Corr.1C; H314 Aquatic Acute1; H400 Aquatic Chronic1; H410	0.25 - 0.99
Alkoxylated alkylamine	30113-45-2	Skin Corr.1B; H314 Aquatic Acute1; H400 Aquatic Chronic1; H410 Acute Tox.4; H302	0.025 - 0.099

For explanation of abbreviations see section 16.

SECTION 4. FIRST-AID MEASU	RES
General advice	: Not expected to be a health hazard when used under normal conditions.
If inhaled	: No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
In case of skin contact	: Remove contaminated clothing. Immediately flush skin with large amounts of water for at least 15 minutes, and follow by washing with soap and water if available. If redness, swelling, pain and/or blisters occur, transport to the nearest medical facility for additional treatment.

Version 2.1	Revision Date 23.07.2025	Print Date 24.07.2025
In case of eye contact	Remove conta rinsing.	n copious quantities of water. act lenses, if present and easy to do. Continue ritation occurs, obtain medical attention.
If swallowed	5	treatment is necessary unless large quantities d, however, get medical advice.
Most important symptoms and effects, both acute and delayed	conditions of u Possible resp a temporary b coughing, and Skin irritation sensation, red Eye irritation s sensation, red Ingestion may Oil acne/follice	ed to be an inhalation hazard under normal use. iratory irritation signs and symptoms may include burning sensation of the nose and throat, d/or difficulty breathing. signs and symptoms may include a burning dness, or swelling. signs and symptoms may include a burning dness, swelling, and/or blurred vision. v result in nausea, vomiting and/or diarrhoea. ulitis signs and symptoms may include formation iles and spots on the skin of exposed areas.
Protection of first-aiders	appropriate pe	stering first aid, ensure that you are wearing the ersonal protective equipment according to the y and surroundings.
Notes to physician	: Call a doctor of Treat symptor	or poison control center for guidance. matically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	:	Do not use water in a jet.
Specific hazards during firefighting	:	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds.
Specific extinguishing methods	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Special protective equipment for firefighters	:	Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in

Spirax S6 GME 40

Version 2.1	Revision Date 23.07.2025	Print Date 24.07.2025
		Select fire fighter's clothing approved to s (e.g. Europe: EN469).
Hazchem Code	: NONE	
SECTION 6. ACCIDENTAL RELI	EASE MEASURES	
Personal precautions, protective equipment and emergency procedures	: Avoid contact with	n skin and eyes.
Environmental precautions	: Local authorities s cannot be contain	should be advised if significant spillages ed.
Methods and materials for containment and cleaning up	Prevent from spre or other containm Reclaim liquid dire Soak up residue v	It. Avoid accidents, clean up immediately. ading by making a barrier with sand, earth ent material. actly or in an absorbent. with an absorbent such as clay, sand or other and dispose of properly.
Additional advice	see Section 8 of t	selection of personal protective equipment his Safety Data Sheet. disposal of spilled material see Section 13 of Sheet.

SECTION 7. HANDLING AND STORAGE

General Precautions	:	Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
Advice on safe handling	:	Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.
Avoidance of contact	:	Strong oxidising agents.
Product Transfer	:	Proper grounding and bonding procedures should be used during all bulk transfer operations to avoid static accumulation.
Storage		
Other data	:	Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closable containers.

Version 2.1	Revision Date 23.07.2025	Print Date 24.07.2025	
	Store at ambien	t temperature.	
Packaging material	steel or high der	 Suitable material: For containers or container linings, use mild steel or high density polyethylene. Unsuitable material: PVC. 	
Container Advice		ntainers should not be exposed to high cause of possible risk of distortion.	

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m3	AU OEL
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m3	Australia. Workplace Exposure Standards for Airborne Contaminant s.
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m3	OSHA Z-1
Oil mist, mineral	Not Assigned	TWA (Inhalable particulate matter)	5 mg/m3	ACGIH

Components with workplace control parameters

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances

Spirax S6 GME 40

http://www.hse.gov.uk/ Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA) , Germany http://www.dguv.de/inhalt/index.jsp L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil Engineering measures : The level of protection and types of controls necessary wi vary depending upon potential exposure conditions. Sele controls based on a risk assessment of local circumstanc Appropriate measures include: Adequate ventilation to control airborne concentrations. Where material is heated, sprayed or mist formed, there i greater potential for airborne concentrations to be genera Eye washes and showers for emergency use. General Information Define procedures for safe handling and maintenance of controls. Educate and train workers in the hazards and control measures relevant to normal activities associated with thi product. Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protec equipment local extension. Drain down system prior to equipment break-in or maintenance. Retain drain downs in sealed storage pending disposal or subsequent recycle. Always observe good personal hygiene measures, such a washing hands after handling and footwear that cannot be cleane practice good housekeeping. Eye washes and showers for emergency use.	rsion 2.1	Revision Date 23.07.2025	Print Date 24.07.2025
http://www.dguv.de/inhalt/index.jsp L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil Engineering measures The level of protection and types of controls necessary wiver depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstance Appropriate measures include: Adequate ventilation to control airborne concentrations. Where material is heated, sprayed or mist formed, there i greater potential for airborne concentrations to be general Eye washes and showers for emergency use. General Information Define procedures for safe handling and maintenance of controls. Educate and train workers in the hazards and control measures relevant to normal activities associated with thi product. Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protect equipment local exhaust ventilation. Drain down system prior to equipment break-in or maintenance. Retain drain downs in sealed storage pending disposal or subsequent recycle. Always observe good personal hygiene measures, such a washing hands after handling the material and before eat drinking, and/or smoking. Routinely wash work clothing a protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned practice good housekeeping.	http://www.hse.gov.uk/		
Engineering measures The level of protection and types of controls necessary wivary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstance Appropriate measures include: Adequate ventilation to control airborne concentrations. Where material is heated, sprayed or mist formed, there i greater potential for airborne concentrations to be general Eye washes and showers for emergency use. General Information Define procedures for safe handling and maintenance of controls. Educate and train workers in the hazards and control measures relevant to normal activities associated with thi product. Ensure appropriate selection, testing and maintenance of equipment, local exhaust ventilation. Drain down system prior to equipment break-in or maintenance. Retain drain downs in sealed storage pending disposal or subsequent recycle. Always observe good personal hygiene measures, such a washing hands after handling the material and before eat drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned Practice good housekeeping.			Jnfallversicherung (IFA), Germany
vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstance Appropriate measures include: Adequate ventilation to control airborne concentrations. Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be general Eye washes and showers for emergency use. General Information Define procedures for safe handling and maintenance of controls. Educate and train workers in the hazards and control measures relevant to normal activities associated with thi product. Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protect equipment, local exhaust ventilation. Drain down system prior to equipment break-in or maintenance. Retain drain downs in sealed storage pending disposal or subsequent recycle. Always observe good personal hygiene measures, such a washing hands after handling the material and before eat drinking, and/or smoking. Routinely wash work clothing a protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleane Practice good housekeeping.	L'Institut National de Rech	erche et de Securité, (IN	RS), France http://www.inrs.fr/accueil
greater potential for airborne concentrations to be genera Eye washes and showers for emergency use. General Information Define procedures for safe handling and maintenance of controls. Educate and train workers in the hazards and control measures relevant to normal activities associated with thi product. Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protec equipment, local exhaust ventilation. Drain down system prior to equipment break-in or maintenance. Retain drain downs in sealed storage pending disposal or subsequent recycle. Always observe good personal hygiene measures, such a washing hands after handling the material and before eat drinking, and/or smoking. Routinely wash work clothing a protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleane Practice good housekeeping.	Engineering measures	vary depending controls based o Appropriate mea	upon potential exposure conditions. Select on a risk assessment of local circumstances. asures include:
General Information Define procedures for safe handling and maintenance of controls. Educate and train workers in the hazards and control measures relevant to normal activities associated with thi product. Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protect equipment, local exhaust ventilation. Drain down system prior to equipment break-in or maintenance. Retain drain downs in sealed storage pending disposal or subsequent recycle. Always observe good personal hygiene measures, such a washing hands after handling the material and before eat drinking, and/or smoking. Routinely wash work clothing a protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleane Practice good housekeeping.			
Define procedures for safe handling and maintenance of controls. Educate and train workers in the hazards and control measures relevant to normal activities associated with thi product. Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protec equipment, local exhaust ventilation. Drain down system prior to equipment break-in or maintenance. Retain drain downs in sealed storage pending disposal or subsequent recycle. Always observe good personal hygiene measures, such a washing hands after handling the material and before eat drinking, and/or smoking. Routinely wash work clothing a protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleane Practice good housekeeping.		Eye washes and	showers for emergency use.
product. Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protec equipment, local exhaust ventilation. Drain down system prior to equipment break-in or maintenance. Retain drain downs in sealed storage pending disposal or subsequent recycle. Always observe good personal hygiene measures, such a washing hands after handling the material and before eat drinking, and/or smoking. Routinely wash work clothing a protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleane Practice good housekeeping.		Define procedur controls.	es for safe handling and maintenance of
equipment, local exhaust ventilation. Drain down system prior to equipment break-in or maintenance. Retain drain downs in sealed storage pending disposal or subsequent recycle. Always observe good personal hygiene measures, such a washing hands after handling the material and before eat drinking, and/or smoking. Routinely wash work clothing a protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleane Practice good housekeeping.		product. Ensure appropri	ate selection, testing and maintenance of
Retain drain downs in sealed storage pending disposal or subsequent recycle. Always observe good personal hygiene measures, such a washing hands after handling the material and before eat drinking, and/or smoking. Routinely wash work clothing a protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleane Practice good housekeeping.		equipment, loca	l exhaust ventilation.
Always observe good personal hygiene measures, such a washing hands after handling the material and before eat drinking, and/or smoking. Routinely wash work clothing a protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleane Practice good housekeeping.		Retain drain dov	
		Always observe washing hands drinking, and/or protective equip contaminated cl Practice good h	good personal hygiene measures, such as after handling the material and before eating, smoking. Routinely wash work clothing and ment to remove contaminants. Discard othing and footwear that cannot be cleaned. busekeeping.
Personal protective equipment	Personal protective equi	ament	
Personal protective equipment Protective measures		JIIGHL	
Personal protective equipment (PPE) should meet recommended national standards. Check			manufacture time to the last of the line is the

1 91	: No respiratory protection is ordinarily required under normal conditions of use.	
	In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material.	

Hand protection

ersion 2.1	Revision Date 23.07.2025	Print Date 24.07.2025
Remarks	: Where hand cont gloves approved US: F739) made suitable chemical gloves Suitability usage, e.g. freque resistance of glov from glove suppli replaced. Person care. Gloves mus gloves, hands sho	act with the product may occur the use of to relevant standards (e.g. Europe: EN374, from the following materials may provide protection. PVC, neoprene or nitrile rubber and durability of a glove is dependent on ency and duration of contact, chemical ve material, dexterity. Always seek advice ers. Contaminated gloves should be al hygiene is a key element of effective hand st only be worn on clean hands. After using ould be washed and dried thoroughly. on-perfumed moisturizer is recommended.
	breakthrough time for > 480 minutes short-term/splash recognize that su may not be availa time maybe acce and replacement a good predictor dependent on the Glove thickness s	ontact we recommend gloves with e of more than 240 minutes with preference s where suitable gloves can be identified. For a protection we recommend the same but itable gloves offering this level of protection able and in this case a lower breakthrough ptable so long as appropriate maintenance regimes are followed. Glove thickness is not of glove resistance to a chemical as it is e exact composition of the glove material. should be typically greater than 0.35 mm e glove make and model.
Eye protection	: Wear full face shi	eld if splashes are likely to occur.
Skin and body protection	For prolonged or	not required under normal conditions of use repeated exposures use impervious clothing body subject to exposure.
Thermal hazards	: Not applicable	
Environmental exposure c	ontrols	
General advice	relevant environm contamination of Section 6. If nece being discharged treated in a munic before discharge Local guidelines of	measures to fulfill the requirements of nental protection legislation. Avoid the environment by following advice given in essary, prevent undissolved material from to waste water. Waste water should be cipal or industrial waste water treatment plan to surface water. on emission limits for volatile substances d for the discharge of exhaust air containing

Appearance : liquid

Colour : clear

Spirax S6 GME 40

/ersion 2.1	Revision Date 23.07.2025	Print Date 24.07.2025	
Odour	: Slight hydrocar	bon	
Odour Threshold	: Data not availa	ble	
рН	: Not applicable		
Pour point	: -42 °C / -44 °F Method: ASTM	D97	
Melting / freezing point	Data not availa	ble	
Boiling point	: Data not availa	ble	
Flash point	: 238 °C / 460 °F Method: ASTM		
Evaporation rate	: Data not availa	ble	
Flammability (solid, gas)	: Not applicable		
Flammability (liquids)	: Not classified a	as flammable but will burn.	
Upper explosion limit	: Typical 10 %(V))	
Lower explosion limit	: Typical 1 %(V)		
Vapour pressure	: < 0.5 Pa (20 °C estimated value		
Relative density	: 0.850 (15 °C /	59 °F)	
Density	: 850 kg/m3 (15 Method: ASTM		
Solubility(ies)			
Water solubility	: negligible		
Solubility in other solvents	: Data not availa	ble	
Partition coefficient: n- octanol/water	: log Pow: > 6 (based on infor	mation on similar products)	
Auto-ignition temperature	: > 320 °C / 608	°F	
Decomposition temperature	: Data not availa	ble	
Viscosity			
Viscosity, dynamic	: Data not availa	ble	
Viscosity, kinematic	: 14.2 - 16.2 mm Method: ASTM	2/s (100 °C / 212 °F) D445	

Version 2.1	Revision Date 23.07.2025	Print Date 24.07.2025
Particle characteristics Particle size	: Data not availa	ble
Explosive properties	: Classification C	Code: Not classified.
Oxidizing properties	: Data not availa	ble
Conductivity	: This material is	not expected to be a static accumulator.

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.
Chemical stability	: Stable.
Possibility of hazardous reactions	: Reacts with strong oxidising agents.
Conditions to avoid	: Extremes of temperature and direct sunlight.
Incompatible materials	: Strong oxidising agents.
Hazardous decomposition products	: No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Basis for assessment	 Information given is based on data on the components and the toxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).
Exposure routes	: Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.
Acute toxicity	
Product:	
Acute oral toxicity	 LD50 rat: > 5,000 mg/kg Remarks: Low toxicity Based on available data, the classification criteria are not met.
Acute inhalation toxicity	: Remarks: Based on available data, the classification criteria are not met.

Spirax S6 GME 40

Version 2.1	Revision Date 23.07.2025	Print Date 24.07.2025
Acute dermal toxicity	: LD50 Rabbit: > 5,000 Remarks: Low toxicity Based on available da	

Skin corrosion/irritation

Product:

Remarks: Slightly irritating to skin., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis., Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Product:

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Product:

Remarks: Based on available data, the classification criteria are not met. Not a skin sensitiser.

Chronic toxicity

Germ cell mutagenicity

Product:

: Remarks: Non mutagenic, Based on available data, the classification criteria are not met.

Carcinogenicity

Product:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

Material	GHS/CLP Carcinogenicity Classification
Highly refined mineral oil	No carcinogenicity classification.
Amine phosphate	No carcinogenicity classification.
2,6-di-tert-butyl phenol	No carcinogenicity classification.
Ethoxylated amine	No carcinogenicity classification.
Alkoxylated alkylamine	No carcinogenicity classification.

Reproductive toxicity

Product:

11 / 17

Spirax S6 GME 40

Version 2.1	Revision Date 23.07.2025	Print Date 24.07.2025
		d on available data, the classification criteria ot a developmental toxicant., Does not impair
STOT - single exposure		

Product:

Remarks: Based on available data, the classification criteria are not met.

STOT - repeated exposure

Product:

Target Organs: lymph node Remarks: May cause damage to organs or organ systems through prolonged or repeated exposure.

Aspiration toxicity

Product:

Not an aspiration hazard.

Further information

Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Slightly irritating to respiratory system.

SECTION 12. ECOLOGICAL INFORMATION

Basis for assessment	 Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).
Ecotoxicity	
Product:	
Toxicity to fish (Acute toxicity)	: Remarks: LL/EL/IL50 > 1 <= 10 mg/l

Spirax S6 GME 40

Version 2.1	Revision Da 23.07.2025				
	Toxic				
Toxicity to crustacean (Acute toxicity)		rks: LL/EL/IL50 > 1 <= 10 mg/I			
Toxicity to algae/aquatic plants (Acute toxicity)	: Remar Toxic	rks: LL/EL/IL50 > 1 <= 10 mg/I			
Toxicity to fish (Chronic toxicity)					
Toxicity to crustacean (Chronic toxicity)	: Remar	: Remarks: Data not available			
Toxicity to microorganisms (Acute toxicity)	: Remar	rks: Data not available			
<u>Components:</u> 2,6-di-tert-butyl phenol:					
M-Factor (Short-term (acute) aquatic hazard) Ethoxylated amine :	: 1				
M-Factor (Short-term (acute) aquatic hazard)	: 10				
M-Factor (Long-term (chronic) aquatic hazard) Alkoxylated alkylamine :	: 1				
M-Factor (Short-term (acute) aquatic hazard)	: 100				
M-Factor (Long-term (chronic) aquatic hazard)	: 1				
Persistence and degradability					
Product:					
Biodegradability	inherei	rks: Not readily biodegradable., Major constituents are ently biodegradable, but contains components that may t in the environment.			
Bioaccumulative potential					
Product:					
Bioaccumulation		rks: Contains components with the potential to cumulate.			
Partition coefficient: n- octanol/water	: log Por produc	ow: > 6Remarks: (based on information on similar cts)			
lobility in soil					
Product:					
Mobility		rks: Liquid under most environmental conditions., If it soli, it will adsorb to soil particles and will not be			

Version 2.1	Revision Date 23.07.2025	Print Date 24.07.2025
	mobile. Remarks: Float	s on water.
Other adverse effects		
No data available Product:		
Additional ecological information	 Does not have ozone depletion potential, photochemical ozone creation potential or global warming potential., Product is a mixture of non-volatile components, which will not be released to air in any significant quantities under normal conditions of use. Poorly soluble mixture., Causes physical fouling of aquatic organisms. 	

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods Waste from residues : Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water courses. Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Waste, spills or used product is dangerous waste. Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand. Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater

 contamination.
 MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides technical aspects at controlling pollutions from ships.
 Contaminated packaging

 Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.

 Local legislation Remarks

 Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

Spirax S6 GME 40

Version 2.1

Revision Date 23.07.2025

Print Date 24.07.2025

SECTION 14. TRANSPORT INFORMATION

National Regulations

ADG

Not regulated as a dangerous good

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Maritime transport in bulk according to IMO instruments

MARPOL Annex 1 rules apply for bulk shipments by sea.

Special precautions for user

Remarks

: Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Therapeutic Goods (Poisons : No poison schedule number allocated Standard) Instrument

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Product classified as per Work Health Safety Regulations – Implementation of the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) 2012 and SDS prepared as per national model code of practice for preparation of safety data sheet for Hazardous chemicals 2020 based on Globally Harmonized Classification version 7.

National Model Code of Practice for the Labelling of Workplace Hazardous Chemicals (2011).

Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG code). Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

Other international regulations

The components of this product are reported in the following inventories:

TSCA	:	All components listed.
AIIC	:	Notified with Restrictions.

Spirax S6 GME 40

Version 2.1

Revision Date 23.07.2025

Print Date 24.07.2025

SECTION 16. OTHER INFORMATION

Full text of H-Statements

H302	Harmful if swallowed.		
H304	May be fatal if swallowed and enters airways.		
H314	Causes severe skin burns and eye damage.		
H315	Causes skin irritation.		
H319	Causes serious eye irritation.		
H372	Causes damage to organs through prolonged or repeated exposure.		
H400	Very toxic to aquatic life.		
H410	Very toxic to aquatic life with long lasting effects.		
H411	Toxic to aquatic life with long lasting effects.		
Full text of other abbreviations			
Acute Tox.	Acute toxicity		
Aquatic Acute	Short-term (acute) aquatic hazard		
Aquatic Chronic	Long-term (chronic) aquatic hazard		

Aquatic Acute	Short-term (acute) aquatic hazard	
Aquatic Chronic	Long-term (chronic) aquatic hazard	
Asp. Tox.	Aspiration hazard	
Eye Irrit.	Eye irritation	
Skin Corr.	Skin corrosion	
Skin Irrit.	Skin irritation	
STOT RE	Specific target organ toxicity - repeated exposure	

Abbreviations and Acronyms

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC -New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG -Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations

Spirax S6 GME 40

Version 2.1	Revision Date 23.07.2025	Print Date 24.07.2025			
Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System					
Date of preparation or re	eview : 23.07.2025				
Further information					
Training advice	: Provide adequa operators.	ate information, instruction and training for			
Other information	: A vertical bar (from the previo) in the left margin indicates an amendment us version.			
Sources of key data use compile the Safety Data Sheet	sources of info Health Service	ta are from, but not limited to, one or more rmation (e.g. toxicological data from Shell s, material suppliers' data, CONCAWE, EU ase, EC 1272 regulation, etc).			

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

AU / EN