Shell Alexia 40

Version 1.9		Revision Date 04.07.2024	Print Date 30.09.2024
SECTION 1. PRODUCT AND COMI	P/	ANY IDENTIFICATION	
Product name	:	Shell Alexia 40	
Product code	:	001H1059	
Manufacturer or supplier's de Supplier		ails Viva Energy Australia Pty Ltd (Formerly: The Shell Company of Austr (ABN 46 004 610 459) 720 Bourke Street Docklands Victoria 3008 Australia	ralia)
Telephone Telefax		+61 (0)3 8823 4444 +61 (0)3 8823 4800	
Emergency telephone number	:	1800 651 818 (Australia). ; POISONS INFORMATION CENTRE:	13 11 26 (Australia).
Recommended use of the che	en	nical and restrictions on use	
Recommended use	:	Engine oil.	
Restrictions on use	:	This product must not be used in applic listed in Section 1 without first seeking supplier.	

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Based on available data this substance / mixture does not meet the classification criteria.

GHS label elements

Hazard pictograms	No Hazard Symbol required	
Signal word	No signal word	
Hazard statements	PHYSICAL HAZARDS: Not classified as a physical hazard under GHS criteria HEALTH HAZARDS: Not classified as a health hazard under GHS criteria. ENVIRONMENTAL HAZARDS: Not classified as an environmental hazard under GHS	

Precautionary statements

:

Shell Alexia 40

 Version 1.9
 Revision Date 04.07.2024
 Print Date 30.09.2024

 Prevention:
 No precautionary phrases.

 Response:
 No precautionary phrases.

Storage: No precautionary phrases.

Disposal: No precautionary phrases.

Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.Used oil may contain harmful impurities.Not classified as flammable but will burn.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture	:	Mixture
Chemical nature	:	Highly refined mineral oils and additives. The highly refined mineral oil contains <3% (w/w) DMSO- extract, according to IP346. Classification based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L).
	:	* contains one or more of the following CAS-numbers: 64742- 53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-65-0, 68037-01-4, 72623-86-0, 72623-87-1, 8042-47-5, 848301-69- 9, 68649-12-7, 151006-60-9, 163149-28-8, 64741-88-4, 64741-89-5.

Chemical name	CAS-No.	Classification	Concentration (% w/w)
Interchangeable low viscosity base oil (<20,5 cSt @40°C) *	Not Assigned	Asp. Tox.1; H304	0 - 90
Overbased sulphurised calcium phenate	220794-90-1	Aquatic Chronic4; H413	1 - 3
Alkylphenol	27193-86-8	Skin Corr.1C; H314 Eye Dam.1; H318 Repr.1B; H360 Aquatic Acute1; H400 Aquatic Chronic1; H410	0.1 - 0.29

Hazardous components

Shell Alexia 40

Version 1.9	Revisio	n Date 04.07.2024	Print Date	30.09.2024
Phenol, dodecyl-, sulfurized, calcium salts	68855-45-8	Aquatic Chronic4; H413	0 - < 3	

For explanation of abbreviations see section 16.

SECTION 4. FIRST-AID MEASURES

If inhaled	: No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
In case of skin contact	 Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.
In case of eye contact	 Flush eye with copious quantities of water. Remove contact lenses, if present and easy to do. Continue rinsing. If persistent irritation occurs, obtain medical attention.
If swallowed	: In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.
Most important symptoms and effects, both acute and delayed	: Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea.
Protection of first-aiders	: When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
Notes to physician	: Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	: Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.	
Unsuitable extinguishing media	: Do not use water in a jet.	
Specific hazards during firefighting	 Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates an gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds. 	b
Specific extinguishing methods	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.	

Shell Alexia 40

Version 1.9		Revision Date 04.07.2024	Print Date 30.09.2024
Special protective equipment for firefighters	:	Proper protective equipment including gloves are to be worn; chemical resista large contact with spilled product is exp Breathing Apparatus must be worn wh a confined space. Select fire fighter's c relevant Standards (e.g. Europe: EN4	ant suit is indicated if bected. Self-Contained en approaching a fire in lothing approved to
Hazchem Code	:	NONE	
SECTION 6. ACCIDENTAL RELEA	AS	E MEASURES	
Personal precautions, protective equipment and	:	Avoid contact with skin and eyes.	
emergency procedures Environmental precautions	:	Use appropriate containment to avoid contamination. Prevent from spreading ditches or rivers by using sand, earth, o barriers.	or entering drains,
		Local authorities should be advised if s cannot be contained.	ignificant spillages
Methods and materials for containment and cleaning up	:	Slippery when spilt. Avoid accidents, of Prevent from spreading by making a ba or other containment material. Reclaim liquid directly or in an absorbed Soak up residue with an absorbent suc suitable material and dispose of proper	arrier with sand, earth ent. ch as clay, sand or other
Additional advice	:	For guidance on selection of personal see Section 8 of this Safety Data Shee For guidance on disposal of spilled ma this Safety Data Sheet.	t.

SECTION 7. HANDLING AND STORAGE

General Precautions	Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposa this material.	l of
Advice on safe handling	Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.	÷

Shell Alexia 40

_

Version 1.9		Revision Date 04.07.2024	Print Date 30.09.2024
Avoidance of contact	:	Strong oxidising agents.	
Product Transfer	:	Proper grounding and bonding procedures should be used during all bulk transfer operations to avoid static accumulation.	
Storage			
Other data	:	 Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closable containers. 	
		Store at ambient temperature.	
Packaging material	: Suitable material: For containers or container linings, use mile steel or high density polyethylene. Unsuitable material: PVC.		tainer linings, use mild
Container Advice	:	: Polyethylene containers should not be exposed to high temperatures because of possible risk of distortion.	

SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m3	AU OEL
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m3	Australia. Workplace Exposure Standards for Airborne Contaminant s.
Oil mist, mineral	Not Assigned	TWA (Mist)	5 mg/m3	OSHA Z-1
Oil mist, mineral	Not Assigned	TWA (Inhalable particulate matter)	5 mg/m3	ACGIH

Components with workplace control parameters

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate. Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or

Shell Alexia 40

rsion 1.9	Revision Date 04.07.2024	Print Date 30.09.2024
	national methods may be available. tional Safety and Health (NIOSH), USA: I	Manual of Analytical Methods
	alth Administration (OSHA), USA: Sampl	ing and Analytical Methods
Health and Safety Executive http://www.hse.gov.uk/	e (HSE), UK: Methods for the Determinati	
http://www.dguv.de/inhalt/inc		
L'Institut National de Recher	che et de Securité, (INRS), France http:/	/www.inrs.fr/accueil
Engineering measures	: The level of protection and types of vary depending upon potential exp controls based on a risk assessme Appropriate measures include: Adequate ventilation to control airb	oosure conditions. Select ent of local circumstances.
	Where material is heated, sprayed greater potential for airborne conce	
	General Information: Define procedures for safe handlir controls.	g and maintenance of
	Educate and train workers in the h measures relevant to normal activi product.	
	Ensure appropriate selection, testi equipment used to control exposu- equipment, local exhaust ventilation	re, e.g. personal protective
	Drain down system prior to equipn maintenance.	nent break-in or
	Retain drain downs in sealed stora subsequent recycle.	
	Always observe good personal hyg washing hands after handling the drinking, and/or smoking. Routine protective equipment to remove co contaminated clothing and footwea	material and before eating, ly wash work clothing and ontaminants. Discard
	Practice good housekeeping.	
Personal protective equipr	ment	
Protective measures		

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Respiratory protection	 No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the
	health, select respiratory protection equipment suitable for the

rsion 1.9	Revision Date 04.07.2024 Print Date 30.09.2024
	specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for the combination of organic gases and vapours and particles [Type A/Type P boiling point >65°C (149°F)].
Hand protection	
Remarks	: Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.
	For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model.
Eye protection	: If material is handled such that it could be splashed into eyes, protective eyewear is recommended.
Skin and body protection	 Skin protection is not ordinarily required beyond standard work clothes. It is good practice to wear chemical resistant gloves.
Thermal hazards	: Not applicable
Environmental exposure c	ontrols
General advice	: Take appropriate measures to fulfill the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in Section 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water should be

being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant

before discharge to surface water.

Shell Alexia 40

Version 1.9	Revision Date 04.07.2024 Print Date 30.02	
	Local guidelines on emission limits for volatile substance must be observed for the discharge of exhaust air contain vapour.	
SECTION 9. PHYSICAL AND CHE	ICAL PROPERTIES	
Appearance	: Liquid at room temperature.	
Colour	: amber	
Odour	: Data not available	
Odour Threshold	: Data not available	
рН	: Not applicable	
pour point	: <= -20 °C / <= -4 °F Method: ISO 3016	
Melting / freezing point	Data not available	
Initial boiling point and boiling range	: > 280 °C / 536 °Festimated value(s)	
Flash point	: >= 210 °C / 410 °F Method: ASTM D93 (PMCC)	
	276 °C / 529 °F Method: ASTM D92 (COC)	
Evaporation rate	: Data not available	
Flammability (solid, gas)	: Not applicable	
Flammability (liquids)	: Not classified as flammable but will burn.	
Upper explosion limit	: Typical 10 %(V)	
Lower explosion limit	: Typical 1 %(V)	
Vapour pressure	: < 0.5 Pa (20 °C / 68 °F) estimated value(s)	
Relative vapour density	: >5	
Relative density	: 0.915 (15.0 °C / 59.0 °F)	
Density	: 915 kg/m3 (15.0 °C / 59.0 °F) Method: DIN EN ISO 12185	
Solubility(ies)		
Water solubility	: negligible	
Solubility in other solvents	: Data not available	

Shell Alexia 40

Version 1.9	Revision Date 04.07.2024	Print Date 30.09.2024
Partition coefficient: n- octanol/water	: log Pow: > 6 (based on information on similar pro	oducts)
Auto-ignition temperature	: > 320 °C / 608 °F	
Decomposition temperature	: Data not available	
Viscosity		
Viscosity, dynamic	: Data not available	
Viscosity, kinematic	: 18.5 mm2/s (100 °C / 212 °F) Method: ASTM D445	
Particle characteristics Particle size	: Data not available	
Explosive properties	: Classification Code: Not classified	
Oxidizing properties	: Data not available	
Conductivity	: This material is not expected to be a	a static accumulator.

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.
Chemical stability	: Stable.
Possibility of hazardous reactions	: Reacts with strong oxidising agents.
Conditions to avoid	: Extremes of temperature and direct sunlight.
Incompatible materials	: Strong oxidising agents.
Hazardous decomposition products	: No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Basis for assessment	:	Information given is based on data on the components and the toxicology of similar products.Unless indicated otherwise, the data presented is representative of the product as a whole rather than for individual component(s)
		whole, rather than for individual component(s).

Version 1.9	Revision Date 04.07.2024	Print Date 30.09.2024	
Exposure routes		Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.	
Acute toxicity			
Product:			
Acute oral toxicity	: LD50 rat: > 5,000 mg/kg Remarks: Low toxicity Based on available data, the clas	sification criteria are not met.	
Acute inhalation toxicity	: Remarks: Based on available dat are not met.	a, the classification criteria	
Acute dermal toxicity	: LD50 Rabbit: > 5,000 mg/kg Remarks: Low toxicity Based on available data, the clas	sification criteria are not met.	

Skin corrosion/irritation

Product:

Remarks: Slightly irritating to skin., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis., Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Product:

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Product:

Remarks: Not a skin sensitiser. Based on available data, the classification criteria are not met.

Chronic toxicity

Germ cell mutagenicity

Product:

: Remarks: Non mutagenic, Based on available data, the classification criteria are not met.

Carcinogenicity

Product:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

Version 1.9

Revision Date 04.07.2024

Print Date 30.09.2024

Remarks: Product contains mineral oils of types shown to be non-carcinogenic in animal skinpainting studies., Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC).

Material	GHS/CLP Carcinogenicity Classification
Highly refined mineral oil	No carcinogenicity classification.

Reproductive toxicity

Product:

Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are not met.

STOT - single exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

÷

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

Aspiration toxicity

Product:

Not an aspiration hazard.

Further information

Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Continuous contact with used engine oils has caused skin cancer in animal tests.

Remarks: Slightly irritating to respiratory system.

SECTION 12. ECOLOGICAL INFORMATION

Shell Alexia 40

Version 1.9	Revision Date 04.07.2024 Print Date 30.09.2024
Basis for assessment	 Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).
Ecotoxicity	
Product:	
Toxicity to fish (Acute toxicity)	: Remarks: LL/EL/IL50 > 100 mg/I Practically non toxic: Based on available data, the classification criteria are not met.
Toxicity to crustacean (Acute toxicity)	: Remarks: LL/EL/IL50 > 100 mg/I Practically non toxic: Based on available data, the classification criteria are not met
Toxicity to algae/aquatic plants (Acute toxicity)	: Remarks: LL/EL/IL50 > 100 mg/I Practically non toxic: Based on available data, the classification criteria are not met
Toxicity to fish (Chronic toxicity)	: Remarks: Based on available data, the classification criteria are not met.
Toxicity to crustacean (Chronic toxicity)	: Remarks: Based on available data, the classification criteria are not met.
Toxicity to microorganisms (Acute toxicity)	: Remarks: Data not available
<u>Components:</u> Alkylphenol :	
M-Factor (Short-term (acute)	: 10
aquatic hazard) M-Factor (Long-term (chronic) aquatic hazard)	: 10
Persistence and degradability	
Product:	
Biodegradability	: Remarks: Not readily biodegradable., Major constituents are inherently biodegradable, but contains components that may persist in the environment.
Bioaccumulative potential	
Product:	
Bioaccumulation	: Remarks: Contains components with the potential to bioaccumulate.

Shell Alexia 40

Version 1.9	Revision Date 04.07.2024	Print Date 30.09.2024
Partition coefficient: n- : octanol/water	: log Pow: > 6Remarks: (based on information on similar products)	
Mobility in soil		
Product:		
Mobility :	Remarks: Liquid under most environme enters soil, it will adsorb to soil particles mobile. Remarks: Floats on water.	-
Other adverse effects		
no data available <u>Product:</u>		
Additional ecological : information	Does not have ozone depletion potentia ozone creation potential or global warm is a mixture of non-volatile components released to air in any significant quantit conditions of use. Poorly soluble mixture., Causes physica organisms. Mineral oil does not cause chronic toxic organisms at concentrations less than a	hing potential., Product s, which will not be ies under normal al fouling of aquatic sity to aquatic

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues	 Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Do not dispose into the environment, in drains or in water courses. Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination. Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.
	MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides technical aspects at controlling pollutions from ships.
Contaminated packaging	: Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand.

Shell Alexia 40

Version 1.9	Revision Date 04.07.2024	Print Date 30.09.2024
	Disposal should be in accordance with applicable regional, national, and local laws and regulations.	
Local legislation Remarks	: Disposal should be in accordance national, and local laws and regul	

SECTION 14. TRANSPORT INFORMATION

National Regulations

ADG Not regulated as a dangerous good

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Maritime transport in bulk according to IMO instruments

MARPOL Annex 1 rules apply for bulk shipments by sea.

Special precautions for user

Remarks

: Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Therapeutic Goods (Poisons : No poison schedule number allocated Standard) Instrument

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Product classified as per Work Health Safety Regulations – Implementation of the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) 2012 and SDS prepared as per national model code of practice for preparation of safety data sheet for Hazardous chemicals 2020 based on Globally Harmonized Classification version 7.

National Model Code of Practice for the Labelling of Workplace Hazardous Chemicals (2011).

Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG code). Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

Version 1.9	Revision Date 04.07.2024	Print Date 30.09.2024		
Other international regulations				
The components of this product are reported in the following inventories:				
TSCA	All components listed.			
AIIC	Listed introduction			

SECTION 16. OTHER INFORMATION

Full text of H-Statements

H304	May be fatal if swallowed and enters airways.		
H314	Causes severe skin burns and eye damage.		
H318	Causes serious eye damage.		
H360	May damage fertility or the unborn child.		
H400	Very toxic to aquatic life.		
H410	Very toxic to aquatic life with long lasting effects.		
H413	May cause long lasting harmful effects to aquatic life.		
Full text of other abbreviations			
Aquatic Acute	Short-term (acute) aquatic hazard		
Aquatic Chronic	Long-term (chronic) aquatic hazard		
Asp. Tox.	Aspiration hazard		
Eye Dam.	Serious eye damage		

Reproductive toxicity

Skin corrosion

Abbreviations and Acronyms

Repr.

Skin Corr.

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response: ELx - Loading rate associated with x% response: EmS - Emergency Schedule: ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC -New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG -

Version 1.9	Revision Date 04.07.2024	Print Date 30.09.2024		
Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System				
Date of preparation or review	: 04.07.2024			
Further information				
Training advice	: Provide adequate information, i operators.	nstruction and training for		
Other information	: A vertical bar () in the left marg from the previous version.	in indicates an amendment		
Sources of key data used to compile the Safety Data Sheet	: The quoted data are from, but n sources of information (e.g. toxi Health Services, material suppli IUCLID date base, EC 1272 reg	icological data from Shell iers' data, CONCAWE, EU		

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

AU / EN