

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## Shell Spirax S6 AXME 75W-90

|         |                 |              |                                |
|---------|-----------------|--------------|--------------------------------|
| Version | Revision Date.: | SDS Number:  | Date of last issue: 28.02.2024 |
| 7.1     | 03.09.2026      | 800001007514 | Print Date. 13.10.2026         |

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

|              |                               |
|--------------|-------------------------------|
| Trade name   | : Shell Spirax S6 AXME 75W-90 |
| Product code | : 001D8290                    |

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

|                               |                                                                                                                                           |
|-------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|
| Use of the Sub-stance/Mixture | : Transmission oil.                                                                                                                       |
| Uses advised against          | :<br>This product must not be used in applications other than those listed in Section 1 without first seeking the advice of the supplier. |

#### 1.3 Details of the supplier of the safety data sheet

|                               |                                                                                               |
|-------------------------------|-----------------------------------------------------------------------------------------------|
| Manufacturer/Supplier         | : <b>Shell France SAS</b><br>Landscape<br>22 Rte de la Demi-Lune<br>F-92800 Puteaux           |
| Telephone                     | : (+33) 0969366018                                                                            |
| Telefax                       | : (+33) 0969366030                                                                            |
| Contact for Safety Data Sheet | : If you have any enquiries about the content of this SDS please email lubricantSDS@shell.com |

#### 1.4 Emergency telephone number

: Shell (en France 24/24h): 0800 33 86 86 (+33 4 82 90 75 50)  
ORFILA (INRS): + 33 (0)1 45 42 59 59

---

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Based on available data this substance / mixture does not meet the classification criteria.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

|                   |                             |
|-------------------|-----------------------------|
| Hazard pictograms | : No Hazard Symbol required |
| Signal word       | : No signal word            |

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## Shell Spirax S6 AXME 75W-90

|         |                 |              |                                |
|---------|-----------------|--------------|--------------------------------|
| Version | Revision Date.: | SDS Number:  | Date of last issue: 28.02.2024 |
| 7.1     | 03.09.2026      | 800001007514 | Print Date. 13.10.2026         |

Hazard statements : PHYSICAL HAZARDS:  
Not classified as a physical hazard according to CLP criteria.  
HEALTH HAZARDS:  
Not classified as a health hazard under CLP criteria.  
ENVIRONMENTAL HAZARDS:  
Not classified as environmental hazard according to CLP criteria.

Precautionary statements : **Prevention:**  
No precautionary phrases.  
**Response:**  
No precautionary phrases.  
**Storage:**  
No precautionary phrases.  
**Disposal:**  
No precautionary phrases.

### 2.3 Other hazards

This mixture does not contain any REACH registered substances that are assessed to be a PBT or a vPvB.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.  
Used oil may contain harmful impurities.  
Not classified as flammable but will burn.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : Synthetic base oil and additives.  
Highly refined mineral oil.  
The highly refined mineral oil contains <3% (w/w) DMSO-extract, according to IP346.  
The highly refined mineral oil is only present as additive diluent.

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## Shell Spirax S6 AXME 75W-90

Version  
7.1

Revision Date.:  
03.09.2026

SDS Number:  
800001007514

Date of last issue: 28.02.2024  
Print Date. 13.10.2026

Classification based on DMSO extract content < 3%.

\* contains one or more of the following CAS-numbers (REACH registration numbers): 64742-53-6 (01-2119480375-34), 64742-54-7 (01-2119484627-25), 64742-55-8 (01-2119487077-29), 64742-56-9 (01-2119480132-48), 64742-65-0 (01-2119471299-27), 68037-01-4 (01-2119486452-34), 72623-86-0 (01-2119474878-16), 72623-87-1 (01-2119474889-13), 8042-47-5 (01-2119487078-27), 848301-69-9 (01-0000020163-82), 68649-12-7 (01-2119527646-33), 151006-60-9 (01-2119523580-47), 163149-28-8 (01-2119543695-30), 64741-88-4 (01-2119488706-23), 64741-89-5 (01-2119487067-30), 157707-86-3 (01-2119486452-34).

### Components

| Chemical name                                              | CAS-No.<br>EC-No.<br>Index-No.<br>Registration number | Classification                                                                                                                                                                                                                                         | Concentration<br>(% w/w) |
|------------------------------------------------------------|-------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|
| Interchangeable low viscosity base oil (<20,5 cSt @40°C) * | Not Assigned                                          | Asp. Tox. 1; H304                                                                                                                                                                                                                                      | 0 - 10                   |
| 1-Propene, 2-methyl-, sulfurized                           | 68511-50-2<br>270-943-2                               | Aquatic Chronic 4;<br>H413                                                                                                                                                                                                                             | 1 - 6                    |
| Alkenyl amine                                              | 1213789-63-9<br>627-034-4<br>01-2119473797-19         | Acute Tox. 4; H302<br>Asp. Tox. 1; H304<br>Skin Corr. 1B; H314<br>STOT SE 3; H335<br>STOT RE 2; H373<br>Aquatic Acute 1;<br>H400<br>Aquatic Chronic 1;<br>H410<br><br>M-Factor (Acute aquatic toxicity): 10<br>M-Factor (Chronic aquatic toxicity): 10 | 0,1 - 0,49               |
| Alkyl amine                                                | 111-86-4<br>203-916-0<br>01-2119474880-31             | Flam. Liq. 3; H226<br>Acute Tox. 3; H301<br>Acute Tox. 3; H311<br>Skin Corr. 1; H314<br>Eye Dam. 1; H318<br>Acute Tox. 4; H332<br>STOT SE 3; H335                                                                                                      | 0,1 - 0,24               |

## SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

### Shell Spirax S6 AXME 75W-90

Version 7.1      Revision Date.: 03.09.2026      SDS Number: 800001007514      Date of last issue: 28.02.2024  
Print Date. 13.10.2026

|                     |                                             |                                                                            |            |
|---------------------|---------------------------------------------|----------------------------------------------------------------------------|------------|
|                     |                                             | Aquatic Acute 1;<br>H400<br>Aquatic Chronic 2;<br>H411                     |            |
|                     |                                             | M-Factor (Acute<br>aquatic toxicity): 1                                    |            |
| Alkoxylated alcohol | 68439-50-9<br>500-213-3<br>01-2119487984-16 | Eye Dam. 1; H318<br>Aquatic Acute 1;<br>H400<br>Aquatic Chronic 3;<br>H412 | 0,1 - 0,24 |

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- Protection of first-aiders : When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
- If inhaled : No treatment necessary under normal conditions of use.  
If symptoms persist, obtain medical advice.
- In case of skin contact : Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available.  
If persistent irritation occurs, obtain medical attention.
- In case of eye contact : Flush eye with copious quantities of water.  
Remove contact lenses, if present and easy to do. Continue rinsing.  
If persistent irritation occurs, obtain medical attention.
- If swallowed : In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.

### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas.  
Ingestion may result in nausea, vomiting and/or diarrhea.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Notes to doctor/physician:

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## Shell Spirax S6 AXME 75W-90

|         |                 |              |                                |
|---------|-----------------|--------------|--------------------------------|
| Version | Revision Date.: | SDS Number:  | Date of last issue: 28.02.2024 |
| 7.1     | 03.09.2026      | 800001007514 | Print Date. 13.10.2026         |

---

Treat symptomatically.

---

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

Suitable extinguishing media : Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media : Do not use water in a jet.

#### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Hazardous combustion products may include:  
A complex mixture of airborne solid and liquid particulates and gases (smoke).  
Carbon monoxide may be evolved if incomplete combustion occurs.  
Unidentified organic and inorganic compounds.

#### 5.3 Advice for firefighters

Special protective equipment for firefighters : Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

---

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : 6.1.1 For non emergency personnel:  
Avoid contact with skin and eyes.  
6.1.2 For emergency responders:  
Avoid contact with skin and eyes.

#### 6.2 Environmental precautions

Environmental precautions : Use appropriate containment to prevent uncontrolled release. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Slippery when spilt. Avoid accidents, clean up immediately.

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## Shell Spirax S6 AXME 75W-90

|         |                 |              |                                |
|---------|-----------------|--------------|--------------------------------|
| Version | Revision Date.: | SDS Number:  | Date of last issue: 28.02.2024 |
| 7.1     | 03.09.2026      | 800001007514 | Print Date. 13.10.2026         |

Prevent from spreading by making a barrier with sand, earth or other containment material.  
Reclaim liquid directly or in an absorbent.  
Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly.

### 6.4 Reference to other sections

For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.,  
For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

- |                         |   |                                                                                                                                                                                                                                                                                                     |
|-------------------------|---|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Technical measures      | : | Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols.<br>Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.         |
| Advice on safe handling | : | Avoid prolonged or repeated contact with skin.<br>Avoid inhaling vapour and/or mists.<br>When handling product in drums, safety footwear should be worn and proper handling equipment should be used.<br>Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. |
| Product Transfer        | : | Proper grounding and bonding procedures should be used during all bulk transfer operations to avoid static accumulation.<br>Proper grounding and bonding procedures should be used during all bulk transfer operations to avoid static accumulation.                                                |

### 7.2 Conditions for safe storage, including any incompatibilities

- |                                          |   |                                                                                                                                                                                                                                                                                                           |
|------------------------------------------|---|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Further information on storage stability | : | Keep container tightly closed and in a cool, well-ventilated place.<br>Use properly labeled and closable containers.<br>Store at ambient temperature.<br>Store at ambient temperature.<br>Refer to section 15 for any additional specific legislation covering the packaging and storage of this product. |
| Packaging material                       | : | Suitable material: For containers or container linings, use mild steel or high density polyethylene.<br>Unsuitable material: PVC.                                                                                                                                                                         |
| Container Advice                         | : | Polyethylene containers should not be exposed to high temperatures because of possible risk of distortion.                                                                                                                                                                                                |

### 7.3 Specific end use(s)

- |                 |   |                 |
|-----------------|---|-----------------|
| Specific use(s) | : | Not applicable. |
|-----------------|---|-----------------|

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## Shell Spirax S6 AXME 75W-90

Version 7.1      Revision Date.: 03.09.2026      SDS Number: 800001007514      Date of last issue: 28.02.2024  
Print Date. 13.10.2026

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

##### Occupational Exposure Limits

| Components        | CAS-No.       | Value type (Form of exposure) | Control parameters | Basis                            |
|-------------------|---------------|-------------------------------|--------------------|----------------------------------|
| Oil mist, mineral | Not As-signed | TWA (inhalable fraction)      | 5 mg/m3            | US. ACGIH Threshold Limit Values |

##### Biological occupational exposure limits

#### 8.2 Exposure controls

##### Engineering measures

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Adequate ventilation to control airborne concentrations.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

##### General Information

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

##### Personal protective equipment

The provided information is made in consideration of the PPE regulation (EU 2016/425) and the CEN European Committee for Standardisation (CEN) standards.

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye protection : If material is handled such that it could be splashed into eyes, protective eyewear is recommended.  
Approved to EU Standard EN166.

Hand protection

## SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

### Shell Spirax S6 AXME 75W-90

|         |                 |              |                                |
|---------|-----------------|--------------|--------------------------------|
| Version | Revision Date.: | SDS Number:  | Date of last issue: 28.02.2024 |
| 7.1     | 03.09.2026      | 800001007514 | Print Date. 13.10.2026         |

---

|                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Remarks                  | : Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model. |
| Skin and body protection | : Skin protection is not ordinarily required beyond standard work clothes.<br>It is good practice to wear chemical resistant gloves.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Respiratory protection   | : No respiratory protection is ordinarily required under normal conditions of use.<br>In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for combined particulate/organic gases and vapours [Type A/Type P boiling point > 65°C (149°F)] meeting EN14387 and EN143.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Thermal hazards          | : Not applicable                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

|                |                               |
|----------------|-------------------------------|
| Physical state | : Liquid at room temperature. |
|----------------|-------------------------------|

## SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

### Shell Spirax S6 AXME 75W-90

|         |                 |              |                                |
|---------|-----------------|--------------|--------------------------------|
| Version | Revision Date.: | SDS Number:  | Date of last issue: 28.02.2024 |
| 7.1     | 03.09.2026      | 800001007514 | Print Date. 13.10.2026         |

---

|                                                                      |   |                                                                                                                  |
|----------------------------------------------------------------------|---|------------------------------------------------------------------------------------------------------------------|
| Colour                                                               | : | amber                                                                                                            |
| Odour                                                                | : | Slight hydrocarbon                                                                                               |
| Odour Threshold                                                      | : | Data not available                                                                                               |
| Pour point                                                           | : | -42 °C<br>Method: ISO 3016                                                                                       |
| Melting / freezing point                                             | : | Data not available                                                                                               |
| Initial boiling point and boiling range                              | : | > 280 °C estimated value(s)                                                                                      |
| Flammability                                                         | : |                                                                                                                  |
| Flammability (solid, gas)                                            | : | Not applicable                                                                                                   |
| Flammability (liquids)                                               | : | Not classified as flammable but will burn.                                                                       |
| Lower explosion limit and upper explosion limit / flammability limit | : |                                                                                                                  |
| Upper explosion limit / Upper flammability limit                     | : | Typical 10 %(V)                                                                                                  |
| Lower explosion limit / Lower flammability limit                     | : | Typical 1 %(V)                                                                                                   |
| Flash point                                                          | : | 210 °C<br>Method: ISO 2592                                                                                       |
| Auto-ignition temperature                                            | : | > 320 °C                                                                                                         |
| Decomposition temperature                                            | : |                                                                                                                  |
| Decomposition temperature                                            | : | Data not available                                                                                               |
| pH                                                                   | : | Not applicable                                                                                                   |
| Viscosity                                                            | : |                                                                                                                  |
| Viscosity, dynamic                                                   | : | Data not available                                                                                               |
| Viscosity, kinematic                                                 | : | 115 mm <sup>2</sup> /s (40,0 °C)<br>Method: ISO 3104<br><br>15,2 mm <sup>2</sup> /s (100 °C)<br>Method: ISO 3104 |
| Solubility(ies)                                                      | : |                                                                                                                  |
| Water solubility                                                     | : | negligible                                                                                                       |
| Solubility in other solvents                                         | : | Data not available                                                                                               |

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## Shell Spirax S6 AXME 75W-90

|         |                 |              |                                |
|---------|-----------------|--------------|--------------------------------|
| Version | Revision Date.: | SDS Number:  | Date of last issue: 28.02.2024 |
| 7.1     | 03.09.2026      | 800001007514 | Print Date. 13.10.2026         |

---

|                                           |   |                                                            |
|-------------------------------------------|---|------------------------------------------------------------|
| Partition coefficient: n-octanol/water    | : | log Pow: > 6<br>(based on information on similar products) |
| Vapour pressure                           | : | < 0,5 Pa (20 °C)<br>estimated value(s)                     |
| Relative density                          | : | 0,878 (15 °C)                                              |
| Density                                   | : | 878 kg/m <sup>3</sup> (15,0 °C)<br>Method: ISO 12185       |
| Relative vapour density                   | : | > 1<br>estimated value(s)                                  |
| Particle characteristics<br>Particle size | : | Data not available                                         |

### 9.2 Other information

|                        |   |                                                           |
|------------------------|---|-----------------------------------------------------------|
| Explosive properties   | : | Classification Code: Not classified                       |
| Oxidizing properties   | : | Data not available                                        |
| Flammability (liquids) | : | Not classified as flammable but will burn.                |
| Evaporation rate       | : | Data not available                                        |
| Conductivity           | : | This material is not expected to be a static accumulator. |

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

### 10.2 Chemical stability

Stable.

No hazardous reaction is expected when handled and stored according to provisions

### 10.3 Possibility of hazardous reactions

|                     |   |                                      |
|---------------------|---|--------------------------------------|
| Hazardous reactions | : | Reacts with strong oxidising agents. |
|---------------------|---|--------------------------------------|

### 10.4 Conditions to avoid

|                     |   |                                              |
|---------------------|---|----------------------------------------------|
| Conditions to avoid | : | Extremes of temperature and direct sunlight. |
|---------------------|---|----------------------------------------------|

### 10.5 Incompatible materials

|                    |   |                          |
|--------------------|---|--------------------------|
| Materials to avoid | : | Strong oxidising agents. |
|--------------------|---|--------------------------|

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## Shell Spirax S6 AXME 75W-90

|         |                 |              |                                |
|---------|-----------------|--------------|--------------------------------|
| Version | Revision Date.: | SDS Number:  | Date of last issue: 28.02.2024 |
| 7.1     | 03.09.2026      | 800001007514 | Print Date. 13.10.2026         |

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

#### Acute toxicity

##### Product:

|                           |                                                                                                                              |
|---------------------------|------------------------------------------------------------------------------------------------------------------------------|
| Acute oral toxicity       | : LD50 (rat): > 5.000 mg/kg<br>Remarks: Low toxicity<br>Based on available data, the classification criteria are not met.    |
| Acute inhalation toxicity | : Remarks: Based on available data, the classification criteria are not met.                                                 |
| Acute dermal toxicity     | : LD50 (Rabbit): > 5.000 mg/kg<br>Remarks: Low toxicity<br>Based on available data, the classification criteria are not met. |

#### Skin corrosion/irritation

##### Product:

|         |                                                                                                                                                                                                                                                        |
|---------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Remarks | : Slightly irritating to skin.<br>Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.<br>Based on available data, the classification criteria are not met. |
|---------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

#### Serious eye damage/eye irritation

##### Product:

|         |                                                                                                        |
|---------|--------------------------------------------------------------------------------------------------------|
| Remarks | : Slightly irritating to the eye.<br>Based on available data, the classification criteria are not met. |
|---------|--------------------------------------------------------------------------------------------------------|

#### Respiratory or skin sensitisation

##### Product:

|         |                                                                                                                                     |
|---------|-------------------------------------------------------------------------------------------------------------------------------------|
| Remarks | : For respiratory and skin sensitisation:<br>Not a sensitiser.<br>Based on available data, the classification criteria are not met. |
|---------|-------------------------------------------------------------------------------------------------------------------------------------|

## SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

### Shell Spirax S6 AXME 75W-90

|         |                 |              |                                |
|---------|-----------------|--------------|--------------------------------|
| Version | Revision Date.: | SDS Number:  | Date of last issue: 28.02.2024 |
| 7.1     | 03.09.2026      | 800001007514 | Print Date. 13.10.2026         |

---

#### Germ cell mutagenicity

##### **Product:**

Genotoxicity in vivo : Remarks: Non mutagenic  
Based on available data, the classification criteria are not met.

Germ cell mutagenicity- Assessment : This product does not meet the criteria for classification in categories 1A/1B.

#### Carcinogenicity

##### **Product:**

Remarks : Not a carcinogen.  
Based on available data, the classification criteria are not met.

Carcinogenicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

| Material                   | GHS/CLP Carcinogenicity Classification |
|----------------------------|----------------------------------------|
| Highly refined mineral oil | No carcinogenicity classification.     |

#### Reproductive toxicity

##### **Product:**

Effects on fertility :  
Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are not met.

Reproductive toxicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

#### STOT - single exposure

##### **Product:**

Remarks : Based on available data, the classification criteria are not met.

#### STOT - repeated exposure

##### **Product:**

Remarks : Based on available data, the classification criteria are not met.

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## Shell Spirax S6 AXME 75W-90

|         |                 |              |                                |
|---------|-----------------|--------------|--------------------------------|
| Version | Revision Date.: | SDS Number:  | Date of last issue: 28.02.2024 |
| 7.1     | 03.09.2026      | 800001007514 | Print Date. 13.10.2026         |

### Repeated dose toxicity

### Aspiration toxicity

#### Product:

Not an aspiration hazard., Based on available data, the classification criteria are not met.

## 11.2 Information on other hazards

### Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### Further information

#### Product:

Remarks : Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal.  
ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks : Slightly irritating to respiratory system.

Remarks : Classifications by other authorities under varying regulatory frameworks may exist.

Remarks : Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Product:

Toxicity to fish : Remarks: LL/EL/IL50 >10 <= 100 mg/l

## SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

### Shell Spirax S6 AXME 75W-90

|         |                 |              |                                |
|---------|-----------------|--------------|--------------------------------|
| Version | Revision Date.: | SDS Number:  | Date of last issue: 28.02.2024 |
| 7.1     | 03.09.2026      | 800001007514 | Print Date. 13.10.2026         |

Harmful

Toxicity to daphnia and other aquatic invertebrates : Remarks: LL/EL/IL50 >10 <= 100 mg/l  
Harmful

Toxicity to algae/aquatic plants : Remarks: LL/EL/IL50 >10 <= 100 mg/l  
Harmful

Toxicity to fish (Chronic toxicity) : Remarks: Data not available

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : Remarks: Data not available

Toxicity to microorganisms :  
Remarks: Data not available

#### **Components:**

##### **Alkenyl amine:**

M-Factor (Acute aquatic toxicity) : 10

M-Factor (Chronic aquatic toxicity) : 10

##### **Alkyl amine:**

M-Factor (Acute aquatic toxicity) : 1

## 12.2 Persistence and degradability

#### **Product:**

Biodegradability : Remarks: Not readily biodegradable.  
Major constituents are inherently biodegradable, but contains components that may persist in the environment.  
Persistent per IMO criteria.  
International Oil Pollution Compensation (IOPC) Fund definition:  
"A non-persistent oil is oil, which, at the time of shipment, consists of hydrocarbon fractions, (a) at least 50% of which, by volume, distills at a temperature of 340°C (645°F) and (b) at least 95% of which, by volume, distills at a temperature of 370°C (700°F) when tested by the ASTM Method D-86/78 or any subsequent revision thereof."

## 12.3 Bioaccumulative potential

#### **Product:**

Bioaccumulation : Remarks: Contains components with the potential to bioaccumulate.

## SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

### Shell Spirax S6 AXME 75W-90

|         |                 |              |                                |
|---------|-----------------|--------------|--------------------------------|
| Version | Revision Date.: | SDS Number:  | Date of last issue: 28.02.2024 |
| 7.1     | 03.09.2026      | 800001007514 | Print Date. 13.10.2026         |

---

#### 12.4 Mobility in soil

**Product:**

Mobility : Remarks: Liquid under most environmental conditions., If it enters soil, it will adsorb to soil particles and will not be mobile.

Remarks: Floats on water.

#### 12.5 Results of PBT and vPvB assessment

**Product:**

Assessment : This mixture does not contain any REACH registered substances that are assessed to be a PBT or a vPvB..

#### 12.6 Endocrine disrupting properties

**Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

#### 12.7 Other adverse effects

**Product:**

Additional ecological information : Does not have ozone depletion potential, photochemical ozone creation potential or global warming potential.  
Product is a mixture of non-volatile components, which will not be released to air in any significant quantities under normal conditions of use.

Poorly soluble mixture.  
Causes physical fouling of aquatic organisms.

Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

---

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

Product : Recover or recycle if possible.  
It is the responsibility of the waste generator to determine the

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## Shell Spirax S6 AXME 75W-90

|         |                 |              |                                |
|---------|-----------------|--------------|--------------------------------|
| Version | Revision Date.: | SDS Number:  | Date of last issue: 28.02.2024 |
| 7.1     | 03.09.2026      | 800001007514 | Print Date. 13.10.2026         |

toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.  
Do not dispose into the environment, in drains or in water courses.

Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment.  
Waste, spills or used product is dangerous waste.  
Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.  
Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination.

MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides technical aspects at controlling pollutions from ships.

Contaminated packaging : Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.

Local legislation

Waste catalogue :

EU Waste Disposal Code (EWC):

Waste Code :

13 02 06\*

Remarks

: Disposal should be in accordance with applicable regional, national, and local laws and regulations.

Classification of waste is always the responsibility of the end user.

## SECTION 14: Transport information

### 14.1 UN number or ID number

ADN

: Not regulated as a dangerous good

## SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

### Shell Spirax S6 AXME 75W-90

|         |                 |              |                                |
|---------|-----------------|--------------|--------------------------------|
| Version | Revision Date.: | SDS Number:  | Date of last issue: 28.02.2024 |
| 7.1     | 03.09.2026      | 800001007514 | Print Date. 13.10.2026         |

**ADR** : Not regulated as a dangerous good

**RID** : Not regulated as a dangerous good

**IMDG** : Not regulated as a dangerous good

**IATA** : Not regulated as a dangerous good

#### 14.2 UN proper shipping name

**ADN** : Not regulated as a dangerous good

**ADR** : Not regulated as a dangerous good

**RID** : Not regulated as a dangerous good

**IMDG** : Not regulated as a dangerous good

**IATA** : Not regulated as a dangerous good

#### 14.3 Transport hazard class(es)

**ADN** : Not regulated as a dangerous good

**ADR** : Not regulated as a dangerous good

**RID** : Not regulated as a dangerous good

**IMDG** : Not regulated as a dangerous good

**IATA** : Not regulated as a dangerous good

#### 14.4 Packing group

**ADN** : Not regulated as a dangerous good

**CDNI Inland Water Waste Agreement** : NST 3411 Mineral Lubricating Oils  
NST 3411 Mineral Lubricating Oils

**ADR** : Not regulated as a dangerous good

**RID** : Not regulated as a dangerous good

**IMDG** : Not regulated as a dangerous good

**IATA** : Not regulated as a dangerous good

#### 14.5 Environmental hazards

**ADN** : Not regulated as a dangerous good

**ADR** : Not regulated as a dangerous good

**RID** : Not regulated as a dangerous good

**IMDG** : Not regulated as a dangerous good

#### 14.6 Special precautions for user

**Remarks** : Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

#### 14.7 Maritime transport in bulk according to IMO instruments

MARPOL Annex 1 rules apply for bulk shipments by sea.

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## Shell Spirax S6 AXME 75W-90

|         |                 |              |                                |
|---------|-----------------|--------------|--------------------------------|
| Version | Revision Date.: | SDS Number:  | Date of last issue: 28.02.2024 |
| 7.1     | 03.09.2026      | 800001007514 | Print Date. 13.10.2026         |

---

**Additional Information** : ADN - Classified ID9006 when carried in tank vessels.

---

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Product is not subject to Authorisation under REACH.

Occupational Illnesses (R-461-3, France) : 36, 36

Volatile organic compounds : Volatile organic compounds (VOC) content: 0 %

#### Other regulations:

The following regulatory information is not intended to be comprehensive and does not exempt the end user of the product to refer to all official documents to determine its obligations.

Labour code : Exposure forbidden to certain works/products to:

- Young people at least 15 years old and under 18 years old: art. D4153-17

- Pregnant or breast-feeding women : art. D4152-10, D4152-11

Social security code - Article L.461-6, Appendix A, no. 601-15.

Labour code - Intensified medical supervision: Articles R.4624-18 and R.4624-19, decree 2012-135 of 30.01.2012.

#### The components of this product are reported in the following inventories:

EU REACH : Notified with Restrictions.

US TSCA : All components listed.

#### 15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

---

### SECTION 16: Other information

#### Full text of H-Statements

|      |                                                 |
|------|-------------------------------------------------|
| H226 | : Flammable liquid and vapour.                  |
| H301 | : Toxic if swallowed.                           |
| H302 | : Harmful if swallowed.                         |
| H304 | : May be fatal if swallowed and enters airways. |
| H311 | : Toxic in contact with skin.                   |
| H314 | : Causes severe skin burns and eye damage.      |
| H318 | : Causes serious eye damage.                    |
| H332 | : Harmful if inhaled.                           |

## SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

### Shell Spirax S6 AXME 75W-90

|         |                 |              |                                |
|---------|-----------------|--------------|--------------------------------|
| Version | Revision Date.: | SDS Number:  | Date of last issue: 28.02.2024 |
| 7.1     | 03.09.2026      | 800001007514 | Print Date. 13.10.2026         |

---

|      |   |                                                                    |
|------|---|--------------------------------------------------------------------|
| H335 | : | May cause respiratory irritation.                                  |
| H373 | : | May cause damage to organs through prolonged or repeated exposure. |
| H400 | : | Very toxic to aquatic life.                                        |
| H410 | : | Very toxic to aquatic life with long lasting effects.              |
| H411 | : | Toxic to aquatic life with long lasting effects.                   |
| H412 | : | Harmful to aquatic life with long lasting effects.                 |
| H413 | : | May cause long lasting harmful effects to aquatic life.            |

#### Full text of other abbreviations

|                 |   |                                                    |
|-----------------|---|----------------------------------------------------|
| Acute Tox.      | : | Acute toxicity                                     |
| Aquatic Acute   | : | Short-term (acute) aquatic hazard                  |
| Aquatic Chronic | : | Long-term (chronic) aquatic hazard                 |
| Asp. Tox.       | : | Aspiration hazard                                  |
| Eye Dam.        | : | Serious eye damage                                 |
| Flam. Liq.      | : | Flammable liquids                                  |
| Skin Corr.      | : | Skin corrosion                                     |
| STOT RE         | : | Specific target organ toxicity - repeated exposure |
| STOT SE         | : | Specific target organ toxicity - single exposure   |

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; BGW - Biological Limit Values; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); LSPN - List of Hazardous Notified Substances (Chile); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of

# SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

## Shell Spirax S6 AXME 75W-90

|         |                 |              |                                |
|---------|-----------------|--------------|--------------------------------|
| Version | Revision Date.: | SDS Number:  | Date of last issue: 28.02.2024 |
| 7.1     | 03.09.2026      | 800001007514 | Print Date. 13.10.2026         |

---

Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

|                                                           |   |                                                                                                                                                                                                                         |
|-----------------------------------------------------------|---|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Training advice                                           | : | Provide adequate information, instruction and training for operators.                                                                                                                                                   |
| Other information                                         | : | A vertical bar ( ) in the left margin indicates an amendment from the previous version.                                                                                                                                 |
| Sources of key data used to compile the Safety Data Sheet | : | The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID data base, EC 1272 regulation, etc). |

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

FR / EN