

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Rimula R6 LME Plus 5W-30

Version	Revision Date.:	SDS Number:	Date of last issue: 06.02.2026
3.0	21.05.2026	800010033846	Print Date. 09.06.2026

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name	: Shell Rimula R6 LME Plus 5W-30
Product code	: 001H2588

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture	: Engine oil.
Uses advised against	: This product must not be used in applications other than those listed in Section 1 without first seeking the advice of the supplier.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier	: Univar Solutions AS NO-1411 Postboks 476 Kolbotn
Telephone	: 22 88 16 00
Telefax	: -
Contact for Safety Data Sheet	: sds.emea@univarsolutions.com

1.4 Emergency telephone number

: Giftinformasjonen: 22 59 13 00 - SGS +32 (0)3 575 55 55 (24h)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.
--	--

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	: No symbol
-------------------	-------------

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Rimula R6 LME Plus 5W-30

Version	Revision Date.:	SDS Number:	Date of last issue: 06.02.2026
3.0	21.05.2026	800010033846	Print Date. 09.06.2026

Signal word	:	No signal word
Hazard statements	:	PHYSICAL HAZARDS: Not classified as a physical hazard according to CLP criteria. HEALTH HAZARDS: Not classified as a health hazard under CLP criteria. ENVIRONMENTAL HAZARDS: H412 Harmful to aquatic life with long lasting effects.
Precautionary statements	:	Prevention: P273 Avoid release to the environment. Response: No precautionary phrases. Storage: No precautionary phrases. Disposal: P501 Dispose of contents/ container to an approved waste disposal plant.

Sensitising components	:	Contains reaction products of boric acid with 2-propylheptan-1-ol (1:3) Contains Dialkyl alkaryl aminomethyl dicarboxylate. May produce an allergic reaction.
------------------------	---	---

2.3 Other hazards

This mixture does not contain any REACH registered substances that are assessed to be a PBT or a vPvB.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.
Used oil may contain harmful impurities.
Not classified as flammable but will burn.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature	:	Synthetic base oil and additives.
-----------------	---	-----------------------------------

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Rimula R6 LME Plus 5W-30

Version
3.0

Revision Date.:
21.05.2026

SDS Number:
800010033846

Date of last issue: 06.02.2026
Print Date. 09.06.2026

Highly refined mineral oil.
The highly refined mineral oil contains <3% (w/w) DMSO-extract, according to IP346.
The highly refined mineral oil is only present as additive diluent.
Classification based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L).

* contains one or more of the following CAS-numbers (REACH registration numbers): 64742-53-6 (01-2119480375-34), 64742-54-7 (01-2119484627-25), 64742-55-8 (01-2119487077-29), 64742-56-9 (01-2119480132-48), 64742-65-0 (01-2119471299-27), 68037-01-4 (01-2119486452-34), 72623-86-0 (01-2119474878-16), 72623-87-1 (01-2119474889-13), 8042-47-5 (01-2119487078-27), 848301-69-9 (01-0000020163-82), 68649-12-7 (01-2119527646-33), 151006-60-9 (01-2119523580-47), 163149-28-8 (01-2119543695-30), 64741-88-4 (01-2119488706-23), 64741-89-5 (01-2119487067-30), 157707-86-3 (01-2119486452-34).

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Interchangeable low viscosity base oil (<20,5 cSt @40°C) *	Not Assigned	Asp. Tox. 1; H304	0 - 90
Reaction products of boric acid with 2-propylheptan-1-ol (1:3)	Trade secret 806-750-2 01-2120079516-48	Skin Sens. 1B; H317	0,1 - < 1
Alkoxylated alcohol	68551-12-2 500-221-7	Eye Dam. 1; H318 Aquatic Acute 1; H400 Aquatic Chronic 3; H412	0,1 - 0,25
Dialkyl alkaryl aminomethyl dicarboxylate	Trade secret	Skin Sens. 1B; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 1	0,25 - 0,99
O,O,O-triphenyl phosphorothioate	597-82-0 209-909-9	Aquatic Chronic, PBT 1; H410, EUH440	0,025 - 0,099

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Rimula R6 LME Plus 5W-30

Version 3.0 Revision Date.: 21.05.2026 SDS Number: 800010033846 Date of last issue: 06.02.2026
Print Date. 09.06.2026

	01-2119979545-21	M-Factor (Chronic aquatic toxicity): 10	
--	------------------	---	--

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Protection of first-aiders : When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
- If inhaled : No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
- In case of skin contact : Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.
- In case of eye contact : Flush eye with copious quantities of water. Remove contact lenses, if present and easy to do. Continue rinsing. If persistent irritation occurs, obtain medical attention.
- If swallowed : In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhea.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Notes to doctor/physician:
Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Foam, water spray or fog. Dry chemical powder, carbon diox-

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Rimula R6 LME Plus 5W-30

Version	Revision Date.:	SDS Number:	Date of last issue: 06.02.2026
3.0	21.05.2026	800010033846	Print Date. 09.06.2026

ide, sand or earth may be used for small fires only.

Unsuitable extinguishing media : Do not use water in a jet.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Hazardous combustion products may include:
A complex mixture of airborne solid and liquid particulates and gases (smoke).
Carbon monoxide may be evolved if incomplete combustion occurs.
Unidentified organic and inorganic compounds.

5.3 Advice for firefighters

Special protective equipment for firefighters : Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : 6.1.1 For non emergency personnel:
Avoid contact with skin and eyes.
6.1.2 For emergency responders:
Avoid contact with skin and eyes.

6.2 Environmental precautions

Environmental precautions : Use appropriate containment to prevent uncontrolled release. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly.

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Rimula R6 LME Plus 5W-30

Version 3.0 Revision Date.: 21.05.2026 SDS Number: 800010033846 Date of last issue: 06.02.2026
Print Date. 09.06.2026

6.4 Reference to other sections

For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.,
For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Technical measures : Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols.
Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
- Advice on safe handling : Avoid prolonged or repeated contact with skin.
Avoid inhaling vapour and/or mists.
When handling product in drums, safety footwear should be worn and proper handling equipment should be used.
Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.
- Product Transfer : Proper grounding and bonding procedures should be used during all bulk transfer operations to avoid static accumulation.

7.2 Conditions for safe storage, including any incompatibilities

- Further information on storage stability : Keep container tightly closed and in a cool, well-ventilated place.
Use properly labeled and closable containers.
Store at ambient temperature.
Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.
- Packaging material : Suitable material: For containers or container linings, use mild steel or high density polyethylene.
Unsuitable material: PVC.
- Container Advice : Polyethylene containers should not be exposed to high temperatures because of possible risk of distortion.

7.3 Specific end use(s)

- Specific use(s) : Not applicable

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Oil mist, mineral	Not As-	TWA (Vapour)	50 mg/m3	FOR-2011-

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Rimula R6 LME Plus 5W-30

Version 3.0 Revision Date.: 21.05.2026 SDS Number: 800010033846 Date of last issue: 06.02.2026
Print Date. 09.06.2026

	signed			12-06-1358
Oil mist, mineral		TWA (Mist and particles)	1 mg/m3	FOR-2011-12-06-1358
Oil mist, mineral		TWA (inhalable fraction)	5 mg/m3	US. ACGIH Threshold Limit Values
Oil mist, mineral		TL (Mist)	1 mg/m3	FOR-2011-12-06-1358

Biological occupational exposure limits

8.2 Exposure controls

Engineering measures

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Adequate ventilation to control airborne concentrations.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

General Information

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Personal protective equipment

The provided information is made in consideration of the PPE regulation (EU 2016/425) and the CEN European Committee for Standardisation (CEN) standards.

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye protection : If material is handled such that it could be splashed into eyes, protective eyewear is recommended.
Approved to EU Standard EN166.

Hand protection

Remarks : Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374,

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Rimula R6 LME Plus 5W-30

Version	Revision Date.:	SDS Number:	Date of last issue: 06.02.2026
3.0	21.05.2026	800010033846	Print Date. 09.06.2026

US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model.

Skin and body protection : Skin protection is not ordinarily required beyond standard work clothes.

Respiratory protection : It is good practice to wear chemical resistant gloves.
: No respiratory protection is ordinarily required under normal conditions of use.
In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material.
If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation.
Check with respiratory protective equipment suppliers.
Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.
Select a filter suitable for combined particulate/organic gases and vapours [Type A/Type P boiling point > 65°C (149°F)] meeting EN14387 and EN143.

Thermal hazards : Not applicable

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	: Liquid at room temperature.
Colour	: amber
Odour	: Slight hydrocarbon
Odour Threshold	: Data not available

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Rimula R6 LME Plus 5W-30

Version	Revision Date.:	SDS Number:	Date of last issue: 06.02.2026
3.0	21.05.2026	800010033846	Print Date. 09.06.2026

Pour point	:	-48 °C Method: ASTM D97
Melting / freezing point	:	Data not available
Initial boiling point and boiling range	:	> 280 °C Estimated value(s)
Flammability	:	
Flammability (solid, gas)	:	Not applicable
Flammability (liquids)	:	Not classified as flammable but will burn.
Lower explosion limit and upper explosion limit / flammability limit	:	
Upper explosion limit / Upper flammability limit	:	Typical 10 %(V)
Lower explosion limit / Lower flammability limit	:	Typical 1 %(V)
Flash point	:	239 °C Method: ASTM D92 (COC)
Auto-ignition temperature	:	> 320 °C
Decomposition temperature	:	
Decomposition temperature	:	Data not available
pH	:	Not applicable
Viscosity	:	
Viscosity, dynamic	:	Data not available
Viscosity, kinematic	:	12,1 mm ² /s (100 °C) Method: ASTM D445 75 mm ² /s (40,0 °C) Method: ASTM D445
Solubility(ies)	:	
Water solubility	:	negligible
Solubility in other solvents	:	Data not available
Partition coefficient: n-octanol/water	:	log Pow: > 6 (based on information on similar products)

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Rimula R6 LME Plus 5W-30

Version	Revision Date.:	SDS Number:	Date of last issue: 06.02.2026
3.0	21.05.2026	800010033846	Print Date. 09.06.2026

Vapour pressure	:	< 0,5 Pa (20 °C) estimated value(s)
Relative density	:	0,845 (15,0 °C)
Density	:	845 kg/m ³ (15,0 °C) Method: ASTM D4052
Relative vapour density	:	> 1 estimated value(s)
Particle characteristics Particle size	:	Data not available

9.2 Other information

Explosive properties	:	Classification Code: Not classified
Oxidizing properties	:	Data not available
Flammability (liquids)	:	Not classified as flammable but will burn.
Evaporation rate	:	Data not available
Conductivity	:	This material is not expected to be a static accumulator.

SECTION 10: Stability and reactivity

10.1 Reactivity

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

10.2 Chemical stability

Stable.

No hazardous reaction is expected when handled and stored according to provisions

10.3 Possibility of hazardous reactions

Hazardous reactions	:	Reacts with strong oxidising agents.
---------------------	---	--------------------------------------

10.4 Conditions to avoid

Conditions to avoid	:	Extremes of temperature and direct sunlight.
---------------------	---	--

10.5 Incompatible materials

Materials to avoid	:	Strong oxidising agents.
--------------------	---	--------------------------

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Rimula R6 LME Plus 5W-30

Version	Revision Date.:	SDS Number:	Date of last issue: 06.02.2026
3.0	21.05.2026	800010033846	Print Date. 09.06.2026

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure : Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

Acute toxicity

Product:

Acute oral toxicity	: LD50 (rat): > 5.000 mg/kg Remarks: Based on available data, the classification criteria are not met. Low toxicity
Acute inhalation toxicity	: Remarks: Based on available data, the classification criteria are not met.
Acute dermal toxicity	: LD50 (Rabbit): > 5.000 mg/kg Remarks: Based on available data, the classification criteria are not met. Low toxicity

Skin corrosion/irritation

Product:

Remarks	: Based on available data, the classification criteria are not met. Slightly irritating to skin. Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.
---------	--

Serious eye damage/eye irritation

Product:

Remarks	: Based on available data, the classification criteria are not met. Slightly irritating to the eye.
---------	--

Respiratory or skin sensitisation

Product:

Remarks	: For respiratory and skin sensitisation: Based on available data, the classification criteria are not met. Not a sensitiser.
---------	---

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Rimula R6 LME Plus 5W-30

Version 3.0	Revision Date.: 21.05.2026	SDS Number: 800010033846	Date of last issue: 06.02.2026 Print Date. 09.06.2026
----------------	-------------------------------	-----------------------------	--

Germ cell mutagenicity

Product:

Genotoxicity in vivo : Remarks: Based on available data, the classification criteria are not met.
Non mutagenic

Germ cell mutagenicity- Assessment : This product does not meet the criteria for classification in categories 1A/1B.

Carcinogenicity

Product:

Remarks : Based on available data, the classification criteria are not met.
Not a carcinogen.

Carcinogenicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

Material	GHS/CLP Carcinogenicity Classification
Highly refined mineral oil	No carcinogenicity classification.

Reproductive toxicity

Product:

Effects on fertility : Remarks: Based on available data, the classification criteria are not met., Not a developmental toxicant., Does not impair fertility.

Reproductive toxicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

STOT - single exposure

Product:

Remarks : Based on available data, the classification criteria are not met.

STOT - repeated exposure

Product:

Remarks : Based on available data, the classification criteria are not met.

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Rimula R6 LME Plus 5W-30

Version	Revision Date.:	SDS Number:	Date of last issue: 06.02.2026
3.0	21.05.2026	800010033846	Print Date. 09.06.2026

Repeated dose toxicity

Aspiration toxicity

Product:

Based on available data, the classification criteria are not met., Not an aspiration hazard.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Further information

Product:

Remarks : Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal.
ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks : Continuous contact with used engine oils has caused skin cancer in animal tests.

Remarks : Slightly irritating to respiratory system.

Remarks : Classifications by other authorities under varying regulatory frameworks may exist.

Remarks : Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Rimula R6 LME Plus 5W-30

Version	Revision Date.:	SDS Number:	Date of last issue: 06.02.2026
3.0	21.05.2026	800010033846	Print Date. 09.06.2026

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish	:	Remarks: LL/EL/IL50 >10 <= 100 mg/l Harmful
Toxicity to daphnia and other aquatic invertebrates	:	Remarks: LL/EL/IL50 >10 <= 100 mg/l Harmful
Toxicity to algae/aquatic plants	:	Remarks: LL/EL/IL50 >10 <= 100 mg/l Harmful
Toxicity to fish (Chronic toxicity)	:	Remarks: Data not available
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	Remarks: Data not available
Toxicity to microorganisms	:	Remarks: Data not available

Components:

Dialkyl alkaryl aminomethyl dicarboxylate:

M-Factor (Acute aquatic toxicity) : 1

12.2 Persistence and degradability

Product:

Biodegradability	:	Remarks: Not readily biodegradable. Major constituents are inherently biodegradable, but contains components that may persist in the environment.
------------------	---	--

12.3 Bioaccumulative potential

Product:

Bioaccumulation	:	Remarks: Contains components with the potential to bioaccumulate.
-----------------	---	---

12.4 Mobility in soil

Product:

Mobility	:	Remarks: Liquid under most environmental conditions., If it enters soil, it will adsorb to soil particles and will not be mobile.
----------	---	---

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Rimula R6 LME Plus 5W-30

Version	Revision Date.:	SDS Number:	Date of last issue: 06.02.2026
3.0	21.05.2026	800010033846	Print Date. 09.06.2026

Remarks: Floats on water.

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This mixture does not contain any REACH registered substances that are assessed to be a PBT or a vPvB..

Components:

O,O,O-triphenyl phosphorothioate:

Assessment : Persistent, Bioaccumulative and Toxic (PBT)..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : Does not have ozone depletion potential, photochemical ozone creation potential or global warming potential.
Product is a mixture of non-volatile components, which will not be released to air in any significant quantities under normal conditions of use.

Poorly soluble mixture.
Causes physical fouling of aquatic organisms.

Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Recover or recycle if possible.
It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal meth-

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Rimula R6 LME Plus 5W-30

Version 3.0	Revision Date.: 21.05.2026	SDS Number: 800010033846	Date of last issue: 06.02.2026 Print Date. 09.06.2026
----------------	-------------------------------	-----------------------------	--

ods in compliance with applicable regulations.
Do not dispose into the environment, in drains or in water courses.

Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment.
Waste, spills or used product is dangerous waste.
Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.
Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination.

MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides technical aspects at controlling pollutions from ships.

Contaminated packaging : Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.

Local legislation

Waste catalogue :

EU Waste Disposal Code (EWC):

Waste Code :

13 02 06*

Remarks : Disposal should be in accordance with applicable regional, national, and local laws and regulations.

Classification of waste is always the responsibility of the end user.

SECTION 14: Transport information

14.1 UN number or ID number

ADR : Not regulated as a dangerous good

RID : Not regulated as a dangerous good

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Rimula R6 LME Plus 5W-30

Version	Revision Date.:	SDS Number:	Date of last issue: 06.02.2026
3.0	21.05.2026	800010033846	Print Date. 09.06.2026

IMDG	:	Not regulated as a dangerous good
IATA	:	Not regulated as a dangerous good

14.2 UN proper shipping name

ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA	:	Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA	:	Not regulated as a dangerous good

14.4 Packing group

ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA	:	Not regulated as a dangerous good

14.5 Environmental hazards

ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good

14.6 Special precautions for user

Remarks	:	Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.
---------	---	--

14.7 Maritime transport in bulk according to IMO instruments

MARPOL Annex 1 rules apply for bulk shipments by sea.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Product Registration number	:	669176
REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,	:	Not applicable

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Rimula R6 LME Plus 5W-30

Version	Revision Date.:	SDS Number:	Date of last issue: 06.02.2026
3.0	21.05.2026	800010033846	Print Date. 09.06.2026

mixtures and articles (Annex XVII)
REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Not applicable
REACH - List of substances subject to authorisation (Annex XIV) : Product is not subject to Authorisation under REACH.
Volatile organic compounds : Volatile organic compounds (VOC) content: 0 %

Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

The components of this product are reported in the following inventories:

EU REACH : All components listed or polymer exempt.

US TSCA : All components listed.

15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

EUH440 : Accumulates in the environment and living organisms including in humans.
H304 : May be fatal if swallowed and enters airways.
H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H400 : Very toxic to aquatic life.
H410 : Very toxic to aquatic life with long lasting effects.
H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard
Asp. Tox. : Aspiration hazard
Eye Dam. : Serious eye damage
PBT : Persistent, bioaccumulative and toxic
Skin Sens. : Skin sensitisation
FOR-2011-12-06-1358 : Norway. Occupational Exposure limits
FOR-2011-12-06-1358 / TL : Threshold limits
FOR-2011-12-06-1358 / TWA : Long term exposure limit
TWA

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Rimula R6 LME Plus 5W-30

Version	Revision Date.:	SDS Number:	Date of last issue: 06.02.2026
3.0	21.05.2026	800010033846	Print Date. 09.06.2026

Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Training advice	:	Provide adequate information, instruction and training for operators.
Other information	:	A vertical bar () in the left margin indicates an amendment from the previous version.
Sources of key data used to compile the Safety Data Sheet	:	The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).

Classification of the mixture:

Aquatic Chronic 3 H412

Classification procedure:

Expert judgement and weight of evidence determination.

Identified Uses according to the Use Descriptor System

Uses - Worker

Title	:	General use of lubricants and greases in vehicles or machin-
-------	---	--

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Rimula R6 LME Plus 5W-30

Version	Revision Date.:	SDS Number:	Date of last issue: 06.02.2026
3.0	21.05.2026	800010033846	Print Date. 09.06.2026

ery.
- Industrial

Uses - Worker

Title : General use of lubricants and greases in vehicles or machinery.
- Professional

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

NO / EN

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Rimula R6 LME Plus 5W-30

Version 3.0 Revision Date.: 21.05.2026 SDS Number: 800010033846 Date of last issue: 06.02.2026
Print Date. 09.06.2026

Exposure Scenario - Worker

300000011059	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	General use of lubricants and greases in vehicles or machinery.- Industrial
Use Descriptor	Sector of Use: SU3 Process Categories: PROC1, PROC2, PROC8b, PROC9 Environmental Release Categories: ERC4, ERC7, ATIEL-ATC SPERC 4.Bi.v1
Scope of process	Covers general use of lubricants and greases in vehicles or machinery in closed systems. Includes filling and draining of containers and operation of enclosed machinery (including engines) and associated maintenance and storage activities.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information	No exposure assessment presented for human health.	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Contributing Scenarios	Risk Management Measures	
Section 2.2	Control of Environmental Exposure	
Amounts Used		
EU tonnage (tonnes per year):		2.631,1
Fraction of EU tonnage used in region:		0,1
Fraction of Regional tonnage used locally:		0,1
Frequency and Duration of Use		
Emission Days (days/year):		300
Environmental factors not influenced by risk management		
Local freshwater dilution factor:		10
Local marine water dilution factor:		100
Other Operational Conditions affecting Environmental Exposure		
Negligible wastewater emissions as process operates without water contact.		
Release fraction to air from process (after typical onsite RMMS) :		5,00E-05
Release fraction to wastewater from process (after typical onsite RMMS and before (municipal) sewage treatment plant):		2,00E-11
Release fraction to soil from process (after typical onsite RMMS):		0
Technical conditions and measures at process level (source) to prevent release		
Common practices vary across sites thus conservative process release estimates used.		
Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil		
Treat air emission to provide a typical removal efficiency of (%)		70

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Rimula R6 LME Plus 5W-30

Version 3.0	Revision Date.: 21.05.2026	SDS Number: 800010033846	Date of last issue: 06.02.2026 Print Date. 09.06.2026
----------------	-------------------------------	-----------------------------	--

Prevent discharge of undissolved substance to or recover from onsite wastewater.	
User sites are assumed to be provided with oil/water separators or equivalent and for waste water to be discharged via public sewer system.	
Organisational measures to prevent/limit release from site	
Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
Conditions and Measures related to municipal sewage treatment plant	
Estimated substance removal from wastewater via domestic sewage treatment (%)	78,7
Assumed domestic sewage treatment plant flow (m3/d)	2,00E+03
Maximum allowable site quantity (MSafe) based on OCs and RMMs as above (kg/day) :	578.447,6
Conditions and Measures related to external treatment of waste for disposal	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
Conditions and measures related to external recovery of waste	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
No exposure assessment presented for human health.	

Section 3.2 -Environment	
Used ECETOC TRA model.	

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
No exposure assessment presented for human health.	

Section 4.2 -Environment	
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.	
Further details on scaling and control technologies are provided in SpERC factsheet (http://cefic.org).	
If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.	
For further information see www.ATIEL.org/REACH_GES .	

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Rimula R6 LME Plus 5W-30

Version
3.0

Revision Date.:
21.05.2026

SDS Number:
800010033846

Date of last issue: 06.02.2026
Print Date. 09.06.2026

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Rimula R6 LME Plus 5W-30

Version 3.0 Revision Date.: 21.05.2026 SDS Number: 800010033846 Date of last issue: 06.02.2026
Print Date. 09.06.2026

Exposure Scenario - Worker

300000011060	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	General use of lubricants and greases in vehicles or machinery.- Professional
Use Descriptor	Sector of Use: SU22 Process Categories: PROC1, PROC2, PROC8a, PROC8b, PROC20 Environmental Release Categories: ERC9a, ERC9b,
Scope of process	Covers general use of lubricants and greases in vehicles or machinery in closed systems. Includes filling and draining of containers and operation of enclosed machinery (including engines) and associated maintenance and storage activities.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information	No exposure assessment presented for human health.	
Section 2.1	Control of Worker Exposure	
Product Characteristics		
Contributing Scenarios	Risk Management Measures	
Section 2.2	Control of Environmental Exposure	
Amounts Used		
EU tonnage (tonnes per year):		5.387,2
Fraction of EU tonnage used in region:		0,1
Fraction of Regional tonnage used locally:		0,1
Frequency and Duration of Use		
Emission Days (days/year):		365
Environmental factors not influenced by risk management		
Local freshwater dilution factor:		10
Local marine water dilution factor:		100
Other Operational Conditions affecting Environmental Exposure		
Negligible wastewater emissions as process operates without water contact.		
Release fraction to air from process (after typical onsite RMMS) :		
Release fraction to wastewater from process (after typical onsite RMMS and before (municipal) sewage treatment plant):		5,00E-04
Release fraction to soil from process (after typical onsite RMMS):		1E-03
Technical conditions and measures at process level (source) to prevent release		
Common practices vary across sites thus conservative process re-lease estimates used.		
Technical onsite conditions and measures to reduce or limit discharges, air emis-sions and releases to soil		
Prevent discharge of undissolved substance to or recover from onsite		

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Rimula R6 LME Plus 5W-30

Version	Revision Date.:	SDS Number:	Date of last issue: 06.02.2026
3.0	21.05.2026	800010033846	Print Date. 09.06.2026

wastewater.	
Organisational measures to prevent/limit release from site	
Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.	
Conditions and Measures related to municipal sewage treatment plant	
Estimated substance removal from wastewater via domestic sewage treatment (%)	78,7
Assumed domestic sewage treatment plant flow (m3/d)	2,00E+03
Maximum allowable site quantity (MSafe) based on OCs and RMMs as above (kg/day) :	448,4
Conditions and Measures related to external treatment of waste for disposal	
External treatment and disposal of waste should comply with applicable local and/or regional regulations.	
Conditions and measures related to external recovery of waste	
External recovery and recycling of waste should comply with applicable local and/or regional regulations.	

SECTION 3	EXPOSURE ESTIMATION
Section 3.1 - Health	
No exposure assessment presented for human health.	

Section 3.2 -Environment
Used ECETOC TRA model.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	
No exposure assessment presented for human health.	

Section 4.2 -Environment
Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.
Further details on scaling and control technologies are provided in SpERC factsheet (http://cefic.org).
If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required.
For further information see www.ATIEL.org/REACH_GES .

SAFETY DATA SHEET.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Rimula R6 LME Plus 5W-30

Version
3.0

Revision Date.:
21.05.2026

SDS Number:
800010033846

Date of last issue: 06.02.2026
Print Date. 09.06.2026
