According to EC No 1907/2006 as amended as at the date of this SDS

# Shell Spirax S3 AX 80W-90

Version	Revision Date:	SDS Number:	Date of last issue: 19.06.2024
4.5	03.09.2024	800001015809	Print Date 04.09.2024

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name	: Shell Spirax S3 AX 80W-90
Product code	: 001D8281

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- stance/Mixture	: Transmission oil.
Uses advised against	: This product must not be used in applications other than those listed in Section 1 without first seeking the advice of the sup- plier.

#### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier	<ul> <li>Shell UK Oil Products Limited</li> <li>Shell Centre</li> <li>London</li> <li>SE1 7NA</li> <li>United Kingdom</li> </ul>
Telephone	: (+44) 08007318888
Telefax	
Contact for Safety Data Sheet	: If you have any enquiries about the content of this SDS please email lubricantSDS@shell.com

#### 1.4 Emergency telephone number

: +44 (0) 20 7934 7778 (This telephone number is available 24 hours per day, 7 days per week)

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

Long-term (chronic) aquatic hazard, Cat-	H412: Harmful to aquatic life with long lasting ef-
egory 3	fects.

#### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	:	No Hazard Symbol required
Signal word	:	No signal word

According to EC No 1907/2006 as amended as at the date of this SDS

# Shell Spirax S3 AX 80W-90

Version 4.5	Revision Date: 03.09.2024	SDS Nu 8000010		Date of last issue: 19.06.2024 Print Date 04.09.2024	
Hazard statements Precautionary statements		H412 : <b>Prev</b>	<ul> <li>PHYSICAL HAZARDS: Not classified as a physical hazard according to CLP criteria. HEALTH HAZARDS: Not classified as a health hazard under CLP criteria. ENVIRONMENTAL HAZARDS:</li> <li>H412 Harmful to aquatic life with long lasting effects.</li> <li>Prevention: P273 Avoid release to the environment.</li> </ul>		
		Resp	onse: No precau	utionary phrases.	
		Stora Dispo P501 dispo	No precau osal:	utionary phrases. If contents/ container to an approved waste	
Sensi	tising components	Con	tains alkylam tains amine p produce an		

#### 2.3 Other hazards

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis. Used oil may contain harmful impurities.

Not classified as flammable but will burn.

### **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Chemical nature	<ul> <li>Highly refined mineral oils and additives. The highly refined mineral oil contains &lt;3% (w/w) DMSO- extract, according to IP346. Classification based on DMSO extract content &lt; 3% (Regula- tion (EC) 1272/2008, Annex VI, Part 3, Note L).</li> </ul>
	* contains one or more of the following CAS-numbers (REACH registration numbers): 64742-53-6 (01-2119480375-

According to EC No 1907/2006 as amended as at the date of this SDS

# Shell Spirax S3 AX 80W-90

Version 4.5	Revision Date: 03.09.2024		Date of last issue: 19.06.202 Print Date 04.09.2024	4
		2119487077-29), 64 0 (01-2119471299- 72623-86-0 (01-211 2119474889-13), 80 9 (01-0000020163- 151006-60-9 (01-21 2119543695-30), 64	-2119484627-25), 64742-55 4742-56-9 (01-2119480132- 27), 68037-01-4 (01-211948 9474878-16), 72623-87-1 (0 042-47-5 (01-2119487078-2 82), 68649-12-7 (01-211952 19523580-47), 163149-28-8 4741-88-4 (01-2119488706- 30), 157707-86-3 (01-21194	48), 64742-65- 6452-34), 01- 7), 848301-69- 7646-33), 3 (01- 23), 64741-89-
	ponents nical name	CAS-No. EC-No. Index-No. Registration numb	Classification	Concentration (% w/w)
	hangeable low viscosity oil (<20,5 cSt @40°C) *	Not Assigned	Asp. Tox. 1; H304	0 - 90
Alken	ıyl amine	1213789-63-9 01-2119473797-1	Acute Tox. 4; H302 Asp. Tox. 1; H304 Skin Corr. 1; H314 STOT SE 3; H335 STOT RE 2; H373 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 10	0.05 - 0.49
Amine	e phosphate	Not Assigned 931-384-6 01-2119493620-3	Acute Tox. 4; H302 Skin Sens. 1; H317 8 Aquatic Chronic 2; H411 Eye Irrit. 2; H319	0 - 2.49
Alkyl	amine	Not Assigned 701-175-2 01-2119456798-1	Acute Tox. 4; H302 Acute Tox. 3; H311	0 - 0.999

According to EC No 1907/2006 as amended as at the date of this SDS

# Shell Spirax S3 AX 80W-90

Version 4.5	Revision Date: 03.09.2024	SDS Number: 800001015809	Date of last issue: 19.06.2024 Print Date 04.09.2024	
		ĺ	aquatic toxicity): 1	
Alkyl	amine	111-86-4 203-916-0	Acute Tox. 3; H301 Acute Tox. 3; H311	0 - 0.24

203-916-0	Acute Tox. 3; H311 Skin Corr. 1; H314 Eye Dam. 1; H318 Acute Tox. 4; H332 STOT SE 3; H335 Aquatic Acute 1; H400 Flam. Liq. 3; H226 Aquatic Chronic 2; H411	
	M-Factor (Acute aquatic toxicity): 1	

For explanation of abbreviations see section 16.

# SECTION 4: First aid measures

4.1 Description of first aid measur	es
Protection of first-aiders	When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
If inhaled	No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
In case of skin contact	Remove contaminated clothing. Flush exposed area with wa- ter and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.
In case of eye contact	Flush eye with copious quantities of water. Remove contact lenses, if present and easy to do. Continue rinsing. If persistent irritation occurs, obtain medical attention.
If swallowed	In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.
4.2 Most important symptoms and	effects, both acute and delayed
	Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea.
4.3 Indication of any immediate me	edical attention and special treatment needed
Treatment	Notes to doctor/physician:

According to EC No 1907/2006 as amended as at the date of this SDS

# Shell Spirax S3 AX 80W-90

Version 4.5	Revision Date: 03.09.2024	SDS Number: 800001015809	Date of last issue: 19.06.2024 Print Date 04.09.2024		
		Treat sympto	natically.		
SECTIO	N 5: Firefighting meas	sures			
5.1 Exting	guishing media				
Suita	ble extinguishing media		spray or fog. Dry chemical powder, carbon diox- arth may be used for small fires only.		
Unsuitable extinguishing media		: Do not use w	Do not use water in a jet.		
5.2 Speci	al hazards arising from	the substance of	mixture		
Spec fightii	ific hazards during fire- ng	A complex mi gases (smoke Carbon monc occurs.	mbustion products may include: xture of airborne solid and liquid particulates and e). xide may be evolved if incomplete combustion rganic and inorganic compounds.		
5.3 Advic	e for firefighters				
	ial protective equipment efighters	gloves are to large contact Breathing Ap a confined sp	tive equipment including chemical resistant be worn; chemical resistant suit is indicated if with spilled product is expected. Self-Contained paratus must be worn when approaching a fire in ace. Select fire fighter's clothing approved to dards (e.g. Europe: EN469).		
Spec ods	ific extinguishing meth-		hing measures that are appropriate to local cir- and the surrounding environment.		

#### **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	:	<ul><li>6.1.1 For non emergency personnel:</li><li>Avoid contact with skin and eyes.</li><li>6.1.2 For emergency responders:</li><li>Avoid contact with skin and eyes.</li></ul>
6.2 Environmental precautions		
Environmental precautions	:	Use appropriate containment to prevent uncontrolled release. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up	Slippery when spilt. Avoid accidents, clean up immediately.
	Prevent from spreading by making a barrier with sand, earth
	or other containment material.

According to EC No 1907/2006 as amended as at the date of this SDS

# Shell Spirax S3 AX 80W-90

Version	Revision Date:	SDS Number:	Date of last issue: 19.06.2024
4.5	03.09.2024	800001015809	Print Date 04.09.2024
		•	directly or in an absorbent. e with an absorbent such as clay, sand or other

#### 6.4 Reference to other sections

For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet., For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

suitable material and dispose of properly.

#### **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

7.1 Trecautions for sale nanuling	,	
Technical measures	:	Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
Advice on safe handling	:	Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning mate- rials in order to prevent fires.
Product Transfer	:	Proper grounding and bonding procedures should be used during all bulk transfer operations to avoid static accumulation.
Hygiene measures	:	Exposure to this product should be reduced as low as reason- ably practicable. Reference should be made to the Health and Safety Executive's publication "COSHH Essentials".
7.2 Conditions for safe storage, i	nc	luding any incompatibilities

#### Keep container tightly closed and in a cool, well-ventilated Further information on stor-: age stability place. Use properly labeled and closable containers. Store at ambient temperature. Refer to section 15 for any additional specific legislation covering the packaging and storage of this product. The storage of this product may be subject to the Control of Pollution (Oil Storage) (England) Regulations. Further guidance may be obtained from the local environmental agency office. Packaging material Suitable material: For containers or container linings, use mild 1 steel or high density polyethylene. Unsuitable material: PVC. **Container Advice** : Polyethylene containers should not be exposed to high temperatures because of possible risk of distortion.

According to EC No 1907/2006 as amended as at the date of this SDS

# Shell Spirax S3 AX 80W-90

Version	Revision Date:	SDS Number:	Date of last issue: 19.0
4.5	03.09.2024	800001015809	Print Date 04.09.2024

#### 7.3 Specific end use(s)

Specific use(s)

: Not applicable

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Oil mist, mineral	Not As- signed	TWA (inhalable fraction)	5 mg/m3	US. ACGIH Threshold Limit Values
Oil mist, mineral		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH

19.06.2024

#### **Biological occupational exposure limits**

#### 8.2 Exposure controls

#### Engineering measures

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Adequate ventilation to control airborne concentrations.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

#### General Information:

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

#### Personal protective equipment

The provided information is made in consideration of the PPE directive (Council Directive 89/686/EEC) and the CEN European Committee for Standardisation (CEN) standards.

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

According to EC No 1907/2006 as amended as at the date of this SDS

# Shell Spirax S3 AX 80W-90

Version 4.5	Revision Date: 03.09.2024	SDS Number: 800001015809	Date of last issue: 19.06.2024 Print Date 04.09.2024
Eye	protection	protective ey	handled such that it could be splashed into eyes, /ewear is recommended. EU Standard EN166.
Han	d protection		
F	Remarks	gloves appro US: F739) m suitable che gloves Suita usage, e.g. f sistance of g glove supplie Personal hyg Gloves musi gloves, hand cation of a n For continue through time 480 minutes short-term/s recognize th may not be a time maybe and replacer a good pred dependent of Glove thickn	contact with the product may occur the use of oved to relevant standards (e.g. Europe: EN374, hade from the following materials may provide mical protection. PVC, neoprene or nitrile rubber bility and durability of a glove is dependent on requency and duration of contact, chemical re- love material, dexterity. Always seek advice from ers. Contaminated gloves should be replaced. giene is a key element of effective hand care. only be worn on clean hands. After using is should be washed and dried thoroughly. Appli- on-perfumed moisturizer is recommended. us contact we recommend gloves with break- of more than 240 minutes with preference for > where suitable gloves can be identified. For plash protection we recommend the same but at suitable gloves offering this level of protection available and in this case a lower breakthrough acceptable so long as appropriate maintenance ment regimes are followed. Glove thickness is not ctor of glove resistance to a chemical as it is in the exact composition of the glove material. ess should be typically greater than 0.35 mm in the glove make and model.
Skin	and body protection	work clothes	on is not ordinarily required beyond standard actice to wear chemical resistant gloves.
Res	piratory protection	conditions o In accordance tions should If engineerin tions to a lev select respir cific conditio Check with r Where air-fil priate combin Select a filte and vapours	ry protection is ordinarily required under normal f use. The with good industrial hygiene practices, precau- be taken to avoid breathing of material. g controls do not maintain airborne concentra- rel which is adequate to protect worker health, atory protection equipment suitable for the spe- ns of use and meeting relevant legislation. espiratory protective equipment suppliers. tering respirators are suitable, select an appro- nation of mask and filter. r suitable for combined particulate/organic gases [Type A/Type P boiling point > 65°C (149°F)] 14387 and EN143.
The	rmal hazards	: Not applicab	le

According to EC No 1907/2006 as amended as at the date of this SDS

# Shell Spirax S3 AX 80W-90

Version	Revision Date:
4.5	03.09.2024

SDS Number: 800001015809

Date of last issue: 19.06.2024 Print Date 04.09.2024

### **SECTION 9: Physical and chemical properties**

# 9.1 Information on basic physical and chemical properties

Physical state	:	Liquid at room temperature.
Colour	:	amber
Odour	:	Slight hydrocarbon
Odour Threshold	:	Data not available
pour point	:	-30 °C Method: ISO 3016
Initial boiling point and boiling range	:	> 280 °Cestimated value(s)
Flammability		
Flammability (solid, gas)	:	Not applicable
Flammability (liquids)	:	Not classified as flammable but will burn.
Lower explosion limit and uppe	er e	xplosion limit / flammability limit
Upper explosion limit / upper flammability limit	:	Typical 10 %(V)
Lower explosion limit / Lower flammability limit	:	Typical 1 %(V)
Flash point	:	220 °C Method: ISO 2592
Auto-ignition temperature	:	> 320 °C
Decomposition temperature Decomposition tempera- ture	:	Data not available
рН	:	Not applicable
Viscosity Viscosity, dynamic	:	Data not available
Viscosity, kinematic	:	169 mm2/s (40.0 °C) Method: ISO 3104
		16.5 - 17.5 mm2/s (100 °C) Method: ISO 3104

According to EC No 1907/2006 as amended as at the date of this SDS

# Shell Spirax S3 AX 80W-90

Vers 4.5	ion	Revision Date: 03.09.2024		S Number: )001015809	Date of last issue: 19.06.2024 Print Date 04.09.2024
		ity(ies) ter solubility ubility in other solvents		negligible Data not availabl	e
	octano	n coefficient: n- l/water	:	log Pow: > 6 (based on inform < 0.5 Pa (20 °C)	ation on similar products)
	·	e density	:	estimated value( 0.900 (15 °C)	s)
	Density		:	900 kg/m3 (15.0 Method: ISO 121	
		e vapour density	:	> 1 estimated value(	s)
0.27	Par	ticle size	:	Data not availabl	e
9.2 (		ive properties	:	Classification Co	de: Not classified
	Oxidizi	ng properties	:	Data not availabl	е
	Flamm	ability (liquids)	:	Not classified as	flammable but will burn.
	Evapor	ation rate	:	Data not availabl	e
	Condu	ctivity	:	This material is r	ot expected to be a static accumulator.

### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

### 10.2 Chemical stability

Stable.

No hazardous reaction is expected when handled and stored according to provisions

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with strong oxidising agents.

#### 10.4 Conditions to avoid

Conditions to avoid

: Extremes of temperature and direct sunlight.

According to EC No 1907/2006 as amended as at the date of this SDS

# Shell Spirax S3 AX 80W-90

Version	Revision Date:	SDS Number:	Date of last issue: 19.06.2024	
4.5	03.09.2024	800001015809	Print Date 04.09.2024	

#### 10.5 Incompatible materials

Materials to avoid : Strong oxidising agents.

#### **10.6 Hazardous decomposition products**

No decomposition if stored and applied as directed.

#### **SECTION 11: Toxicological information**

# 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of :	Skin and eye contact are the primary routes of exposure alt-
exposure	hough exposure may occur following accidental ingestion.

Acute toxicity	
----------------	--

Product:	
FIUUUCI.	

Acute oral toxicity	:	LD50 (rat): > 5,000 mg/kg Remarks: Low toxicity Based on available data, the classification criteria are not met.
Acute inhalation toxicity	:	Remarks: Based on available data, the classification criteria are not met.
Acute dermal toxicity	:	LD50 (Rabbit): > 5,000 mg/kg Remarks: Low toxicity Based on available data, the classification criteria are not met.
Skin corrosion/irritation		
Product:		
Remarks	:	Slightly irritating to skin. Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis. Based on available data, the classification criteria are not met.
Serious eye damage/eye irrita	ati	on
Product: Remarks	:	Slightly irritating to the eye. Based on available data, the classification criteria are not met.
Components:		
Amine phosphate: Remarks	:	Based on available data, the classification criteria are not met.

According to EC No 1907/2006 as amended as at the date of this SDS

# Shell Spirax S3 AX 80W-90

rsion			0S Number: 0001015809	Date of last issue: 19.06.2024 Print Date 04.09.2024	
Resp	iratory or skin sensitis	satic	on		
Produ	uct:				
Rema		:	Not a sensitiser.	nd skin sensitisation: ble data, the classification criteria are not me	
<u>Comp</u>	oonents:				
Amin	e phosphate:				
Rema	irks	:	tially sensitising of induce skin sens	a has shown that the concentration of poter components present in this product does no itisation. ergic skin reaction in sensitive individuals.	
Germ	cell mutagenicity				
<u>Produ</u>	uct:				
Geno	toxicity in vivo	:	Remarks: Non m Based on availat	utagenic ole data, the classification criteria are not me	
Germ sessn	cell mutagenicity- As- nent	:	This product doe categories 1A/1E	s not meet the criteria for classification in 3.	
Carci	nogenicity				
Produ	uct:				
Rema	ırks	:	Not a carcinoger Based on availat	n. Die data, the classification criteria are not me	
Rema	ırks	:	carcinogenic in a Highly refined mi	mineral oils of types shown to be non- nimal skin-painting studies. neral oils are not classified as carcinogenic nal Agency for Research on Cancer (IARC).	
Carcir ment	nogenicity - Assess-	:	This product doe categories 1A/1E	s not meet the criteria for classification in 3.	
Mater	iol			enicity Classification	

Material	GHS/CLP Carcinogenicity Classification
Highly refined mineral oil	No carcinogenicity classification.

# Reproductive toxicity

Product: Effects on fertility

Remarks: Not a developmental toxicant., Does not impair

:

According to EC No 1907/2006 as amended as at the date of this SDS

# Shell Spirax S3 AX 80W-90

Vers 4.5	sion	Revision Date: 03.09.2024		OS Number: 0001015809	Date of last issue: 19.06.2024 Print Date 04.09.2024
				fertility., Based or not met.	n available data, the classification criteria are
	Reproc sessmo	ductive toxicity - As- ent	:	This product does categories 1A/1B	s not meet the criteria for classification in
	STOT	- single exposure			
	Produ	<u>ct:</u>			
	Remar	ks	:	Based on availab	le data, the classification criteria are not met.
	STOT	- repeated exposure			
	Produ	<u>ct:</u>			
	Remar	ks	:	Based on availab	le data, the classification criteria are not met.
	Aspira	tion toxicity			
	<u>Produ</u>	<u>ct:</u>			
	Not an	aspiration hazard., Ba	ised	on available data,	the classification criteria are not met.
11.2	Inform	nation on other hazar	ds		
	Endoc	rine disrupting prope	ertie	S	
	Produ	<u>ct:</u>			
	Assess	sment	:	ered to have ende REACH Article 57	ixture does not contain components consid- ocrine disrupting properties according to 7(f) or Commission Delegated regulation or Commission Regulation (EU) 2018/605 at higher.
	Furthe	er information			
	Produ	<u>ct:</u>			
	Remar	ks	:	lated during use. depend on use ar environment on d	uld be handled with caution and skin contact
	Remar	ks	:	Slightly irritating t	o respiratory system.
	Remar	ks	:	Classifications by frameworks may	other authorities under varying regulatory exist.
	Remar	ks	:		otherwise, the data presented is representa- t as a whole, rather than for individual com-

According to EC No 1907/2006 as amended as at the date of this SDS

# Shell Spirax S3 AX 80W-90

Version Revis 4.5 03.09

Revision Date: 03.09.2024

SDS Number: 800001015809

Date of last issue: 19.06.2024 Print Date 04.09.2024

### **SECTION 12: Ecological information**

#### 12.1 Toxicity

	<u>Product:</u> Toxicity to fish	:	Remarks: LL/EL/IL50 10-100 mg/l Harmful
	Toxicity to daphnia and other aquatic invertebrates	:	Remarks: LL/EL/IL50 10-100 mg/l Harmful
	Toxicity to algae/aquatic plants	:	Remarks: LL/EL/IL50 10-100 mg/l Harmful
	Toxicity to fish (Chronic tox- icity)	:	Remarks: Data not available
	Toxicity to daphnia and other aquatic invertebrates (Chron- ic toxicity)	:	Remarks: Data not available
	Toxicity to microorganisms	:	Remarks: Data not available
	Components:		
	Alkenyl amine:		
	M-Factor (Acute aquatic tox- icity)	:	10
	M-Factor (Chronic aquatic toxicity)	:	10
	<b>Alkyl amine:</b> M-Factor (Acute aquatic tox- icity)	:	1
	<b>Alkyl amine:</b> M-Factor (Acute aquatic tox- icity)	:	1
12.2	2 Persistence and degradabili	ty	
	Product:		
	Biodegradability	:	Remarks: Not readily biodegradable. Major constituents are inherently biodegradable, but contains com- ponents that may persist in the environment.

According to EC No 1907/2006 as amended as at the date of this SDS

# Shell Spirax S3 AX 80W-90

Version 4.5	Revision Date: 03.09.2024	SDS Number: 800001015809	Date of last issue: 19.06.2024 Print Date 04.09.2024
12.3 Bioac	cumulative potentia	al	
<u>Produ</u>	<u>ict:</u>		
Bioaco	cumulation	: Remarks: Contai	ns components with the potential to bioaccumulate.
12.4 Mobil	ity in soil		
<u>Produ</u>	<u>ict:</u>		
Mobili	ty		d under most environmental conditions., Ad- d has low mobility
		Remarks: Float	s on water.
12.5 Resu	Its of PBT and vPvB	assessment	
Not re	levant		
12.6 Endo	crine disrupting pro	perties	
<u>Produ</u> Asses	<u>ıct:</u> sment	have endocrine d 57(f) or Commis	ixture does not contain components considered to isrupting properties according to REACH Article sion Delegated regulation (EU) 2017/2100 or sulation (EU) 2018/605 at levels of 0.1% or higher.
12.7 Other	adverse effects		
Produ	<u>ict:</u>		
Addition mation	onal ecological infor- า	tion potential or g Product is a mixt	one depletion potential, photochemical ozone crea- global warming potential. ure of non-volatile components, which will not be any significant quantities under normal conditions
		Poorly soluble m Causes physical	ixture. fouling of aquatic organisms.
		Mineral oil does concentrations le	not cause chronic toxicity to aquatic organisms at ss than 1 mg/l.
			otherwise, the data presented is representative of whole, rather than for individual component(s).

### SECTION 13: Disposal considerations

:

### 13.1 Waste treatment methods

Product

#### Recover or recycle if possible.

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to

According to EC No 1907/2006 as amended as at the date of this SDS

# Shell Spirax S3 AX 80W-90

Versio 4.5	on	Revision Date: 03.09.2024		DS Number: 0001015809	Date of last issue: 19.06.2024 Print Date 04.09.2024
				ods in compliance	per waste classification and disposal meth- with applicable regulations. to the environment, in drains or in water
				ground water, or I Waste, spills or us Waste arising from posed of in accord to a recognised or collector or contra Do not dispose of	ould not be allowed to contaminate soil or be disposed of into the environment. sed product is dangerous waste. In a spillage or tank cleaning should be dis- dance with prevailing regulations, preferably ollector or contractor. The competence of the actor should be established beforehand. I tank water bottoms by allowing them to und. This will result in soil and groundwater
				Pollution from Shi	ternational Convention for the Prevention of ps (MARPOL 73/78) which provides tech- ontrolling pollutions from ships.
C	Contan	ninated packaging	:	to a recognized of the collector or co Disposal should b	dance with prevailing regulations, preferably ollector or contractor. The competence of ontractor should be established beforehand. be in accordance with applicable regional, I laws and regulations.
L	Local le	egislation			
١	Waste	catalogue	:		
				EU Waste Dispos	al Code (EWC):
١	Waste	Code	:		
				13 02 05*	
F	Remarl	٢S	:		e in accordance with applicable regional, I laws and regulations.
				Classification of wuser.	vaste is always the responsibility of the end
				Hazardous Waste	e (England and Wales) Regulations 2005.

According to EC No 1907/2006 as amended as at the date of this SDS

# Shell Spirax S3 AX 80W-90

Version	Revision Date:	SDS Number:	Date of last issue: 19.06.2024
4.5	03.09.2024	800001015809	Print Date 04.09.2024

### **SECTION 14: Transport information**

14.1 UN number or ID number					
ADR	:	Not regulated as a dangerous good			
RID	:	Not regulated as a dangerous good			
IMDG IATA	:	Not regulated as a dangerous good Not regulated as a dangerous good			
14.2 UN proper shipping name					
ADR	:	Not regulated as a dangerous good			
RID	:	Not regulated as a dangerous good			
IMDG IATA	:	Not regulated as a dangerous good Not regulated as a dangerous good			
14.3 Transport hazard class(es)					
ADR	:	Not regulated as a dangerous good			
RID	:	Not regulated as a dangerous good			
IMDG IATA	:	Not regulated as a dangerous good Not regulated as a dangerous good			
14.4 Packing group					
ADR	:	Not regulated as a dangerous good			
RID	:	Not regulated as a dangerous good			
IMDG IATA	:	Not regulated as a dangerous good Not regulated as a dangerous good			
14.5 Environmental hazards					
ADR	:	Not regulated as a dangerous good			
RID	:	Not regulated as a dangerous good			
IMDG	:	Not regulated as a dangerous good			
14.6 Special precautions for use	r				
Remarks	:	Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.			

#### 14.7 Maritime transport in bulk according to IMO instruments

MARPOL Annex 1 rules apply for bulk shipments by sea.

According to EC No 1907/2006 as amended as at the date of this SDS

# Shell Spirax S3 AX 80W-90

Version	Revision Date:	SDS Number:	Date of last issue: 19.06.2024
4.5	03.09.2024	800001015809	Print Date 04.09.2024

#### **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:	Not applicable
REACH - List of substances subject to authorisation (Annex XIV)	:	Product is not subject to Authorisa- tion under REACH.
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	:	This product does not contain sub- stances of very high concern (Regu- lation (EC) No 1907/2006 (REACH), Article 57).

Volatile organic compounds : Volatile organic compounds (VOC) content: 0 %

#### Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Environmental Protection Act 1990 (as amended). Health and Safety at Work etc. Act 1974. Consumers Protection Act 1987. Pollution Prevention and Control Act 1999. Environment Act 1995. Factories Act 1961. The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment (Amendment) Regulations 2011. Chemicals (Hazard Information and Packaging for Supply) Regulations 2009. Control of Substances Hazardous to Health Regulations 2002 (as amended). Merchant Shipping (Dangerous Goods and Marine Pollutants) Regulations 1997. Reporting of Injuries, Diseases and Dangerous Occurrences Regulations 1995 (as amended). Personal Protective Equipment Regulations 2002. Personal Protective Equipment at Work Regulations 1992. Hazardous Waste (England and Wales) Regulations 2005(as amended). Control of Major Accident Hazards Regulations 1999 (as amended). Renewable Transport Fuel Obligations Order 2007 (as amended). Energy Act 2011. Environmental Permitting (England and Wales) Regulations 2010 (as amended). Waste (England and Wales) Regulations 2011 (as amended). Planning (Hazardous Substances) Act 1990 and associated regulations. The Environmental Protection (Controls on Ozone-Depleting Substances) Regulations 2011.

#### The components of this product are reported in the following inventories:

REACH	:	Not established.	

TSCA	:	All components listed.
------	---	------------------------

#### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

According to EC No 1907/2006 as amended as at the date of this SDS

# Shell Spirax S3 AX 80W-90

Version Re 4.5 03

Revision Date: 03.09.2024

SDS Number: 800001015809 Date of last issue: 19.06.2024 Print Date 04.09.2024

### **SECTION 16: Other information**

#### Full text of H-Statements

11000		
H226	:	Flammable liquid and vapour.
H301	:	Toxic if swallowed.
H302	:	Harmful if swallowed.
H304	:	May be fatal if swallowed and enters airways.
H311	:	Toxic in contact with skin.
H314	:	Causes severe skin burns and eye damage.
H317	:	May cause an allergic skin reaction.
H318	:	Causes serious eye damage.
H319	:	Causes serious eye irritation.
H330	:	Fatal if inhaled.
H332	:	Harmful if inhaled.
H335	:	May cause respiratory irritation.
H373	:	May cause damage to organs through prolonged or repeated
		exposure.
H400	:	Very toxic to aquatic life.
H410	:	Very toxic to aquatic life with long lasting effects.
H411	:	Toxic to aquatic life with long lasting effects.
Full text of other abbrevia	tions	
Acute Tox.	:	Acute toxicity
Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatia Chrania		Long torre (chronic) or votic honored

Acute TOX.	•	
Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Eye Dam.	:	Serious eye damage
Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
Skin Corr.	:	Skin corrosion
Skin Sens.	:	Skin sensitisation
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH / TWA	:	8-hour, time-weighted average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL

According to EC No 1907/2006 as amended as at the date of this SDS

# Shell Spirax S3 AX 80W-90

Version	Revision Date:	SDS Number:	Date of last issue: 19.06.2024
4.5	03.09.2024	800001015809	Print Date 04.09.2024

- Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance: PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI -Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

#### Further information

Training advice	:	Provide adequate information, instruction and training for op- erators.
Other information	:	A vertical bar ( ) in the left margin indicates an amendment from the previous version.
Sources of key data used to compile the Safety Data Sheet	:	The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).
Classification of the mixture: Classification procedure:		
Aquatic Chronic 3	H4	12 Expert judgement and weight of evi- dence determination.
Identified Uses according to the Use Descriptor System Uses - Worker		
Title	:	General use of lubricants and greases in vehicles or machin-

ery.

- Professional

#### Uses - Worker Title

: General use of lubricants and greases in vehicles or machinery. - Industrial

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific

According to EC No 1907/2006 as amended as at the date of this SDS

# Shell Spirax S3 AX 80W-90

Version Revision Date: 4.5 03.09.2024

Date:SDS Number:4800001015809

Date of last issue: 19.06.2024 Print Date 04.09.2024

material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN

According to EC No 1907/2006 as amended as at the date of this SDS

# Shell Spirax S3 AX 80W-90

Version	Revision
4.5	03.09.20

sion Date: 9.2024 SDS Number: 800001015809 Date of last issue: 19.06.2024 Print Date 04.09.2024

#### Exposure Scenario - Worker 30000010642 **SECTION 1** EXPOSURE SCENARIO TITLE Title General use of lubricants and greases in vehicles or machinerv.- Professional Sector of Use: SU22 **Use Descriptor** Process Categories: PROC 1, PROC 2, PROC 8a, PROC 8b. PROC 20 Environmental Release Categories: ERC9a, ERC9b, ATIEL-ATC SPERC 9.Bp.v1 Scope of process Covers general use of lubricants and greases in vehicles or machinery in closed systems. Includes filling and draining of containers and operation of enclosed machinery (including engines) and associated maintenance and storage activities. **SECTION 2** OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES Additional Information No exposure assessment presented for human health. Section 2.1 **Control of Worker Exposure Product Characteristics Contributing Scenarios Risk Management Measures** Section 2.2 **Control of Environmental Exposure** Amounts Used EU tonnage (tonnes per year): 5,387.2 Fraction of EU tonnage used in region: 0.1 Fraction of Regional tonnage used locally: 0.1 Frequency and Duration of Use Emission Days (days/year): 365 Environmental factors not influenced by risk management Local freshwater dilution factor: 10 Local marine water dilution factor: 100 Other Operational Conditions affecting Environmental Exposure Negligible wastewater emissions as process operates without water contact. Release fraction to air from process (after typical onsite RMMs) : 1E-04 Release fraction to wastewater from process (after typical onsite 5.00E-04 RMMs and before (municipal) sewage treatment plant): Release fraction to soil from process (after typical onsite RMMs): 1E-03 Technical conditions and measures at process level (source) to prevent release Common practices vary across sites thus conservative process release estimates used. Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil Prevent discharge of undissolved substance to or recover from onsite wastewater. Organisational measures to prevent/limit release from site

According to EC No 1907/2006 as amended as at the date of this SDS

# Shell Spirax S3 AX 80W-90

Version	Revision Date:	SDS Number:	Date of last issue: 19.06.2024
4.5	03.09.2024	800001015809	Print Date 04.09.2024

Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

Conditions and Measures related to municipal sewage treatment plant		
Estimated substance removal from wastewater via domestic sewage	87.3	
treatment (%)		
Assumed domestic sewage treatment plant flow (m3/d)	2.00E+03	
Maximum allowable site quantity (MSafe) based on OCs and RMMs	424.6	
as above (kg/day) :		
Conditions and Measures related to external treatment of waste for disposal		

External treatment and disposal of waste should comply with applicable local and/or regional regulations.

#### Conditions and measures related to external recovery of waste

External recovery and recycling of waste should comply with applicable local and/or regional regulations.

### SECTION 3

### EXPOSURE ESTIMATION

Section 3.1 - Health

No exposure assessment presented for human health.

### Section 3.2 - Environment

Used ECETOC TRA model.

# SECTION 4 GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

#### Section 4.1 - Health

No exposure assessment presented for human health.

#### Section 4.2 - Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Further details on scaling and control technologies are provided in SpERC factsheet (http://cefic.org).

If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a sitespecific chemical safety assessment is required.

For further information see www.ATIEL.org/REACH\_GES.

According to EC No 1907/2006 as amended as at the date of this SDS

# Shell Spirax S3 AX 80W-90

Version	Revision Date:
4.5	03.09.2024

SDS Number: 800001015809 Date of last issue: 19.06.2024 Print Date 04.09.2024

### Exposure Scenario - Worker 300000010643

SECTION 1	EXPOSURE SCENARIO TITLE		
Title	General use of lubricants and greases in vehicles or machin- ery Industrial		
Use Descriptor	Sector of Use: SU3 Process Categories: PROC 1, PROC 2, PROC 8b, PROC 9 Environmental Release Categories: ERC4, ERC7, ATIEL- ATC SPERC 4.Bi.v1		
Scope of process	Covers general use of lubricants and greases in vehicles or machinery in closed systems. Includes filling and draining of containers and operation of enclosed machinery (including engines) and associated maintenance and storage activities.		

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES				
Additional Information	No exposure assessment presented for human health.				
Section 2.1	Control of Worker Exposure				
Product Characteristics					
Contributing Scenarios	Risk Management Measures				
Section 2.2	Control of Environmental Exposure				
Amounts Used					
EU tonnage (tonnes per year	r):	2.63E+03			
Fraction of EU tonnage used in region:		0.1			
Fraction of Regional tonnage used locally:		0.1			
Frequency and Duration of	Use				
Emission Days (days/year):		300			
	influenced by risk management				
Local freshwater dilution factor:		10			
Local marine water dilution factor:		100			
	ons affecting Environmental Exposure	1			
Negligible wastewater emissions as process operates without water					
contact.		_			
Release fraction to air from process (after typical onsite RMMs) :		5.00E-05			
Release fraction to wastewa	2.00E-11				
RMMs and before (municipal) sewage treatment plant):					
Release fraction to soil from	0				
	neasures at process level (source) to pr	event release			
	ss sites thus conservative process re-				
lease estimates used.	I				
	s and measures to reduce or limit disch	arges, air emis-			
sions and releases to soil	a typical removal officiancy of (9)	70			
Treat air emission to provide a typical removal efficiency of (%) Prevent discharge of undissolved substance to or recover from onsite		70			
wastewater.					
User sites are assumed to be	e provided with oil/water separators or				

According to EC No 1907/2006 as amended as at the date of this SDS

# Shell Spirax S3 AX 80W-90

Version	Revision Date:	SDS Number:	Date of last issue: 19.06.2024
4.5	03.09.2024	800001015809	Print Date 04.09.2024

a minister de la constante de la clierte constante de la constante de la constante de la constante de la consta				
equivalent and for waste water to be discharged via public sewer sys-				
tem.				
Organisational measures to prevent/limit release from site				
Do not apply industrial sludge to natural soils.				
Sludge should be incinerated, contained or reclaimed.				
Conditions and Measures related to municipal sewage treatment plant				
Estimated substance removal from wastewater via domestic sewage	87.3			
treatment (%)				
Assumed domestic sewage treatment plant flow (m3/d)	2.00E+03			
Maximum allowable site quantity (MSafe) based on OCs and RMMs	43,615.4			
as above (kg/day) :				
Conditions and Measures related to external treatment of waste for disposal				
External treatment and disposal of waste should comply with applicable local and/or regional				
regulations.				

#### Conditions and measures related to external recovery of waste

External recovery and recycling of waste should comply with applicable local and/or regional regulations.

#### **SECTION 3**

#### EXPOSURE ESTIMATION

Section 3.1 - Health

No exposure assessment presented for human health.

#### Section 3.2 - Environment

Used ECETOC TRA model.

### **SECTION 4**

# GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

#### Section 4.1 - Health

No exposure assessment presented for human health.

#### Section 4.2 - Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Further details on scaling and control technologies are provided in SpERC factsheet (http://cefic.org).

If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a sitespecific chemical safety assessment is required.

For further information see www.ATIEL.org/REACH\_GES.