

PENNZOIL PLATINUM® HIGH MILEAGE SAE 0W-20 FULL SYNTHETIC MOTOR OIL - MADE FROM NATURAL GAS

TECHNICAL DATA SHEET



Pennzoil Platinum® High Mileage helps extend engine life and protects for up to 15 years or 500,000 miles, whichever comes first. Guaranteed*. Pennzoil is made from natural gas, not crude. Its base oil is 99.5% free from engine clogging impurities. Pennzoil Platinum® High Mileage is designed for complete protection for engines with 75k+ miles. The Proof is in the Pennzoil.

* Enrollment required. Keep your receipts. Other conditions apply. See pennzoil.com/warranty for full details

PERFORMANCE, FEATURES & BENEFITS

Pennzoil Platinum® High Mileage is specially formulated to reduce leaks and oil consumption in older vehicles. It is designed to deliver complete engine protection for top engine performance.

Complete Protection:

CONDITIONS SEALS ON OLDER ENGINES

Helps reduce leaks and oil consumption

BETTER FUEL ECONOMY¹

CLEANER PISTONS

Keeps pistons up to 45% cleaner than the toughest industry standards²

UNSURPASSED WEAR PROTECTION

No other leading high mileage motor oil provides better protection from friction³

PROTECTS HORSEPOWER

Helps protect loss of horsepower

EXCELLENT PERFORMANCE IN EXTREME TEMPERATURES

Provides faster low temperature oil flow and protects in extreme heat

MAIN APPLICATIONS

Pennzoil Platinum® High Mileage SAE 0W-20 with PurePlus™ Technology is recommended for use in all vehicles requiring the use of SAE 0W-20 viscosity grade engine oils under all driving conditions.

Pennzoil Platinum® High Mileage SAE 0W-20 is also suitable for use and offers the same protection as SAE 5W-20.

Pennzoil Platinum® High Mileage SAE 0W-20 with PurePlus™ Technology can be mixed with other synthetic and mineral oils and is recommended for use in all vehicle applications under all driving conditions.

Always consult your owner's manual for the correct viscosity grade and performance recommendation required for your vehicle.

¹ 0W motor oils deliver better fuel economy compared to higher viscosity grades

² Based on Sequence IIHF results

³ Based on Sequence IVA wear test using SAE 5W-30

PENNZOIL PLATINUM® HIGH MILEAGE SAE 0W-20 FULL SYNTHETIC MOTOR OIL- MADE FROM NATURAL GAS

SPECIFICATIONS, APPROVALS & RECOMMENDATIONS

Meets or exceeds the following OEM requirements:

- Chrysler MS-6395
- Ford WSS-M2C947-A
- WSS-M2C947-B1
- General Motors GM 6094M

Exceeds the requirements of the following industry specifications:

TYPICAL PHYSICAL CHARACTERISTICS

Properties			Method	PENNZOIL PLATINUM® HIGH MILEAGE SAE 0W- 20 FULL SYNTHETIC MOTOR OIL
Viscosity Grade			SAE J300	0W-20
API Service Category				SP-RC
ILSAC				GF-6A
Density	kg/m³		ASTM D4052	839
Flash Point	°C		ASTM D93	205
Pour Point	°C		ASTM D97	-42
Kinematic Viscosity	@40°C	cSt	ASTM D445	46.5
Kinematic Viscosity	@100°C	cSt	ASTM D445	8.5
Viscosity Index			ASTM D2270	160
CCS Viscosity	@-35°C	cP	ASTM D5293	5 380
MRV Viscosity	@-40°C	cP	ASTM D4684	17 900

These characteristics are typical of current production. While future production will conform to Pennzoil's® specification, variations in these characteristics may occur.

HEALTH, SAFETY & ENVIRONMENT

Health and Safety

This Product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from <https://www.epc.shell.com>

- API SP-Resource Conserving and all previous Categories
- API SP
- ILSAC GF-6A and all previous ILSAC Standards

For a full listing of equipment approvals and recommendations, please consult your local Technical Helpdesk.

To find the right Pennzoil product for your vehicles and equipment, please consult www.pennzoil.com to look up the right motor oil recommendation using our oil selector.

Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

ADDITIONAL INFORMATION

Advice

Advice on applications not covered here may be obtained from your Pennzoil® Lubricants distributor representatives or local technical helpdesk.